



## Education and Research Department

### Demo Programs for **Java Programming Part-2**

*September 2009*

Document No.	Authorized By	Ver. Revision	Signature / Date
<i>ER/CORP/CRS/ERJEEML10 1/018</i>	Srikantan Moorthy	Ver. <i>1.0</i>	September 2009

## COPYRIGHT NOTICE

*All ideas and information contained in this document are the intellectual property of Education and Research Department, Infosys Technologies Limited. This document is not for general distribution and is meant for use only for the person they are specifically issued to. This document shall not be loaned to anyone, within or outside Infosys, including its customers. Copying or unauthorized distribution of this document, in any form or means including electronic, mechanical, photocopying or otherwise is illegal.*

Education and Research Department  
Infosys Technologies Limited  
Electronic City  
Hosur Road  
Bangalore - 561 229, India.

Tel: 91 80 852 0261-270

Fax: 91 80 852 0362

[www.infosys.com](http://www.infosys.com)

<mailto:E&R@infosys.com>

## Document Revision History

Ver. Revision	Date	Author(s)	Reviewer(s)	Description
1.0	Sep-2009	Avinash Pratap Singh and Sanjeev S.	Soni Ramchandani	Baseline

## Contents

<i>Demo Programs for Java Programming Part 2.....</i>	<i>1</i>
<i>1-Creating thread Using Thread class .....</i>	<i>1</i>
<i>2-Creating thread using Runnable interface .....</i>	<i>2</i>
<i>3-Example to demonstrate ExecutorService class .....</i>	<i>3</i>
<i>4-Using Scanner class to receive user input .....</i>	<i>5</i>
<i>5-Understanding FileInputStream and FileOutputStream Class.....</i>	<i>6</i>
<i>6-Creating FileWriter class using BufferedWriter .....</i>	<i>6</i>
<i>7-Understanding how to create Scrollable ResultSet .....</i>	<i>7</i>
<i>8-Example to use Updatable Resultset .....</i>	<i>8</i>
<i>9-Example to use database Transaction .....</i>	<i>9</i>
<i>10-Example to understand Generics .....</i>	<i>10</i>
<i>End of Demo Document .....</i>	<i>11</i>

## Demo Programs for *Java Programming Part 2*

### 1-Creating thread using Thread class

```
/**
 * This demo explains Thread creation and usage in
 * Java
 */
import java.io.IOException;

class MyThread extends Thread {
    public MyThread(String firstName, String secondName, long delay) {
        this.firstName = firstName;
        this.secondName = secondName;
        aWhile = delay;
        setDaemon(true);
    }
    public void run() {
        try {
            while (true) {
                System.out.print(firstName);
                sleep(aWhile);
                System.out.print(secondName + "\n");
            }
        } catch (InterruptedException e) {
            System.out.println(firstName + secondName + e);
        }
    }
    private String firstName;
    private String secondName;
    private long aWhile;
}

public class MainClass {
    public static void main(String[] args) {
        Thread first = new MyThread
("A ", "a ", 200L);
        Thread second = new MyThread
("B ", "b ", 300L);
```

```
Thread third = new MyThread ("C ", "c ", 500L);
System.out.println("Press Enter when you have h
ad enough...\n");
first.start();
second.start();
third.start();
try {
    System.in.read();
    System.out.println("Enter pressed...\n");
} catch (IOException e) {
    System.out.println(e);
}
return;
}
```

## 2-Creating thread using Runnable interface

```
/**
 * This demo explains how to use Runnable interface
 * to create Threads in Java
 */
import java.io.IOException;

class MyThread implements Runnable {
    public MyThread
(String firstName, String secondName, long delay) {
        this.firstName = firstName;
        this.secondName = secondName;
        aWhile = delay;
    }
    public void run() {
        try {
            while (true) {
                System.out.print(firstName);
                Thread.sleep(aWhile);
                System.out.print(secondName + "\n");
            }
        }
    }
}
```

```
    }  
    } catch (InterruptedException e) {  
        System.out.println(firstName + secondName + e  
);  
    }  
}  
private String firstName;  
private String secondName;  
private long aWhile;  
}  
public class MainClass {  
    public static void main(String[] args) {  
        Thread first = new Thread(new MyThread("A ", "a ",  
        200L));  
        Thread second = new Thread(new MyThread("B ", "b "  
        , 300L));  
        Thread third = new Thread(new MyThread  
        ("C ", "c ", 500L));  
        System.out.println("Press Enter when you have h  
ad enough...\n");  
        first.start();  
        second.start();  
        third.start();  
        try {  
            System.in.read();  
            System.out.println("Enter pressed...\n");  
        } catch (IOException e) {  
            System.out.println(e);  
        }  
        System.out.println("Ending main()");  
        return;  
    }  
}
```

### 3-Example to demonstrate ExecutorService class

```
/**
```

```
* This demo explains how to use ExecutorService
in Java.
*/

import java.util.concurrent.ExecutorService;
import java.util.concurrent.Executors;

public class MainClass {
    public static void main(String[] args) {
        MyTask task1 = new MyTask ("thread1");
        MyTask task2 = new MyTask ("thread2");
        MyTask task3 = new MyTask ("thread3");

        System.out.println("Starting threads");

        ExecutorService threadExecutor = Executors.newC
achedThreadPool();

        // start threads and place in runnable state
        threadExecutor.execute(task1); // start task1
        threadExecutor.execute(task2); // start task2
        threadExecutor.execute(task3); // start task3

        threadExecutor.shutdown(); // shutdown worker t
hreads

        System.out.println("Threads started, main ends\
n");
    }
}

class MyTask implements Runnable {
    private int sleepTime;

    private String threadName;

    public MyTask (String name) {
        threadName = name;
        sleepTime = 1000;
    }
}
```



```
}

public void run() {
    try {
        System.out.printf("%s going to sleep for %d milliseconds.\n", threadName, sleepTime);

        Thread.sleep(sleepTime); // thread to sleep
    } catch (InterruptedException exception) {
        exception.printStackTrace();
    }
    System.out.printf("%s done sleeping\n", threadName);
}
}
```

## 4-Using Scanner class to receive user input

```
/**
 * This demo explains how Scanner class is used in Java.
 */

import java.util.Scanner;

public class MainClass{

    public static void main(String[] args){

        Scanner scanner = new Scanner (System.in);
        String s = scanner.next ();

        System.out.println(s);
    }

}
```

## 5-Understanding FileInputStream and FileOutputStream

```
/**
 * This demo explains how File Stream is
 * implemented in Java.
 */

import java.io.FileInputStream;
import java.io.FileOutputStream;
import java.io.InputStream;
import java.io.OutputStream;

public class FileInputOutputExample {
    public static void main(String[] args) throws Exception {

        InputStream is = new FileInputStream("in.txt");
        OutputStream os = new FileOutputStream("out.txt");

        int c;
        while ((c = is.read()) != -1) {
            System.out.print((char) c);
            os.write(c);
        }
        is.close();
        os.close();
    }
}
```

## 6-Creating FileWriter using BufferedWriter

```
/**
 * This demo explains how FileWriter and
 * BufferedWriter is implemented in Java.
 */
```

```
import java.io.BufferedWriter;
import java.io.FileWriter;
import java.io.PrintWriter;

class TestClass {

    public static void main(String args[]) throws Exception {

        FileWriter fw = new FileWriter(args[0]);
        BufferedWriter bw = new BufferedWriter(fw);
        PrintWriter pw = new PrintWriter(bw, false);

        pw.println(true);
        pw.println('A');
        pw.println(500);
        pw.println(40000L);
        pw.println(45.67f);
        pw.println(45.67);
        pw.println("HelloWorld");
        pw.println(new Integer("99"));

        pw.close();
    }
}
```

## 7-Understanding How to create scrollable ResultSet

```
/**
 * This demo explains how ResultSet is implemented
 * in Java.
 * Please change driver name and url as you change
 * your database.
 */
```

```
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.ResultSet;
import java.sql.Statement;

public class TestClass {
    public static void main(String[] args) throws Exception {
        Class.forName("com.mysql.jdbc.Driver");
        Connection connection = DriverManager.getConnection("jdbc:mysql://localhost/testdb", "root", "");

        Statement statement = connection.createStatement(ResultSet.TYPE_SCROLL_INSENSITIVE,
            ResultSet.CONCUR_READ_ONLY);

        ResultSet resultSet = statement.executeQuery("SELECT * FROM products");
        connection.close();
    }
}
```

## 8-Example to use updatable ResultSet

```
/**
 * This demo explains how updatable ResultSet is
 * implemented in Java.
 */

import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.ResultSet;
import java.sql.Statement;

public class PrintResultSetClass {
    public static void main(String args[]) throws Exception {
```

```
ption {  
    Class.forName("sun.jdbc.odbc.JdbcOdbcDriver");  
    Connection con = DriverManager.getConnection("j  
dbc:odbc:Contacts");  
    Statement stmt = con.createStatement(ResultSet.  
TYPE_SCROLL_INSENSITIVE, ResultSet.CONCUR_UPDATABLE  
);  
    ResultSet rs = stmt.executeQuery("select * from  
employee");  
    rs.moveToInsertRow();  
  
    rs.updateInt("Contact_ID", 150);  
    rs.updateString("First_Name", "India");  
    rs.updateString("Last_Name", "Bharat");  
  
    rs.insertRow();  
}  
}
```

## 9-Example to use database Transaction

```
/**  
 * This demo explains how Transaction can be  
 implemented in Java.  
 Please replace your driver name and url as you  
 change you database or driver.  
 */  
  
import java.sql.Connection;  
import java.sql.DriverManager;  
import java.sql.SQLException;  
import java.sql.Statement;  
  
public class TestClass {  
    public static void main(String[] args) throws Exc  
 eption {  
        Connection connection = null;
```

```
try {
    Class.forName("com.mysql.jdbc.Driver ");

    connection = DriverManager.getConnection("url", "USERID", "PASSWORD");

    connection.setAutoCommit(false);

    Statement statement = connection.createStatement();

    statement.executeUpdate("UPDATE Table1 SET Value = 1 WHERE Name = 'xyz'");
    statement.executeUpdate("UPDATE Table2 SET Value = 2 WHERE Name = 'abc'");

    connection.commit();

} catch (SQLException ex) {
    connection.rollback();
}

}
```

## 10-Example to understand Generics

```
/**
 * This demo explains how Generics is implemented in Java.
 */

public class TestGenericMethods {
    public static <E> void displayArray(E[] inputArray)
    {
        for (E element : inputArray)
            System.out.printf("%s ", element);
    }
}
```

```
System.out.println();  
}  
public static void main(String args[]) {  
Integer[] array = { 10, 20, 30, 40, 50, 60 };  
System.out.println("The Array contains:");  
displayArray(array);  
}  
}
```

**End of Demo Document**