This node is a branch out.

C6 [13]

3.94 in

From	To	Conductor	Color	Size	Notes
C6.1	C1.8	W31.White-Black-Blue		22 AWG	SHUTDOWN_FIREWALLOUT_ESTOP
C6.2	C3.11	W32.White-Black-Blue		22 AWG	SHUTDOWN_SOURCE_ESTOP

Path from Bottom node shouldn't enable a direct bend to TSSI

431.28 mm

C4 [10]
13.73 in

From	To	Conductor	Color	Size	Notes
C4.1	C2.19	W13.White-Red		22 AWG	RTM_LIGHT
C4.2	C1.16	W14.White-Red		22 AWG	TSSI_GREEN
C4.3	C1.17	W15.White-Red		22 AWG	TSSI_RED
C4.4	C3.18	W16.Black		22 AWG	GND TSSI RTM

From	To	Conductor	Color	Size	Notes
C3.1	C1.7	W1.Red		14 AWG	20V PENTHOUSE 1
C3.2	C1.1	W37.Unspecified		22 AWG	CAN1H
C3.3	C1.2				CAN1L
C3.4	C1.11	W2.Black		14 AWG	GND PENTHOUSE 1
C3.5	C1.14	W3.Red		14 AWG	20V PENTHOUSE 2
C3.6	C1.25	W4.Black		20 AWG	GND PENTHOUSE 2
C3.7	C1.3				CAN1DRAIN
C3.8	C1.4	W38.Unspecified		22 AWG	CAN2H
C3.9	C1.5				CAN2L
C3.10	C1.6				CAN2DRAIN
C3.11	C6.2	W32.White-Black-Blue		22 AWG	SHUTDOWN_SOURCE_ESTOP
C3.12	C2.10	W33.White-Black-Blue		22 AWG	SHUTDOWN_BCU_ATTIC
C3.13	C2.1	W5.Red		20 AWG	20V BCU
C3.14	C2.2	W6.Black		20 AWG	GND BCU
C3.15	C2.3	W7.Yellow		20 AWG	20V BCU 1
C3.16	C2.4	W8.Yellow		20 AWG	20V BCU 2
C3.17	C1.15	W12.White-Blue		22 AWG	SDC_RESET
C3.18	C4.4	W16.Black		22 AWG	GND TSSI RTM
C3.19	C5.2	W18.Black		22 AWG	GND_BRAKE
C3.20	C8.1	W19.Red		22 AWG	20V FLOOR
C3.21	C8.2	W20.Black		22 AWG	GND FLOOR
C3.22	C7.1	W21.Red		22 AWG	20V SENS
C3.23	C7.2	W22.Black		22 AWG	GND SENS
C3.26	C2.15	W28.White		22 AWG	BSPD_TEST-
C3.25	C2.13	W27.White		22 AWG	BSPD_TEST+

ATTIC CONNECTOR

C3 [3]

2.72 in

From	To	Notes
S5	C7.3	CAN2H SENS


From	To	Notes
S6	C7.4	CAN2L SENS

From	To	Notes
S9	C10.1	20V FLOOR 2


From	To	Notes
S10	C10.2	GND FLOOR 2

From	To	Notes
S7	C2.5	CAN1H BCU
S7	C10.3	CAN1H FLOOR

From	To	Notes
S8	C2.6	CAN1L BCU
S8	C10.4	CAN1L FLOOR



24-35
3 size 16
& 32 size 20
N,E



24-47
5 size16
& 42 size 20
E

REAR BULKHEAD CONNECTOR

C1 [1]

11.78 in

From	To	Conductor	Color	Size	Notes
C1.1	C3.2	W37.Unspecified		22 AWG	CAN1H
C1.2	C3.3				CAN1L
C1.3	C3.7				CAN1DRAIN
C1.4	C3.8	W38.Unspecified		22 AWG	CAN2H
C1.5	C3.9				CAN2L
C1.6	C3.10				CAN2DRAIN
C1.7	C3.1	W1.Red		14 AWG	20V PENTHOUSE 1
C1.8	C6.1	W31.White-Black-Blue		22 AWG	SHUTDOWN_FIREWALLOUT_ESTOP
C1.9	C2.12	W34.White-Black-Blue		22 AWG	SHUTDOWN_BCU_FIREWALLIN
C1.10	C2.18	W11.White-Blue		22 AWG	BSPD_CURRENT
C1.11	C3.4	W2.Black		14 AWG	GND PENTHOUSE 1
C1.12	C2.16	W9.White-Blue		22 AWG	BMS_OK
C1.13	C2.17	W10.White-Blue		22 AWG	IMD_OK
C1.14	C3.5	W3.Red		14 AWG	20V PENTHOUSE 2
C1.15	C3.17	W12.White-Blue		22 AWG	SDC_RESET
C1.16	C4.2	W14.White-Red		22 AWG	TSSI_GREEN
C1.17	C4.3	W15.White-Red		22 AWG	TSSI_RED
C1.18	C5.1	W17.White-Red		22 AWG	BRAKE_LIGHT
C1.25	C3.6	W4.Black		20 AWG	GND PENTHOUSE 2

(Fake Bend Point)

11.81 in

S5 [15]
S6 [15]

11.75 in

S1 [15]
S2 [15]
S7 [15]
S8 [15]
S10 [15]
S9 [15]

BRAKE LIGHT

From	To	Conductor	Color	Size	Notes
C5.1	C1.18	W17.White-Red		22 AWG	BRAKE_LIGHT
C5.2	C3.19	W18.Black		22 AWG	GND_BRAKE

C5 [13]

11.81 in

13.2 in

9.74 in

ACU/BCU Connector

C2 [2]

From	To	Conductor	Color	Size	Notes
C2.1	C3.13	W5.Red		20 AWG	20V BCU
C2.2	C3.14	W6.Black		20 AWG	GND BCU
C2.3	C3.15	W7.Yellow		20 AWG	20V BCU 1
C2.4	C3.16	W8.Yellow		20 AWG	20V BCU 2
C2.5	S7	W41.Unspecified		22 AWG	CAN1H BCU
C2.6	S8				CAN1L BCU
C2.8	S1	W39.Unspecified		22 AWG	CAN2H BCU
C2.9	S2				CAN2L BCU
C2.10	C3.12	W33.White-Black-Blue		22 AWG	SHUTDOWN_BCU_ATTIC
C2.12	C1.9	W34.White-Black-Blue		22 AWG	SHUTDOWN_BCU_FIREWALLIN
C2.13	C3.25	W27.White		22 AWG	BSPD_TEST+
C2.15	C3.26	W28.White		22 AWG	BSPD_TEST-
C2.16	C1.12	W9.White-Blue		22 AWG	BMS_OK
C2.17	C1.13	W10.White-Blue		22 AWG	IMD_OK
C2.18	C1.10	W11.White-Blue		22 AWG	BSPD_CURRENT
C2.19	C4.1	W13.White-Red		22 AWG	RTM_LIGHT

From	To
S1	C2.8
S1	C8.3

CAN2H FLOOR

From	To
S2	C2.9
S2	C8.4

CAN2L FLOOR

14.96 in

14.96 in

C10 [10]

dual floor connectors to CAN1 & CAN2. Debug good here

From	To	Notes
C10.1	S9	20V FLOOR 2
C10.2	S10	GND FLOOR 2
C10.3	S7	CAN1H FLOOR
C10.4	S8	CAN1L FLOOR

C8 [10]

From	To	Conductor	Color	Size	Notes
C8.1	C3.20	W19.Red		22 AWG	20V FLOOR
C8.2	C3.21	W20.Black		22 AWG	GND FLOOR
C8.3	S1	W42.Unspecified		22 AWG	CAN2H FLOOR
C8.4	S2				CAN2L FLOOR

5.71 in

C7 [10]

REAR SUSPENSION NODE

From	To	Conductor	Color	Size	Notes
C7.1	C3.22	W21.Red		22 AWG	20V SENS
C7.2	C3.23	W22.Black		22 AWG	GND SENS
C7.3	S5	W40.Unspecified		22 AWG	CAN2H SENS
C7.4	S6				CAN2L SENS

GR26 Rear Wire Harness Diagram

Schemed poorly by Vin Shin

wires!
January 2026

Gaucho Racing's "next generation" wire harness

Revision Notes: adjusted bend points to fit ANSI E

Other notes: lets build a car!

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

rapidHARNESS

Rev.	Date	Author	Description

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

rapidHARNESS

Flag	Quantity	Note

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

rapidHARNESS

Id	Type	Manufacturer	Part Number	Description	Quantity	Usage
1	Connector	TE Connectivity / DEUTSCH	HDP24-24-35PE	Conn Circular PIN 35 POS Crimp ST Jam Nut 35 Terminal 1 Port Automotive Bulk	1	C1
2	Connector	TE Connectivity / DEUTSCH	HDP26-24-35SE	35 Position Circular Connector Plug Housing Free Hanging (In-Line) Coupling Nu	1	C2
3	Connector	TE Connectivity / DEUTSCH	HDP26-24-47SE-L017	Circular Connector, Circular Industrial, HDP20 Series, Straight Plug, 47 Contacts	1	C3
4	Wire		M22759/32-14-2	M22759 14 AWG Red Tin Plated Copper wire	52.5 in	W1, W3
5	Wire		M22759/32-14-0	M22759 14 AWG Black Tin Plated Copper wire	26.25 in	W2
6	Wire		M22759/32-20-0	M22759 20 AWG Black Tin Plated Copper wire	50.46 in	W4, W6
7	Wire		M22759/32-20-2	M22759 20 AWG Red Tin Plated Copper wire	24.21 in	W5
8	Wire		M22759/32-20-4	M22759 20 AWG Yellow Tin Plated Copper wire	48.42 in	W7, W8
9	Wire		M22759/32-22-96	M22759 22 AWG White with Blue stripes Tin Plated Copper wire	90.81 in	W9, W10, W11, W12
10	Connector	TE Connectivity / DEUTSCH	DTM06-4S	Combination Line Connector, 4 Contact(s), Female, Crimp Terminal, Plug	4	C4, C7, C8, C10
11	Wire		M22759/32-22-92	M22759 22 AWG White with Red stripes Tin Plated Copper wire	185.78 in	W13, W14, W15, W17, W25
12	Wire		M22759/32-22-0	M22759 22 AWG Black Tin Plated Copper wire	161.16 in	W16, W18, W20, W22, W24, W36
13	Connector	TE Connectivity / DEUTSCH	DTM06-2S	Automotive Connector Housing, IP68, DTM Series, Plug, 2 Ways, AMP DTM Series Socket Contacts	2	C5, C6
15	Splice	Molex	19207-0001	VersaKrimp Terminal Inline Individual Openings (Parallel) Crimp Connector 18-22 AWG	8	S1, S2, S5, S6, S7, S8, S9, S10
16	Wire		M22759/32-22-2	M22759 22 AWG Red Tin Plated Copper wire	76.44 in	W19, W21, W23, W35
17	Wire		M22759/32-22-97	M22759 22 AWG White with Violet stripes Tin Plated Copper wire	0 in	W26
18	Wire		M22759/32-22-9	M22759 22 AWG White Tin Plated Copper wire	48.42 in	W27, W28
19	Wire		M22759/32-22-3	M22759 22 AWG Orange Tin Plated Copper wire	0 in	W29, W30
20	Wire		M22759/32-22-906	M22759 22 AWG White with Black-Blue stripes Tin Plated Copper wire	113.82 in	W31, W32, W33, W34
21	Wire	Judd Wire	M22759/32-22-9	Hook-up Wire 22AWG 1.14mm Tinned Copper 600VAC	131.23 in	W37, W38, W39, W40, W41, W42, W43

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

rapidHARNESS

From	To	Conductor	Conductor PN	Twisted With	Size	Length	From Contact PN	Notes
C1.7	C3.1	W1.Red	M22759/32-14-2		14 AWG	26.25 in		20V PENTHOUSE 1
C1.8	C6.1	W31.White-Black-Blue	M22759/32-22-906		22 AWG	830.57 mm		SHUTDOWN_FIREWALLOUT_ESTOP
C1.10	C2.18	W11.White-Blue	M22759/32-22-96		22 AWG	21.52 in		BSPD_CURRENT
C1.11	C3.4	W2.Black	M22759/32-14-0		14 AWG	26.25 in		GND PENTHOUSE 1
C1.12	C2.16	W9.White-Blue	M22759/32-22-96		22 AWG	21.52 in		BMS_OK
C1.13	C2.17	W10.White-Blue	M22759/32-22-96		22 AWG	21.52 in		IMD_OK
C1.14	C3.5	W3.Red	M22759/32-14-2		14 AWG	26.25 in		20V PENTHOUSE 2
C1.15	C3.17	W12.White-Blue	M22759/32-22-96		22 AWG	26.25 in		SDC_RESET
C1.16	C4.2	W14.White-Red	M22759/32-22-92		22 AWG	42.49 in		TSSI_GREEN
C1.17	C4.3	W15.White-Red	M22759/32-22-92		22 AWG	42.49 in		TSSI_RED
C1.18	C5.1	W17.White-Red	M22759/32-22-92		22 AWG	60.35 in		BRAKE_LIGHT
C1.25	C3.6	W4.Black	M22759/32-20-0		20 AWG	26.25 in		GND PENTHOUSE 2
C2.10	C3.12	W33.White-Black-Blue	M22759/32-22-906		22 AWG	24.21 in		SHUTDOWN_BCU_ATTIC
C2.12	C1.9	W34.White-Black-Blue	M22759/32-22-906		22 AWG	21.52 in		SHUTDOWN_BCU_FIREWALLIN
C2.19	C4.1	W13.White-Red	M22759/32-22-92		22 AWG	40.45 in		RTM_LIGHT
C3.2	C1.1	W37.Unspecified	M22759/32-22-9		22 AWG	26.25 in		CAN1H
C3.3	C1.2					26.25 in		CAN1L
C3.7	C1.3					26.25 in		CAN1DRAIN
C3.8	C1.4	W38.Unspecified	M22759/32-22-9		22 AWG	26.25 in		CAN2H
C3.9	C1.5					26.25 in		CAN2L
C3.10	C1.6					26.25 in		CAN2DRAIN
C3.13	C2.1	W5.Red	M22759/32-20-2		20 AWG	24.21 in		20V BCU
C3.14	C2.2	W6.Black	M22759/32-20-0		20 AWG	24.21 in		GND BCU
C3.15	C2.3	W7.Yellow	M22759/32-20-4		20 AWG	24.21 in		20V BCU 1
C3.16	C2.4	W8.Yellow	M22759/32-20-4		20 AWG	24.21 in		20V BCU 2
C3.18	C4.4	W16.Black	M22759/32-22-0		22 AWG	45.18 in		GND TSSI RTM
C3.19	C5.2	W18.Black	M22759/32-22-0		22 AWG	39.54 in		GND_BRAKE
C3.20	C8.1	W19.Red	M22759/32-22-2		22 AWG	29.43 in		20V FLOOR
C3.21	C8.2	W20.Black	M22759/32-22-0		22 AWG	29.43 in		GND FLOOR
C3.22	C7.1	W21.Red	M22759/32-22-2		22 AWG	32.05 in		20V SENS
C3.23	C7.2	W22.Black	M22759/32-22-0		22 AWG	32.05 in		GND SENS
C3.25	C2.13	W27.White	M22759/32-22-9		22 AWG	24.21 in		BSPD_TEST+
C3.26	C2.15	W28.White	M22759/32-22-9		22 AWG	24.21 in		BSPD_TEST-
C6.2	C3.11	W32.White-Black-Blue	M22759/32-22-906		22 AWG	35.39 in		SHUTDOWN_SOURCE_ESTOP
S1	C2.8	W39.Unspecified	M22759/32-22-9		22 AWG	9.74 in		CAN2H BCU
S1	C8.3	W42.Unspecified	M22759/32-22-9		22 AWG	14.96 in		CAN2H FLOOR
S2	C2.9					9.74 in		CAN2L BCU
S2	C8.4					14.96 in		CAN2L FLOOR
S5	C7.3	W40.Unspecified	M22759/32-22-9		22 AWG	29.33 in		CAN2H SENS
S6	C7.4					29.33 in		CAN2L SENS
S7	C2.5	W41.Unspecified	M22759/32-22-9		22 AWG	9.74 in		CAN1H BCU

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

From	To	Conductor	Conductor PN	Twisted With	Size	Length	From Contact PN	Notes
S7	C10.3	W43.Unspecified	M22759/32-22-9		22 AWG	14.96 in		CAN1H FLOOR
S8	C2.6					9.74 in		CAN1L BCU
S8	C10.4					14.96 in		CAN1L FLOOR
S9	C10.1	W35.Red	M22759/32-22-2		22 AWG	14.96 in		20V FLOOR 2
S10	C10.2	W36.Black	M22759/32-22-0		22 AWG	14.96 in		GND FLOOR 2

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

rapidHARNESS

#	Type	Reference Designator	Manufacturer	Part Number	Color	Size	From Strip	To Strip	Length	Twisted With	Notes
1	Wire	W1		M22759/32-14-2	Red	14 AWG			26.25 in		20V PENTHOUSE 1
2	Wire	W2		M22759/32-14-0	Black	14 AWG			26.25 in		GND PENTHOUSE 1
3	Wire	W3		M22759/32-14-2	Red	14 AWG			26.25 in		20V PENTHOUSE 2
4	Wire	W4		M22759/32-20-0	Black	20 AWG			26.25 in		GND PENTHOUSE 2
5	Wire	W5		M22759/32-20-2	Red	20 AWG			24.21 in		20V BCU
6	Wire	W6		M22759/32-20-0	Black	20 AWG			24.21 in		GND BCU
7	Wire	W7		M22759/32-20-4	Yellow	20 AWG			24.21 in		20V BCU 1
8	Wire	W8		M22759/32-20-4	Yellow	20 AWG			24.21 in		20V BCU 2
9	Wire	W9		M22759/32-22-96	White-Blue	22 AWG			21.52 in		BMS_OK
10	Wire	W10		M22759/32-22-96	White-Blue	22 AWG			21.52 in		IMD_OK
11	Wire	W11		M22759/32-22-96	White-Blue	22 AWG			21.52 in		BSPD_CURRENT
12	Wire	W12		M22759/32-22-96	White-Blue	22 AWG			26.25 in		SDC_RESET
13	Wire	W13		M22759/32-22-92	White-Red	22 AWG			40.45 in		RTM_LIGHT
14	Wire	W14		M22759/32-22-92	White-Red	22 AWG			42.49 in		TSSI_GREEN
15	Wire	W15		M22759/32-22-92	White-Red	22 AWG			42.49 in		TSSI_RED
16	Wire	W16		M22759/32-22-0	Black	22 AWG			45.18 in		GND TSSI RTM
17	Wire	W17		M22759/32-22-92	White-Red	22 AWG			60.35 in		BRAKE_LIGHT
18	Wire	W18		M22759/32-22-0	Black	22 AWG			39.54 in		GND_BRAKE
19	Wire	W19		M22759/32-22-2	Red	22 AWG			29.43 in		20V FLOOR
20	Wire	W20		M22759/32-22-0	Black	22 AWG			29.43 in		GND FLOOR
21	Wire	W21		M22759/32-22-2	Red	22 AWG			32.05 in		20V SENS
22	Wire	W22		M22759/32-22-0	Black	22 AWG			32.05 in		GND SENS
23	Wire	W27		M22759/32-22-9	White	22 AWG			24.21 in		BSPD_TEST+
24	Wire	W28		M22759/32-22-9	White	22 AWG			24.21 in		BSPD_TEST-
25	Wire	W31		M22759/32-22-906	White-Black-Blue	22 AWG			830.57 mm		SHUTDOWN_FIREWALLOUT_ESTOP
26	Wire	W32		M22759/32-22-906	White-Black-Blue	22 AWG			35.39 in		SHUTDOWN_SOURCE_ESTOP
27	Wire	W33		M22759/32-22-906	White-Black-Blue	22 AWG			24.21 in		SHUTDOWN_BCU_ATTIC
28	Wire	W34		M22759/32-22-906	White-Black-Blue	22 AWG			21.52 in		SHUTDOWN_BCU_FIREWALLIN
29	Wire	W35		M22759/32-22-2	Red	22 AWG			14.96 in		20V FLOOR 2
30	Wire	W36		M22759/32-22-0	Black	22 AWG			14.96 in		GND FLOOR 2
31	Wire	W37	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			26.25 in		CAN1H
32	Wire	W38	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			26.25 in		CAN2H
33	Wire	W39	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			9.74 in		CAN2H BCU
34	Wire	W40	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			29.33 in		CAN2H SENS
35	Wire	W41	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			9.74 in		CAN1H BCU
36	Wire	W42	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			14.96 in		CAN2H FLOOR
37	Wire	W43	Judd Wire	M22759/32-22-9	Unspecified	22 AWG			14.96 in		CAN1H FLOOR
38		C3.3 - C1.2							26.25 in		CAN1L
39		C3.7 - C1.3							26.25 in		CAN1DRAIN
40		C3.9 - C1.5							26.25 in		CAN2L
41		C3.10 - C1.6							26.25 in		CAN2DRAIN

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

rapidHARNESS

#	Type	Reference Designator	Manufacturer	Part Number	Color	Size	From Strip	To Strip	Length	Twisted With	Notes
42		S2 - C2.9							9.74 in		CAN2L BCU
43		S2 - C8.4							14.96 in		CAN2L FLOOR
44		S6 - C7.4							29.33 in		CAN2L SENS
45		S8 - C2.6							9.74 in		CAN1L BCU
46		S8 - C10.4							14.96 in		CAN1L FLOOR

Title:	----
Part Number:	LV26.HARNESS2
Description:	The Rear Master Harness preceding Firewall bulkhead

#	Manufacturer	Part Number	Description	Label Text