

Exp No: 15

EMBEDDED C PROGRAM TO CONVERT THE HEXADECIMAL DATA 0XCFH TO DECIMAL AND DISPLAY THE DIGITS ON PORTS P0, P1 AND P2

PROGRAM:

```
#include <reg51.h>

void main(void)
{
    unsigned char hexa = 0x08;
    unsigned char hundreds, tens, units;
```

```
    ACC = hexa;
```

```
    B = 10;
```

```
    ACC = ACC / B;
```

```
    units = B;
```

```
    B = 10;
```

```
    ACC = ACC / B;
```

```
    tens = B;
```

```
    hundreds = ACC;
```

```
    P0 = units;
```

```
    P1 = tens;
```

```
    P2 = hundreds;
```

```
    while(1);
```

```
}
```

OUTPUT:

Parallel Port 0

Port 0

P0: 0x08 7 Bits 0

Pins: 0x08

Parallel Port 1

Port 1

P1: 0x00 7 Bits 0

Pins: 0x00

Parallel Port 2

Port 2

P2: 0x00 7 Bits 0

Pins: 0x00

Call Stack + Locals		
Name	Location/Value	Type
MAIN	C:0x0800	
hexa	0x00	uchar
hundreds	0x00	uchar
tens	0x00	uchar
units	0x00	uchar