

In [4]:

```
import pandas as pd
from sklearn.metrics import mean_squared_error
```

In [38]:

```
df = pd.read_csv('Real estate.csv')
```

In [40]:

```
df = df.drop(df.columns[0] ,axis = 1)
```

In [42]:

```
df
x = df.iloc[:, :6]
y = df.iloc[:, -1]
```

In [43]:

x

Out[43]:

	<b>X1 transaction date</b>	<b>X2 house age</b>	<b>X3 distance to the nearest MRT station</b>	<b>X4 number of convenience stores</b>	<b>X5 latitude</b>	<b>X6 longitude</b>
<b>0</b>	2012.917	32.0	84.87882	10	24.98298	121.54024
<b>1</b>	2012.917	19.5	306.59470	9	24.98034	121.53951
<b>2</b>	2013.583	13.3	561.98450	5	24.98746	121.54391
<b>3</b>	2013.500	13.3	561.98450	5	24.98746	121.54391
<b>4</b>	2012.833	5.0	390.56840	5	24.97937	121.54245
<b>...</b>	...	...	...	...	...	...
<b>409</b>	2013.000	13.7	4082.01500	0	24.94155	121.50381
<b>410</b>	2012.667	5.6	90.45606	9	24.97433	121.54310
<b>411</b>	2013.250	18.8	390.96960	7	24.97923	121.53986
<b>412</b>	2013.000	8.1	104.81010	5	24.96674	121.54067
<b>413</b>	2013.500	6.5	90.45606	9	24.97433	121.54310

414 rows × 6 columns

In [44]:

y

Out[44]:

0 37.9  
1 42.2  
2 47.3  
3 54.8  
4 43.1  
...  
409 15.4  
410 50.0  
411 40.6  
412 52.5  
413 63.9

Name: Y house price of unit area, Length: 414, dtype: float64

In [33]:

x

Out[33]:

	506	13	Unnamed: 2	Unnamed: 3	Unnamed: 4	Unnamed: 5	Unnamed: 6	Unnamed: 7	Unnamed: 8	Unnamed: 9	Unnamed: 10
1	0.00632	18	2.31	0	0.538	6.575	65.2	4.09	1	296	15.3
2	0.02731	0	7.07	0	0.469	6.421	78.9	4.9671	2	242	17.4
3	0.02729	0	7.07	0	0.469	7.185	61.1	4.9671	2	242	17.4
4	0.03237	0	2.18	0	0.458	6.998	45.8	6.0622	3	222	18.5
5	0.06905	0	2.18	0	0.458	7.147	54.2	6.0622	3	222	18.5
...	...	...	...	...	...	...	...	...	...	...	...
502	0.06263	0	11.93	0	0.573	6.593	69.1	2.4786	1	273	21.0
503	0.04527	0	11.93	0	0.573	6.12	76.7	2.2875	1	273	21.0
504	0.06076	0	11.93	0	0.573	6.976	91	2.1675	1	273	21.0
505	0.10959	0	11.93	0	0.573	6.794	89.3	2.3889	1	273	21.0

	506	13	Unnamed: 2	Unnamed: 3	Unnamed: 4	Unnamed: 5	Unnamed: 6	Unnamed: 7	Unnamed: 8	Unnamed: 9	Unnamed: 10
506	0.04741	0	11.93	0	0.573	6.03	80.8	2.505	1	273	21

506 rows × 13 columns

In [36]:

y

Out[36]:

```

1      24
2     21.6
3     34.7
4     33.4
5     36.2
...
502    22.4
503    20.6
504    23.9
505     22
506    11.9
Name: Unnamed: 13, Length: 506, dtype: object

```

In [45]:

```

import math
n = len(df)
maxk = int(math.sqrt(len(df)))

```

In [47]:

```

mse_values = []

```

In [48]:

```

from sklearn.model_selection import train_test_split
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size = 0.30,random_state = 102)
from sklearn.neighbors import KNeighborsRegressor
for i in range(1,maxk):
    model = KNeighborsRegressor(n_neighbors=i)
    model.fit(x_train,y_train)
    predicted = model.predict(x_test)
    mse_error = mean_squared_error(y_test,predicted)
    mse_values.append(mse_error)

```

In [49]:

```
print(mse_values)

[62.46855999999999, 49.58268, 52.730755555555554, 58.64525999999999, 63.3356864,
68.67109333333332, 70.36192489795918, 70.31558500000001, 69.93693728395064,
69.58304159999999, 68.62950280991735, 68.13115833333335, 68.3538901775148,
69.01559877551021, 69.6200792888889, 69.24840687499999, 68.6647626297578,
68.6024103703704, 67.9558129639889]
```

In [53]:

```
import numpy as np
elbow = 0;
inds = np.argsort(mse_values)
for i in inds:
    diff1 = mse_values[i-1] - mse_values[i]
    diff2 = mse_values[i] - mse_values[i+1]
    elbow = i
    if(diff1>0 and diff2<0):
        break
elbow = elbow + 1;
```

In [54]:

```
elbow
```

Out[54]:

```
2
```

In [56]:

```
rknn = KNeighborsRegressor(n_neighbors = elbow)
rknn.fit(x_train,y_train)
```

Out[56]:

```
KNeighborsRegressor(n_neighbors=2)
```

**In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.  
On GitHub, the HTML representation is unable to render, please try loading this page with  
nbviewer.org.**

KNeighborsRegressor

```
KNeighborsRegressor(n_neighbors=2)
```

In [58]:

```
k = np.arange(1,maxk)
```

In [60]:


```
import matplotlib.pyplot as plt
```

In [63]:

```
plt.xlabel("k")  
plt.ylabel("mse")  
plt.plot(k,mse_values)  
plt.plot(elbow,mse_values[elbow-1], 'rx')  
plt.annotate("elbow point" , (elbow,mse_values[elbow-1]))
```

Out[63]:

```
Text(2, 49.58268, 'elbow point')
```



In [ ]: