

UNIT – III**FUNCTIONS, ARRAYS**

Fruitful functions: return values, parameters, local and global scope, function composition, recursion; Strings: string slices, immutability, string functions and methods, string module; Python arrays, Access the Elements of an Array, array methods.

Functions, Arrays:**Fruitful functions:**

We write functions that return values, which we will call fruitful functions. We have seen the return statement before, but in a fruitful function the return statement includes a return value. This statement means: "Return immediately from this function and use the following expression as a return value."

(or)

Any function that returns a value is called Fruitful function. A Function that does not return a value is called a void function

Return values:

The Keyword return is used to return back the value to the called function.

returns the area of a circle with the given radius:

```
def area(radius):  
    temp = 3.14 * radius**2  
    return temp  
print(area(4))
```

(or)

```
def area(radius):  
    return 3.14 * radius**2  
print(area(2))
```

Sometimes it is useful to have multiple return statements, one in each branch of a conditional:

```
def absolute_value(x):  
    if x < 0:
```

```
    return -x
else:
    return x
```

Since these return statements are in an alternative conditional, only one will be executed.

As soon as a return statement executes, the function terminates without executing any subsequent statements. Code that appears after a return statement, or any other place the flow of execution can never reach, is called dead code.

In a fruitful function, it is a good idea to ensure that every possible path through the program hits a return statement. For example:

```
def absolute_value(x):
    if x < 0:
        return -x
    if x > 0:
        return x
```

This function is incorrect because if x happens to be 0, both conditions is true, and the function ends without hitting a return statement. If the flow of execution gets to the end of a function, the return value is None, which is not the absolute value of 0.

```
>>> print absolute_value(0)
None
```

By the way, Python provides a built-in function called abs that computes absolute values.

Write a Python function that takes two lists and returns True if they have at least one common member.

```
def common_data(list1, list2):
    for x in list1:
        for y in list2:
            if x == y:
                result = True
                return result
print(common_data([1,2,3,4,5], [1,2,3,4,5]))
print(common_data([1,2,3,4,5], [1,7,8,9,10]))
print(common_data([1,2,3,4,5], [6,7,8,9,10]))
```

Output:

C:\Users\MRCET\AppData\Local\Programs\Python\Python38-32\pyyy\fu1.py

```
True  
True  
None
```

```
#-----
```

```
def area(radius):  
    b = 3.14159 * radius**2  
    return b
```

Parameters:

Parameters are passed during the definition of function while Arguments are passed during the function call.

Example:

#here a and b are parameters

```
def add(a,b): #function definition  
    return a+b
```

```
#12 and 13 are arguments  
#function call  
result=add(12,13)  
print(result)
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/paraarg.py
```

```
25
```

Some examples on functions:

To display vandemataram by using function use no args no return type

```
#function defination  
def display():  
    print("vandemataram")  
print("i am in main")
```

```
#function call  
display()  
print("i am in main")
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py  
i am in main  
vandemataram  
i am in main
```

#Type1 : No parameters and no return type

```
def Fun1() :  
    print("function 1")  
Fun1()
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py  
  
function 1
```

#Type 2: with param with out return type

```
def fun2(a) :  
    print(a)  
fun2("hello")
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py  
  
Hello
```

#Type 3: without param with return type

```
def fun3():  
    return "welcome to python"  
print(fun3())
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py
```

```
welcome to python
```

#Type 4: with param with return type

```
def fun4(a):  
    return a  
print(fun4("python is better then c"))
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py
```

```
python is better then c
```

Local and Global scope:**Local Scope:**

A variable which is defined inside a function is local to that function. It is accessible from the point at which it is defined until the end of the function, and exists for as long as the function is executing

Global Scope:

A variable which is defined in the main body of a file is called a global variable. It will be visible throughout the file, and also inside any file which imports that file.

- The variable defined inside a function can also be made global by using the global statement.

```
def function_name(args):  
    .....  
    global x    #declaring global variable inside a function  
    .....
```

create a global variable

```
x = "global"

def f():
    print("x inside :", x)

f()
print("x outside:", x)
```

Output:

C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py

```
x inside : global
x outside: global
```

create a local variable

```
def f1():
    y = "local"
    print(y)

f1()
```

Output:

```
local
```

- If we try to access the local variable outside the scope for example,

```
def f2():
    y = "local"

f2()
print(y)
```

Then when we try to run it shows an error,

Traceback (most recent call last):

File "C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py", line 6, in <module>

```
print(y)
NameError: name 'y' is not defined
```

The output shows an error, because we are trying to access a local variable y in a global scope whereas the local variable only works inside f2() or local scope.

use local and global variables in same code

```
x = "global"

def f3():
    global x
    y = "local"
    x = x * 2
    print(x)
    print(y)
```

```
f3()
```

Output:

```
C:/Users/MRCET/AppData/Local/Programs/Python/Python38-32/pyyy/fu1.py
globalglobal
local
```

- In the above code, we declare x as a global and y as a local variable in the f3(). Then, we use multiplication operator * to modify the global variable x and we print both x and y.
- After calling the f3(), the value of x becomes global global because we used the x * 2 to print two times global. After that, we print the value of local variable y i.e local.

use Global variable and Local variable with same name

```
x = 5

def f4():
    x = 10
    print("local x:", x)

f4()
print("global x:", x)
```