📘 DEVOPS INTERVIEW – 150+

1️⃣ What is DevOps?

Answer:
DevOps is a **culture + practice + set of tools** that brings **Development** and **Operations** teams together to **deliver software faster, safer, and continuously**.

Before DevOps:

- Developers write code
- Operations deploy manually
- If production fails → blame game
- Releases take weeks or months

With DevOps:

- Same team mindset
- Automated build, test, deploy
- Continuous monitoring & feedback
- Releases can happen **multiple times a day**

Real-time example:

When a developer pushes code to Git:

1. Jenkins automatically builds it
2. Tests are executed
3. Docker image is created
4. Kubernetes deploys it

5. Monitoring checks health

👉 **This full automation is DevOps**

2️⃣ Why DevOps is required?

Answer:
DevOps is required to **solve problems of traditional software delivery**.

Traditional problems:

- Slow deployments
- Manual errors
- Poor collaboration
- Late bug detection

DevOps solves by:

- Automating deployments
- Early testing (CI)
- Continuous feedback
- Infrastructure as Code

Interview line (important):

> “DevOps reduces time-to-market while improving reliability.”

3️⃣ What are the core principles of DevOps?

Answer:
DevOps works on **5 main principles**:

1. **Collaboration** – Dev & Ops work together

2. **Automation** – CI/CD, Infra automation
3. **Continuous Improvement** – monitoring & feedback
4. **Customer-centric action** – faster bug fixes
5. **Responsibility ownership** – You build it, you run it

4️⃣ Explain DevOps lifecycle in detail

DevOps Lifecycle Stages:

1. **Plan** – Requirement analysis (Jira)
2. **Code** – Developers write code (Git)
3. **Build** – Compile code (Maven)
4. **Test** – Automated testing (JUnit)
5. **Release** – Versioning
6. **Deploy** – Jenkins + Kubernetes
7. **Operate** – Server management
8. **Monitor** – Prometheus, Grafana

🔁 Continuous feedback loop

5️⃣ What is CI (Continuous Integration)?

Answer:
CI means **automatically integrating code changes multiple times a day**.

What happens in CI?

- Developer pushes code
- Jenkins triggers build

- Unit tests run
- Errors detected early

Benefits:

- Early bug detection
- No “integration hell”
- Stable codebase

---

6 What is CD (Continuous Delivery vs Deployment)?

Continuous Delivery:

- Code is **ready for production**
- Manual approval needed

Continuous Deployment:

- Code **automatically goes to production**
- No manual intervention

Example:

Banking apps → Delivery
E-commerce apps → Deployment

---

7 Difference between DevOps & Agile (Detailed)

Agile	DevOps
Focus on development	Focus on deployment
Sprint based	Continuous

Ends at release Ends at monitoring

👉 Agile + DevOps = Full SDLC automation

8️⃣ What is Infrastructure as Code (IaC)?

Answer:
Managing infrastructure using **code instead of manual configuration**.

Tools:

- Terraform
- CloudFormation
- ARM Templates

Benefits:

- Version control
- Repeatable infra
- No human error

Example:

```
resource "aws_instance" "server" {
  ami = "ami-123"
  instance_type = "t2.micro"
}
```

9️⃣ What are DevOps tools categories?

1. Version Control – Git
2. CI/CD – Jenkins
3. Containers – Docker

4. Orchestration – Kubernetes
5. IaC – Terraform
6. Monitoring – Prometheus

🔟 What is Version Control?

Answer:
System that tracks **who changed what, when, and why**.

Benefits:

- Rollback
- Collaboration
- Audit trail

1️⃣1️⃣ Git vs GitHub

Git	GitHub
Tool	Platform
Local	Cloud
Version control	Hosting

1️⃣2️⃣ What is Automation in DevOps?

Answer:
Replacing **manual repetitive tasks** with scripts/tools.

Automated tasks:

- Build
- Test

- Deploy
- Server provisioning

1️⃣3️⃣ What is Monitoring in DevOps?

Answer:
Continuous observation of:

- CPU
- Memory
- Disk
- Application health

Tools:

- Prometheus
- Grafana
- CloudWatch

1️⃣4️⃣ What is Blue-Green Deployment?

Answer:
Two identical environments:

- Blue → Old version
- Green → New version

Switch traffic after validation → **Zero downtime**

1️⃣5️⃣ What is Canary Deployment?

Answer:
Deploy new version to **small % of users first**.

If stable → rollout to all users.

---

16 What is Rollback?

Answer:
Reverting to **previous stable version** when deployment fails.

---

17 What is SRE vs DevOps?

DevOps = Culture
SRE = Engineering implementation using SLAs/SLOs

---

18 What is SLA, SLO, SLI?

- **SLA** – Contract promise
- **SLO** – Target reliability
- **SLI** – Actual measurement

---

19 What is Mean Time To Recovery (MTTR)?

Time taken to recover from failure.

Lower MTTR = Better DevOps maturity

---

20 What is Configuration Management?

Managing system state using tools like:

- Ansible

- Puppet
- Chef

2️⃣1️⃣ DevOps Engineer daily responsibilities?

- CI/CD pipeline
- Cloud infra
- Automation scripts
- Monitoring
- Incident handling

2️⃣2️⃣ What is Immutable Infrastructure?

Servers are **replaced, not modified**.

2️⃣3️⃣ What is Shift-Left testing?

Testing early in development.

2️⃣4️⃣ What is DevSecOps?

Security integrated into DevOps pipeline.

2️⃣5️⃣ Why DevOps engineer is important?

Because modern applications need:

- Speed

- Reliability
- Automation
- Scalability

2️⃣6️⃣ What is Linux? (Deep Explanation)

Answer:
Linux is an **open-source, multi-user, multi-tasking operating system** widely used in **servers, cloud, containers, and DevOps environments**.

Why Linux is preferred in DevOps?

- Stable and secure
- Command-line automation
- Lightweight
- Free & open source
- Strong community support

Real-time example:

AWS EC2 instances mostly run **Amazon Linux / Ubuntu / RHEL**.

2️⃣7️⃣ Difference between Linux and Unix?

Linux	Unix
Open source	Mostly paid
Community supported	Vendor supported
Flexible	Less flexible
Widely used in cloud	Limited

Interview tip:

> “Linux is Unix-like but open-source.”

2️⃣8️⃣ What is Kernel?

Answer:
Kernel is the **core of Linux OS**.

Kernel responsibilities:

- Process management
- Memory management
- Hardware communication
- File system control

Types of kernel:

- Monolithic (Linux)
- Microkernel

2️⃣9️⃣ What are Linux distributions?

Answer:
Linux distributions = Kernel + Utilities + Package manager.

Common distros:

- Ubuntu
- RedHat
- CentOS
- Amazon Linux

3️⃣0️⃣ Linux directory structure (VERY IMPORTANT)

Directory	Purpose
`/etc`	Config files
`/var`	Logs & variable data
`/home`	User files
`/root`	Root user
`/bin`	Commands
`/usr`	Software
`/tmp`	Temporary files

3️⃣1️⃣ What is Root user?

Answer:
Root user is **superuser** with **full system access**.

Why root is dangerous?

- One wrong command can delete OS

Best practice:

Use `sudo` instead of root login.

3️⃣2️⃣ What is sudo?

Answer:
`sudo` allows **temporary admin access**.

```
sudo yum install nginx
```

Benefit:

- Security
- Audit trail

3️⃣3️⃣ Difference between su and sudo?

su	sudo
Switch user	Run single command
Requires root password	User password
Less secure	More secure

3️⃣4️⃣ How to check CPU usage?

```
top
htop
```

Production scenario:

If application is slow → check CPU spike.

3️⃣5️⃣ How to check memory usage?

```
free -m
```

Important fields:

- total
- used
- available

3️⃣6️⃣ How to check disk usage?

```
df -h
```

Disk space per directory:

```
du -sh /var/*
```

3️⃣7️⃣ What is a process?

Answer:
A process is a **running program**.

Process states:

- Running
- Sleeping
- Zombie

3️⃣8️⃣ How to list processes?

```
ps -ef
```

3️⃣9️⃣ How to kill a process?

```
kill PID
kill -9 PID
```

Difference:

- `kill` → graceful
- `kill -9` → force

4️⃣0️⃣ What is systemd?

Answer:
`systemd` is **service manager** in modern Linux.

Why important?

- Faster boot
- Dependency handling

4️⃣1️⃣ How to manage services?

```
systemctl start nginx
systemctl stop nginx
systemctl restart nginx
systemctl status nginx
```

4️⃣2️⃣ What is a daemon?

Answer:
Background service (nginx, sshd).

4️⃣3️⃣ What is Cron Job?

Answer:
Cron is used to **schedule tasks automatically**.

Example:

Backup script daily at 2 AM.

4️⃣4️⃣ Cron syntax (IMPORTANT)

```
* * * * * command
```

Field	Meaning

1	Minute
2	Hour
3	Day
4	Month
5	Weekday

---

45 Run cron every 2 minutes?

```
*/2 * * * * command
```

---

46 What is log file?

Answer:
Logs record system/application activity.

Common logs:

- `/var/log/messages`
- `/var/log/secure`
- `/var/log/syslog`

---

47 What is swap memory?

Answer:
Swap is **disk space used as RAM backup**.

When used?

When RAM is full.

---

48 What is inode?

Answer:
Inode stores **file metadata**, not content.

Includes:

- Size
- Permissions
- Owner

4️⃣9️⃣ Difference between soft link and hard link?

Soft Link	Hard Link
Pointer	Same inode
Can cross FS	Same FS
Breaks if file deleted	Still exists

5️⃣0️⃣ What is SELinux?

Answer:
Security layer that **restricts access**.

Modes:

- Enforcing
- Permissive
- Disabled

5️⃣1️⃣ What is Git? (Deep Explanation)

Answer:
Git is a **distributed version control system** used to **track changes in source code**, collaborate with teams, and maintain history.

Why Git is critical for DevOps?

- CI/CD pipelines depend on Git
- Every commit can trigger automation
- Rollback and audit are easy

Real-world example:

Developer pushes code → Jenkins pipeline starts automatically.

5️⃣2️⃣ Centralized vs Distributed Version Control

Centralized (SVN)	Distributed (Git)
Single server	Every user has full repo
Offline work not possible	Offline work possible
Slower	Faster

5️⃣3️⃣ Git Architecture (IMPORTANT)

Git has **3 main areas**:

1. **Working Directory** – where you edit files
2. **Staging Area (Index)** – selected changes
3. **Repository** – committed history

```
Working → Staging → Repository
```

5️⃣4️⃣ What is a Repository?

Answer:
A repository is a **storage area for project files and Git history**.

- Local repo → on your machine

- Remote repo → GitHub/GitLab

5️⃣5️⃣ Git Workflow (End-to-End)

1. `git clone`
2. Modify files
3. `git status`
4. `git add`
5. `git commit`
6. `git push`

5️⃣6️⃣ What is git clone?

Answer:
Downloads a remote repository to local machine.

```
git clone https://github.com/user/repo.git
```

5️⃣7️⃣ What is git status?

Answer:
Shows:

- Modified files
- Staged files
- Untracked files

5️⃣8️⃣ Difference between git add and git commit?

git add	git commit
Stage changes	Save changes permanently
Temporary	Permanent

5️⃣9️⃣ What is a Commit?

Answer:
A commit is a **snapshot of code** at a specific time.

Best practice:

- Small commits
- Meaningful messages

6️⃣0️⃣ What is git push?

Answer:
Uploads commits from local repo to remote repo.

6️⃣1️⃣ What is git pull vs git fetch? (INTERVIEW FAVORITE)

git fetch	git pull
Only downloads	Downloads + merges
Safe	Can cause conflict
Review first	Immediate change

Interview tip:

> “I prefer fetch before pull to avoid surprises.”

6️⃣2️⃣ What is a Branch?

Answer:
A branch is an **independent line of development**.

Default branch:

- `main` or `master`

6️⃣3️⃣ Why branches are important?

- Parallel development
- Safe experimentation
- CI pipelines per branch

6️⃣4️⃣ How to create and switch branch?

```
git branch dev
git checkout dev
```

or

```
git checkout -b dev
```

6️⃣5️⃣ What is git merge?

Answer:
Combines changes from one branch into another.

```
git merge dev
```

Merge types:

- Fast-forward
- 3-way merge

6️⃣6️⃣ What is git rebase? (VERY IMPORTANT)

Answer:
Rebase moves commits **on top of another branch**, creating clean history.

```
git rebase main
```

Difference:

- Merge keeps history
- Rebase rewrites history

6️⃣7️⃣ Merge vs Rebase (INTERVIEW TABLE)

Merge	Rebase
Keeps history	Clean history
Extra commit	Linear commits
Safer	Risky for shared branches

👉 **Never rebase public branches**

6️⃣8️⃣ What is a Git Conflict?

Answer:
Occurs when **same file & same lines** are modified in different branches.

Example:

Two developers edit `config.yml` same line.

6️⃣9️⃣ How to resolve Git conflict?

1. Open conflicted file
2. Choose correct changes
3. Remove conflict markers
4. `git add`
5. `git commit`

7️⃣0️⃣ What is git stash?

Answer:
Temporarily saves uncommitted changes.

```
git stash
git stash pop
```

Use case:

Switch branch without committing incomplete work.

7️⃣1️⃣ What is git reset?

Answer:
Moves HEAD pointer backward.

Types:

- `--soft`
- `--mixed`
- `--hard`

```
git reset --hard HEAD~1
```

⚠️ Dangerous if misused.

7️⃣2️⃣ What is git revert?

Answer:
Creates a **new commit** that undoes changes.

Safe for production:

```
git revert commit_id
```

7️⃣3️⃣ Difference between reset and revert?

Reset	Revert
Deletes history	Keeps history
Dangerous	Safe
Local use	Production use

7️⃣4️⃣ What is HEAD in Git?

Answer:
HEAD points to **current branch/commit**.

7️⃣5️⃣ What is git cherry-pick?

Answer:
Apply a **specific commit** from one branch to another.

```
git cherry-pick commit_id
```

7️⃣6️⃣ What is CI/CD? (Deep Explanation)

Answer:
CI/CD is an **automation process** that helps teams **build, test, and deploy software continuously**.

CI (Continuous Integration)

- Developers push code frequently
- Automatic build & test
- Detect bugs early

CD (Continuous Delivery / Deployment)

- Code is always production-ready
- Automated deployment

Real-time flow:

Git push → Jenkins → Build → Test → Deploy

7️⃣7️⃣ Why CI/CD is important in DevOps?

Answer:
CI/CD:

- Reduces manual work
- Improves software quality
- Enables fast releases
- Prevents production failures

7️⃣8️⃣ What is Jenkins?

Answer:
Jenkins is an **open-source CI/CD automation tool** written in Java.

Why Jenkins is popular?

- Plugin ecosystem
- Pipeline as code
- Works with any tech stack

7️⃣9️⃣ Jenkins Architecture (IMPORTANT)

Jenkins Components:

1. **Jenkins Master (Controller)**
    - Schedules jobs
    - Manages UI & plugins
2. **Jenkins Agent (Worker)**
    - Executes builds

Why agents?

- Scalability
- Isolation

8️⃣0️⃣ What is a Jenkins Job?

Answer:
A job is a **task Jenkins executes**.

Types:

- Freestyle

- Pipeline
- Multibranch
- Folder

8️⃣1️⃣ What is Jenkins Pipeline?

Answer:
A pipeline is **CI/CD workflow defined as code** using Groovy.

Benefits:

- Version controlled
- Reusable
- Automated

8️⃣2️⃣ Declarative vs Scripted Pipeline

Declarative	Scripted
Simple syntax	Complex
Easy to read	More control
Recommended	Advanced use

8️⃣3️⃣ What is Jenkinsfile?

Answer:
A `Jenkinsfile` defines **pipeline stages**.

Example:

```
pipeline {
  agent any
  stages {
```

```
    stage('Build') {
      steps {
        sh 'mvn clean install'
      }
    }
  }
}
```

8️⃣4️⃣ Jenkins Pipeline Stages Explained

1. **Build** – Compile code
2. **Test** – Unit/integration tests
3. **Package** – Create artifact
4. **Deploy** – Release application

8️⃣5️⃣ What is Jenkins Agent?

Answer:
Agent is a **machine that runs pipeline steps**.

Agent types:

- Static
- Dynamic (Docker, Kubernetes)

8️⃣6️⃣ Jenkins Master vs Agent

Master	Agent
Controls Jenkins	Executes jobs
Lightweight	Heavy workloads

Scheduling	Actual work

---

87 What is Jenkins Plugin?

Answer:
Plugins extend Jenkins functionality.

Examples:

- Git
- Docker
- Kubernetes
- Blue Ocean

---

88 How does Jenkins integrate with Git?

Answer:
Using:

- Git plugin
- Webhooks

Flow:

Git push → Webhook → Jenkins job triggered

---

89 What is Webhook?

Answer:
Webhook is an **HTTP callback** that triggers Jenkins automatically.

---

90 What are Jenkins Credentials?

Answer:
Secure storage for:

- Passwords
- Tokens
- SSH keys

Best practice:

Never hardcode secrets in pipeline.

9️⃣1️⃣ How to handle secrets in Jenkins?

- Jenkins credentials store
- Environment variables
- Vault integration

9️⃣2️⃣ What is an Artifact?

Answer:
Artifact is the **output of build**.

Examples:

- JAR
- WAR
- Docker image

9️⃣3️⃣ How to archive artifacts in Jenkins?

```
archiveArtifacts artifacts: '**/*.jar'
```

9️⃣4️⃣ What is Blue Ocean?

Answer:
Modern Jenkins UI for pipelines.

9️⃣5️⃣ Jenkins Failure Scenarios (VERY IMPORTANT)

Common failures:

- Build failure
- Test failure
- Dependency failure
- Permission issue

How to debug?

- Check console output
- Verify logs
- Re-run locally

9️⃣6️⃣ How to retry failed stages?

```
retry(3) {
  sh 'mvn test'
}
```

9️⃣7️⃣ What is Jenkins Parameterized Build?

Answer:
Allows dynamic input.

```
parameters {
  string(name: 'ENV', defaultValue: 'dev')
}
```

9️⃣8️⃣ What is Jenkins Shared Library?

Answer:
Reusable pipeline code stored centrally.

Benefit:

- DRY principle
- Standard pipelines

9️⃣9️⃣ Jenkins Security Best Practices

- Role-based access
- Disable anonymous access
- Secure credentials
- Use HTTPS

🔟0️⃣0️⃣ Jenkins Best Practices (INTERVIEW GOLD)

- Pipeline as code
- Minimal plugins
- Separate build agents
- Automated testing
- Version Jenkinsfile

1️⃣0️⃣1️⃣ What is Docker? (Deep Explanation)

Answer:
Docker is a **containerization platform** that packages an application along with its **dependencies, libraries, and configuration** into a single unit called a **container**.

Why Docker is important in DevOps?

- Same app runs everywhere
- Faster deployments
- Lightweight compared to VMs
- Perfect for CI/CD & Kubernetes

Real-world example:

Developer laptop → QA → Production → Same Docker image

1️⃣0️⃣2️⃣ Difference between Virtual Machine and Container (DEEP)

Virtual Machine	Container
Full OS	Shares host kernel
Heavy	Lightweight
Slow startup	Fast startup
High resource usage	Low usage

👉 Docker containers **do not need a guest OS**.

1️⃣0️⃣3️⃣ How Docker Works Internally?

Docker uses Linux features:

- **Namespaces** – isolation
- **Cgroups** – resource limits
- **UnionFS** – layered filesystem

1️⃣0️⃣4️⃣ What is Docker Image?

Answer:
A Docker image is a **read-only template** used to create containers.

Image contains:

- Base OS
- Application
- Dependencies

1️⃣0️⃣5️⃣ What is Docker Container?

Answer:
A container is a **running instance of a Docker image**.

👉 Image = blueprint
👉 Container = running app

1️⃣0️⃣6️⃣ What is Dockerfile? (VERY IMPORTANT)

Answer:
A Dockerfile is a **text file** that contains instructions to build a Docker image.

Example:

```
FROM ubuntu:22.04
RUN apt update && apt install -y nginx
CMD ["nginx", "-g", "daemon off;"]
```

1️⃣0️⃣7️⃣ Dockerfile Instructions Explained

Instruction	Purpose
FROM	Base image
RUN	Execute command
COPY	Copy files
ADD	Copy + extract
CMD	Default command
ENTRYPOINT	Fixed command
EXPOSE	Port
ENV	Environment variable

1️⃣0️⃣8️⃣ CMD vs ENTRYPOINT (INTERVIEW FAVORITE)

CMD	ENTRYPOINT
Can be overridden	Cannot be overridden
Default args	Fixed command

👉 Best practice: Use **ENTRYPOINT + CMD**

1️⃣0️⃣9️⃣ What is Docker Volume?

Answer:
Docker volume is used for **persistent storage**.

Why needed?

Containers are ephemeral.

```
docker volume create data_vol
```

1️⃣1️⃣0️⃣ Types of Docker Storage

1. Volumes (recommended)
2. Bind mounts
3. tmpfs

---

111 What is Docker Networking?

Answer:
Docker networking allows containers to **communicate with each other**.

Network types:

- Bridge (default)
- Host
- None
- Overlay

---

112 Expose vs Publish Port

EXPOSE	-p
Documentation	Maps port
Internal	External access

---

113 What is Docker Compose?

Answer:
Docker Compose is used to **run multi-container applications**.

Example:

App + DB + Cache

1️⃣1️⃣4️⃣ docker-compose.yml Example

```
version: '3'
services:
  web:
    image: nginx
    ports:
      - "80:80"
```

1️⃣1️⃣5️⃣ docker build vs docker run

build	run
Creates image	Runs container
Once	Many times

1️⃣1️⃣6️⃣ docker ps vs docker ps -a

docker ps	docker ps -a
Running containers	All containers

1️⃣1️⃣7️⃣ docker exec

Answer:
Used to access running container.

```
docker exec -it container_id bash
```

1️⃣1️⃣8️⃣ docker logs

Answer:
View container logs.

```
docker logs container_id
```

1️⃣1️⃣9️⃣ What is Docker Registry?

Answer:
Registry stores Docker images.

Examples:

- Docker Hub
- ECR
- GCR

1️⃣2️⃣0️⃣ What is Multi-stage Build?

Answer:
Build image in **multiple stages** to reduce size.

Benefit:

- Smaller image
- More secure

1️⃣2️⃣1️⃣ Docker Image Optimization Best Practices

- Use small base images
- Combine RUN commands
- Remove cache
- Use .dockerignore

1️⃣2️⃣2️⃣ Docker Security Best Practices

- Non-root user
- Scan images
- Minimal images
- Secrets management

1️⃣2️⃣3️⃣ What is Docker Swarm?

Answer:
Native Docker orchestration tool.

👉 Mostly replaced by Kubernetes.

1️⃣2️⃣4️⃣ Docker vs Kubernetes

Docker	Kubernetes
Container runtime	Orchestrator
Single host	Multi-node
Simple	Advanced

1️⃣2️⃣5️⃣ Common Docker Interview Traps

❌ Running containers as root
❌ Huge image sizes
❌ Hardcoding secrets
❌ No health checks

1️⃣2️⃣6️⃣ What is Kubernetes? (Deep Explanation)

Answer:
Kubernetes (K8s) is an **open-source container orchestration platform** that automates:

- Deployment
- Scaling
- Load balancing
- Self-healing
- Rollouts & rollbacks

👉 Docker runs containers
👉 Kubernetes **manages containers at scale**

1️⃣2️⃣7️⃣ Why Kubernetes is needed?

Without Kubernetes:

- Manual container management
- No auto-healing
- No scaling
- Downtime during deployment

With Kubernetes:

- Pods restart automatically
- Traffic is load-balanced
- Zero-downtime deployments
- Auto-scaling

1️⃣2️⃣8️⃣ Kubernetes Architecture (VERY IMPORTANT)

Main Components:

Control Plane (Master):

1. **API Server**
2. **Scheduler**
3. **Controller Manager**
4. **ETCD**

Worker Node:

1. **Kubelet**
2. **Container Runtime**
3. **Kube-proxy**

1️⃣2️⃣9️⃣ What is API Server?

Answer:
API Server is the **entry point** to Kubernetes.

- All `kubectl` commands go through it
- Communicates with ETCD
- Validates requests

👉 If API server is down → cluster is unusable

1️⃣3️⃣0️⃣ What is ETCD?

Answer:
ETCD is a **key-value database** that stores:

- Cluster state
- Configurations
- Secrets metadata

⚠️ ETCD backup is **CRITICAL**

1️⃣3️⃣1️⃣ What is Scheduler?

Answer:
Scheduler decides **which pod runs on which node** based on:

- Resource availability
- Node labels
- Taints & tolerations

1️⃣3️⃣2️⃣ What is Controller Manager?

Answer:
Ensures **desired state == actual state**.

Example:
If replicas = 3 and 1 pod dies → controller creates new pod.

1️⃣3️⃣3️⃣ What is a Node?

Answer:
A node is a **worker machine** that runs pods.

Each node has:

- Kubelet
- Container runtime
- Kube-proxy

1️⃣3️⃣4️⃣ What is Kubelet?

Answer:
Kubelet is an **agent** running on nodes.

- Talks to API server
- Ensures pods are running

1️⃣3️⃣5️⃣ What is a Pod? (VERY IMPORTANT)

Answer:
Pod is the **smallest deployable unit** in Kubernetes.

- One or more containers
- Shared network & storage

👉 Containers never run directly, always inside a Pod.

1️⃣3️⃣6️⃣ Pod vs Container

Pod	Container
Kubernetes concept	Docker concept
Can have many containers	Single process
Shared resources	Isolated

1️⃣3️⃣7️⃣ What is a Deployment?

Answer:
Deployment manages **replicas and updates** of pods.

Features:

- Rolling updates
- Rollback

- Scaling

1️⃣3️⃣8️⃣ What is ReplicaSet?

Answer:
Ensures **specified number of pods are always running**.

👉 Deployment uses ReplicaSet internally.

1️⃣3️⃣9️⃣ What is a Service?

Answer:
Service exposes pods and provides **stable networking**.

Because pod IPs change.

1️⃣4️⃣0️⃣ Types of Services (INTERVIEW FAVORITE)

Type	Use Case
ClusterIP	Internal access
NodePort	External testing
LoadBalancer	Production
ExternalName	External service

1️⃣4️⃣1️⃣ What is Ingress?

Answer:
Ingress manages **HTTP/HTTPS routing** to services.

Benefits:

- One load balancer
- SSL termination

- Path-based routing

1️⃣4️⃣2️⃣ What is ConfigMap?

Answer:
Stores **non-sensitive configuration data**.

Example:

- App config
- Environment variables

1️⃣4️⃣3️⃣ What is Secret?

Answer:
Stores **sensitive data**:

- Passwords
- Tokens
- Keys

⚠️ Secrets are base64 encoded, not encrypted by default.

1️⃣4️⃣4️⃣ What are Liveness & Readiness Probes?

Liveness Probe:

Checks if app is alive
→ Restarts container

Readiness Probe:

Checks if app can accept traffic
→ Stops traffic temporarily

1️⃣4️⃣5️⃣ What is Rolling Update?

Answer:
Updates pods **gradually** without downtime.

Example:
Old pod → New pod → Traffic switch

1️⃣4️⃣6️⃣ What is HPA (Horizontal Pod Autoscaler)?

Answer:
Automatically scales pods based on:

- CPU
- Memory
- Custom metrics

1️⃣4️⃣7️⃣ What is Namespace?

Answer:
Logical separation inside cluster.

Examples:

- dev
- qa
- prod

1️⃣4️⃣8️⃣ What is DaemonSet?

Answer:
Runs **one pod on every node**.

Use cases:

- Monitoring agents
- Log collectors

1️⃣4️⃣9️⃣ What is StatefulSet?

Answer:
Used for **stateful applications**.

Features:

- Stable network ID
- Persistent storage

Example:
Databases

1️⃣5️⃣0️⃣ Kubernetes Troubleshooting (INTERVIEW GOLD)

Step-by-step:

1. `kubectl get pods`
2. `kubectl describe pod`
3. `kubectl logs`
4. Check events
5. Check node status

1️⃣5️⃣1️⃣ What is Cloud Computing? (Deep Explanation)

Answer:
Cloud computing means **using computing resources (servers, storage, networking) over the internet on-demand** instead of managing physical hardware.

Key benefits:

- Pay-as-you-go
- Scalability
- High availability
- No hardware maintenance

1️⃣5️⃣2️⃣ Types of Cloud Models

Service models:

1. **IaaS** – EC2, VM
2. **PaaS** – Elastic Beanstalk
3. **SaaS** – Gmail

1️⃣5️⃣3️⃣ Public vs Private vs Hybrid Cloud

Type	Description
Public	AWS, Azure
Private	Company owned
Hybrid	Both

1️⃣5️⃣4️⃣ What is AWS?

Answer:
AWS is a **public cloud provider** offering compute, storage, networking, security, and DevOps services.

1️⃣5️⃣5️⃣ What is EC2?

Answer:
EC2 (Elastic Compute Cloud) is a **virtual server** in AWS.

Key concepts:

- Instance type
- AMI
- Security Group
- Key pair

1️⃣5️⃣6️⃣ What is AMI?

Answer:
AMI is a **template** used to launch EC2 instances.

1️⃣5️⃣7️⃣ What is Security Group?

Answer:
A **virtual firewall** controlling inbound & outbound traffic.

👉 Stateful firewall.

1️⃣5️⃣8️⃣ What is VPC?

Answer:
VPC is a **logically isolated virtual network** in AWS.

1️⃣5️⃣9️⃣ Public vs Private Subnet

Public	Private
Has internet gateway	No direct internet
Web servers	DB servers

---

160 What is IAM?

Answer:
IAM manages **users, roles, and permissions** in AWS.

Best practice:

Use **roles instead of users** for EC2.

---

161 What is S3?

Answer:
S3 is **object storage** for:

- Backups
- Logs
- Static websites

---

162 What is Load Balancer?

Answer:
Distributes traffic across multiple servers.

Types:

- ALB
- NLB
- CLB

1️⃣6️⃣3️⃣ What is Auto Scaling?

Answer:
Automatically adjusts EC2 count based on load.

1️⃣6️⃣4️⃣ What is CloudWatch?

Answer:
Monitoring service for AWS resources.

1️⃣6️⃣5️⃣ What is Terraform? (Deep Explanation)

Answer:
Terraform is an **Infrastructure as Code (IaC) tool** used to create, update, and manage cloud resources using code.

1️⃣6️⃣6️⃣ Why Terraform is used?

- Automation
- Version control
- Reusable modules
- Multi-cloud support

1️⃣6️⃣7️⃣ Terraform Workflow (VERY IMPORTANT)

1. `terraform init`
2. `terraform plan`

3. `terraform apply`
4. `terraform destroy`

---

168 What is Terraform Provider?

Answer:
Provider connects Terraform with cloud platforms.

Example:

- AWS
- Azure
- GCP

---

169 What is Terraform State?

Answer:
State file tracks **real infrastructure**.

⚠️ Critical file – never delete.

---

170 Local vs Remote Backend

Local	Remote
Stored locally	Stored in S3
Risky	Safe
No locking	State locking

---

171 What is Terraform Variable?

Answer:
Variables make code **dynamic and reusable**.

---

172 What are Output Variables?

Answer:
Display resource information after apply.

---

173 What is Terraform Module?

Answer:
A module is **reusable Terraform code**.

Example:

- VPC module
- EC2 module

---

174 What is Terraform Workspace?

Answer:
Used to manage **multiple environments**.

Example:

- dev
- qa
- prod

---

175 What is Terraform Lifecycle?

Answer:
Controls resource behavior.

```
lifecycle {
  prevent_destroy = true
}
```

1️⃣7️⃣6️⃣ What is Terraform Taint?

Answer:
Forces recreation of resource.

1️⃣7️⃣7️⃣ What is Terraform Import?

Answer:
Imports existing infrastructure into Terraform state.

1️⃣7️⃣8️⃣ Terraform vs Ansible (INTERVIEW FAVORITE)

Terraform	Ansible
Provisioning	Configuration
Declarative	Procedural
Immutable	Mutable

1️⃣7️⃣9️⃣ Common Terraform Mistakes

❌ Not using remote backend
❌ Editing state manually
❌ Hardcoding secrets
❌ No modules

1️⃣8️⃣0️⃣ DevOps Engineer Cloud Responsibilities

- Cloud infra design

- IaC automation
- Security
- Monitoring
- Cost optimization