

[Home](#) » [Compete](#) » [March Challenge 2017](#) » Bandwidth of a matrix

# Bandwidth of a matrix

Problem Code: **BANDMATR**



[Tweet](#) [Like](#) [Share](#) Sign Up to see what your friends like.

All submissions for this problem are available.

Read problems statements in [Mandarin Chinese](#), [Russian](#) and [Vietnamese](#) as well.

Bandwidth of a matrix  $A$  is defined as the smallest non-negative integer  $K$  such that  $A_{ij} = 0$  for  $|i - j| > K$ .

For example, a matrix with all zeros will have its bandwidth equal to zero. Similarly bandwidth of [diagonal matrix](#) will also be zero.

For example, for the below given matrix, the bandwidth of this matrix is 2.

```
1 0 0
0 1 1
1 1 0
```

Bandwidth of the below matrix is 1.

$$\begin{bmatrix} 1 & 1 & 0 & \dots & \dots & 0 \\ 1 & 1 & 1 & \ddots & \ddots & \vdots \\ 0 & 1 & 1 & 1 & \ddots & \vdots \\ \vdots & \ddots & 1 & 1 & 1 & 0 \\ \vdots & \ddots & \ddots & 1 & 1 & 1 \\ 0 & \dots & \dots & 0 & 1 & 1 \end{bmatrix}$$

All Submissions

Successful Submissions



We use cookies to personalise your experience, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services. You consent to our cookies if you continue to use our website.

Read our [Privacy Policy](#) and [Terms](#) to know more.

Save my Cookies

Bandwidth of the below matrix is 2.

$$\begin{bmatrix} 1 & 1 & 1 & 0 & \dots & 0 \\ 1 & 1 & 1 & 1 & \ddots & \vdots \\ 1 & 1 & 1 & 1 & 1 & 0 \\ 0 & 1 & 1 & 1 & 1 & 1 \\ \vdots & \ddots & 1 & 1 & 1 & 1 \\ 0 & \dots & 0 & 1 & 1 & 1 \end{bmatrix}$$

Bandwidth of the below matrix is also 2.

$$\begin{bmatrix} 1 & 0 & 1 & 0 & \dots & 0 \\ 1 & 0 & 1 & 1 & \ddots & \vdots \\ 1 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & 1 & 1 & 1 & 1 \\ \vdots & \ddots & 0 & 1 & 1 & 1 \\ 0 & \dots & 0 & 1 & 1 & 1 \end{bmatrix}$$

You will be given a binary matrix **A** of dimensions  $N \times N$ . You are allowed to make following operation as many times as you wish (possibly zero or more). In a single operation, you can swap any two entries of the matrix. Your aim is to minimize the bandwidth of the matrix. Find the minimum bandwidth of the matrix **A** you can get after making as many operations of above type as you want.

---

### Input

The first line of the input contains an integer **T** denoting the number of test cases. The description of **T** test cases follow.

First line of each test case contains an integer **N** denoting the height/width of the matrix.

Next **N** lines of each test case contain **N** space separated binary integers (either zero or one) corresponding to the entries of the matrix.

---

## Output

For each test case, output a single integer corresponding to the minimum bandwidth that you can obtain.

---

## Constraints

- $1 \leq T \leq 10$
  - $1 \leq N \leq 500$
  - $0 \leq A_{(i, j)} \leq 1$
- 

## Subtasks

- Subtask #1 (40 points) :  $1 \leq N \leq 100$
  - Subtask #2 (60 points) : original constraints
- 

## Example

**Input :**

```
6
2
0 0
0 0
2
1 0
0 1
2
1 0
1 0
2
1 0
1 1
3
1 0 0
0 1 1
1 1 0
4
1 1 1 1
1 1 1 1
1 1 1 1
1 1 1 1
```

**Output :**

```
0
0
0
1
1
3
```

---

## Explanation

**Example case 1.** The bandwidth of a matrix with all zero entries will be zero. This is the minimum bandwidth you can get, so there is no need of performing any swap operation.

**Example case 2.** The bandwidth of a diagonal matrix will also be zero.

**Example case 3.** You can make the given matrix a diagonal matrix by swapping  $A_{(2, 1)}$  and  $A_{(2, 2)}$ , which will have zero bandwidth.

**Example case 4.** You can not make swaps in any way that can reduce the bandwidth of this matrix. Bandwidth of this matrix is equal to 1, which is the minimum bandwidth that you can get.

**Example case 5.** Bandwidth of the given matrix is 2. You can make it equal to be 1 by swapping  $A_{(3, 1)}$  and  $A_{(3, 3)}$ , i.e. the matrix after the operation will look like

```
1 0 0
0 1 1
0 1 1
```

The bandwidth of this matrix is 1.

**Example case 6.** The swap operations won't have any effect on the matrix. Its bandwidth is equal to 3.

Author: [admin2](#)

Tester: [6★ xcwgf666](#)

Editorial: <https://discuss.codechef.com/problems/BANDMATR>

Tags: [admin2](#), [basic-prog](#), [march17](#), [matrix](#), [simple](#)

Date Added: 23-02-2017

Time Limit: 2 secs

Source Limit: 50000 Bytes

Languages: C, CPP14, JAVA, PYTH, PYTH 3.5, PYPY, CS2, PAS fpc, PAS gpc, RUBY, PHP, GO, NODEJS, HASK, SCALA, D, PERL, FORT, WSPC, ADA, CAML, ICK, BF, ASM, CLPS, PRLG, ICON, SCM qobi, PIKE, ST, NICE, LUA, BASH, NEM, LISP sbcl, LISP clisp, SCM guile, JS, ERL, TCL, PERL6, TEXT, SCM chicken, CLOJ, FS

## Comments ►

CodeChef is a non-commercial competitive programming community.

[About CodeChef](#) | [About Directi](#) | [CEO's Corner](#) | [C-Programming](#) | [Programming Languages](#) | [Contact Us](#)

© 2009 Directi Group. All Rights Reserved. CodeChef uses SPOJ © by [Sphere Research Labs](#)  
In order to report copyright violations of any kind, send in an email to [copyright@codechef.com](mailto:copyright@codechef.com)

### CodeChef - A Platform for Aspiring Programmers

CodeChef was created as a platform to help programmers make it big in the world of algorithms, **computer programming** and **programming contests**. At CodeChef we work hard to revive the geek in you by hosting a **programming contest** at the start of the month and another smaller programming challenge in the middle of the month. We also aim to have training sessions and discussions related to **algorithms**, **binary search**, technicalities like **array size** and the likes. Apart from providing a platform for **programming competitions**, CodeChef also has various algorithm tutorials and forum discussions to help those who are new to the world of **computer programming**.

**Directi**  
Intelligent People. Uncommon Ideas.

The time now is: 10:40:53 AM  
Your IP: 169.54.6.221

**Practice Section - A Place to hone your 'Computer Programming Skills'**

Try your hand at one of our many practice problems and submit your solution in a language of your choice. Our **programming contest** judge accepts solutions in over 35+ programming languages. Preparing for coding contests were never this much fun! Receive points, and move up through the CodeChef ranks. Use our practice section to better prepare yourself for the multiple **programming challenges** that take place through-out the month on CodeChef.

**Compete - Monthly Programming Contests and Cook-offs**

Here is where you can show off your **computer programming skills**. Take part in our 10 day long monthly coding contest and the shorter format Cook-off **coding contest**. Put yourself up for recognition and win great prizes. Our **programming contests** have prizes worth up to INR 20,000 (for Indian Community), \$700 (for Global Community) and lots more CodeChef goodies up for grabs.

**Programming Tools**

[Online IDE](#)

[Upcoming Coding Contests](#)

[Contest Hosting](#)

[Problem Setting](#)

[CodeChef Tutorials](#)

[CodeChef Wiki](#)

**Practice Problems**

[Easy](#)

[Medium](#)

[Hard](#)

[Challenge](#)

[Peer](#)

[School](#)

[FAQ's](#)

**Initiatives**

[Go for Gold](#)

[CodeChef for Schools](#)

[Campus Chapters](#)

