

# Reproducibility & Environments

---

**CS 203: Software Tools and Techniques for AI**

Prof. Nipun Batra, IIT Gandhinagar

# The Reproducibility Crisis

---

**"It works on my machine!"**

## **Common scenarios:**

- Research paper: "We achieved 95% accuracy"
- You: Run their code → 73% accuracy (or crash)
- Collaborator: "I can't install your dependencies"
- 6 months later: You can't run your own code

## **Root causes:**

- Different Python versions
- Missing dependencies
- OS-specific issues
- Hardware differences
- Random seeds not set

# What is Reproducibility?

---

**Reproducibility:** Ability to obtain same results using same code and data

**Levels:**

1. **Computational Reproducibility:** Same code + data = same results
2. **Statistical Reproducibility:** Control for randomness
3. **Scientific Reproducibility:** Independent verification

**Why it matters:**

- Scientific integrity
- Collaboration
- Debugging
- Deployment
- Future you will thank present you

# Environment Management

---

## The Problem:

```
Project A: Python 3.8, TensorFlow 2.4  
Project B: Python 3.10, TensorFlow 2.12  
System: Python 3.9, TensorFlow 2.8
```

## Solution: Isolated environments

### Tools:

- **venv/virtualenv**: Python virtual environments
- **conda**: Package and environment manager
- **Poetry**: Modern dependency management
- **Docker**: OS-level isolation

# Python Virtual Environments (venv)

---

## Create isolated Python environments

```
# Create virtual environment
python -m venv myenv

# Activate (Linux/Mac)
source myenv/bin/activate

# Activate (Windows)
myenv\Scripts\activate

# Install packages
pip install numpy pandas scikit-learn

# Save dependencies
pip freeze > requirements.txt

# Deactivate
deactivate
```

# requirements.txt

---

## Standard way to specify dependencies

```
numpy=1.24.3  
pandas=2.0.2  
scikit-learn=1.2.2  
matplotlib=3.7.1  
torch=2.0.1
```

## Install from requirements.txt:

```
pip install -r requirements.txt
```

## Best practices:

- Pin versions (==) for reproducibility
- Use >= for flexibility
- Separate dev dependencies

# Conda Environments

---

## More powerful than venv, handles non-Python dependencies

```
# Create environment with specific Python version
```

```
conda create -n myenv python=3.10
```

```
# Activate
```

```
conda activate myenv
```

```
# Install packages
```

```
conda install numpy pandas scikit-learn
```

```
# Install from conda-forge
```

```
conda install -c conda-forge librosa
```

```
# Export environment
```

```
conda env export > environment.yml
```

```
# Create from YAML
```

```
conda env create -f environment.yml
```

```
# Deactivate
```

```
conda deactivate
```

# environment.yml

---

## Conda environment specification

```
name: ml-project
channels:
  - pytorch
  - conda-forge
  - defaults
dependencies:
  - python=3.10
  - numpy=1.24
  - pandas=2.0
  - pytorch=2.0
  - cudatoolkit=11.8
  - pip
  - pip:
    - transformers=4.30.0
    - wandb=0.15.0
```

## Advantages:



# Poetry: Modern Dependency Management

---

## Handles dependencies, virtual environments, and packaging

```
# Install Poetry
curl -sSL https://install.python-poetry.org | python3 -

# Initialize project
poetry init

# Add dependencies
poetry add numpy pandas scikit-learn

# Add dev dependencies
poetry add --group dev pytest black

# Install all dependencies
poetry install

# Run command in environment
poetry run python train.py

# Build package
poetry build
```

# pyproject.toml (Poetry)

---

## **[tool.poetry]**

```
name = "ml-project"  
version = "0.1.0"  
description = "My ML project"  
authors = ["Your Name <you@example.com>"]
```

## **[tool.poetry.dependencies]**

```
python = "^3.10"  
numpy = "^1.24"  
pandas = "^2.0"  
scikit-learn = "^1.2"  
torch = "^2.0"
```

## **[tool.poetry.group.dev.dependencies]**

```
pytest = "^7.3"  
black = "^23.3"  
mypy = "^1.3"
```

## **[build-system]**

```
requires = ["poetry-core"]  
build-backend = "poetry.core.masonry.api"
```

# Setting Random Seeds

---

## Ensure reproducible results

```
import random
import numpy as np
import torch

def set_seed(seed=42):
    random.seed(seed)
    np.random.seed(seed)
    torch.manual_seed(seed)
    torch.cuda.manual_seed_all(seed)

    # Make CUDA deterministic
    torch.backends.cudnn.deterministic = True
    torch.backends.cudnn.benchmark = False

# Set at start of script
set_seed(42)

# Now your code is reproducible
```

# What is Docker?

---

Containerization platform: Package code + dependencies + OS

Container vs VM:

Container	Virtual Machine
Lightweight (MB)	Heavy (GB)
Fast startup (seconds)	Slow startup (minutes)
Shares host kernel	Full OS
Less isolation	More isolation

Benefits:

- Works identically everywhere
- No "works on my machine" problems
- Easy to share and deploy

# Docker Architecture

---

## Key concepts:

- **Image:** Template for containers (like a class)
- **Container:** Running instance (like an object)
- **Dockerfile:** Instructions to build image
- **Registry:** Store images (Docker Hub, GitHub Container Registry)

## Workflow:

```
Dockerfile → (build) → Image → (run) → Container
```

# Dockerfile Basics

---

## Create Dockerfile :

```
# Start from base image
FROM python:3.10-slim

# Set working directory
WORKDIR /app

# Copy requirements
COPY requirements.txt .

# Install dependencies
RUN pip install --no-cache-dir -r requirements.txt

# Copy project files
COPY . .

# Set environment variable
ENV PYTHONUNBUFFERED=1

# Run command
CMD ["python", "train.py"]
```

# Building and Running Docker Images

---

## Build image:

```
docker build -t my-ml-project:v1 .
```

## Run container:

```
# Basic run
```

```
docker run my-ml-project:v1
```

```
# Interactive mode
```

```
docker run -it my-ml-project:v1 /bin/bash
```

```
# Mount volume (share files)
```

```
docker run -v $(pwd)/data:/app/data my-ml-project:v1
```

```
# Expose port (for APIs)
```

```
docker run -p 8000:8000 my-ml-project:v1
```

```
# Run with GPU
```

```
docker run --gpus all my-ml-project:v1
```

# Dockerfile for ML Projects

---

```
FROM pytorch/pytorch:2.0.1-cuda11.7-cudnn8-runtime

WORKDIR /app

# Install system dependencies
RUN apt-get update && apt-get install -y \
    git \
    wget \
    && rm -rf /var/lib/apt/lists/*

# Copy and install Python dependencies
COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt

# Copy project
COPY . .

# Create directories
RUN mkdir -p /app/data /app/models /app/outputs

# Set Python path
ENV PYTHONPATH=/app

# Default command
CMD ["python", "train.py"]
```



# Docker Compose

---

## Manage multi-container applications

Create `docker-compose.yml` :

```
version: '3.8'

services:
  ml-training:
    build: .
    volumes:
      - ./data:/app/data
      - ./models:/app/models
    environment:
      - CUDA_VISIBLE_DEVICES=0
    deploy:
      resources:
        reservations:
          devices:
            - driver: nvidia
              count: 1
              capabilities: [gpu]

  api:
    image: my-api:latest
    ports:
      - "8000:8000"
```

# Using Docker Compose

---

```
# Start all services
```

```
docker-compose up
```

```
# Start in background
```

```
docker-compose up -d
```

```
# Stop services
```

```
docker-compose down
```

```
# View logs
```

```
docker-compose logs -f
```

```
# Run specific service
```

```
docker-compose run ml-training python train.py
```

```
# Rebuild images
```

```
docker-compose build
```

# Multi-Stage Docker Builds

---

## Reduce image size

```
# Stage 1: Build
FROM python:3.10 AS builder

WORKDIR /app
COPY requirements.txt .
RUN pip install --user --no-cache-dir -r requirements.txt

# Stage 2: Runtime
FROM python:3.10-slim

WORKDIR /app

# Copy installed packages from builder
COPY --from=builder /root/.local /root/.local

# Copy application
COPY . .

# Update PATH
ENV PATH=/root/.local/bin:$PATH

CMD ["python", "app.py"]
```

# Docker Best Practices

---

## 1. Use specific base images

```
# Good
FROM python:3.10-slim

# Avoid
FROM python:latest
```

## 2. Minimize layers

```
# Good: Single RUN
RUN apt-get update && apt-get install -y \
    package1 package2 \
    && rm -rf /var/lib/apt/lists/*

# Bad: Multiple RUNs
RUN apt-get update
RUN apt-get install -y package1
RUN apt-get install -y package2
```

# .dockerignore

---

## Exclude files from Docker context

```
# .dockerignore
__pycache__
*.pyc
*.pyo
*.pyd
.Python
*.so
*.egg
*.egg-info
dist
build
.git
.gitignore
.vscode
.idea
*.ipynb_checkpoints
data/
models/*.pth
*.log
.env
```

# Version Control for ML

---

## Git + DVC (Data Version Control)

**Problem:** Git doesn't handle large files well

**DVC:** Version control for data and models

```
# Initialize DVC
dvc init

# Track large file
dvc add data/large_dataset.csv

# Commit
git add data/large_dataset.csv.dvc .gitignore
git commit -m "Add dataset"

# Push data to remote storage (S3, GCS, etc.)
dvc remote add -d myremote s3://mybucket/dvc-storage
dvc push

# Pull data
```

# DVC Pipeline

---

## Define reproducible ML pipelines

```
# dvc.yaml
stages:
  prepare:
    cmd: python prepare.py
    deps:
      - prepare.py
      - data/raw
    outs:
      - data/processed

  train:
    cmd: python train.py
    deps:
      - train.py
      - data/processed
    params:
      - train.learning_rate
      - train.epochs
    outs:
      - models/model.pkl
    metrics:
      - metrics.json:
        cache: false
```

# Running DVC Pipelines

---

```
# Reproduce pipeline
```

```
dvc repro
```

```
# Visualize pipeline
```

```
dvc dag
```

```
# Compare experiments
```

```
dvc params diff
```

```
# Track metrics
```

```
dvc metrics show
```

```
# Create experiment
```

```
dvc exp run
```

```
# Compare experiments
```

```
dvc exp diff
```



# MLflow for Experiment Tracking

---

## Track experiments, models, and parameters

```
import mlflow
import mlflow.sklearn

# Start tracking
mlflow.set_tracking_uri("http://localhost:5000")
mlflow.set_experiment("my-experiment")

with mlflow.start_run():
    # Log parameters
    mlflow.log_param("learning_rate", 0.01)
    mlflow.log_param("epochs", 100)

    # Train model
    model = train_model()

    # Log metrics
    mlflow.log_metric("accuracy", 0.95)
    mlflow.log_metric("loss", 0.05)

    # Log model
    mlflow.sklearn.log_model(model, "model")

    # Log artifacts
    mlflow.log_artifact("plots/confusion_matrix.png")
```

# MLflow UI

---

```
# Start MLflow server
mlflow ui --host 0.0.0.0 --port 5000

# Access at http://localhost:5000
```

## Features:

- Compare experiment runs
- Visualize metrics
- Download models and artifacts
- Search and filter experiments
- Deploy models

# Weights & Biases (wandb)

---

## Modern experiment tracking and collaboration

```
import wandb

# Initialize
wandb.init(
    project="my-project",
    config={
        "learning_rate": 0.01,
        "epochs": 100,
        "batch_size": 32
    }
)

# Log metrics during training
for epoch in range(epochs):
    train_loss = train_epoch()
    val_loss = validate()

    wandb.log({
        "epoch": epoch,
        "train_loss": train_loss,
        "val_loss": val_loss
    })

# Log media
wandb.log({"confusion_matrix": wandb.plot.confusion_matrix( ... )})

# Finish
wandb.finish()
```

# Configuration Management

---

Use config files instead of hardcoding

## 1. YAML/JSON configs:

```
# config.yaml
model:
  name: "resnet50"
  pretrained: true

training:
  batch_size: 32
  learning_rate: 0.001
  epochs: 100
  device: "cuda"

data:
  train_path: "data/train"
  val_path: "data/val"
  num_workers: 4
```

# Loading Configs

---

```
import yaml
from dataclasses import dataclass

@dataclass
class TrainingConfig:
    batch_size: int
    learning_rate: float
    epochs: int
    device: str

def load_config(config_path):
    with open(config_path) as f:
        config = yaml.safe_load(f)

    training_config = TrainingConfig(**config['training'])
    return training_config

# Usage
config = load_config('config.yaml')
print(config.learning_rate)
```

# Hydra for Configuration

---

## Powerful configuration management

```
import hydra
from omegaconf import DictConfig

@hydra.main(config_path="configs", config_name="config", version_base=None)
def train(cfg: DictConfig):
    print(f"Learning rate: {cfg.training.learning_rate}")
    print(f"Batch size: {cfg.training.batch_size}")

    # Access nested config
    model = build_model(cfg.model)
    train_model(model, cfg.training)

if __name__ == "__main__":
    train()
```

## Run with overrides:

```
python train.py training.learning_rate=0.01 training.epochs=50
```

# Environment Variables

---

## Store secrets and config

Create `.env` file:

```
API_KEY=your_secret_key
DATABASE_URL=postgresql://localhost/db
MODEL_PATH=/path/to/models
DEBUG=True
```

## Load in Python:

```
import os
from dotenv import load_dotenv

load_dotenv()

api_key = os.getenv("API_KEY")
db_url = os.getenv("DATABASE_URL")
debug = os.getenv("DEBUG", "False") == "True"
```

# Logging Best Practices

---

## Structured logging for debugging

```
import logging

# Configure logging
logging.basicConfig(
    level=logging.INFO,
    format='%(asctime)s - %(name)s - %(levelname)s - %(message)s',
    handlers=[
        logging.FileHandler('training.log'),
        logging.StreamHandler()
    ]
)

logger = logging.getLogger(__name__)

# Use throughout code
logger.info("Starting training")
logger.debug(f"Batch size: {batch_size}")
logger.warning("Learning rate is very high")
logger.error("Failed to load checkpoint")

try:
    load_model()
except Exception as e:
    logger.exception("Error loading model")
```



# Model Checkpointing

---

## Save model state regularly

```
import torch

def save_checkpoint(model, optimizer, epoch, loss, path):
    checkpoint = {
        'epoch': epoch,
        'model_state_dict': model.state_dict(),
        'optimizer_state_dict': optimizer.state_dict(),
        'loss': loss,
        'config': config
    }
    torch.save(checkpoint, path)
    logger.info(f"Checkpoint saved to {path}")

def load_checkpoint(model, optimizer, path):
    checkpoint = torch.load(path)
    model.load_state_dict(checkpoint['model_state_dict'])
    optimizer.load_state_dict(checkpoint['optimizer_state_dict'])
    epoch = checkpoint['epoch']
    loss = checkpoint['loss']
    return model, optimizer, epoch, loss

# Save every N epochs
if epoch % 10 == 0:
    save_checkpoint(model, optimizer, epoch, loss,
                    f'checkpoints/model_epoch_{epoch}.pth')
```

# Project Structure

---

## Standard ML project layout:

```
ml-project/
├── data/
│   ├── raw/
│   ├── processed/
│   └── external/
├── models/
│   └── trained/
├── notebooks/
│   └── exploration.ipynb
├── src/
│   ├── __init__.py
│   ├── data/
│   │   ├── __init__.py
│   │   └── dataset.py
│   ├── models/
│   │   ├── __init__.py
│   │   └── model.py
│   └── utils/
│       └── __init__.py
├── tests/
│   └── test_model.py
├── configs/
│   └── config.yaml
├── requirements.txt
├── Dockerfile
├── docker-compose.yml
├── .env.example
├── .gitignore
├── .dockerignore
├── README.md
└── setup.py
```

# Reproducibility Checklist

---

## Before sharing code:

- ☐ Pin all dependency versions
- ☐ Set random seeds
- ☐ Document Python version
- ☐ Include requirements.txt or environment.yml
- ☐ Provide Docker setup (Dockerfile)
- ☐ Document data sources
- ☐ Include sample data or download scripts
- ☐ Write clear README with setup instructions
- ☐ Test on clean environment
- ☐ Document hardware requirements (GPU, RAM)
- ☐ Include configuration files
- ☐ Version control with Git

# README Template

---

```
# Project Name

## Setup

### Requirements
- Python 3.10+
- CUDA 11.7 (for GPU support)
- 16GB RAM minimum

### Installation

1. Clone repository
  ```bash
  git clone https://github.com/user/project.git
  cd project
  ```

2. Create virtual environment
  ```bash
  python -m venv venv
  source venv/bin/activate
  ```

3. Install dependencies
  ```bash
  pip install -r requirements.txt
  ```

4. Download data
  ```bash
  python scripts/download_data.py
  ```

## Usage

Train model:
  ```bash
  python train.py --config configs/config.yaml
  ```

## Docker

  ```bash
  docker build -t myproject .
  docker run -v $(pwd)/data:/app/data myproject
  ```
```

# Continuous Integration for ML

---

## Automate testing and validation

`.github/workflows/train.yml` :

```
name: Train Model

on:
  push:
    branches: [ main ]

jobs:
  train:
    runs-on: ubuntu-latest

    steps:
      - uses: actions/checkout@v2

      - name: Set up Python
        uses: actions/setup-python@v2
        with:
          python-version: 3.10

      - name: Install dependencies
        run: |
          pip install -r requirements.txt

      - name: Run training
        run: |
          python train.py --epochs 5

      - name: Upload metrics
        uses: actions/upload-artifact@v2
        if: success()
        with:
          name: metrics
          path: metrics
```

# Model Cards

---

## Document model details

### # Model Card: Sentiment Classifier

#### ## Model Details

- **Model type**: DistilBERT
- **Version**: 1.0
- **Date**: 2025-12-08

#### ## Intended Use

- **Primary use**: Sentiment analysis of product reviews
- **Out-of-scope**: Political content, medical text

#### ## Training Data

- **Dataset**: Amazon reviews (100k samples)
- **Splits**: 80/10/10 (train/val/test)
- **Preprocessing**: Lowercase, remove URLs

#### ## Performance

- **Test Accuracy**: 92%
- **F1 Score**: 0.91

#### ## Limitations

- Struggles with sarcasm
- Biased toward longer reviews

#### ## Ethical Considerations

- May amplify existing biases in training data

# What We've Learned

---

## Environment Management:

- venv, conda, Poetry for Python environments
- requirements.txt, environment.yml, pyproject.toml

## Containerization:

- Docker for reproducible environments
- Dockerfile, docker-compose
- Multi-stage builds

## Version Control:

- Git for code
- DVC for data and models

## Experiment Tracking:

- ML flow and Weights & Biases

# Resources

---

## Tools:

- Docker: <https://docs.docker.com/>
- Poetry: <https://python-poetry.org/>
- DVC: <https://dvc.org/>
- MLflow: <https://mlflow.org/>
- Weights & Biases: <https://wandb.ai/>

## Guides:

- Reproducible ML: <https://www.nature.com/articles/s41592-021-01256-7>
- Docker for Data Science: <https://towardsdatascience.com/docker-for-data-science>
- DVC Tutorial: <https://dvc.org/doc/start>



# Questions?

---

Next: Testing & CI/CD for AI

Lab: Dockerize ML project, setup experiment tracking