

2D Image Processing & Augmented Reality

Winter Semester 2019/2020


Survey on Face Tracking with Deep Learning

Vinay Balasubramanian

v_balasubr18@cs.uni-kl.de


Supervisor: Jilliam Diaz Barros

Outline



Quick recap

Face Tracking



Tracking a face across all frames of a video.
Bounding-box or landmark based.



Applications - Face analysis, Person identification,
Activity recognition, Expression analysis, Face
modeling etc.




Challenges - Videos can be captured in unconstrained
conditions.

May have illumination variations, large head poses,
occlusions, etc.


General Idea

- Video – Sequence of frames with temporal connection
- Sequence data? (Use RNN)



General Idea

- **Video – Sequence of frames with temporal connection**
- **Sequence data? (Use RNN)**
- **Give frames in temporal order, detect landmarks, feedback along with next frame.**



Why Deep Learning?

- **State-of-the-art in image processing tasks**
- **Operate directly on data**
- **Learn more generic features directly from data**
- **Domain knowledge is never obsolete**

Datasets

- 👤 **AFLW** – Around 25k annotated face **images**. 21 points [AFLW]
- 👤 **COFW** – 1007 occluded face **images**. 29 points [COFW]
- 👤 **Helen** – 2000 training and 330 test **images**. 194 points [Helen]
- 👤 **IBUG** – 135 **images** with difficult poses and expressions. 68 points [IBUG]
- 👤 **LFPW** – 1432 **images**. 29 points [LFPW]
- 👤 **LFW** – 13233 **images** of 5749 people. 10 points [LFW]
- 👤 **300-W** – 600 **images** in the wild. 68 points [300-W]
- 👤 **3D Menpo** – 12k **images**, 280k **video frames**, with 2D and 3D landmarks. 84 points [3D-Menpo]
- 👤 **FM** – 2150 images of 6 **videos**. 68 points [FM]
- 👤 **RWMB** – 20 **videos** with motion blur. 68/98 points [RWMB]
- 👤 **TF** – 5000 **frames** of a person engaged in a conversation. 68 points [TF]
- 👤 **300-VW** – 114 **videos** with 218,595 **frames**. 68 points [300-VW]

Approaches


- **RNN** [Jinwei Gu et al., 2017]
- **Two-stream network** [Hao Liu et al., 2017]
- **LSTM** [Qiqi Hou et al., 2017]
- **Encoder-Decoder network** [Xi Peng et al., 2018]
- **Deep reinforcement learning** [Minghao Guo et al., 2018]

Using RNNs [Jinwei Gu et al., 2017]


- RNNs and Bayesian filters are operationally similar



(a) Per-Frame



(b) Bayesian Filters




(c) Post-RNN



(d) RNN

Using RNNs [Jinwei Gu et al., 2017]




- FC-RNN is used to retain generalization of pre-trained CNN
- Trained end-to-end
- **300-VW** dataset for facial landmark localization
- L2 loss function
- Evaluation - Area Under the Curve (AUC), Failure Rate (FR %)

Two-stream network [Hao Liu et al., 2017]

- **Exploit both appearance information from still frames(spatial) and temporal information across frames(temporal)**
 - Spatial stream – Image pixels (still) -> landmark locations
 - Temporal stream – Compress video as active appearance codes

Two-stream network [Hao Liu et al., 2017]




- Spatial stream transforms local facial patches to shape residuals used to refine current face shape from previous.
- Temporal stream – Encoder-decoder network with 2-layer RNN. Capture facial dynamics in temporal dimension
- Final prediction is a weighted fusion of spatial and temporal streams shape updates

Two-stream network [Hao Liu et al., 2017]


- Tested on **300-VW** and **TF** datasets
- Evaluation – Normalized RMSE and Cumulative Error Distribution plots
- Weighted fusion – β_1 and $\beta_2 = 0.5$ yields the best performance

LSTMs [Qiqi Hou et al., 2017]

- LSTM is used to exploit spatial and temporal information



LSTMs [Qiqi Hou et al., 2017]



- Input – Image and Initial face shape
- Output – Predicted shape increment for the initial face shape
- Input -> several conv + max pooling -> ROI pooling for initial face shape -> concat -> FC layer -> LSTM -> predicted shape increment
- Update initial shape according to predicted shape increment


LSTMs [Qiqi Hou et al., 2017]

- Landmark detection method
- Trained on COFW, LFPW, Helen, AFW
- Evaluated on – COFW, Helen, 300-W, 300-VW
- Evaluation – Point-to-point RMSE
- Runtime – 18ms

Encoder-Decoder Network [Xi Peng et al., 2018]


- **Encoder – Image pixels -> Low dimensional feature space**
- **Decoder – Features in low dimensional space -> facial landmark heatmaps**
- **Feedback loop between the output(facial points) and the input**

Encoder-Decoder Network [Xi Peng et al., 2018]




- Encoder -> Feature disentangling on low dimensional representation -> Decoder
- Disentangle temporal-variant and temporal-invariant factors
- Temporal-invariant: Person identity
- Temporal-variant: Pose, expression, illumination

Encoder-Decoder Network [Xi Peng et al., 2018]



- **Spatial recurrent learning: Coarse-to-fine landmark search**
- **Feedback loop: Previous prediction + image**
- **Landmark detection: Detect major landmarks**
- **Landmark regression: Refine predicted locations from previous detection step**

Encoder-Decoder Network [Xi Peng et al., 2018]




- Temporal recurrent learning: Model non-identity factors (temporal-variant) using LSTM

Encoder-Decoder Network [Xi Peng et al., 2018]


- Evaluated on – **AFLW**, **LFW**, **Helen**, **LFPW**, **TF**, **FM**, **300-VW**
- Evaluation – Inter-ocular distance normalized RMSE

Reinforcement Learning [Minghao Guo et al., 2018]

- Bounding box generation and facial landmark detection are heavily dependent
- Two agents – bounding box **T**racking and facial landmark **A**lignment



Reinforcement Learning [Minghao Guo et al., 2018]



- Communication channels between agents (Deep Q-learning)
- Current state initialized to terminal state of previous frame
- Agents decide sequence of actions based on observed state and received messages

Reinforcement Learning [Minghao Guo et al., 2018]

- Go to next frame when landmarks are finalized
- State – Current image region extracted by bounding box
- Action – Tracking agent(Movement), Alignment agent(stop/continue iterations)



- Reward – Landmark detection accuracy improvements

Reinforcement Learning [Minghao Guo et al., 2018]

- Evaluated on Category 3 of **300-VW**
- Supervised learning stage –
 - Alignment agent trained on **300-W**
 - Tracking agent trained on **300-VW**
- Reinforcement learning stage –
 - Whole network trained on **300-VW**
- Evaluation – Normalized RMSE and cumulative error distribution plots
- DADRL-3D – Trained with 3D data from **3D Menpo**. 3D landmarks.

Comparison


Approach	Evaluated on dataset	Evaluation metrics
RNN	300-VW	RMSE, AUC, FR
Two-stream network	TF, 300-VW	RMSE, CED plot
LSTM	COFW, Helen, 300-W, 300-VW	RMSE
Encoder-decoder network	TF, 300-VW, FM	RMSE
Reinforcement Learning	300-VW	RMSE and CED plot

$$RMSE_i = \frac{1}{Pd_i} \sum_{p=1}^P \sqrt{(x_{i,p} - \hat{x}_{i,p})^2 + (y_{i,p} - \hat{y}_{k,p})^2}$$

Comparison

Approach	300-VW		TF		Runtime (ms)
	RMSE (68 landmarks)	RMSE (7 landmarks)	RMSE (68 landmarks)	RMSE (7 landmarks)	
RNN	6.16				
Two-stream network	5.59			2.13	33
LSTM	5.9				18
Encoder-decoder network	5.15	5.29	2.77	2.89	40
Reinforcement Learning	3.09				

Conclusion

- **RNN based approach**
 - FC-RNN to model temporal information.
- **Two-stream network**
 - Spatial and temporal streams
 - Least error on **TF** dataset for 7 landmarks
- **LSTM approach**
 - LSTM to model temporal information
 - Performs in real-time – 18ms
- **Encoder-Decoder approach**
 - Separate temporal-variant and temporal-invariant factors.
- **Reinforcement Learning approach**
 - Bounding box tracking  Facial alignment.
 - Least error on the category-3 of 300-VW

References

Jinwei Gu, Xiaodong Yang, Shalini De Mello, Jan Kautz: Dynamic Facial Analysis: From Bayesian Filtering to Recurrent Neural Network(2017).

Hao Liu, Jiwen Lu, Jianjiang Feng, Jie Zhou: Two-Stream Transformer Networks for Video-based Face Alignment(2017).

Qiqi Hou, Jinjun Wang, Ruibin Bai, Sanping Zhou, Yihong Gong: Face Alignment Recurrent Network(2017).

Xi Peng, Rogerio S. Feris, Xiaoyu Wang, Dimitris N. Metaxas: RED-Net: A Recurrent Encoder-Decoder Network for Video-based Face Alignment(2018).

Minghao Guo, Jiwen Lu, and Jie Zhou: Dual-Agent Deep Reinforcement Learning for Deformable Face Tracking(2018).

References

[TF], Fgnet: Talking face video. Tech. rep., 2004.

[LFW], Gary Huang, Marwan Mattar, Tamara Berg, and Eric Learned-Miller. Labeled faces in the wild: A database for studying face recognition in unconstrained environments. Tech. rep., 10 2008.

[AFLW], Martin Kořstinger, Paul Wohlhart, Peter M. Roth, and Horst Bischof. Annotated facial landmarks in the wild: A large-scale, real-world database for facial landmark localization(2011)

[Helen], Vuong Le, Jonathan Brandt, Zhe Lin, Lubomir Bourdev, and Thomas S Huang. Interactive facial feature localization. In European conference on computer vision(2012)

[COFW], X. P. Burgos-Artizzu, P. Perona, and P. Dollar. Robust face landmark estimation under occlusion(2013)

References

[LFPW], Peter Belhumeur, David Jacobs, David Kriegman, and Neeraj Kumar. Localizing parts of faces using a consensus of exemplars. IEEE transactions on pattern analysis and machine intelligence(2013)

[FM], Xi Peng, Shaoting Zhang, Yu Yang, and Dimitris N Metaxas. Piefa: Personalized incremental and ensemble face alignment(2015)

[300-VW], Jie Shen, Stefanos Zafeiriou, Grigoris G Chrysos, Jean Kossai, Georgios Tzimiropoulos, and Maja Pantic. The rst facial landmark tracking in-the-wild challenge: Benchmark and results(2015)

[IBUG], [300-W], Christos Sagonas a, Epameinondas Antonakosa, Georgios Tzimiropoulosb, Stefanos Zafeirioua, and Maja Pantic. 300 faces in-the-wild challenge: database and results, 2016.

[3D-Menpo], Stefanos Zafeiriou, Grigorios G Chrysos, Anastasios Roussos, Evangelos Ververas, Jiankang Deng, and George Trigeorgis. The 3d menpo facial landmark tracking challenge(2017)

References

[RWMB], Keqiang Sun, Wayne Wu, Tinghao Liu, Shuo Yang, Quan Wang, Qiang Zhou, Zuochang Ye, and Chen Qian. Fab: A robust facial landmark detection framework for motion-blurred videos(2019)

THANK YOU

QUESTIONS?