

2D Image Processing & Augmented Reality

3rd Semester

Survey on Face Tracking with Deep Learning

Vinay Balasubramanian

v_balasubr18@cs.uni-kl.de

Supervisor: Jilliam Diaz Barros

Outline

- **Face tracking is a computer vision task that involves tracking a specific number of landmarks on the face detected across all frames of a video.**
- **Applications include Face analysis, Person identification, Activity recognition, Sentiment analysis, Face modeling etc.**
- **It is a challenging problem as the videos are captured in unconstrained conditions which may include illumination variations, large head poses, occlusions.**

Outline

- There are two basic approaches – Image-based and Video-based.
- Image-based methods operate only on still frames.
- Video-based methods make use of temporal information to predict facial landmarks in each frame.

Recurrent Encoder-Decoder Network for Video-based Face Alignment

- Temporal-variant features such as pose and expression are separated from Temporal-invariant features such as facial identity.
- Employs recurrent learning at both spatial and temporal dimensions.
- The network consists of 4 modules - Encoder-Decoder, Spatial recurrent learning, Temporal recurrent learning and Supervised identity disentangling.

Dynamic Facial Analysis: From Bayesian Filtering to Recurrent Neural Network

- Improvises on previous approaches for dynamic facial analysis that use Kalman/Particle filters.
- CNN layers followed by recurrent layers as dense layers.
- Uses FC-RNN to exploit generalization from a pre-trained CNN.

Dual-Agent Deep Reinforcement Learning for Deformable Face Tracking

- Exploits the fact that bounding box tracking and landmark detection tasks are dependent. The accuracy of the latter depends on how good the former is.
- The two tasks are modeled in a probabilistic manner by following a Bayesian model.
- The architecture consists of a *Tracking agent*, *Alignment agent* and *Communication channels* between the agents.

Two-stream Transformer Networks for Video-based Face Alignment

- Two stream deep learning method to capture spatial as well as temporal information.
- Spatial stream captures information on still frames.
- Temporal stream captures temporal consistency information across successive frames. It is followed by a RNN to model the sequential information over consecutive frames.
- Finally, facial landmarks are determined by a weighted fusion of spatial and temporal streams.

Face Alignment Recurrent Neural Network

- Recurrent regression based approach
- Uses LSTM to exploit both spatial and temporal information.
- Spatial – The predicted landmark location is used as basis for estimation in the next stage.
- Temporal – The predicted landmark location is used as basis for estimation in the next frame.

Comparison metrics

- **Following are some of the metrics used to compare the above methods in this survey :—**
 - Dataset used for training (In the wild vs constrained)
 - Evaluation metrics
 - Number of landmarks tracked
 - Kind of landmarks retrieved (2D or 3D)
 - Robustness to large pose variations, illumination changes

Thank You