


AWS-Solution-Architect-Associate Dumps

Amazon AWS Certified Solutions Architect - Associate

<https://www.certleader.com/AWS-Solution-Architect-Associate-dumps.html>



NEW QUESTION 1

You are trying to launch an EC2 instance, however the instance seems to go into a terminated status immediately. What would probably not be a reason that this is happening?

- A. The AMI is missing a required part.
- B. The snapshot is corrupt.
- C. You need to create storage in EBS first.
- D. You've reached your volume limit

Answer: C

Explanation:

Amazon EC2 provides a virtual computing environments, known as an instance.

After you launch an instance, AWS recommends that you check its status to confirm that it goes from the pending status to the running status, the not terminated status.

The following are a few reasons why an Amazon EBS-backed instance might immediately terminate: You've reached your volume limit.

The AMI is missing a required part. The snapshot is corrupt. Reference:

http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using_InstanceStraightToTerminated.html

NEW QUESTION 2

You have set up an Auto Scaling group. The cool down period for the Auto Scaling group is 7 minutes. The first instance is launched after 3 minutes, while the second instance is launched after 4 minutes. How many minutes after the first instance is launched will Auto Scaling accept another scaling activity request?

- A. 11 minutes
- B. 7 minutes
- C. 10 minutes
- D. 14 minutes

Answer: A

Explanation:

If an Auto Scaling group is launching more than one instance, the cool down period for each instance starts after that instance is launched. The group remains locked until the last instance that was launched has completed its cool down period. In this case the cool down period for the first instance starts after 3 minutes and finishes at the 10th minute (3+7 cool down), while for the second instance it starts at the 4th minute and finishes at the 11th minute (4+7 cool down). Thus, the Auto Scaling group will receive another request only after 11 minutes.

Reference: http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html

NEW QUESTION 3

Can a user get a notification of each instance start / terminate configured with Auto Scaling?

- A. Yes, if configured with the Launch Config
- B. Yes, always
- C. Yes, if configured with the Auto Scaling group
- D. No

Answer: C

Explanation:

The user can get notifications using SNS if he has configured the notifications while creating the Auto Scaling group.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/GettingStartedTutorial.html>

NEW QUESTION 4

Amazon EBS provides the ability to create backups of any Amazon EC2 volume into what is known as

- A. snapshots
- B. images
- C. instance backups
- D. mirrors

Answer: A

Explanation:

Amazon allows you to make backups of the data stored in your EBS volumes through snapshots that can later be used to create a new EBS volume.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Storage.html>

NEW QUESTION 5

To specify a resource in a policy statement, in Amazon EC2, can you use its Amazon Resource Name (ARN)?

- A. Yes, you can.
- B. No, you can't because EC2 is not related to ARN.
- C. No, you can't because you can't specify a particular Amazon EC2 resource in an IAM policy.
- D. Yes, you can but only for the resources that are not affected by the action

Answer: A

Explanation:

Some Amazon EC2 API actions allow you to include specific resources in your policy that can be created or modified by the action. To specify a resource in the statement, you need to use its Amazon Resource Name (ARN).

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-ug.pdf>

NEW QUESTION 6

A user is storing a large number of objects on AWS S3. The user wants to implement the search functionality among the objects. How can the user achieve this?

- A. Use the indexing feature of S3.
- B. Tag the objects with the metadata to search on that.
- C. Use the query functionality of S3.
- D. Make your own DB system which stores the S3 metadata for the search functionalit

Answer: D

Explanation:

In Amazon Web Services, AWS S3 does not provide any query facility. To retrieve a specific object the user needs to know the exact bucket / object key. In this case it is recommended to have an own DB system which manages the S3 metadata and key mapping.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 7

A client needs you to import some existing infrastructure from a dedicated hosting provider to AWS to try and save on the cost of running his current website. He also needs an automated process that manages backups, software patching, automatic failure detection, and recovery. You are aware that his existing set up currently uses an Oracle database. Which of the following AWS databases would be best for accomplishing this task?

- A. Amazon RDS
- B. Amazon Redshift
- C. Amazon SimpleDB
- D. Amazon ElastiCache

Answer: A

Explanation:

Amazon RDS gives you access to the capabilities of a familiar MySQL, Oracle, SQL Server, or PostgreSQL database engine. This means that the code, applications, and tools you already use today with your existing databases can be used with Amazon RDS. Amazon RDS automatically patches the database software and backs up your database, storing the backups for a user-defined retention period and enabling point-in-time recovery.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 8

Do Amazon EBS volumes persist independently from the running life of an Amazon EC2 instance?

- A. Yes, they do but only if they are detached from the instance.
- B. No, you cannot attach EBS volumes to an instance.
- C. No, they are dependent.
- D. Yes, they d

Answer: D

Explanation:

An Amazon EBS volume behaves like a raw, unformatted, external block device that you can attach to a single instance. The volume persists independently from the running life of an Amazon EC2 instance. Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Storage.html>

NEW QUESTION 9

Your manager has just given you access to multiple VPN connections that someone else has recently set up between all your company's offices. She needs you to make sure that the communication between the VPNs is secure. Which of the following services would be best for providing a low-cost hub-and-spoke model for primary or backup connectMty between these remote offices?

- A. Amazon C|oudFront
- B. AWS Direct Connect
- C. AWS C|oudHSM
- D. AWS VPN CloudHub

Answer: D

Explanation:

If you have multiple VPN connections, you can provide secure communication between sites using the AWS VPN CloudHub. The VPN CloudHub operates on a simple hub-and-spoke model that you can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing Internet connections who would like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectMty between these remote offices.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html

NEW QUESTION 10

Amazon EC2 provides a . It is an HTTP or HTTPS request that uses the HTTP verbs GET or POST.

- A. web database
- B. .net framework
- C. Query API
- D. C library

Answer: C

Explanation:

Amazon EC2 provides a Query API. These requests are HTTP or HTTPS requests that use the HTTP verbs GET or POST and a Query parameter named Action. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/APIReference/making-api-requests.html>

NEW QUESTION 10

In Amazon AWS, which of the following statements is true of key pairs?

- A. Key pairs are used only for Amazon SDKs.
- B. Key pairs are used only for Amazon EC2 and Amazon CloudFront.
- C. Key pairs are used only for Elastic Load Balancing and AWS IAM.
- D. Key pairs are used for all Amazon service

Answer: B

Explanation:

Key pairs consist of a public and private key, where you use the private key to create a digital signature, and then AWS uses the corresponding public key to validate the signature. Key pairs are used only for Amazon EC2 and Amazon CloudFront. Reference: <http://docs.aws.amazon.com/general/latest/gr/aws-sec-cred-types.html>

NEW QUESTION 11

An organization has three separate AWS accounts, one each for development, testing, and production. The organization wants the testing team to have access to certain AWS resources in the production account. How can the organization achieve this?

- A. It is not possible to access resources of one account with another account.
- B. Create the IAM roles with cross account access.
- C. Create the IAM user in a test account, and allow it access to the production environment with the IAM policy.
- D. Create the IAM users with cross account acces

Answer: B

Explanation:

An organization has multiple AWS accounts to isolate a development environment from a testing or production environment. At times the users from one account need to access resources in the other account, such as promoting an update from the development environment to the production environment. In this case the IAM role with cross account access will provide a solution. Cross account access lets one account share access to their resources with users in the other AWS accounts.

Reference: http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf

NEW QUESTION 13

You need to migrate a large amount of data into the cloud that you have stored on a hard disk and you decide that the best way to accomplish this is with AWS Import/Export and you mail the hard disk to AWS. Which of the following statements is incorrect in regards to AWS Import/Export?

- A. It can export from Amazon S3
- B. It can Import to Amazon Glacier
- C. It can export from Amazon Glacier.
- D. It can Import to Amazon EBS

Answer: C

Explanation:

AWS Import/Export supports: Import to Amazon S3

Export from Amazon S3 Import to Amazon EBS Import to Amazon Glacier

AWS Import/Export does not currently support export from Amazon EBS or Amazon Glacier. Reference:

<https://docs.aws.amazon.com/AWSImportExport/latest/DG/whatisdisk.html>

NEW QUESTION 16

In EC2, what happens to the data in an instance store if an instance reboots (either intentionally or unintentionally)?

- A. Data is deleted from the instance store for security reasons.
- B. Data persists in the instance store.
- C. Data is partially present in the instance store.
- D. Data in the instance store will be los

Answer: B

Explanation:

The data in an instance store persists only during the lifetime of its associated instance. If an instance reboots (intentionally or unintentionally), data in the instance store persists. However, data on instance store volumes is lost under the following circumstances.

Failure of an underlying drive

Stopping an Amazon EBS-backed instance Terminating an instance

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/InstanceStorage.html>

NEW QUESTION 17

You are setting up a VPC and you need to set up a public subnet within that VPC. Which following requirement must be met for this subnet to be considered a public subnet?

- A. Subnet's traffic is not routed to an internet gateway but has its traffic routed to a virtual private gateway.
- B. Subnet's traffic is routed to an internet gateway.
- C. Subnet's traffic is not routed to an internet gateway.
- D. None of these answers can be considered a public subne

Answer: B

Explanation:

A virtual private cloud (VPC) is a virtual network dedicated to your AWS account. It is logically isolated from other virtual networks in the AWS cloud. You can launch your AWS resources, such as Amazon EC2 instances, into your VPC. You can configure your VPC: you can select its IP address range, create subnets, and configure route tables, network gateways, and security settings.

A subnet is a range of IP addresses in your VPC. You can launch AWS resources into a subnet that you select. Use a public subnet for resources that must be connected to the internet, and a private subnet for resources that won't be connected to the Internet.

If a subnet's traffic is routed to an internet gateway, the subnet is known as a public subnet.

If a subnet doesn't have a route to the internet gateway, the subnet is known as a private subnet.

If a subnet doesn't have a route to the internet gateway, but has its traffic routed to a virtual private gateway, the subnet is known as a VPN-only subnet.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html

NEW QUESTION 21

Can you specify the security group that you created for a VPC when you launch an instance in EC2-Classi

- A. No, you can specify the security group created for EC2-Classi
- B. No
- C. Yes
- D. No, you can specify the security group created for EC2-Classi to a non-VPC based instance onl

Answer: B

Explanation:

If you're using EC2-Classi

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html#ec2-classic-securit y-groups>

NEW QUESTION 22

While using the EC2 GET requests as URLs, the is the URL that serves as the entry point for the web service.

- A. token
- B. endpoint
- C. action
- D. None of these

Answer: B

Explanation:

The endpoint is the URL that serves as the entry point for the web service.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-query-api.html>

NEW QUESTION 27

You have been given a scope to deploy some AWS infrastructure for a large organisation. The requirements are that you will have a lot of EC2 instances but may need to add more when the average utilization of your Amazon EC2 fileet is high and conversely remove them when CPU utilization is low. Which AWS services would be best to use to accomplish this?

- A. Auto Scaling, Amazon CloudWatch and AWS Elastic Beanstalk
- B. Auto Scaling, Amazon CloudWatch and Elastic Load Balancing.
- C. Amazon CloudFront, Amazon CloudWatch and Elastic Load Balancing.
- D. AWS Elastic Beanstalk , Amazon CloudWatch and Elastic Load Balancin

Answer: B

Explanation:

Auto Scaling enables you to follow the demand curve for your applications closely, reducing the need to manually provision Amazon EC2 capacity in advance. For example, you can set a condition to add new

Amazon EC2 instances in increments to the Auto Scaling group when the average utilization of your Amazon EC2 fileet is high; and similarly, you can set a condition to remove instances in the same increments when CPU utilization is low. If you have predictable load changes, you can set a schedule through Auto Scaling to plan your scaling actMties. You can use Amazon CloudWatch to send alarms to trigger scaling actMties and Elastic Load Balancing to help distribute traffic to your instances within Auto Scaling groups. Auto Scaling enables you to run your Amazon EC2 fileet at optimal utilization. Reference:

<http://aws.amazon.com/autoscaling/>

NEW QUESTION 30

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. In DynamoDB there is no need to grant access
- B. Depended to the type of access
- C. No
- D. Yes

Answer: D

Explanation:

Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

NEW QUESTION 34

Your EBS volumes do not seem to be performing as expected and your team leader has requested you look into improving their performance. Which of the following is not a true statement relating to the performance of your EBS volumes?

- A. Frequent snapshots provide a higher level of data durability and they will not degrade the performance of your application while the snapshot is in progress.
- B. General Purpose (SSD) and Provisioned IOPS (SSD) volumes have a throughput limit of 128 MB/s per volume.
- C. There is a relationship between the maximum performance of your EBS volumes, the amount of I/O you are drMng to them, and the amount of time it takes for each transaction to complete.
- D. There is a 5 to 50 percent reduction in IOPS when you first access each block of data on a newly created or restored EBS volume

Answer: A

Explanation:

Several factors can affect the performance of Amazon EBS volumes, such as instance configuration, I/O characteristics, workload demand, and storage configuration.

Frequent snapshots provide a higher level of data durability, but they may slightly degrade the performance of your application while the snapshot is in progress. This trade off becomes critical when you have data that changes rapidly. Whenever possible, plan for snapshots to occur during off-peak times in order to minimize workload impact.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSPerformance.html>

NEW QUESTION 35

You've created your first load balancer and have registered your EC2 instances with the load balancer. Elastic Load Balancing routinely performs health checks on all the registered EC2 instances and automatically distributes all incoming requests to the DNS name of your load balancer across your registered, healthy EC2 instances. By default, the load balancer uses the _ protocol for checking the health of your instances.

- A. HTTPS
- B. HTTP
- C. ICMP
- D. IPv6

Answer: B

Explanation:

In Elastic Load Balancing a health configuration uses information such as protocol, ping port, ping path (URL), response timeout period, and health check interval to determine the health state of the instances registered with the load balancer.

Currently, HTTP on port 80 is the default health check. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 40

A user has launched 10 EC2 instances inside a placement group. Which of the below mentioned statements is true with respect to the placement group?

- A. All instances must be in the same AZ
- B. All instances can be across multiple regions
- C. The placement group cannot have more than 5 instances
- D. All instances must be in the same region

Answer: A

Explanation:

A placement group is a logical grouping of EC2 instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gbps network. Placement groups are recommended for applications that benefit from low network latency, high network throughput or both.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

NEW QUESTION 43

Which of the following AWS CLI commands is syntactically incorrect?

1. \$ aws ec2 describe-instances
2. \$ aws ec2 start-instances --instance-ids i-1348636c
3. \$ aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError -message "Script Failure"
4. \$ aws sqs receive-message --queue-url https://queue.amazonaws.com/546419318123/Test

- A. 3
- B. 4
- C. 2
- D. 1

Answer: A

Explanation:

The following CLI command is missing a hyphen before "-message".

aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError -message "Script Failure"

It has been added below in red

aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError ---message "Script Failure"

Reference: <http://aws.amazon.com/cli/>

NEW QUESTION 48

An organization has developed a mobile application which allows end users to capture a photo on their mobile device, and store it inside an application. The application internally uploads the data to AWS S3. The organization wants each user to be able to directly upload data to S3 using their Google ID. How will the mobile app allow this?

- A. Use the AWS Web identity federation for mobile applications, and use it to generate temporary security credentials for each user.
- B. It is not possible to connect to AWS S3 with a Google ID.
- C. Create an IAM user every time a user registers with their Google ID and use IAM to upload files to S3.
- D. Create a bucket policy with a condition which allows everyone to upload if the login ID has a Google part to it.

Answer: A

Explanation:

For Amazon Web Services, the Web identity federation allows you to create cloud-backed mobile apps that use public identity providers, such as login with Facebook, Google, or Amazon. It will create temporary security credentials for each user, which will be authenticated by the AWS services, such as S3.

Reference: <http://docs.aws.amazon.com/STS/latest/UsingSTS/CreatingWIF.html>

NEW QUESTION 52

An online gaming site asked you if you can deploy a database that is a fast, highly scalable NoSQL database service in AWS for a new site that he wants to build. Which database should you recommend?

- A. Amazon DynamoDB
- B. Amazon RDS
- C. Amazon Redshift
- D. Amazon SimpleDB

Answer: A

Explanation:

Amazon DynamoDB is ideal for database applications that require very low latency and predictable performance at any scale but don't need complex querying capabilities like joins or transactions. Amazon DynamoDB is a fully-managed NoSQL database service that offers high performance, predictable throughput and low cost. It is easy to set up, operate, and scale.

With Amazon DynamoDB, you can start small, specify the throughput and storage you need, and easily scale your capacity requirements on the fly. Amazon DynamoDB automatically partitions data over a number of servers to meet your request capacity. In addition, DynamoDB automatically replicates your data synchronously across multiple Availability Zones within an AWS Region to ensure high-availability and data durability.

Reference: https://aws.amazon.com/running_databases/#dynamodb_anchor

NEW QUESTION 57

You log in to IAM on your AWS console and notice the following message. "Delete your root access keys." Why do you think IAM is requesting this?

- A. Because the root access keys will expire as soon as you log out.
- B. Because the root access keys expire after 1 week.
- C. Because the root access keys are the same for all users.
- D. Because they provide unrestricted access to your AWS resource

Answer: D

Explanation:

In AWS an access key is required in order to sign requests that you make using the command-line interface (CLI), using the AWS SDKs, or using direct API calls. Anyone who has the access key for your root account has unrestricted access to all the resources in your account, including billing information. One of the best ways to protect your account is to not have an access key for your root account. We recommend that unless you must have a root access key (this is very rare), that you do not generate one. Instead, AWS best practice is to create one or more AWS Identity and Access Management (IAM) users, give them the necessary permissions, and use IAM users for everyday interaction with AWS.

Reference:

<http://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html#root-password>

NEW QUESTION 60

Once again your customers are concerned about the security of their sensitive data and with their latest enquiry ask about what happens to old storage devices on AWS. What would be the best answer to this QUESTION ?

- A. AWS reformats the disks and uses them again.
- B. AWS uses the techniques detailed in DoD 5220.22-M to destroy data as part of the decommissioning process.
- C. AWS uses their own proprietary software to destroy data as part of the decommissioning process.
- D. AWS uses a 3rd party security organization to destroy data as part of the decommissioning process

Answer: B

Explanation:

When a storage device has reached the end of its useful life, AWS procedures include a decommissioning process that is designed to prevent customer data from being exposed to unauthorized individuals.

AWS uses the techniques detailed in DoD 5220.22-M ("National Industrial Security Program Operating Manual ") or NIST 800-88 ("Guidelines for Media Sanitization") to destroy data as part of the decommissioning process.

All decommissioned magnetic storage devices are degaussed and physically destroyed in accordance with industry-standard practices.

Reference: <http://d0.awsstatic.com/whitepapers/Security/AWS%20Security%20Whitepaper.pdf>

NEW QUESTION 65

A customer enquires about whether all his data is secure on AWS and is especially concerned about Elastic Map Reduce (EMR) so you need to inform him of

some of the security features in place for AWS. Which of the below statements would be an incorrect response to your customers enquiry?

- A. Amazon ENIR customers can choose to send data to Amazon S3 using the HTTPS protocol for secure transmission.
- B. Amazon S3 provides authentication mechanisms to ensure that stored data is secured against unauthorized access.
- C. Every packet sent in the AWS network uses Internet Protocol Security (IPsec).
- D. Customers may encrypt the input data before they upload it to Amazon S3.

Answer: C

Explanation:

Amazon S3 provides authentication mechanisms to ensure that stored data is secured against unauthorized access. Unless the customer who is uploading the data specifies otherwise, only that customer can access the data. Amazon EMR customers can also choose to send data to Amazon S3 using the HTTPS protocol for secure transmission. In addition, Amazon EMR always uses HTTPS to send data between Amazon S3 and Amazon EC2. For added security, customers may encrypt the input data before they upload it to Amazon S3 (using any common data compression tool); they then need to add a decryption step to the beginning of their cluster when Amazon EMR fetches the data from Amazon S3. Reference: <https://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 70

You are setting up a very complex financial services grid and so far it has 5 Elastic IP (EIP) addresses.

You go to assign another EIP address, but all accounts are limited to 5 Elastic IP addresses per region by default, so you aren't able to. What is the reason for this?

- A. For security reasons.
- B. Hardware restrictions.
- C. Public (IPv4) internet addresses are a scarce resource.
- D. There are only 5 network interfaces per instance

Answer: C

Explanation:

Public (IPv4) internet addresses are a scarce resource. There is only a limited amount of public IP space available, and Amazon EC2 is committed to helping use that space efficiently.

By default, all accounts are limited to 5 Elastic IP addresses per region. If you need more than 5 Elastic IP addresses, AWS asks that you apply for your limit to be raised. They will ask you to think through your use case and help them understand your need for additional addresses.

Reference: http://aws.amazon.com/ec2/faqs/#How_many_instances_can_I_run_in_Amazon_EC2

NEW QUESTION 71

Amazon RDS provides high availability and failover support for DB instances using .

- A. customized deployments
- B. Appstream customizations
- C. log events
- D. Multi-AZ deployments

Answer: D

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. Multi-AZ deployments for Oracle, PostgreSQL, MySQL, and MariaDB DB instances use Amazon technology, while SQL Server DB instances use SQL Server Mirroring.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.IV|u|tiAZ.html>

NEW QUESTION 76

A major customer has asked you to set up his AWS infrastructure so that it will be easy to recover in the case of a disaster of some sort. Which of the following is important when thinking about being able to quickly launch resources in AWS to ensure business continuity in case of a disaster?

- A. Create and maintain AMIs of key servers where fast recovery is required.
- B. Regularly run your servers, test them, and apply any software updates and configuration changes.
- C. All items listed here are important when thinking about disaster recovery.
- D. Ensure that you have all supporting custom software packages available in AW

Answer: C

Explanation:

In the event of a disaster to your AWS infrastructure you should be able to quickly launch resources in Amazon Web Services (AWS) to ensure business continuity.

The following are some key steps you should have in place for preparation:

1. Set up Amazon EC2 instances to replicate or mirror data.
2. Ensure that you have all supporting custom software packages available in AWS.
3. Create and maintain AMIs of key servers where fast recovery is required.
4. Regularly run these servers, test them, and apply any software updates and configuration changes.
5. Consider automating the provisioning of AWS resources.

Reference: http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 81

What would be the best way to retrieve the public IP address of your EC2 instance using the CLI?

- A. Using tags
- B. Using traceroute
- C. Using ipconfig
- D. Using instance metadata

Answer: D

Explanation:

To determine your instance's public IP address from within the instance, you can use instance metadata. Use the following command to access the public IP address: For Linux use, \$ curl

<http://169.254.169.254/latest/meta-data/public-ipv4>, and for Windows use, \$ wget <http://169.254.169.254/latest/meta-data/public-ipv4>.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-instance-addressing.htm>

NEW QUESTION 82

An existing client comes to you and says that he has heard that launching instances into a VPC (virtual private cloud) is a better strategy than launching instances into a EC2-classic which he knows is what you currently do. You suspect that he is correct and he has asked you to do some research about this and get back to him. Which of the following statements is true in regards to what ability launching your instances into a VPC instead of EC2-Classic gives you?

- A. All of the things listed here.
- B. Change security group membership for your instances while they're running
- C. Assign static private IP addresses to your instances that persist across starts and stops
- D. Define network interfaces, and attach one or more network interfaces to your instances

Answer: A

Explanation:

By launching your instances into a VPC instead of EC2-Classic, you gain the ability to: Assign static private IP addresses to your instances that persist across starts and stops Assign multiple IP addresses to your instances

Define network interfaces, and attach one or more network interfaces to your instances Change security group membership for your instances while they're running

Control the outbound traffic from your instances (egress filtering) in addition to controlling the inbound traffic to them (ingress filtering)

Add an additional layer of access control to your instances in the form of network access control lists (ACL)

Run your instances on single-tenant hardware

Reference: http://media.amazonwebservices.com/AWS_Cloud_Best_Practices.pdf

NEW QUESTION 85

A user wants to achieve High Availability with PostgreSQL DB. Which of the below mentioned functionalities helps achieve HA?

- A. Multi AZ
- B. Read Replica
- C. Multi region
- D. PostgreSQL does not support HA

Answer: A

Explanation:

The Multi AZ feature allows the user to achieve High Availability. For Multi AZ, Amazon RDS automatically provisions and maintains a synchronous "standby" replica in a different Availability Zone. Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 88

A user has created an application which will be hosted on EC2. The application makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK to connect with from the EC2 instance. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create an IAM user with DynamoDB access and use its credentials within the application to connect with DynamoDB
- B. The user should attach an IAM role with DynamoDB access to the EC2 instance
- C. The user should create an IAM role, which has EC2 access so that it will allow deploying the application
- D. The user should create an IAM user with DynamoDB and EC2 access
- E. Attach the user with the application so that it does not use the root account credentials

Answer: B

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to

AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. Instead, the user should use roles for EC2 and give that role access to DynamoDB /S3. When the roles are attached to EC2, it will give temporary security credentials to the application hosted on that EC2, to connect with DynamoDB / S3.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 92

A user has attached 1 EBS volume to a VPC instance. The user wants to achieve the best fault tolerance of data possible. Which of the below mentioned options can help achieve fault tolerance?

- A. Attach one more volume with RAID 1 configuration.
- B. Attach one more volume with RAID 0 configuration.
- C. Connect multiple volumes and stripe them with RAID 6 configuration.
- D. Use the EBS volume as a root device

Answer: A

Explanation:

The user can join multiple provisioned IOPS volumes together in a RAID 1 configuration to achieve better fault tolerance. RAID 1 does not provide a write performance improvement; it requires more bandwidth than non-RAID configurations since the data is written simultaneously to multiple volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

NEW QUESTION 97

A user is aware that a huge download is occurring on his instance. He has already set the Auto Scaling policy to increase the instance count when the network I/O increases beyond a certain limit. How can the user ensure that this temporary event does not result in scaling?

- A. The network I/O are not affected during data download
- B. The policy cannot be set on the network I/O
- C. There is no way the user can stop scaling as it is already configured
- D. Suspend scaling

Answer: D

Explanation:

The user may want to stop the automated scaling processes on the Auto Scaling groups either to perform manual operations or during emergency situations. To perform this, the user can suspend one or more scaling processes at any time. Once it is completed, the user can resume all the suspended processes.

Reference: http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html

NEW QUESTION 101

Select a true statement about Amazon EC2 Security Groups (EC2-Classic).

- A. After you launch an instance in EC2-Classic, you can't change its security groups.
- B. After you launch an instance in EC2-Classic, you can change its security groups only once.
- C. After you launch an instance in EC2-Classic, you can only add rules to a security group.
- D. After you launch an instance in EC2-Classic, you cannot add or remove rules from a security group.

Answer: A

Explanation:

After you launch an instance in EC2-Classic, you can't change its security groups. However, you can add rules to or remove rules from a security group, and those changes are automatically applied to all instances that are associated with the security group.

Reference: <http://docs.amazonaws.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 106

A user has created photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Queue Service
- C. AWS Elastic Transcoder
- D. AWS Glacier

Answer: B

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 109

An accountant asks you to design a small VPC network for him and, due to the nature of his business, just needs something where the workload on the network will be low, and dynamic data will be accessed infrequently. Being an accountant, low cost is also a major factor. Which EBS volume type would best suit his requirements?

- A. Magnetic
- B. Any, as they all perform the same and cost the same.
- C. General Purpose (SSD)
- D. Magnetic or Provisioned IOPS (SSD)

Answer: A

Explanation:

You can choose between three EBS volume types to best meet the needs of their workloads: General Purpose (SSD), Provisioned IOPS (SSD), and Magnetic.

General Purpose (SSD) is the new, SSD-backed, general purpose EBS volume type that we recommend as the default choice for customers. General Purpose (SSD) volumes are suitable for a broad range of workloads, including small to medium sized databases, development and test environments, and boot volumes.

Provisioned IOPS (SSD) volumes offer storage with consistent and low-latency performance, and are designed for I/O intensive applications such as large relational or NoSQL databases. Magnetic volumes provide the lowest cost per gigabyte of all EBS volume types. Magnetic volumes are ideal for workloads where data is accessed infrequently, and applications where the lowest storage cost is important.

Reference: <https://aws.amazon.com/ec2/faqs/>

NEW QUESTION 114

A user is planning to launch a scalable web application. Which of the below mentioned options will not affect the latency of the application?

- A. Region.
- B. Provisioned IOPS.
- C. Availability Zone.

D. Instance siz

Answer: C

Explanation:

In AWS, the instance size decides the I/O characteristics. The provisioned IOPS ensures higher throughput, and lower latency. The region does affect the latency; latency will always be less when the instance is near to the end user. Within a region the user uses any AZ and this does not affect the latency. The AZ is mainly for fault toleration or HA.

Reference: http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf

NEW QUESTION 117

In Amazon EC2, if your EBS volume stays in the detaching state, you can force the detachment by clicking .

- A. Force Detach
- B. Detach Instance
- C. AttachVolume
- D. AttachInstance

Answer: A

Explanation:

If your volume stays in the detaching state, you can force the detachment by clicking Force Detach. Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 122

An organization has a statutory requirement to protect the data at rest for data stored in EBS volumes. Which of the below mentioned options can the organization use to achieve data protection?

- A. Data replication.
- B. Data encryption.
- C. Data snapshot.
- D. All the options listed her

Answer: D

Explanation:

For protecting the Amazon EBS data at REST, the user can use options, such as Data Encryption (Windows / Linux / third party based), Data Replication (AWS internally replicates data for redundancy), and Data Snapshot (for point in time backup).

Reference: http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf

NEW QUESTION 127

Name the disk storage supported by Amazon Elastic Compute Cloud (EC2).

- A. None of these
- B. Amazon AppStream store
- C. Amazon SNS store
- D. Amazon Instance Store

Answer: D

Explanation:

Amazon EC2 supports the following storage options: Amazon Elastic Block Store (Amazon EBS) Amazon EC2 Instance Store Amazon Simple Storage Service (Amazon S3)

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Storage.html>

NEW QUESTION 130

A user is observing the EC2 CPU utilization metric on CloudWatch. The user has observed some interesting patterns while filtering over the 1 week period for a particular hour. The user wants to zoom that data point to a more granular period. How can the user do that easily with CloudWatch?

- A. The user can zoom a particular period by selecting that period with the mouse and then releasing the mouse
- B. The user can zoom a particular period by specifying the aggregation data for that period
- C. The user can zoom a particular period by double clicking on that period with the mouse
- D. The user can zoom a particular period by specifying the period in the Time Range

Answer: A

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The AWS CloudWatch console provides the option to change the granularity of a graph and zoom in to see data over a shorter time period. To zoom, the user has to click in the graph details pane, drag on the graph area for selection, and then release the mouse button.

Reference: http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/zoom_in_on_graph.html

NEW QUESTION 133

A scope has been handed to you to set up a super fast gaming server and you decide that you will use Amazon DynamoDB as your database. For efficient access to data in a table, Amazon DynamoDB creates and maintains indexes for the primary key attributes. A secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations. How many types of secondary indexes does DynamoDB support?

- A. 2
- B. 16
- C. 4
- D. As many as you need

Answer: A

Explanation:

DynamoDB supports two types of secondary indexes:

Local secondary index — an index that has the same hash key as the table, but a different range key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a table partition that has the same hash key.

Global secondary index — an index with a hash and range key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 136

The common use cases for DynamoDB Fine-Grained Access Control (FGAC) are cases in which the end user wants .

- A. to change the hash keys of the table directly
- B. to check if an IAM policy requires the hash keys of the tables directly
- C. to read or modify any codecommit key of the table directly, without a middle-tier service
- D. to read or modify the table directly, without a middle-tier service

Answer: D

Explanation:

FGAC can benefit any application that tracks information in a DynamoDB table, where the end user (or application client acting on behalf of an end user) wants to read or modify the table directly, without a middle-tier service. For instance, a developer of a mobile app named Acme can use FGAC to track the top score of every Acme user in a DynamoDB table. FGAC allows the application client to modify only the top score for the user that is currently running the application.

Reference: http://aws.amazon.com/dynamodb/faqs/#security_anchor

NEW QUESTION 140

A user comes to you and wants access to Amazon CloudWatch but only wants to monitor a specific LoadBalancer. Is it possible to give him access to a specific set of instances or a specific LoadBalancer?

- A. No because you can't use IAM to control access to CloudWatch data for specific resources.
- B. Yes
- C. You can use IAM to control access to CloudWatch data for specific resources.
- D. No because you need to be Sysadmin to access CloudWatch data.
- E. Yes
- F. Any user can see all CloudWatch data and needs no access right

Answer: A

Explanation:

Amazon CloudWatch integrates with AWS Identity and Access Management (IAM) so that you can

specify which CloudWatch actions a user in your AWS Account can perform. For example, you could create an IAM policy that gives only certain users in your organization permission to use GetMetricStatistics. They could then use the action to retrieve data about your cloud resources.

You can't use IAM to control access to CloudWatch data for specific resources. For example, you can't give a user access to CloudWatch data for only a specific set of instances or a specific LoadBalancer. Permissions granted using IAM cover all the cloud resources you use with CloudWatch. In addition, you can't use IAM roles with the Amazon CloudWatch command line tools.

Using Amazon CloudWatch with IAM doesn't change how you use CloudWatch. There are no changes to CloudWatch actions, and no new CloudWatch actions related to users and access control.

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/UsingIAM.html>

NEW QUESTION 143

A user is planning to make a mobile game which can be played online or offline and will be hosted on EC2.

The user wants to ensure that if someone breaks the highest score or they achieve some milestone they can inform all their colleagues through email. Which of the below mentioned AWS services helps achieve this goal?

- A. AWS Simple Workflow Service.
- B. AWS Simple Email Service.
- C. Amazon Cognito
- D. AWS Simple Queue Service

Answer: B

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. It integrates with other AWS services, making it easy to send emails from applications that are hosted on AWS.

Reference: <http://aws.amazon.com/ses/faqs/>

NEW QUESTION 147

After setting up an EC2 security group with a cluster of 20 EC2 instances, you find an error in the security group settings. You quickly make changes to the security group settings. When will the changes to the settings be effective?

- A. The settings will be effective immediately for all the instances in the security group.
- B. The settings will be effective only when all the instances are restarted.

- C. The settings will be effective for all the instances only after 30 minutes.
D. The settings will be effective only for the new instances added to the security group

Answer: A

Explanation:

Amazon Redshift applies changes to a cluster security group immediately. So if you have associated the cluster security group with a cluster, inbound cluster access rules in the updated cluster security group apply immediately.

Reference: <http://docs.aws.amazon.com/redshift/latest/mgmt/working-with-security-groups.html>

NEW QUESTION 150

Regarding Amazon Route 53, if your application is running on Amazon EC2 instances in two or more Amazon EC2 regions and if you have more than one Amazon EC2 instance in one or more regions, you can use to route traffic to the correct region and then use to route traffic to instances within the region, based on probabilities that you specify.

- A. weighted-based routing; alias resource record sets
B. latency-based routing; weighted resource record sets
C. weighted-based routing; weighted resource record sets
D. latency-based routing; alias resource record sets

Answer: B

Explanation:

Regarding Amazon Route 53, if your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

NEW QUESTION 151

You are setting up some EBS volumes for a customer who has requested a setup which includes a RAID (redundant array of inexpensive disks). AWS has some recommendations for RAID setups. Which RAID setup is not recommended for Amazon EBS?

- A. RAID 5 only
B. RAID 5 and RAID 6
C. RAID 1 only
D. RAID 1 and RAID 6

Answer: B

Explanation:

With Amazon EBS, you can use any of the standard RAID configurations that you can use with a traditional bare metal server, as long as that particular RAID configuration is supported by the operating system for your instance. This is because all RAID is accomplished at the software level. For greater I/O performance than you can achieve with a single volume, RAID 0 can stripe multiple volumes together; for on-instance redundancy, RAID 1 can mirror two volumes together. RAID 5 and RAID 6 are not recommended for Amazon EBS because the parity write operations of these RAID modes consume some of the IOPS available to your volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

NEW QUESTION 154

Doug has created a VPC with CIDR 10.201.0.0/16 in his AWS account. In this VPC he has created a public subnet with CIDR block 10.201.31.0/24. While launching a new EC2 from the console, he is not able to assign the private IP address 10.201.31.6 to this instance. Which is the most likely reason for this issue?

- A. Private IP address 10.201.31.6 is blocked via ACLs in Amazon infrastructure as a part of platform security.
B. Private address IP 10.201.31.6 is currently assigned to another interface.
C. Private IP address 10.201.31.6 is not part of the associated subnet's IP address range.
D. Private IP address 10.201.31.6 is reserved by Amazon for IP networking purpose

Answer: B

Explanation:

In Amazon VPC, you can assign any Private IP address to your instance as long as it is: Part of the associated subnet's IP address range

Not reserved by Amazon for IP networking purposes Not currently assigned to another interface Reference: <http://aws.amazon.com/vpc/faqs/>

NEW QUESTION 155

You need to create a JSON-formatted text file for AWS CloudFormation. This is your first template and the only thing you know is that the templates include several major sections but there is only one that is required for it to work. What is the only section required?

- A. Mappings
B. Outputs
C. Resources
D. Conditions

Answer: C

Explanation:

AWS CloudFormation is a service that helps you model and set up your Amazon Web Services resources so that you can spend less time managing those resources and more time focusing on your applications that run in AWS. You create a template that describes all the AWS resources that you want (like Amazon EC2 instances or Amazon RDS DB instances), and AWS CloudFormation takes care of provisioning and configuring those resources for you.

A template is a JSON-formatted text file that describes your AWS infrastructure. Templates include several major sections.

The Resources section is the only section that is required.

The first character in the template must be an open brace {}, and the last character must be a closed brace (). The following template fragment shows the template structure and sections.

Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/template-anatomy.html>

NEW QUESTION 159

A user is hosting a website in the US West-1 region. The website has the highest client base from the Asia-Pacific (Singapore / Japan) region. The application is accessing data from S3 before serving it to client. Which of the below mentioned regions gives a better performance for S3 objects?

- A. Japan
- B. Singapore
- C. US East
- D. US West-1

Answer: D

Explanation:

Access to Amazon S3 from within Amazon EC2 in the same region is fast. In this aspect, though the client base is Singapore, the application is being hosted in the US West-1 region. Thus, it is recommended that S3 objects be stored in the US-West-1 region.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 163

Which of the following statements is true of tagging an Amazon EC2 resource?

- A. You don't need to specify the resource identifier while terminating a resource.
- B. You can terminate, stop, or delete a resource based solely on its tags.
- C. You can't terminate, stop, or delete a resource based solely on its tags.
- D. You don't need to specify the resource identifier while stopping a resource.

Answer: C

Explanation:

You can assign tags only to resources that already exist. You can't terminate, stop, or delete a resource based solely on its tags; you must specify the resource identifier.

Reference: http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Using_Tags.html

NEW QUESTION 168

You have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region, and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region.

How many EC2 instances would be sufficient to distribute requests in other regions?

- A. 3
- B. 9
- C. 2
- D. 1

Answer: D

Explanation:

If your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

For example, suppose you have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region. Just one Amazon EC2 instance is sufficient in the other regions, although you can apply the same technique to many regions at once.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

NEW QUESTION 169

You have just finished setting up an advertisement server in which one of the obvious choices for a service was Amazon Elastic Map Reduce (EMR) and are now troubleshooting some weird cluster states that you are seeing. Which of the below is not an Amazon EMR cluster state?

- A. STARTING
- B. STOPPED
- C. RUNNING
- D. WAITING

Answer: B

Explanation:

Amazon Elastic Map Reduce (EMR) is a web service that enables businesses, researchers, data analysts, and developers to easily and cost-effectively process vast amounts of data.

Amazon EMR historically referred to an Amazon EMR cluster (and all processing steps assigned to it) as a "cluster". Every cluster has a unique identifier that starts with "j-".

The different cluster states of an Amazon EMR cluster are listed below. STARTING — The cluster provisions, starts, and configures EC2 instances.

BOOTSTRAPPING — Bootstrap actions are being executed on the cluster. RUNNING — A step for the cluster is currently being run.

WAITING — The cluster is currently active, but has no steps to run. TERMINATING - The cluster is in the process of shutting down. TERMINATED - The cluster was shut down without error. TERMINATED_WITH_ERRORS - The cluster was shut down with errors.

Reference: <https://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 171

You have just set up your first Elastic Load Balancer (ELB) but it does not seem to be configured properly. You discover that before you start using ELB, you have to configure the listeners for your load balancer. Which protocols does ELB use to support the load balancing of applications?

- A. HTTP and HTTPS
- B. HTTP, HTTPS, TCP, SSL and SSH
- C. HTTP, HTTPS, TCP, and SSL
- D. HTTP, HTTPS, TCP, SSL and SFTP

Answer: C

Explanation:

Before you start using Elastic Load Balancing (ELB), you have to configure the listeners for your load balancer. A listener is a process that listens for connection requests. It is configured with a protocol and a port number for front-end (client to load balancer) and back-end (load balancer to back-end instance) connections. Elastic Load Balancing supports the load balancing of applications using HTTP, HTTPS (secure HTTP), TCP, and SSL (secure TCP) protocols. The HTTPS uses the SSL protocol to establish secure connections over the HTTP layer. You can also use SSL protocol to establish secure connections over the TCP layer. The acceptable ports for both HTTPS/SSL and HTTP/TCP connections are 25, 80, 443, 465, 587, and 1024-65535.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-listener-config.html>

NEW QUESTION 175

After setting up some EC2 instances you now need to set up a monitoring solution to keep track of these instances and to send you an email when the CPU hits a certain threshold. Which statement below best describes what thresholds you can set to trigger a CloudWatch Alarm?

- A. Set a target value and choose whether the alarm will trigger when the value is greater than (>), greater than or equal to (>=), less than (<), or less than or equal to (<=) that value.
- B. Thresholds need to be set in IAM not CloudWatch
- C. Only default thresholds can be set you can't choose your own thresholds.
- D. Set a target value and choose whether the alarm will trigger when the value hits this threshold

Answer: A

Explanation:

Amazon CloudWatch is a monitoring service for AWS cloud resources and the applications you run on AWS. You can use Amazon CloudWatch to collect and track metrics, collect and monitor log files, and set alarms.

When you create an alarm, you first choose the Amazon CloudWatch metric you want it to monitor. Next, you choose the evaluation period (e.g., five minutes or one hour) and a statistical value to measure (e.g., Average or Maximum).

To set a threshold, set a target value and choose whether the alarm will trigger when the value is greater than (>), greater than or equal to (>=), less than (<), or less than or equal to (<=) that value.

Reference: <http://aws.amazon.com/cloudwatch/faqs/>

NEW QUESTION 177

After moving an E-Commerce website for a client from a dedicated server to AWS you have also set up auto scaling to perform health checks on the instances in your group and replace instances that fail these checks. Your client has come to you with his own health check system that he wants you to use as it has proved to be very useful prior to his site running on AWS. What do you think would be an appropriate response to this given all that you know about auto scaling?

- A. It is not possible to implement your own health check system
- B. You need to use AWS's health check system.
- C. It is not possible to implement your own health check system due to compatibility issues.
- D. It is possible to implement your own health check system and then send the instance's health information directly from your system to Cloud Watch.
- E. It is possible to implement your own health check system and then send the instance's health information directly from your system to Cloud Watch but only in the US East (Virginia) region.
- F. Virginia) region.

Answer: C

Explanation:

Auto Scaling periodically performs health checks on the instances in your group and replaces instances that fail these checks. By default, these health checks use the results of EC2 instance status checks to determine the health of an instance. If you use a load balancer with your Auto Scaling group, you can optionally choose to include the results of Elastic Load Balancing health checks.

Auto Scaling marks an instance unhealthy if the calls to the Amazon EC2 action DescribeInstanceStatus returns any other state other than running, the system status shows impaired, or the calls to Elastic Load Balancing action DescribeInstanceHealth returns OutOfService in the instance state field.

After an instance is marked unhealthy because of an Amazon EC2 or Elastic Load Balancing health check, it is scheduled for replacement.

You can customize the health check conducted by your Auto Scaling group by specifying additional checks or by having your own health check system and then sending the instance's health information directly from your system to Auto Scaling.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/healthcheck.html>

NEW QUESTION 179

When does the billing of an Amazon EC2 system begin?

- A. It starts when the Status column for your distribution changes from Creating to Deployed.
- B. It starts as soon as you click the create instance option on the main EC2 console.
- C. It starts when your instance reaches 720 instance hours.
- D. It starts when Amazon EC2 initiates the boot sequence of an AM instance

Answer: D

Explanation:

Billing commences when Amazon EC2 initiates the boot sequence of an AM instance. Billing ends when the instance terminates, which could occur through a web services command, by running "shutdown -h", or through instance failure. When you stop an instance, Amazon shuts it down but doesn't charge hourly usage for a stopped instance, or data transfer fees, but charges for the storage for any Amazon EBS volumes.

Reference: <http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 184

You have created a Route 53 latency record set from your domain to a machine in Northern Virginia and a similar record to a machine in Sydney. When a user located in U S visits your domain he will be routed to:

- A. Northern Virginia
- B. Sydney
- C. Both, Northern Virginia and Sydney
- D. Depends on the Weighted Resource Record Sets

Answer: A

Explanation:

If your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

For example, suppose you have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region. Just one Amazon EC2 instance is sufficient in the other regions, although you can apply the same technique to many regions at once.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

NEW QUESTION 187

You are using Amazon SES as an email solution but are unsure of what its limitations are. Which statement below is correct in regards to that?

- A. New Amazon SES users who have received production access can send up to 1,000 emails per 24-hour period, at a maximum rate of 10 emails per second.
- B. Every Amazon SES sender has a the same set of sending limits
- C. Sending limits are based on messages rather than on recipients
- D. Every Amazon SES sender has a unique set of sending limits

Answer: D

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. Amazon SES eliminates the complexity and expense of building an in-house email solution or licensing, installing, and operating a third-party email service for this type of email communication.

Every Amazon SES sender has a unique set of sending limits, which are calculated by Amazon SES on an ongoing basis:

Sending quota — the maximum number of emails you can send in a 24-hour period. Maximum send rate — the maximum number of emails you can send per second.

New Amazon SES users who have received production access can send up to 10,000 emails per 24-hour period, at a maximum rate of 5 emails per second.

Amazon SES automatically adjusts these limits upward, as long as you send high-quality email. If your existing quota is not adequate for your needs and the system has not automatically increased your quota, you can submit an SES Sending Quota Increase case at any time.

Sending limits are based on recipients rather than on messages. You can check your sending limits at any time by using the Amazon SES console.

Note that if your email is detected to be of poor or QUESTION able quality (e.g., high complaint rates, high bounce rates, spam, or abusive content), Amazon SES might temporarily or permanently reduce your permitted send volume, or take other action as AWS deems appropriate.

Reference: <https://aws.amazon.com/ses/faqs/>

NEW QUESTION 188

Having just set up your first Amazon Virtual Private Cloud (Amazon VPC) network, which defined a default network interface, you decide that you need to create and attach an additional network interface, known as an elastic network interface (ENI) to one of your instances. Which of the following statements is true regarding attaching network interfaces to your instances in your VPC?

- A. You can attach 5 ENIs per instance type.
- B. You can attach as many ENIs as you want.
- C. The number of ENIs you can attach varies by instance type.
- D. You can attach 100 ENIs total regardless of instance typ

Answer: C

Explanation:

Each instance in your VPC has a default network interface that is assigned a private IP address from the IP address range of your VPC. You can create and attach an additional network interface, known as an elastic network interface (ENI), to any instance in your VPC. The number of ENIs you can attach varies by instance type.

NEW QUESTION 193

You have set up an S3 bucket with a number of images in it and you have decided that you want anybody to be able to access these images, even anonymous users. To accomplish this you create a bucket policy. You will need to use an Amazon S3 bucket policy that specifies a in the principal element, which means anyone can access the bucket.

- A. hash tag (#)
- B. anonymous user
- C. wildcard (*)
- D. S3 user

Answer: C

Explanation:

You can use the AWS Policy Generator to create a bucket policy for your Amazon S3 bucket. You can then use the generated document to set your bucket policy by using the Amazon S3 console, by a number of third-party tools, or via your application.

You use an Amazon S3 bucket policy that specifies a wildcard (*) in the principal element, which means anyone can access the bucket. With anonymous access, anyone (including users without an AWS account) will be able to access the bucket.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/iam-troubleshooting.html#d0e20565>

NEW QUESTION 196

You have been asked to build AWS infrastructure for disaster recovery for your local applications and within that you should use an AWS Storage Gateway as part of the solution. Which of the following best describes the function of an AWS Storage Gateway?

- A. Accelerates transferring large amounts of data between the AWS cloud and portable storage devices .
- B. A web service that speeds up distribution of your static and dynamic web content.
- C. Connects an on-premises software appliance with cloud-based storage to provide seamless and secure integration between your on-premises IT environment and AWS's storage infrastructure.
- D. Is a storage service optimized for infrequently used data, or "cold data."

Answer: C

Explanation:

AWS Storage Gateway connects an on-premises software appliance with cloud-based storage to provide seamless integration with data security features between your on-premises IT environment and the Amazon Web Services (AWS) storage infrastructure. You can use the service to store data in the AWS cloud for scalable and cost-effective storage that helps maintain data security. AWS Storage Gateway offers both volume-based and tape-based storage solutions:

Volume gateways Gateway-cached volumes Gateway-stored volumes

Gateway-virtual tape library (VTL)

Reference:

http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_disasterrecovery_07.pdf

NEW QUESTION 197

Which of the following features are provided by Amazon EC2?

- A. Exadata Database Machine, Optimized Storage Management, Flashback Technology, and Data Warehousing
- B. Instances, Amazon Machine Images (AMIs), Key Pairs, Amazon EBS Volumes, Firewall, Elastic IP address, Tags, and Virtual Private Clouds (VPCs)
- C. Real Application Clusters (RAC), ElastiCache Machine Images (EMIs), Data Warehousing, Flashback Technology, Dynamic IP address
- D. Exadata Database Machine, Real Application Clusters (RAC), Data Guard, Table and Index Partitioning, and Data Pump Compression

Answer: B

Explanation:

Amazon EC2 provides the following features:

- Virtual computing environments, known as instances;
- Pre-configured templates for your instances, known as Amazon Machine Images (AMIs), that package the bits you need for your server (including the operating system and additional software)
- Various configurations of CPU, memory, storage, and networking capacity for your instances, known as instance types
- Secure login information for your instances using key pairs (AWS stores the public key, and you store the private key in a secure place)
- Storage volumes for temporary data that's deleted when you stop or terminate your instance, known as instance store volumes
- Persistent storage volumes for your data using Amazon Elastic Block Store (Amazon EBS), known as Amazon EBS volumes
- Multiple physical locations for your resources, such as instances and Amazon EBS volumes, known as regions and Availability Zones
- A firewall that enables you to specify the protocols, ports, and source IP ranges that can reach your instances using security groups
- Static IP addresses for dynamic cloud computing, known as Elastic IP addresses
- Metadata, known as tags, that you can create and assign to your Amazon EC2 resources
- Virtual networks you can create that are logically isolated from the rest of the AWS cloud, and that you can optionally connect to your own network, known as virtual private clouds (VPCs).

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/concepts.html>

NEW QUESTION 202

In Amazon Elastic Compute Cloud, which of the following is used for communication between instances in the same network (EC2-Classic or a VPC)?

- A. Private IP addresses
- B. Elastic IP addresses
- C. Static IP addresses
- D. Public IP addresses

Answer: A

Explanation:

A private IP address is an IP address that's not reachable over the Internet. You can use private IP addresses for communication between instances in the same network (EC2-Classic or a VPC). Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-instance-addressing.html>

NEW QUESTION 203

A user is sending bulk emails using AWS SES. The emails are not reaching some of the targeted audience because they are not authorized by the ISPs. How can the user ensure that the emails are all delivered?

- A. Send an email using DKIM with SES.
- B. Send an email using SMTP with SES.
- C. Open a ticket with AWS support to get it authorized with the ISP.
- D. Authorize the ISP by sending emails from the development account

Answer: A

Explanation:

Domain Keys Identified Mail (DKIM) is a standard that allows senders to sign their email messages and ISPs, and use those signatures to verify that those messages are legitimate and have not been modified by a third party in transit.

Reference: <http://docs.aws.amazon.com/ses/latest/DeveloperGuide/dkim.html>

NEW QUESTION 208

Content and IV|edia Server is the latest requirement that you need to meet for a client.

The client has been very specific about his requirements such as low latency, high availability, durability, and access control. Potentially there will be millions of views on this server and because of "spiky" usage patterns, operations teams will need to provision static hardware, network, and management resources to support the maximum expected need. The Customer base will be initially low but is expected to grow and become more geographically distributed.

Which of the following would be a good solution for content distribution?

- A. Amazon S3 as both the origin server and for caching
- B. AWS Storage Gateway as the origin server and Amazon EC2 for caching
- C. AWS CloudFront as both the origin server and for caching
- D. Amazon S3 as the origin server and Amazon CloudFront for caching

Answer: D

Explanation:

As your customer base grows and becomes more geographically distributed, using a high- performance edge cache like Amazon CloudFront can provide substantial improvements in latency, fault tolerance, and cost.

By using Amazon S3 as the origin server for the Amazon CloudFront distribution, you gain the advantages of fast in-network data transfer rates, simple publishing/caching workflow, and a unified security framework.

Amazon S3 and Amazon CloudFront can be configured by a web service, the AWS Management Console, or a host of third-party management tools.

Reference:http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_media_02.pdf

NEW QUESTION 209

You are setting up your first Amazon Virtual Private Cloud (Amazon VPC) network so you decide you should probably use the AWS Management Console and the VPC Wizard. Which of the following is not an option for network architectures after launching the "Start VPC Wizard" in Amazon VPC page on the AWS Management Console?

- A. VPC with a Single Public Subnet Only
- B. VPC with a Public Subnet Only and Hardware VPN Access
- C. VPC with Public and Private Subnets and Hardware VPN Access
- D. VPC with a Private Subnet Only and Hardware VPN Access

Answer: B

Explanation:

Amazon VPC enables you to build a virtual network in the AWS cloud - no VPNs, hardware, or physical datacenters required.

Your AWS resources are automatically provisioned in a ready-to-use default VPC. You can choose to create additional VPCs by going to Amazon VPC page on the AWS Management Console and click on the "Start VPC Wizard" button.

You'll be presented with four basic options for network architectures. After selecting an option, you can modify the size and IP address range of the VPC and its subnets. If you select an option with Hardware VPN Access, you will need to specify the IP address of the VPN hardware on your network. You can modify the VPC to add more subnets or add or remove gateways at any time after the VPC has been created.

The four options are:

VPC with a Single Public Subnet Only VPC with Public and Private Subnets

VPC with Public and Private Subnets and Hardware VPN Access VPC with a Private Subnet Only and Hardware VPN Access Reference:

<https://aws.amazon.com/vpc/faqs/>

NEW QUESTION 210

Which one of the below doesn't affect Amazon CloudFront billing?

- A. Distribution Type
- B. Data Transfer Out
- C. Dedicated IP SSL Certificates
- D. Requests

Answer: A

Explanation:

Amazon CloudFront is a web service for content delivery. CloudFront delivers your content using a global network of edge locations and works seamlessly with Amazon S3 which durably stores the original and definitive versions of your files.

Amazon CloudFront billing is mainly affected by Data Transfer Out

Edge Location Traffic Distribution Requests

Dedicated IP SSL Certificates

Reference: <http://calculator.s3.amazonaws.com/index.html>

NEW QUESTION 215

A user is trying to launch a similar EC2 instance from an existing instance with the option "Launch More like this". The AMI of the selected instance is deleted. What will happen in this case?

- A. AWS does not need an AMI for the "Launch more like this" option
- B. AWS will launch the instance but will not create a new AMI
- C. AWS will create a new AMI and launch the instance
- D. AWS will throw an error saying that the AMI is deregistered

Answer: D

Explanation:

If the user has deregistered the AMI of an EC2 instance and is trying to launch a similar instance with the option "Launch more like this", AWS will throw an error saying that the AMI is deregistered or not available.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/launching-instance.html>

NEW QUESTION 219

A user is planning a highly available application deployment with EC2. Which of the below mentioned options will not help to achieve HA?

- A. Elastic IP address
- B. PIOPS
- C. AMI
- D. Availability Zones

Answer: B

Explanation:

In Amazon Web Service, the user can achieve HA by deploying instances in multiple zones. The elastic IP helps the user achieve HA when one of the instances is down but still keeps the same URL. The AM helps launching the new instance. The PIOPS is for the performance of EBS and does not help for HA. Reference:

http://media.amazonwebservices.com/AWS_Web_Hosting_Best_Practices.pdf

NEW QUESTION 220

After deploying a new website for a client on AWS, he asks if you can set it up so that if it fails it can be automatically redirected to a backup website that he has stored on a dedicated server elsewhere. You are wondering whether Amazon Route 53 can do this. Which statement below is correct in regards to Amazon Route 53?

- A. Amazon Route 53 can't help detect an outag
- B. You need to use another service.
- C. Amazon Route 53 can help detect an outage of your website and redirect your end users to alternate locations.
- D. Amazon Route 53 can help detect an outage of your website but can't redirect your end users to alternate locations.
- E. Amazon Route 53 can't help detect an outage of your website, but can redirect your end users to alternate locations.

Answer: B

Explanation:

With DNS Failover, Amazon Route 53 can help detect an outage of your website and redirect your end users to alternate locations where your application is operating properly.

Reference:

<http://aws.amazon.com/about-aws/whats-new/2013/02/11/announcing-dns-failover-for-route-53/>

NEW QUESTION 221

Which of the following statements is true of Amazon EC2 security groups?

- A. You can change the outbound rules for EC2-Classi
- B. Also, you can add and remove rules to a group at any time.
- C. You can modify an existing rule in a grou
- D. However, you can't add and remove rules to a group.
- E. None of the statements are correct.
- F. You can't change the outbound rules for EC2-Classi
- G. However, you can add and remove rules to agroup at any tim

Answer: D

Explanation:

When dealing with security groups, bear in mind that you can freely add and remove rules from a group, but you can't change the outbound rules for EC2-Classic. If you're using the Amazon EC2 console, you can modify existing rules, and you can copy the rules from an existing security group to a new security group.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 225

Can I change the EC2 security groups after an instance is launched in EC2-Classic?

- A. Yes, you can change security groups after you launch an instance in EC2-Classic.
- B. No, you cannot change security groups after you launch an instance in EC2-Classic.
- C. Yes, you can only when you remove rules from a security group.
- D. Yes, you can only when you add rules to a security grou

Answer: B

Explanation:

After you launch an instance in EC2-Classic, you can't change its security groups. However, you can add rules to or remove rules from a security group, and those changes are automatically applied to all instances that are associated with the security group.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 227

George has launched three EC2 instances inside the US-East-1a zone with his AWS account. Ray has launched two EC2 instances in the US-East-1a zone with his AWS account. Which of the below mentioned statements will help George and Ray understand the availability zone (AZ) concept better?

- A. All the instances of George and Ray can communicate over a private IP with a minimal cost
- B. The US-East-1a region of George and Ray can be different availability zones
- C. All the instances of George and Ray can communicate over a private IP without any cost
- D. The instances of George and Ray will be running in the same data centre

Answer: B

Explanation:

Each AWS region has multiple, isolated locations known as Availability Zones. To ensure that the AWS resources are distributed across the Availability Zones for a region, AWS independently maps the Availability Zones to identifiers for each account. In this case the Availability Zone US-East-1a where George's EC2 instances are running might not be the same location as the US-East-1a zone of Ray's EC2 instances. There is no way for the user to coordinate the Availability Zones between accounts.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-regions-availability-zones.html>

NEW QUESTION 231

You are in the process of moving your friend's WordPress site onto AWS to try and save him some money, and you have told him that he should probably also move his domain name. He asks why he can't leave his domain name where it is and just have his infrastructure on AWS. What would be an incorrect response to his question ?

- A. Route 53 offers low query latency for your end users.
- B. Route 53 is designed to automatically answer queries from the optimal location depending on network conditions.
- C. The globally distributed nature of AWS's DNS servers helps ensure a consistent ability to route your end users to your application.
- D. Route 53 supports Domain Name System Security Extensions (DNSSEC).

Answer: D

Explanation:

Amazon Route 53 provides highly available and scalable Domain Name System (DNS), domain name registration, and health-checking web services.

Route 53 is built using AWS's highly available and reliable infrastructure. The globally distributed nature of our DNS servers helps ensure a consistent ability to route your end users to your application by circumventing any internet or network related issues. Route 53 is designed to provide the level of dependability required by important applications. Using a global anycast network of DNS servers around the world, Route 53 is designed to automatically answer queries from the optimal location depending on network conditions. As a result, the service offers low query latency for your end users.

Amazon Route 53 does not support Domain Name System Security Extensions (DNSSEC) at this time. Reference: <https://aws.amazon.com/route53/faqs/>

NEW QUESTION 233

In Amazon EC2, you are billed instance-hours when .

- A. your EC2 instance is in a running state
- B. the instance exits from Amazon S3 console
- C. your instance still exits the EC2 console
- D. EC2 instances stop

Answer: A

Explanation:

You are billed instance-hours as long as your EC2 instance is in a running state. Reference: <http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 234

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB auto registration Off
- D. ELB connection draining

Answer: D

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/config-conn-drain.html>

NEW QUESTION 239

You need to quickly set up an email-sending service because a client needs to start using it in the next hour. Amazon Simple Email Service (Amazon SES) seems to be the logical choice but there are several options available to set it up. Which of the following options to set up SES would best meet the needs of the client?

- A. Amazon SES console
- B. AWS CloudFormation
- C. SMTP Interface
- D. AWS Elastic Beanstalk

Answer: A

Explanation:

Amazon SES is an outbound-only email-sending service that provides an easy, cost-effective way for you to send email.

There are several ways that you can send an email by using Amazon SES. You can use the Amazon SES console, the Simple Mail Transfer Protocol (SMTP)

interface, or you can call the Amazon SES API. Amazon SES console—This method is the quickest way to set up your system
Reference: <http://docs.aws.amazon.com/ses/latest/DeveloperGuide/Welcome.html>

NEW QUESTION 240

You have a Business support plan with AWS. One of your EC2 instances is running Microsoft Windows Server 2008 R2 and you are having problems with the software. Can you receive support from AWS for this software?

- A. Yes
- B. No, AWS does not support any third-party software.
- C. No, Microsoft Windows Server 2008 R2 is not supported.
- D. No, you need to be on the enterprise support plan

Answer: A

Explanation:

Third-party software support is available only to AWS Support customers enrolled for Business or Enterprise Support. Third-party support applies only to software running on Amazon EC2 and does not extend to assisting with on-premises software. An exception to this is a VPN tunnel configuration running supported devices for Amazon VPC.

Reference: <https://aws.amazon.com/premiumsupport/features/>

NEW QUESTION 242

In Amazon EC2, how many Elastic IP addresses can you have by default?

- A. 10
- B. 2
- C. 5
- D. 20

Answer: C

Explanation:

The number of Elastic IP addresses you can have in EC2 is 5.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 246

You need to create a load balancer in a VPC network that you are building. You can make your load balancer internal (private) or internet-facing (public). When you make your load balancer internal, a DNS name will be created, and it will contain the private IP address of the load balancer. An internal load balancer is not exposed to the internet. When you make your load balancer internet-facing, a DNS name will be created with the public IP address. If you want the Internet-facing load balancer to be connected to the Internet, where must this load balancer reside?

- A. The load balancer must reside in a subnet that is connected to the internet using the internet gateway.
- B. The load balancer must reside in a subnet that is not connected to the internet.
- C. The load balancer must not reside in a subnet that is connected to the internet.
- D. The load balancer must be completely outside of your VPC

Answer: A

Explanation:

When you create an internal Elastic Load Balancer in a VPC, you need to select private subnets that are in the same Availability Zone as your instances. If the VPC Elastic Load Balancer is to be public facing, you need to create the Elastic Load Balancer in a public subnet. A subnet is a public subnet if it is attached to an Internet Gateway (IGW) with a defined route to that gateway. Selecting more than one public subnet increases the availability of your Elastic Load Balancer.

NB - Elastic Load Balancers in EC2-Classic are always Internet-facing load balancers. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-internet-facing-load-balancers.html>

NEW QUESTION 250

Can you move a Reserved Instance from one Availability Zone to another?

- A. Yes, but each Reserved Instance is associated with a specific Region that cannot be changed.
- B. Yes, only in US-West-2.
- C. Yes, only in US-East-1.
- D. No

Answer: A

Explanation:

Each Reserved Instance is associated with a specific Region, which is fixed for the lifetime of the reservation and cannot be changed. Each reservation can, however, be used in any of the available AZs within the associated Region.

Reference: <https://aws.amazon.com/rds/faqs/>

NEW QUESTION 255

When controlling access to Amazon EC2 resources, each Amazon EBS Snapshot has a attribute that controls which AWS accounts can use the snapshot.

- A. createVolumePermission
- B. LaunchPermission
- C. SharePermission
- D. RequestPermission

Answer:

A

Explanation:

Each Amazon EBS Snapshot has a `createVolumePermission` attribute that you can set to one or more AWS Account IDs to share the AM with those AWS Accounts. To allow several AWS Accounts to use a particular EBS snapshot, you can use the snapshot's `createVolumePermission` attribute to include a list of the accounts that can use it.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/UsingIAM.html>

NEW QUESTION 257

Company B is launching a new game app for mobile devices. Users will log into the game using their existing social media account to streamline data capture. Company B would like to directly save player data and scoring information from the mobile app to a DynamoDB table named Score Data. When a user saves their game the progress data will be stored to the Game state 53 bucket. What is the best approach for storing data to DynamoDB and 53?

- A. Use an EC2 Instance that is launched with an EC2 role providing access to the Score Data DynamoDB table and the GameState 53 bucket that communicates with the mobile app via web services.
- B. Use temporary security credentials that assume a role providing access to the Score Data DynamoDB table and the Game State 53 bucket using web identity federation.
- C. Use Login with Amazon allowing users to sign in with an Amazon account providing the mobile app with access to the Score Data DynamoDB table and the Game State 53 bucket.
- D. Use an IAM user with access credentials assigned a role providing access to the Score Data DynamoDB table and the Game State 53 bucket for distribution with the mobile app.

Answer: B

Explanation:

Web Identity Federation

Imagine that you are creating a mobile app that accesses AWS resources, such as a game that runs on a mobile device and stores player and score information using Amazon 53 and DynamoDB. When you write such an app, you'll make requests to AWS services that must be signed with an AWS access key. However, we strongly recommend that you do not embed or distribute long-term AWS credentials with apps that a user downloads to a device, even in an encrypted store. Instead, build your app so that it requests temporary AWS security credentials dynamically when needed using web identity federation. The supplied temporary credentials map to an AWS role that has only the permissions needed to perform the tasks required by the mobile app.

With web identity federation, you don't need to create custom sign-in code or manage your own user identities. Instead, users of your app can sign in using a well-known identity provider (IdP) - such as Login with Amazon, Facebook, Google, or any other OpenID Connect (OIDC)-compatible IdP, receive an authentication token, and then exchange that token for temporary security credentials in AWS that map to an IAM role with permissions to use the resources in your AWS account. Using an IdP helps you keep your AWS account secure, because you don't have to embed and distribute longterm security credentials with your application.

For most scenarios, we recommend that you use Amazon Cognito because it acts as an identity broker and does much of the federation work for you. For details, see the following section, Using Amazon Cognito for Mobile Apps.

If you don't use Amazon Cognito, then you must write code that interacts with a web IdP (Login with Amazon, Facebook, Google, or any other OIDC-compatible IdP) and then calls the Assume Role With Web Identity API to trade the authentication token you get from those IdPs for AWS temporary security credentials. If you have already used this approach for existing apps, you can continue to use it.

Using Amazon Cognito for Nmobile Apps

The preferred way to use web identity federation is to use Amazon Cognito. For example, Adele the developer is building a game for a mobile device where user data such as scores and profiles is stored in Amazon 53 and Amazon DynamoDB. Adele could also store this data locally on the device and use Amazon Cognito to keep it synchronized across devices. She knows that for security and maintenance reasons, long-term AWS security credentials should not be distributed with the game. She also knows that the game might have a large number of users. For all of these reasons, she does not want to create new user identities in IAM for each player. Instead, she builds the game so that users can sign in using an identity that they've already established with a well-known identity provider, such as Login with Amazon, Facebook, Google, or any OpenID Connect (OIDC)-compatible identity provider.

Her game can take advantage of the authentication mechanism from one of these providers to validate the user's identity.

To enable the mobile app to access her AWS resources, Adele first registers for a developer 10 with her chosen IdPs. She also configures the application with each of these providers. In her AWS account that contains the Amazon 53 bucket and DynamoDB table for the game, Adele uses Amazon Cognito to create IAM roles that precisely define permissions that the game needs. If she is using an OIDC IdP, she also creates an IAM OIDC identity provider entity to establish trust between her AWS account and the IdP.

In the app's code, Adele calls the sign-in interface for the IdP that she configured previously. The IdP handles all the details of letting the user sign in, and the app gets an OAuth access token or OIDC ID token from the provider. Adele's app can trade this authentication information for a set of temporary security credentials that consist of an AWS access key 10, a secret access key, and a session token.

The app can then use these credentials to access web services offered by AWS. The app is limited to the permissions that are defined in the role that it assumes. The following figure shows a simplified flow for how this might work, using Login with Amazon as the IdP.

For Step 2, the app can also use Facebook, Google, or any OIDC-compatible identity provider, but that's not shown here.

Sample workflow using Amazon Cognito to federate users for a mobile application



A customer starts your app on a mobile device. The app asks the user to sign in. The app uses Login with Amazon resources to accept the user's credentials. The app uses Cognito APIs to exchange the Login with Amazon 10 token for a Cognito token. The app requests temporary security credentials from AWS STS, passing the Cognito token.

The temporary security credentials can be used by the app to access any AWS resources required by the app to operate. The role associated with the temporary

security credentials and its assigned policies determines what can be accessed.

Use the following process to configure your app to use Amazon Cognito to authenticate users and give your app access to AWS resources. For specific steps to accomplish this scenario, consult the documentation for Amazon Cognito.

(Optional) Sign up as a developer with Login with Amazon, Facebook, Google, or any other OpenID Connect (OIDC)-compatible identity provider and configure one or more apps with the provider. This step is optional because Amazon Cognito also supports unauthenticated (guest) access for your users.

Go to Amazon Cognito in the AWS IAM Management Console. Use the Amazon Cognito wizard to create an identity pool, which is a container that Amazon Cognito uses to keep end user identities organized for your apps. You can share identity pools between apps. When you set up an identity pool, Amazon Cognito creates one or two IAM roles (one for authenticated identities, and one for unauthenticated "guest" identities) that define permissions for Amazon Cognito users.

Download and integrate the AWS SDK for iOS or the AWS SDK for Android with your app, and import the files required to use Amazon Cognito.

Create an instance of the Amazon Cognito credentials provider, passing the identity pool ID, your AWS account number, and the Amazon Resource Name (ARN) of the roles that you associated with the identity pool. The Amazon Cognito wizard in the AWS Management Console provides sample code to help you get started.

When your app accesses an AWS resource, pass the credentials provider instance to the client object, which passes temporary security credentials to the client.

The permissions for the credentials are based on the role or roles that you defined earlier.

NEW QUESTION 260

You need a persistent and durable storage to trace call activity of an IVR (Interactive Voice Response) system. Call duration is mostly in the 2-3 minutes timeframe. Each traced call can be either active or terminated. An external application needs to know each minute the list of currently active calls, which are usually a few calls/second. Put once per month there is a periodic peak up to 1000 calls/second for a few hours. The system is open 24/7 and any downtime should be avoided.

Historical data is periodically archived to files. Cost saving is a priority for this project.

What database implementation would better fit this scenario, keeping costs as low as possible?

- A. Use RDS Multi-AZ with two tables, one for "Active calls" and one for "Terminated calls". In this way the "Active calls" table is always small and effective to access.
- B. Use DynamoDB with a "Calls" table and a Global Secondary Index on a "IsActive" attribute that is present for active calls only. In this way the Global Secondary index is sparse and more effective.
- C. Use DynamoDB with a "Calls" table and a Global secondary index on a "State" attribute that can equal to "active" or "terminated" in this way the Global Secondary index can be used for all items in the table.
- D. Use RDS Multi-AZ with a "CALLS" table and an Indexed "STATE" field that can be equal to "ACTIVE" or "TERMINATED". In this way the SQL query is optimized by the use of the Index.

Answer: A

NEW QUESTION 265

You would like to create a mirror image of your production environment in another region for disaster recovery purposes. Which of the following AWS resources do not need to be recreated in the second region? (Choose 2 answers)

- A. Route 53 Record Sets
- B. IAM Roles
- C. Elastic IP Addresses (EIP)
- D. EC2 Key Pairs
- E. Launch configurations
- F. Security Groups

Answer: AC

Explanation:

Reference:

http://tech.com/wp-content/themes/optimize/download/AWSDisaster_Recovery.pdf (page 6)

NEW QUESTION 269

You are responsible for a legacy web application whose server environment is approaching end of life. You would like to migrate this application to AWS as quickly as possible, since the application environment currently has the following limitations:

The VM's single 10GB VMDK is almost full. The virtual network interface still uses the 10Mbps driver, which leaves your 100Mbps WAN connection completely underutilized.

It is currently running on a highly customized Windows VM within a VMware environment. You do not have the installation media.


This is a mission critical application with an RTO (Recovery Time Objective) of 8 hours. RPO (Recovery Point Objective) of 1 hour. How could you best migrate this application to AWS while meeting your business continuity requirements?

- A. Use the EC2 VM Import Connector for vCenter to import the VM into EC2.
- B. Use Import/Export to import the VM as an ESS snapshot and attach to EC2.
- C. Use S3 to create a backup of the VM and restore the data into EC2.
- D. Use the ec2-bundle-instance API to import an image of the VM into EC2.

Answer: A

NEW QUESTION 274

Refer to the architecture diagram above of a batch processing solution using Simple Queue Service (SQS) to set up a message queue between EC2 instances which are used as batch processors. CloudWatch monitors the number of Job requests (queued messages) and an Auto Scaling group adds or deletes batch servers automatically based on parameters set in CloudWatch alarms. You can use this architecture to implement which of the following features in a cost effective and efficient manner?



- A. Reduce the overall time for executing jobs through parallel processing by allowing a busy EC2 instance that receives a message to pass it to the next instance in a daisy-chain setup.
- B. Implement fault tolerance against EC2 instance failure since messages would remain in SQS and work can continue with recovery of EC2 instances implement fault tolerance against SQS failure by backing up messages to S3.
- C. Implement message passing between EC2 instances within a batch by exchanging messages through SQS.
- D. Coordinate number of EC2 instances with number of job requests automatically thus Improving cost effectiveness.
- E. Handle high priority jobs before lower priority jobs by assigning a priority metadata field to SQS messages.

Answer: D

Explanation:

Reference:

There are cases where a large number of batch jobs may need processing, and where the jobs may need to be re-prioritized.

For example, one such case is one where there are differences between different levels of services for unpaid users versus subscriber users (such as the time until publication) in services enabling, for example, presentation files to be uploaded for publication from a web browser. When the user uploads a presentation file, the conversion processes, for example, for publication are performed as batch

processes on the system side, and the file is published after the conversion. Is it then necessary to be able to assign the level of priority to the batch processes for each type of subscriber.

Explanation of the Cloud Solution/Pattern

A queue is used in controlling batch jobs. The queue need only be provided with priority numbers. Job requests are controlled by the queue, and the job requests in the queue are processed by a batch server. In Cloud computing, a highly reliable queue is provided as a service, which you can use to structure a highly reliable batch system with ease. You may prepare multiple queues depending on priority levels, with job requests put into the queues depending on their priority levels, to apply prioritization to batch processes. The performance (number) of batch servers corresponding to a queue must be in accordance with the priority level thereof.

Implementation

In AWS, the queue service is the Simple Queue Service (SQS). Multiple SQS queues may be prepared to prepare queues for individual priority levels (with a priority queue and a secondary queue).

Moreover, you may also use the message Delayed Send function to delay process execution. Use SQS to prepare multiple queues for the individual priority levels. Place those processes to be executed immediately (job requests) in the high priority queue. Prepare numbers of batch servers, for processing the job requests of the queues, depending on the priority levels.

Queues have a message "Delayed Send" function. You can use this to delay the time for starting a process.

Configuration

Benefits

You can increase or decrease the number of servers for processing jobs to change automatically the processing speeds of the priority queues and secondary queues.

You can handle performance and service requirements through merely increasing or decreasing the number of EC2 instances used in job processing.

Even if an EC2 were to fail, the messages (jobs) would remain in the queue service, enabling processing to be continued immediately upon recovery of the EC2 instance, producing a system that is robust to failure.

Cautions

Depending on the balance between the number of EC2 instances for performing the processes and the number of messages that are queued, there may be cases where processing in the secondary queue may be completed first, so you need to monitor the processing speeds in the primary queue and the secondary queue.

NEW QUESTION 277

You have deployed a web application targeting a global audience across multiple AWS Regions under the domain name.example.com. You decide to use Route53 Latency-Based Routing to serve web requests to users from the region closest to the user. To provide business continuity in the event of server downtime you configure weighted record sets associated with two web servers in separate Availability Zones per region. During a DR test you notice that when you disable all web servers in one of the regions Route53 does not automatically direct all users to the other region. What could be happening? (Choose 2 answers)

- A. Latency resource record sets cannot be used in combination with weighted resource record sets.
- B. You did not setup an HTTP health check for one or more of the weighted resource record sets associated with the disabled web servers.
- C. The value of the weight associated with the latency alias resource record set in the region with the disabled servers is higher than the weight for the other region.
- D. One of the two working web servers in the other region did not pass its HTTP health check.
- E. You did not set "Evaluate Target Health" to "Yes" on the latency alias resource record set associated with example.com in the region where you disabled the servers.

Answer: BE

Explanation:

How Health Checks Work in Complex Amazon Route 53 Configurations

Checking the health of resources in complex configurations works much the same way as in simple configurations. However, in complex configurations, you use a combination of alias resource record sets (including weighted alias, latency alias, and failover alias) and nonalias resource record sets to build a decision tree that gives you greater control over how Amazon Route 53 responds to requests.

For more information, see [How Health Checks Work in Simple Amazon Route 53 Configurations](#).

For example, you might use latency alias resource record sets to select a region close to a user and use weighted resource record sets for two or more resources within each region to protect against the failure of a single endpoint or an Availability Zone. The following diagram shows this configuration.

Here's how Amazon EC2 and Amazon Route 53 are configured:

You have Amazon EC2 instances in two regions, us-east-1 and ap-southeast-2. You want Amazon Route 53 to respond to queries by using the resource record sets in the region that provides the lowest latency for your customers, so you create a latency alias resource record set for each region.

(You create the latency alias resource record sets after you create resource record sets for the individual Amazon EC2 instances.)

Within each region, you have two Amazon EC2 instances. You create a weighted resource record set for each instance. The name and the type are the same for both of the weighted resource record sets in each region.

When you have multiple resources in a region, you can create weighted or failover resource record sets for your resources. You can also create even more complex configurations by creating weighted alias or failover alias resource record sets that, in turn, refer to multiple resources.

Each weighted resource record set has an associated health check. The IP address for each health check matches the IP address for the corresponding resource record set. This isn't required, but it's the most common configuration.

For both latency alias resource record sets, you set the value of Evaluate Target Health to Yes.

You use the Evaluate Target Health setting for each latency alias resource record set to make Amazon Route 53 evaluate the health of the alias targets-the weighted resource record sets-and respond accordingly.

The preceding diagram illustrates the following sequence of events:

Amazon Route 53 receives a query for example.com. Based on the latency for the user making the request, Amazon Route 53 selects the latency alias resource record set for the us-east-1 region.

Amazon Route 53 selects a weighted resource record set based on weight. Evaluate Target Health is Yes for the latency alias resource record set, so Amazon Route 53 checks the health of the selected weighted resource record set.

The health check failed, so Amazon Route 53 chooses another weighted resource record set based on weight and checks its health. That resource record set also is unhealthy.

Amazon Route 53 backs out of that branch of the tree, looks for the latency alias resource record set with the next-best latency, and chooses the resource record set for ap-southeast-2.

Amazon Route 53 again selects a resource record set based on weight, and then checks the health of the selected resource record set. The health check passed, so Amazon Route 53 returns the applicable value in response to the query.

What Happens When You Associate a Health Check with an Alias Resource Record Set?

You can associate a health check with an alias resource record set instead of or in addition to setting the value of Evaluate Target Health to Yes. However, it's generally more useful if Amazon Route 53 responds to queries based on the health of the underlying resources- the HTTP servers, database servers, and other resources that your alias resource record sets refer to. For example, suppose the following configuration:

You assign a health check to a latency alias resource record set for which the alias target is a group of weighted resource record sets.

You set the value of Evaluate Target Health to Yes for the latency alias resource record set.

In this configuration, both of the following must be true before Amazon Route 53 will return the applicable value for a weighted resource record set:

The health check associated with the latency alias resource record set must pass.

At least one weighted resource record set must be considered healthy, either because it's associated with a health check that passes or because it's not associated with a health check. In the latter case, Amazon Route 53 always considers the weighted resource record set healthy.

If the health check for the latency alias resource record set fails, Amazon Route 53 stops responding to queries using any of the weighted resource record sets in the alias target, even if they're all healthy. Amazon Route 53 doesn't know the status of the weighted resource record sets because it never looks past the failed health check on the alias resource record set.

What Happens When You Omit Health Checks?

In a complex configuration, it's important to associate health checks with all of the non-alias resource record sets. Let's return to the preceding example, but assume that a health check is missing on one of the weighted resource record sets in the us-east-1 region:

Here's what happens when you omit a health check on a non-alias resource record set in this configuration:

Amazon Route 53 receives a query for example.com. Based on the latency for the user making the request, Amazon Route 53 selects the latency alias resource record set for the us-east-1 region.

Amazon Route 53 looks up the alias target for the latency alias resource record set, and checks the status of the corresponding health checks. The health check for one weighted resource record set failed, so that resource record set is omitted from consideration.

The other weighted resource record set in the alias target for the us-east-1 region has no health check. The corresponding resource might or might not be healthy, but without a health check, Amazon Route 53 has no way to know. Amazon Route 53 assumes that the resource is healthy and returns the applicable value in response to the query.

What Happens When You Set Evaluate Target Health to No?

In general, you also want to set Evaluate Target Health to Yes for all of the alias resource record sets. In the following example, all of the weighted resource record sets have associated health checks, but Evaluate Target Health is set to No for the latency alias resource record set for the us-east-1 region:

Here's what happens when you set Evaluate Target Health to No for an alias resource record set in this configuration:

Amazon Route 53 receives a query for example.com. Based on the latency for the user making the request, Amazon Route 53 selects the latency alias resource record set for the us-east-1 region.

Amazon Route 53 determines what the alias target is for the latency alias resource record set, and checks the corresponding health checks. They're both failing.

Because the value of Evaluate Target Health is No for the latency alias resource record set for the us-east-1 region, Amazon Route 53 must choose one resource record set in this branch instead of backing out of the branch and looking for a healthy resource record set in the ap-southeast-2 region.

NEW QUESTION 279

A customer has established an AWS Direct Connect connection to AWS. The link is up and routes are being advertised from the customer's end, however the customer is unable to connect from EC2 instances inside its VPC to servers residing in its datacenter.

Which of the following options provide a viable solution to remedy this situation? (Choose 2 answers)

- A. Add a route to the route table with an IPsec VPN connection as the target.
- B. Enable route propagation to the virtual pinnate gateway (VGW).
- C. Enable route propagation to the customer gateway (CGW).
- D. Modify the route table of all Instances using the 'route' command.
- E. Modify the Instances VPC subnet route table by adding a route back to the customer's on-premises environment.

Answer: AC

NEW QUESTION 281

You have deployed a three-tier web application in a VPC with a CIDR block of 10.0.0.0/28. You initially deploy two web servers, two application servers, two database servers and one NAT instance for a total of seven EC2 instances. The web, application and database servers are deployed across two availability zones (AZs). You also deploy an ELB in front of the two web servers, and use Route53 for DNS. Web traffic gradually increases in the first few days following the

deployment, so you attempt to double the number of instances in each tier of the application to handle the new load unfortunately some of these new instances fail to launch.

Which of the following could be the root cause? (Choose 2 answers)

- A. AWS reserves the first and the last private IP address in each subnet's CIDR block so you do not have enough addresses left to launch all of the new EC2 instances
- B. The Internet Gateway (IGW) of your VPC has scaled-up, adding more instances to handle the traffic spike, reducing the number of available private IP addresses for new instance launches
- C. The ELB has scaled-up, adding more instances to handle the traffic spike, reducing the number of available private IP addresses for new instance launches
- D. AWS reserves one IP address in each subnet's CIDR block for Route53 so you do not have enough addresses left to launch all of the new EC2 instances
- E. AWS reserves the first four and the last IP address in each subnet's CIDR block so you do not have enough addresses left to launch all of the new EC2 instances

Answer: CE

NEW QUESTION 283

You've been brought in as solutions architect to assist an enterprise customer with their migration of an e-commerce platform to Amazon Virtual Private Cloud (VPC). The previous architect has already deployed a 3-tier VPC. The configuration is as follows:

VPC: vpc-2f8bc447 IGW: igw-2d8bc445 NACL: ad-208bc448

Subnets and Route Tables: Web servers: subnet-258bc44d

Application servers: subnet-248bc44c Database servers: subnet-9189c6f9 Route Tables:

rtb-218bc449 rtb-238bc44b Associations:

subnet-258bc44d : rtb-218bc449 subnet-248bc44c : rtb-238bc44b subnet-9189c6f9 : rtb-238bc44b

You are now ready to begin deploying EC2 instances into the VPC. Web servers must have direct access to the internet. Application and database servers cannot have direct access to the internet.

Which configuration below will allow you the ability to remotely administer your application and database servers, as well as allow these servers to retrieve updates from the Internet?

- A. Create a bastion and NAT instance in subnet-258bc44d, and add a route from rtb-238bc44b to the NAT instance.
- B. Add a route from rtb-238bc44b to igw-2d8bc445 and add a bastion and NAT instance within subnet-248bc44c.
- C. Create a bastion and NAT instance in subnet-248bc44c, and add a route from rtb-238bc44b to subnet-258bc44d.
- D. Create a bastion and NAT instance in subnet-258bc44d, add a route from rtb-238bc44b to igw-2d8bc445, and a new NACL that allows access between subnet-258bc44d and subnet-248bc44c.

Answer: A

NEW QUESTION 288

You are migrating a legacy client-server application to AWS. The application responds to a specific DNS domain (e.g. www.example.com) and has a 2-tier architecture, with multiple application servers and a database server. Remote clients use TCP to connect to the application servers. The application servers need to know the IP address of the clients in order to function properly and are currently taking that information from the TCP socket. A Multi-AZ RDS MySQL instance will be used for the database. During the migration you can change the application code, but you have to file a change request.

How would you implement the architecture on AWS in order to maximize scalability and high availability?

- A. File a change request to implement Alias Resource support in the application
- B. Use Route 53 Alias Resource Record to distribute load on two application servers in different AZs.
- C. File a change request to implement Latency Based Routing support in the application
- D. Use Route 53 with Latency Based Routing enabled to distribute load on two application servers in different AZs.
- E. File a change request to implement Cross-Zone support in the application
- F. Use an ELB with a TCP Listener and Cross-Zone Load Balancing enabled, two application servers in different AZs.
- G. File a change request to implement Proxy Protocol support in the application
- H. Use an ELB with a TCP Listener and Proxy Protocol enabled to distribute load on two application servers in different AZs.

Answer: D

NEW QUESTION 293

A corporate web application is deployed within an Amazon Virtual Private Cloud (VPC) and is connected to the corporate data center via an IPsec VPN. The application must authenticate against the on-premises LDAP server. After authentication, each logged-in user can only access an Amazon Simple Storage Service (S3) bucket specific to that user.

Which two approaches can satisfy these objectives? (Choose 2 answers)

- A. Develop an identity broker that authenticates against IAM Security Token service to assume an IAM role in order to get temporary AWS security credentials. The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.
- B. The application authenticates against LDAP and retrieves the name of an IAM role associated with the user.
- C. The application then calls the IAM Security Token Service to assume that IAM role. The application can use the temporary credentials to access the appropriate S3 bucket.
- D. Develop an identity broker that authenticates against LDAP and then calls IAM Security Token Service to get IAM federated user credentials. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- E. The application authenticates against LDAP. The application then calls the AWS Identity and Access Management (IAM) Security service to log in to IAM using the LDAP credentials. The application can use the IAM temporary credentials to access the appropriate S3 bucket.
- F. The application authenticates against IAM Security Token Service using the LDAP credentials. The application uses those temporary AWS security credentials to access the appropriate S3 bucket.

Answer: BC

NEW QUESTION 296

You are designing a multi-platform web application for AWS. The application will run on EC2 instances and will be accessed from PCs, tablets and smart phones. Supported accessing platforms are Windows, MacOS, iOS and Android. Separate sticky session and SSL certificate setups are required for different platform types. Which of the following describes the most cost effective and performance efficient architecture setup?

- A. Setup a hybrid architecture to handle session state and SSL certificates on-prem and separate EC2 Instance groups running web applications for different platform types running in a VPC
- B. Set up one ELB for all platforms to distribute load among multiple instance under it Each EC2 instance implements ail functionality for a particular platform.
- C. Set up two ELBs The first ELB handles SSL certificates for all platforms and the second ELB handles session stickiness for all platforms for each ELB run separate EC2 instance groups to handle the web application for each platform.
- D. Assign multiple ELBS to an EC2 instance or group of EC2 instances running the common components of the web application, one ELB for each platform type Session stickiness and SSL termination are done at the ELBs.

Answer: D

NEW QUESTION 299

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your AWS-Solution-Architect-Associate Exam with Our Prep Materials Via below:

<https://www.certleader.com/AWS-Solution-Architect-Associate-dumps.html>