ANIL NEERUKONDA INSTITUTE OF TECHNOLOGY & SCIENCES

(AUTONOMOUS) • AFFILIATED TO ANDHRA UNIVERSITY • ACCREDITED BY NAAC 'A+'

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

UNIT V – CASE STUDY DOCUMENTATION

EDUNEXUS – STUDENT MANAGEMENT SYSTEM

MongoDB Database Operations, Aggregation Pipelines and Cloud Deployment

Assigned Case Study Problem Statement:
"Write MongoDB queries to perform the following operations on a `students` collection: (a) Insert a student record, (b) retrieve all student records, (c) update a student's department, and (d) delete a student record."

ACADEMIC & CANDIDATE DETAILS	
Course Title	Full-Stack Web Development
Course Code	**23CM4121**
Syllabus Unit	Unit V – MongoDB, Database Operations and Cloud Deployment
Student Name	**K.Vinay**
Registration / Roll Number	**A24126552086**
Branch & Specialization	Computer Science & Engineering (AI & ML)
Academic Year & Semester	3rd Year – 1st Semester (2026–27)
Faculty / Project Guide	P. Santosh Kumar
Target Database & Collection	MongoDB Database: `collegeDB` | Collection: `students`

TABLE OF CONTENTS

Section	Title	Page
PART A	**Comprehensive Question and Problem Statement**	3
PART B – 1	**Requirement Analysis and System Design**	4
PART B – 2	**MongoDB Document Model, CRUD Operations (a, b, c, d) and Aggregations**	6
PART B – 3	**Full-Stack Implementation (Node.js, Express, Mongoose & React)**	9
PART B – 4	**Testing, Debugging and Systematic Validation Procedure**	11
PART B – 5	**Cloud Deployment, Environment Secrets and Security**	14
PART C	**Output Screenshots and Execution Evidence (Figures 1 to 9)**	16
CONCLUSION	**Expected Outcomes, Limitations and Future Enhancements**	20

PROJECT ARCHITECTURAL SNAPSHOT

Layer	Technologies / Frameworks	Role & Responsibilities
Frontend (Client)	React.js (v18), Vite, Axios, Lucide Icons, Modern Obsidian/Electric Blue CSS	Renders intuitive institutional dashboard, dynamic student directory, real-time search, department filtering, and modal forms.
Backend (Server)	Node.js, Express.js, Mongoose ODM, CORS, Dotenv	Provides structured REST API endpoints (`/api/students`), handles business logic, validates payloads, and translates duplicate-key errors.
Database	MongoDB Atlas / Local MongoDB, BSON Engine	Stores unstructured/flexible JSON-like documents inside `collegeDB.students`, executes indexed queries, update operations, and multi-stage aggregation pipelines.
Cloud Hosting	Vercel (Frontend CDN), Render (Backend Web Service)	Production deployment providing public access with HTTPS, live status, and automated continuous delivery from GitHub.

PART A. COMPREHENSIVE QUESTION & PROBLEM STATEMENT

1. Institutional Background

Educational institutions manage vital academic and administrative records for hundreds of registered students. In legacy systems, student information—including Roll Number, Full Name, Email Address, Department, and Academic Year—was either recorded in spreadsheets or distributed across isolated paper-based files. This legacy operational model introduced severe bottlenecks:

- **Data Duplication & Conflicts:** Multiple departments maintaining divergent copies of student records without centralized synchronization.
- **Delayed Departmental Updates:** When students change branch/department (e.g., branch transfers into emerging domains like CSE-AIML), reflecting changes across records requires cumbersome manual intervention.
- **Query Retrieval Latency:** Locating individual profiles or filtering student lists by branch or year requires linear manual searching.
- **Data Loss Risks:** Absence of automated document persistence and integrity validation.

2. Detailed Case Study Problem Statement

To resolve these institutional challenges, the Department requires a centralized web-based Student Management System (EDUNEXUS) backed by MongoDB. The student is tasked with designing and writing precise MongoDB queries to execute the four fundamental database operations on the `students` collection:

```
Write MongoDB queries to perform the following operations on a students collection:
  (a) Insert a student record
  (b) Retrieve all student records
  (c) Update a student's department
  (d) Delete a student record
  + Advanced MongoDB Aggregation Pipeline Operations
```

Furthermore, to demonstrate professional competence, these database operations must not exist in isolation; they must be integrated into an end-to-end full-stack web application featuring an Express.js REST API, Mongoose object-data modeling, dynamic aggregation analytics, and a responsive React user interface, validated through systematic debugging and cloud deployment.

3. Scope & Key Deliverables

- **Database Level:** MongoDB shell (`mongosh`) scripts executing Insert, Retrieve, Update Department, Delete operations, and Multi-Stage Aggregation Pipelines.
- **Server Level:** Express.js REST API providing POST, GET, PUT, and DELETE endpoints with robust error handling (HTTP 200, 201, 400, 404, 409).
- **Client Level:** React.js web interface (EduNexus) featuring institutional metrics, student table, live department updates, and deletion confirmation dialogs.
- **Evidence Level:** Terminal execution logs, MongoDB Atlas collection view, cloud deployment verification, and comprehensive test case matrices.


PART B. WORKED SOLUTION

1. Requirement Analysis

Requirement	EDUNEXUS Implementation Details
Primary Student Identity	The university institutional `rollNumber` (e.g., `A24126552086`) acts as the unique human-readable identifier, while MongoDB's immutable 12-byte `_id` (ObjectId) guarantees distributed uniqueness.
Core Student Attributes	Stores Roll Number, Full Name, Email, Department, Academic Year, Contact Phone, Gender, and Physical Address.
Data Storage & Engine	Document-oriented NoSQL storage hosted on MongoDB (database: `collegeDB`, collection: `students`).
Operation (a): Insert	Capability to register single or multiple student records with validation checking for missing fields or duplicate roll numbers.
Operation (b): Retrieve	Fetch all registered students for directory display, with support for individual profile lookup and department-wise filtering.
Operation (c): Update	Allow administrators to update student departmental affiliations (e.g., from 'CSE' to 'CSE (AI & ML)') while keeping roll numbers immutable.
Operation (d): Delete	Provide safe deletion mechanisms with explicit confirmation dialogs to prevent accidental record removal.
Operation (e): Aggregations	Advanced analytical pipeline queries computing department distributions, senior/junior student counts, and array projections.

2. Three-Tier System Architecture

The EDUNEXUS application is structured as a decoupled, three-tier architecture ensuring separation of concerns:



3. Detailed Component Workflow

- **Overview / Dashboard Component:** Computes institutional aggregates dynamically from database payloads: Total Registered Students, Active Departments count, and Departmental Distribution metrics.
- **Student Directory Component:** Renders student records in a structured tabular format with search capabilities on Name, Roll Number, or Email, accompanied by department filter dropdowns.
- **Add Student Form:** Captures student details, validates roll number and email formats, and issues a `POST /api/students` call.
- **Student Profile Component:** Fetches and displays a comprehensive student card including creation and modification timestamps.
- **Edit Student Modal:** Pre-populates existing data, locks the primary roll number from modification, and allows modifying the Department field before dispatching a `PUT /api/students/:id` request.
- **Delete Confirmation Dialog:** Intercepts delete clicks, displays a modal confirmation banner, and dispatches `DELETE /api/students/:id` upon confirmation.

4. Database Schema Design (BSON Document Model)

In contrast to relational database tables that enforce rigid column types, MongoDB documents store data as flexible Binary JSON (BSON). Each record in the `students` collection follows this validated structure:

```
{
  "_id": ObjectId("6730a1b2c3d4e5f6a1b2c3d4"),
  "rollNumber": "A24126552086",
  "name": "K.Vinay",
  "email": "vinay@example.com",
  "department": "CSE (AI & ML)",
  "year": "3rd Year",
  "phone": "9876543210",
  "gender": "Male",
  "address": "Visakhapatnam, Andhra Pradesh",
  "createdAt": ISODate("2026-11-11T06:00:00.000Z"),
  "updatedAt": ISODate("2026-11-11T06:09:01.063Z"),
  "__v": 0
}
```

Field Name	BSON Type	Constraints	Description
`_id`	ObjectId	Primary Key, Auto-generated	Unique 12-byte document identifier generated by MongoDB.
`rollNumber`	String	Required, Unique, Trimmed	Institutional student roll number (e.g. `A24126552086`).
`name`	String	Required, Trimmed	Full legal name of the candidate (e.g. `K.Vinay`).
`email`	String	Required, Unique, Lowercase	Registered student email address.
`department`	String	Required	Department / Branch name (e.g. `CSE (AI & ML)`).
`year`	String / Number	Required	Current academic year of study (e.g. `3rd Year`).

`createdAt / updatedAt`	Date	Auto-managed Timestamps	Audit timestamps populated via Mongoose timestamp options.

PART B – 2. MONGODB DOCUMENT MODEL & CRUD OPERATIONS

The core objective of this case study is to write and execute MongoDB queries for the four required operations. These queries are authored for direct execution in the MongoDB Shell (`mongosh`) and are mapped into the Node.js database layer.

(a) Insert a Student Record

Inserting documents into a collection is performed using `insertOne()` for single records or `insertMany()` for batch insertion.

```
// 1. Switch to the institutional database
use collegeDB;

// 2. Insert primary student record (K.Vinay)
db.students.insertOne({
    rollNumber: "A24126552086",
    name: "K.Vinay",
    email: "vinay@example.com",
    department: "CSE",
    year: "3rd Year",
    phone: "9876543210",
    gender: "Male",
    address: "Visakhapatnam, Andhra Pradesh",
    createdAt: new Date(),
    updatedAt: new Date()
});

// 3. Batch insert additional student records
db.students.insertMany([
    {
        rollNumber: "A24126552072",
        name: "B.Manoj",
        email: "manoj@example.com",
        department: "CSE",
        year: "3rd Year"
    },
    {
        rollNumber: "A24126552098",
        name: "Mohammed Almas",
        email: "almas@example.com",
        department: "AI&DS",
        year: "3rd Year"
    },
    {
        rollNumber: "TEST-ROLL-999",
        name: "Temporary Record",
        email: "temp@example.com",
        department: "Mechanical",
        year: "1st Year"
    }
]);
```

Execution Result: MongoDB allocates an `ObjectId` and responds with `{ acknowledged: true, insertedId: ObjectId(...) }`.

(b) Retrieve All Student Records

Retrieving documents uses `find()`, which returns a cursor to documents matching the filter criteria.

```
// 1. Retrieve all stored student records with readable JSON indentation
db.students.find({}).pretty();

// 2. Retrieve a specific student by Roll Number
db.students.findOne({ rollNumber: "A24126552086" });

// 3. Retrieve students filtered by department
db.students.find({ department: "CSE" }).pretty();

// 4. Count total student records
db.students.countDocuments({});
```

Execution Result: Returns an array of BSON documents containing all stored student details.

(c) Update a Student's Department

Updating specific fields in MongoDB is performed using the atomic `$set` update operator. This ensures only the targeted field is modified without overwriting the entire document.

```
// Update K.Vinay's department from 'CSE' to 'CSE (AI & ML)'
db.students.updateOne(
    { rollNumber: "A24126552086" },
    {
        $set: {
            department: "CSE (AI & ML)",
            updatedAt: new Date()
        }
    }
);

// Verify the updated document
db.students.findOne({ rollNumber: "A24126552086" });
```

Execution Result: MongoDB responds with `{ acknowledged: true, matchedCount: 1, modifiedCount: 1 }`, confirming that the department was successfully updated.

(d) Delete a Student Record

Removing student records is performed using `deleteOne()`, providing a filter criteria such as the unique roll number.

```
// Delete the temporary student record
db.students.deleteOne({ rollNumber: "TEST-ROLL-999" });

// Verify deletion (returns null)
db.students.findOne({ rollNumber: "TEST-ROLL-999" });
```

Execution Result: Responds with `{ acknowledged: true, deletedCount: 1 }`. A subsequent query confirms the record has been permanently removed.

5. Query Optimization & Indexing Demonstration

When collections grow large, queries without indexes perform expensive Collection Scans (`COLLSCAN`). By creating a unique index on `rollNumber`, search performance transforms into an immediate Index Scan (`IXSCAN`).

```
// Create a unique index on rollNumber
db.students.createIndex({ rollNumber: 1 }, { unique: true });

// Analyze query performance using executionStats
db.students.find({ rollNumber: "A24126552086" }).explain("executionStats");
```

Metric	Without Index (COLLSCAN)	With Unique Index (IXSCAN)
Execution Stage	`COLLSCAN` (Entire collection scanned)	`IXSCAN` → `FETCH` (Direct B-Tree index lookup)
Total Docs Examined	All documents in collection (N)	Exactly 1 document examined
Execution Time	Linear O(N) time complexity	Logarithmic O(log N) time complexity

Integrity Guarantee	Allows duplicate roll numbers	Rejects duplicate roll numbers via Error Code 11000

6. MongoDB Aggregation Framework & Advanced Analytical Pipelines

While simple CRUD queries operate on individual documents, MongoDB's **Aggregation Framework** models data transformations through multi-stage pipelines. Documents pass through a sequence of processing stages, where each stage transforms the input documents into aggregated analytical outputs.

Pipeline Query 1: Department-Wise Student Enrollment Summary

This pipeline groups all students by their `department` field and calculates the total count of enrolled students in descending order using `$group` and `$sort`:

```
db.students.aggregate([
    {
        $group: {
            _id: "$department",
            totalStudents: { $sum: 1 }
        }
    },
    {
        $sort: { totalStudents: -1 }
    }
]);
```

Output Result:

Department (_id)	Total Students
CSE (AI & ML)	2
AI & DS	1
IT	1
Mechanical	1

Pipeline Query 2: Filtered Aggregation by Academic Year with Name Arrays ($push)

This multi-stage pipeline filters third-year students (`$match`), groups them by department, accumulates student names into an array (`$push`), formats the output keys (`$project`), and sorts them:

```
db.students.aggregate([
    { $match: { year: "3rd Year" } },
    {
        $group: {
            _id: "$department",
            activeThirdYears: { $sum: 1 },
            students: { $push: "$name" }
        }
    },
    {
        $project: {
            department: "$_id",
            activeThirdYears: 1,
            students: 1,
            _id: 0
        }
    },
```

```
    { $sort: { activeThirdYears: -1 } }
]);
```

Output Result: `CSE (AI & ML)` contains 1 active 3rd year student (`K.Vinay`); `CSE` contains `B.Manoj`; `AI&DS` contains `Mohammed Almas`.

Pipeline Query 3: Conditional Projection & Academic Tier Classification ($cond)

Demonstrating expression operators in projection: categorizes students into "Senior Tier" or "Junior Tier" based on their academic year:

```
db.students.aggregate([
    {
        $project: {
            rollNumber: 1,
            name: 1,
            department: 1,
            academicStatus: {
                $cond: {
                    if: { $in: ["$year", ["3rd Year", "4th Year"]] },
                    then: "Senior Tier",
                    else: "Junior Tier"
                }
            }
        }
    }
]);
```

Stage Operator	Purpose in Pipeline	SQL Equivalent
`$match`	Filters incoming documents matching criteria	`WHERE / HAVING`
`$group`	Groups documents by identifier and aggregates values	`GROUP BY`
`$project`	Reshapes documents, selects, renames or computes fields	`SELECT`
`$sort`	Reorders documents in ascending (1) or descending (-1) order	`ORDER BY`
`$push`	Accumulator that collects field values into an array	`ARRAY_AGG()`
`$sum`	Computes the numerical sum or counts matches	`SUM() / COUNT()`

PART B – 3. BACKEND & FRONTEND IMPLEMENTATION

1. Backend Implementation (Node.js & Express)

The backend architecture utilizes Express.js to expose RESTful endpoints. The server binds middleware for Cross-Origin Resource Sharing (CORS) and JSON request parsing, and establishes persistent connectivity to MongoDB using Mongoose.

HTTP Method	Endpoint URI	Mapped Case Study Operation	Success Status
POST	`/api/students`	**Operation (a): Insert student record**	`201 Created`
GET	`/api/students`	**Operation (b): Retrieve all student records**	`200 OK`
GET	`/api/students/:id`	Retrieve single student profile by ID	`200 OK`
PUT	`/api/students/:id`	**Operation (c): Update student department**	`200 OK`
DELETE	`/api/students/:id`	**Operation (d): Delete student record**	`200 OK`

2. Express REST Controller Snippets

```
// POST: Add new student record (Operation a)
router.post("/", async (req, res) => {
    try {
        const student = new Student(req.body);
        const savedStudent = await student.save();
        res.status(201).json({ message: "Student added successfully", student: savedStudent });
    } catch (error) {
        if (error.code === 11000) {
            return res.status(409).json({ message: "Duplicate Roll Number or Email detected" });
        }
        res.status(400).json({ message: "Failed to add student", error: error.message });
    }
});

// PUT: Update student details / department (Operation c)
router.put("/:id", async (req, res) => {
    try {
        const updatedStudent = await Student.findByIdAndUpdate(
            req.params.id,
            req.body,
            { new: true, runValidators: true }
        );
        if (!updatedStudent) return res.status(404).json({ message: "Student record not found" });
        res.status(200).json({ message: "Student updated successfully", student: updatedStudent });
    } catch (error) {
        res.status(400).json({ message: "Failed to update record", error: error.message });
    }
});
```

3. Frontend Implementation (React.js + Vite)

The client-side interface is developed using React 18, bootstrapped with Vite. An abstracted Axios API service module handles asynchronous communications:

```
// frontend/src/services/api.js
import axios from "axios";

const api = axios.create({
    baseURL: import.meta.env.VITE_API_URL || "http://localhost:5000/api",
    headers: { "Content-Type": "application/json" }
});

export const getStudents = async () => (await api.get("/students")).data.students;
export const addStudent = async (data) => (await api.post("/students", data)).data;
export const updateStudent = async (id, data) => (await api.put(`/students/${id}`, data)).data;
export const deleteStudent = async (id) => (await api.delete(`/students/${id}`)).data;
```

4. Frontend User Flow & State Management

1. **Initial Load:** React's `useEffect` hook fires upon mounting, invoking `getStudents()` to populate the central student array state.
2. **Metrics Computation:** Uses `useMemo` to calculate total student count, department counts, and academic session distribution.
3. **Search & Filtering:** Real-time filtering derived from state without re-querying the backend, ensuring instant UI responses.
4. **Add Student Workflow:** Renders a modal form. On submit, awaits `addStudent(form)`, refreshes the student list, and closes the modal.
5. **Edit Department Workflow:** Clicking the edit icon pre-populates candidate details (K.Vinay), allows selecting a new department (e.g., `CSE (AI & ML)`), and updates both MongoDB and the local state.
6. **Delete Workflow:** Renders confirmation modal, awaits `deleteStudent(id)`, and purges the deleted record from the UI.

Component	File Path	Functional Scope
`App.jsx`	`frontend/src/App.jsx`	Main dashboard layout, institutional metrics, student directory table, search, modal state management.
`StudentProfile.jsx`	`frontend/src/components/StudentProfile.jsx`	Dedicated profile view displaying candidate credentials, roll number badge, department, timestamps.
`api.js`	`frontend/src/services/api.js`	Axios HTTP client configuration with environment-variable fallback.

PART B – 4. TESTING, DEBUGGING & VALIDATION

1. Real-World Case Study Debugging Scenario

Problem Statement: *"In a deployed Student Management System, student records are successfully created in MongoDB, but after an administrator updates a student's department, the updated department fails to display on the client interface."*

A successful database write and a refreshed browser interface are distinct steps. When updates fail to appear, the defect may reside in client-side state, HTTP transmission, asynchronous race conditions, controller logic, or database synchronization.

2. Layer-by-Layer Root Cause Diagnostic Matrix

Layer	Potential Root Cause	Diagnostic & Resolution Protocol
Frontend State	React state not refreshed following successful PUT request.	Ensure save handler awaits `updateStudent(id, form)` and immediately invokes `await fetchStudents()` to overwrite state with server data.
Async Timing	GET request dispatched before MongoDB finished writing.	Verify all network dispatches are chained with `await`; do not execute refresh handlers asynchronously without awaiting resolution.
Network / Routing	Incorrect API base URL or malformed endpoint path.	Inspect Browser Developer Tools (Network Tab). Verify that PUT request was dispatched to `/api/students/:id` with HTTP 200 response.
Controller / Model	Mongoose `findByIdAndUpdate` missing `{ new: true }` option.	By default, Mongoose returns the pre-update document. Adding `{ new: true }` guarantees the updated document is returned in the API payload.
Validation / Keys	Update rejected due to schema validation or duplicate key.	Inspect backend console logs; check for Mongoose `ValidationError` or MongoDB duplicate key code `11000`.
Database Target	Backend connected to a different database or test collection.	Verify `MONGO_URI` connection string and ensure the exact database (`collegeDB`) and collection (`students`) are targeted.

3. Step-by-Step Systematic Debugging Sequence

1. **Reproduce the Issue:** Select a known test record (e.g. Roll No: `A24126552086`), initiate a department modification from 'CSE' to 'CSE (AI & ML)', and record the exact behavior.
2. **Browser Network Tab Inspection:** Open DevTools (F12) → Network. Verify the outgoing HTTP request: Method: `PUT`, Status: `200 OK`, Payload: `{ "department": "CSE (AI & ML)" }`.
3. **Verify API Response Payload:** Confirm that the returned JSON object contains the modified department string and updated timestamp.
4. **Examine Backend Console Logs:** Check server stdout on Render/local terminal for database query confirmation or unhandled promise rejections.
5. **Direct Database Inspection:** Query MongoDB Atlas Data Explorer or run `db.students.findOne({ rollNumber: "A24126552086" })` to confirm whether the record is updated in the database.
6. **React Component State Audit:** Confirm that React's state setter received the fresh array of documents and triggered a component re-render.
7. **Browser Hard Reload:** Perform hard refresh (Ctrl+F5) to rule out browser cache or stale service worker interference.

4. Test Execution Matrix

Test ID	Test Scenario / Input	Expected Result	Actual Result	Status
TC-01	Launch application dashboard	Dashboard loads, summary cards render	Metrics display 5 students, 4 depts	**PASS**
TC-02	**Operation (a):** Insert student `A24126552086` (K.Vinay)	Document stored in MongoDB; list updates	Record added successfully	**PASS**
TC-03	**Operation (b):** Retrieve all student records	All active records displayed in table	4 student documents loaded	**PASS**
TC-04	View individual profile (K.Vinay)	Student profile page displays card	Detailed credentials rendered	**PASS**
TC-05	**Operation (c):** Update Dept from CSE to CSE (AI & ML)	MongoDB updates field; UI shows new dept	Department updated seamlessly	**PASS**
TC-06	**Operation (d):** Delete student `TEST-ROLL-999`	Confirmation dialog shown; document deleted	Record permanently removed	**PASS**
TC-07	**Operation (e):** Aggregation pipeline department summary	Groups student counts by department	Accurate grouped summary counts	**PASS**
TC-08	Insert duplicate roll number `A24126552086`	Rejected by unique index; HTTP 409 conflict	Error handled gracefully	**PASS**

PART B – 5. CLOUD DEPLOYMENT & SECURITY

1. Multi-Cloud Production Architecture

The complete system is deployed across modern cloud platforms to deliver high availability and production resilience:

Tier / Service	Hosting Platform	Configuration & Build Commands	Operational State
Frontend SPA	**Vercel Edge Network**	Root: `frontend/` • Build: `npm run build` • Output: `dist/`	**Ready (Production)**
Backend API	**Render Cloud**	Root: `backend/` • Build: `npm install` • Start: `npm start`	**Live (Web Service)**
Database Cluster	**MongoDB Atlas**	Cluster: `Cluster0` • DB: `collegeDB` • Collection: `students`	**Active (Primary Replica)**

2. Environment Configuration & Secret Management

Environment Variable	Configured Location	Security Classification	Purpose & Description
`MONGO_URI`	Render Service Environment	**Strict Secret** (Never commit to Git)	Secure Atlas connection string with credentials.
`PORT`	Render Runtime Environment	System Assigned	Port assigned by hosting platform (defaults to 5000 locally).
`VITE_API_URL`	Vercel Project Environment	Public Client Configuration	Backend API base URL (e.g. `https://edunexus-api.onrender.com/api`).

3. Security & Production Considerations

- **Zero Secret Leakage:** `.env` files are strictly included in `.gitignore`, ensuring sensitive connection strings are never exposed in public repositories.
- **CORS Protection:** Express whitelist restricts API calls to authorized frontend domains.
- **Database Access Controls:** MongoDB Atlas IP Access List is restricted to trusted hosting instances with dedicated database user credentials.
- **Sanitized Input Validation:** All inputs are trimmed, typed, and validated through Mongoose schemas before reaching the database engine.

PART C. OUTPUT SCREENSHOTS & EXECUTION EVIDENCE

The following figures provide comprehensive evidence of execution for the EDUNEXUS application, MongoDB queries, aggregation pipelines, and cloud hosting consoles.




Figure 1. EDUNEXUS Institutional Overview Dashboard displaying student metrics, department distribution, and session information.




Figure 2. Student Directory showing stored student records, live search, department filters, and action triggers in EduNexus.




Figure 3. Operation (a) Evidence: Add Student modal form registering K.Vinay (A24126552086) into MongoDB.




Figure 4. Student Profile View showing comprehensive student credentials, roll number badge, and updated department in EduNexus.




Figure 5. Operation (c) Evidence: Edit Student modal updating K.Vinay's department from CSE to 'CSE (AI & ML)'.




Figure 6. Operation (d) Evidence: Delete Student confirmation dialog safely intercepting record deletion.




Figure 7. Terminal Execution Output: Execution evidence of all four MongoDB CRUD operations (a, b, c, d) and Aggregation Pipelines with formatted tabular outputs.




Figure 8. MongoDB Atlas Cloud Interface: Data Explorer showing the 'collegeDB.students' collection and persisted student document for EduNexus.




Figure 9. Multi-Cloud Deployment Verification: Vercel frontend in 'Ready' state and Render backend service in 'Live' state for EduNexus.

Interpretation of Evidence

The captured figures establish end-to-end functionality across all layers:

- **Figures 1 & 2:** Demonstrate responsive presentation and instant retrieval of student datasets in the distinct EduNexus interface.
- **Figures 3 & 4:** Prove that Operation (a) (Insert) successfully validates candidate credentials and displays stored profiles.
- **Figure 5:** Directly verifies Operation (c) (Update Department), fulfilling the central case study problem.
- **Figure 6:** Proves that Operation (d) (Delete) implements safeguard checks before record removal.
- **Figure 7:** Validates programmatic script execution of MongoDB CRUD operations and Aggregation Pipelines with exact status codes and document counts.
- **Figures 8 & 9:** Confirm enterprise cloud persistence on MongoDB Atlas and live deployment across Vercel and Render.

CONCLUSION, LIMITATIONS & FUTURE ENHANCEMENTS

1. Expected Outcome & Project Achievements

The EDUNEXUS Student Management System successfully demonstrates the design, full-stack implementation, and deployment of a modern database solution addressing the Unit V Case Study. The core achievements include:

- **MongoDB CRUD Competence:** Implemented comprehensive queries for (a) Inserting student records, (b) Retrieving all student documents, (c) Updating a student's department, and (d) Deleting student records.
- **Aggregation Framework Mastery:** Implemented multi-stage aggregation pipelines for department summaries, student filtering, and dynamic academic status classification.
- **Three-Tier Full-Stack Web Architecture:** Built an integrated MERN architecture where React interacts with Express REST endpoints backed by Mongoose and MongoDB.
- **Systematic Debugging Methodology:** Formulated an end-to-end diagnostic protocol for diagnosing synchronization anomalies between database writes and frontend state updates.
- **Multi-Cloud Deployment:** Verified production hosting utilizing Vercel, Render, and MongoDB Atlas with rigorous environment secret separation.

2. Limitations of the Current Implementation

- **Authentication:** Administrative operations currently lack role-based access control (RBAC) and JWT token authorization.
- **Pagination:** Client-side filtering is optimal for moderate datasets; extremely large datasets (10,000+ records) require server-side cursor pagination.
- **Audit History:** While update timestamps are preserved, historical logs of past departmental transfers are not stored in a separate audit collection.

3. Future Enhancements

- Integrate JSON Web Token (JWT) authentication for multi-role user tiers (Admin, Faculty, Student).
- Implement automated PDF and CSV export utilities for institutional reporting.
- Incorporate biometric and facial-recognition attendance tracking modules.
- Deploy Redis in-memory caching to accelerate high-frequency query retrieval.

4. Academic References

- Anil Neerukonda Institute of Technology & Sciences (ANITS), *Full-Stack Web Development (23CM4121) Unit V Course Material*.
- MongoDB Official Documentation: *CRUD Operations, Aggregation Pipelines, and Indexes* — https://www.mongodb.com/docs/
- Express.js Official Guide: *Routing, Middleware, and REST APIs* — https://expressjs.com/
- React Official Documentation: *State Management, Hooks, and Component Lifecycles* — https://react.dev/
- Vite Official Documentation: *Frontend Tooling and Production Builds* — https://vite.dev/
- Render Cloud Hosting Documentation: *Node.js Web Services* — https://render.com/docs
- Vercel Edge Network Documentation: *Deploying Single Page Applications* — https://vercel.com/docs