

In [1]:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

In [2]:

```
print(sns.__version__)
```

0.12.2

In [3]:

```
print(sns.get_dataset_names())
```

```
['anagrams', 'anscombe', 'attention', 'brain_networks', 'car_crashes', 'diamonds', 'dolls', 'dowjones', 'exercise', 'flights', 'fmri', 'geyser', 'glucose', 'healthexp', 'iris', 'mpg', 'penguins', 'planets', 'seaice', 'taxis', 'tips', 'titanic']
```

In [4]:

```
# df = pd.read_csv(r'C:\Users\divesh\Downloads\archive\tips.csv')
#df = pd.read_csv('tips.csv')
#df.head()
df = sns.load_dataset('tips')
df.head()
```

Out[4]:

	total_bill	tip	sex	smoker	day	time	size
0	16.99	1.01	Female	No	Sun	Dinner	2
1	10.34	1.66	Male	No	Sun	Dinner	3
2	21.01	3.50	Male	No	Sun	Dinner	3
3	23.68	3.31	Male	No	Sun	Dinner	2
4	24.59	3.61	Female	No	Sun	Dinner	4

In [5]:

```
df.dtypes
```

Out[5]:

```
total_bill    float64
tip           float64
sex           category
smoker        category
day           category
time          category
size          int64
dtype: object
```

In [6]:

```
df.describe(include='category')
```

Out[6]:

	sex	smoker	day	time
count	244	244	244	244
unique	2	2	4	2
top	Male	No	Sat	Dinner
freq	157	151	87	176

## BI-VARIANT GRAPHS

### CONTINUOUS vs CONTINUOUS

In [7]:

```
df.columns
```

Out[7]:


```
Index(['total_bill', 'tip', 'sex', 'smoker', 'day', 'time', 'size'], dtype='object')
```

In [8]:

```
sns.relplot(data=df, x='total_bill',y='tip')
```


Out[8]:

<seaborn.axisgrid.FacetGrid at 0x25e47613430>




In [9]:

```
sns.relplot(data = df,x = 'total_bill',y='tip')  
plt.show()
```




In [10]:

```
sns.scatterplot(data=df,x='total_bill',y='tip')  
plt.show()
```



In [11]:

```
sns.lineplot(data=df,x='total_bill',y='tip')  
plt.show()
```




# UNI-VARIANT GRAPHS

## CONTINUOUS


In [12]:

```
sns.displot(data=df,x='total_bill')  
plt.show()
```



In [13]:


```
# kernel density estimate  
sns.displot(data=df,x='total_bill',kde=True)  
plt.show()
```






In [14]:

```
sns.histplot(data=df,x ='total_bill')  
plt.show()
```




In [15]:

```
sns.kdeplot(data=df,x='total_bill')  
plt.show()
```




In [16]:

```
sns.ecdfplot(data=df,x='total_bill')  
plt.show()
```



In [17]:

```
sns.rugplot(data=df,x='total_bill')  
plt.show()
```




## BI-VARIANT

### CATEGORICAL VS CONTINUOUS


In [18]:

```
sns.catplot(data=df, x='day', y="total_bill")  
plt.show()
```




In [19]:

```
sns.stripplot(data=df, x='day', y="total_bill")  
plt.show()
```



In [20]:

```
sns.swarmplot(data=df, x='day', y="total_bill")  
plt.show()
```




# UNI-VARIANT GRAPHS

## CONTINUOUS - OUTLIERS

In [21]:


```
sns.boxplot(data=df,x='total_bill')  
plt.show()
```






In [22]:

```
sns.violinplot(data=df,x='total_bill')  
plt.show()
```




In [23]:

```
sns.boxenplot(data=df,x='total_bill')  
plt.show()
```




In [24]:

```
sns.pointplot(data=df, x='day', y="total_bill")  
plt.show()
```




In [25]:

```
sns.barplot(data=df, x='day',y="total_bill")  
plt.show()
```




In [26]:

```
sns.countplot(data=df, x='day')  
plt.show()
```




In [27]:

```
sns.lmplot(data=df,x='total_bill',y='tip')  
plt.show()
```




In [28]:

```
sns.regplot(data=df,x='total_bill',y='tip')  
plt.show()
```



In [29]:

```
sns.residplot(data=df,x='total_bill',y='tip')  
plt.show()
```



In [ ]:

```
df1=sns.load_dataset('iris')  
df1.head()
```

In [ ]:

```
df1.drop(['species'],axis=1,inplace=True)
```

In [ ]:

```
df1.head()
```

In [ ]:

```
sns.heatmap(df1.corr(), annot=True)  
plt.show()
```

In [ ]:

```
sns.heatmap(df1.corr())  
plt.show()
```

In [ ]:

```
sns.scatterplot(data=df1,x="sepal_width",y="petal_length")  
plt.show()
```

In [ ]:

In [ ]:

In [ ]: