





Scheduler

Start instance

 Google Cloud

 AIDE-MELCC

 Cloud Scheduler

 start-instances-on-sob

• Define the schedule


Region

us-central1


Description

Frequency *

0 9 * * 1-5




Schedules are specified using unix-cron format. E.g. every minute: "* * * * *", every 3 hours: "0 */3 * * *", every Monday at 9:00: "0 9 * * 1". [Learn more](#)




- Minute and Hour:
 - At 9:00 AM
- and Day:
 - From Monday to Friday

Timezone *

Eastern Standard Time (EST)





Jobs in set in timezones affected by Daylight Saving Time can run outside of cadence during DST change. Using a UTC timezone can avoid the problem. [Learn more](#)

CONTINUE

- **Configure the execution**

Target type *

Pub/Sub



Select a Cloud Pub/Sub topic *

projects/aide-melcc/topics/start-instance-event



Message body *

{"label": "env=dev"}



Message size cannot exceed 10MB.

Message attributes

[+ ADD AN ATTRIBUTE](#)

[CONTINUE](#)

- **Configure optional settings**

Retry config

If a job does not complete successfully, it is retried, with exponential backoff, according to the settings in retry config. [Learn more](#)

Max retry attempts

0

Maximum number of retry attempts for a failed job

Max retry duration *

0s

Time limit for retrying a failed job, 0s means unlimited

Min backoff duration *

5s

Minimum time to wait before retrying a job after it fails

Max backoff duration *

1h

Maximum time to wait before retrying a job after it fails

Max doublings *

16

The time between retries will double max doublings times

UPDATE

CANCEL

Stop instance



Cloud Scheduler



stop-instances-on-cob

- Define the schedule

Region

us-central1

Description

Frequency *

0 18 * * 1-5



Schedules are specified using unix-cron format. E.g. every minute: "* * * * *", every 3 hours: "0 */3 * * *", every Monday at 9:00: "0 9 * * 1". [Learn more](#)



- Minute and Hour:
 - At 6:00 PM
- and Day:
 - From Monday to Friday

Timezone *

Eastern Standard Time (EST)



Jobs in set in timezones affected by Daylight Saving Time can run outside of cadence during DST change. Using a UTC timezone can avoid the problem. [Learn more](#)

CONTINUE

- **Configure the execution**

Target type *

Pub/Sub



Select a Cloud Pub/Sub topic *

projects/aide-melcc/topics/stop-instance-event



Message body *

{"label": "env=dev"}



Message size cannot exceed 10MB.

Message attributes

[+ ADD AN ATTRIBUTE](#)

[CONTINUE](#)

- **Configure optional settings**

Retry config

If a job does not complete successfully, it is retried, with exponential backoff, according to the settings in retry config. [Learn more](#)

Max retry attempts

0

Maximum number of retry attempts for a failed job

Max retry duration *

0s

Time limit for retrying a failed job, 0s means unlimited

Min backoff duration *

5s

Minimum time to wait before retrying a job after it fails

Max backoff duration *

1h

Maximum time to wait before retrying a job after it fails

Max doublings *

16

The time between retries will double max doublings times

UPDATE

CANCEL