

CLI reference

calepin

Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:

new	Create a new example Typst file
health	Check Calepin's local runtime environment
compile	Preprocess, then invoke typst compile
watch	Watch, preprocess, and delegate recompiles to typst watch
stop	Stop a running calepin watch process
clean	Remove <code>`.calepin`</code> directories and generated artifacts
help	Print this message or the help of the given subcommand(s)

Options:

-v, --version	Print version
-h, --help	Print help

calepin new

Create a new example Typst file

Usage: calepin new [OPTIONS] <PATH>

Arguments:

<PATH> Path to the new `.typ` file

Options:

-f, --force	Overwrite the file if it already exists
-h, --help	Print help

calepin health

Check Calepin's local runtime environment

Usage: calepin health [OPTIONS]

Options:

--config <CONFIG>	Path to project config TOML
--json	Print machine-readable JSON
--strict	Exit with an error when warnings are present
-h, --help	Print help

calepin compile

Preprocess, then invoke typst compile

Usage: calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

<INPUT>
Input `.typ` file

[OUTPUT]
Output path passed to typst compile

[TYPST_ARGS]...

Arguments forwarded to typst compile after `--`

Options:

`--format <FORMAT>`

Output format passed to typst compile

[possible values: pdf, png, svg, html]

`--template <TEMPLATE>`

Output template name applied after compilation.

Use `basic`, `pico`, or a directory name under the configured themes directory.

`--config <CONFIG>`

Path to project config TOML

`-q, --quiet`

Quiet mode

`--timeout <TIMEOUT>`

Per-chunk timeout in seconds

`-h, --help`

Print help (see a summary with '-h')

calepin watch

Watch, preprocess, and delegate recompiles to typst watch

Usage: calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

<INPUT> Input .typ file

[OUTPUT] Output path passed to typst watch

[TYPST_ARGS]... Arguments forwarded to typst watch after `--`

Options:

`--format <FORMAT>` Output format passed to typst watch [possible values: pdf, png, svg, html]

`--config <CONFIG>` Path to project config TOML

`-q, --quiet` Quiet mode

`--timeout <TIMEOUT>` Per-chunk timeout in seconds

`-h, --help` Print help

calepin stop

Stop a running calepin watch process

Usage: calepin stop [INPUT]

Arguments:

[INPUT] Input .typ file to stop the matching calepin watch. Omit this value to stop all active watches under the current project's `.calepin` directory

Options:

`-h, --help` Print help

calepin clean

Remove ``.calepin`` directories and generated artifacts

Usage: `calepin clean [OPTIONS]`

Options:

<code>-d, --depth <DEPTH></code>	Maximum recursion depth when searching for <code>`.calepin`</code> directories
<code>-y, --yes</code>	Skip interactive confirmation and delete immediately
<code>-h, --help</code>	Print help