

CLI reference

calepin

Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:

new	Create a notebook file, website scaffold, or ejected theme
health	Check Calepin's local runtime environment and local links
compile	Preprocess, then invoke typst compile
watch	Watch and preprocess, optionally delegating rendering to typst watch
serve	Serve static files locally
update	Update Calepin using the official installer updater
clean	Remove <code>`.calepin`</code> directories and generated artifacts
help	Print this message or the help of the given subcommand(s)

Options:

-v, --version	Print version
-h, --help	Print help

calepin new

Create a notebook file, website scaffold, or ejected theme

Usage: calepin new [OPTIONS] <PATH|website|theme> [DIR]

Arguments:

<PATH website theme>	What to create: a <code>.typ</code> notebook path, <code>`website`</code> , or <code>`theme`</code>
[DIR]	Destination directory when creating a website scaffold or ejected theme

Options:

--theme <THEME>	Built-in theme to use when creating a website scaffold or ejected theme [possible values: calepin, academic]
-f, --force	Overwrite the file if it already exists
-h, --help	Print help

Examples:

```
calepin new paper.typ
calepin new website
calepin new website --theme academic
calepin new theme
calepin new theme --theme academic
calepin new theme themes/my-theme
```

calepin health

Check Calepin's local runtime environment and local links

Usage: calepin health [OPTIONS]

Options:

--config <CONFIG>	Path to project config TOML
-d, --depth <DEPTH>	Maximum recursion depth when searching for links
--json	Print machine-readable JSON
--strict	Exit with an error when warnings are present
--check-external-links	Also check external links
-h, --help	Print help

calepin compile

Preprocess, then invoke typst compile

Usage: calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

- <INPUT>
Input .typ file, or a website source directory containing calepin.toml
- [OUTPUT]
Output file path, or website output directory when INPUT is a directory
- [TYPST_ARGS]...
Arguments forwarded to typst compile after `--`

Options:

- format <FORMAT>
Output format, including source-code script extraction

[possible values: pdf, png, svg, html, script]
- minify
Minify HTML output after theming and asset processing
- f, --force
Re-execute all code chunks even when cached results are up to date
- config <CONFIG>
Path to project config TOML
- q, --quiet
Quiet mode
- timeout <TIMEOUT>
Per-chunk timeout in seconds
- set <KEY=VALUE>
Override a Calepin config value as `key=value` (repeatable).

Uses dotted paths for nested config, such as `theme=./theme`, `store.region=CA`, or `toc.enabled=false`.
- h, --help
Print help (see a summary with '-h')

calepin watch

Watch and preprocess, optionally delegating rendering to typst watch

Usage: calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

- <INPUT>
Input .typ file, or a website source directory containing calepin.toml
- [OUTPUT]
Output file path, or website output directory when INPUT is a directory
- [TYPST_ARGS]...
Arguments forwarded to typst watch after `--`

Options:

- format <FORMAT>
Output format passed to typst watch

[possible values: pdf, png, svg, html]
- eval-only
Evaluate changed chunks and refresh artifacts without starting typst watch
- serve
Serve the website while watching a directory

```
--open
    Open the served website in the default browser

--host <HOST>
    Interface to bind when serving a watched website

    [default: 127.0.0.1]

--port <PORT>
    Port to bind when serving a watched website (default: first free port from 8000)

--config <CONFIG>
    Path to project config TOML

-q, --quiet
    Quiet mode

--timeout <TIMEOUT>
    Per-chunk timeout in seconds

--set <KEY=VALUE>
    Override a Calepin config value as `key=value` (repeatable).

    Uses dotted paths for nested config, such as `theme=./theme`, `store.region=CA`, or
    `toc.enabled=false`.

-h, --help
    Print help (see a summary with '-h')
```

calepin serve

Serve static files locally

Usage: calepin serve [OPTIONS] <DIR>

Arguments:

<DIR> Directory containing static files to serve

Options:

```
--host <HOST> Interface to bind [default: 127.0.0.1]
-p, --port <PORT> Port to bind (default: first free port from 8000)
--open        Open the website in the default browser
-h, --help    Print help
```

calepin update

Update Calepin using the official installer updater

Usage: calepin update

Options:

```
-h, --help  Print help
```

calepin clean

Remove `.calepin` directories and generated artifacts

Usage: calepin clean [OPTIONS] [DIR]

Arguments:

[DIR] Directory to search for Calepin artifacts (default: current directory)

Options:

```
-d, --depth <DEPTH> Maximum recursion depth when searching for `.calepin` directories
-y, --yes           Skip interactive confirmation and delete immediately
-h, --help          Print help
```