

CLI reference

calepin

Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:

new	Create a notebook file, website scaffold, or ejected theme
health	Check Calepin's local runtime environment and local links
compile	Preprocess, then invoke typst compile
watch	Watch, preprocess, and delegate recompiles to typst watch
serve	Serve static files locally
stop	Stop a running calepin watch process
clean	Remove `.calepin` directories and generated artifacts
help	Print this message or the help of the given subcommand(s)

Options:

-v, --version	Print version
-h, --help	Print help

calepin new

Create a notebook file, website scaffold, or ejected theme

Usage: calepin new [OPTIONS] <PATH|website|theme> [DIR]

Arguments:

<PATH website theme>	What to create: a .typ notebook path, `website`, or `theme`
[DIR]	Destination directory when creating a website scaffold or ejected theme

Options:

-f, --force	Overwrite the file if it already exists
--theme <THEME>	Builtin theme for website scaffolds or ejected themes (default: calepin)
-h, --help	Print help

Examples:

```
calepin new paper.typ
calepin new website my_site/ --theme calepin
calepin new website my_site/ --theme academic
calepin new theme --theme academic
calepin new theme themes/my-theme --theme academic
```

calepin health

Check Calepin's local runtime environment and local links

Usage: calepin health [OPTIONS]

Options:

--config <CONFIG>	Path to project config TOML
-d, --depth <DEPTH>	Maximum recursion depth when searching links
--json	Print machine-readable JSON
--strict	Exit with an error when warnings are present

`--check-external-links` Also check external links
`-h, --help` Print help

calepin compile

Preprocess, then invoke typst compile

Usage: `calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...`

Arguments:

`<INPUT>`

Input .typ file, or a website source directory containing `calepin.toml`

`[OUTPUT]`

Output file path, or website output directory when `INPUT` is a directory

`[TYPST_ARGS]...`

Arguments forwarded to typst compile after `--``

Options:

`--format <FORMAT>`

Output format passed to typst compile

[possible values: pdf, png, svg, html]

`--theme <THEME>`

Theme bundle: a builtin name (`calepin`, `academic`), a path to a theme directory, or false

`--minify`

Minify HTML output after theming and asset processing

`--config <CONFIG>`

Path to project config TOML

`-q, --quiet`

Quiet mode

`--timeout <TIMEOUT>`

Per-chunk timeout in seconds

`-P, --param <KEY=VALUE>`

Override a document parameter as ``key=value`` (repeatable).

Takes precedence over ``calepin.setup(params: ...)``, so the same document can render with different values without editing the source.

`-h, --help`

Print help (see a summary with `'-h'`)

calepin watch

Watch, preprocess, and delegate recompiles to typst watch

Usage: `calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...`

Arguments:

<INPUT>

Input .typ file, or a website source directory containing calepin.toml

[OUTPUT]

Output file path, or website output directory when INPUT is a directory

[TYPST_ARGS]...

Arguments forwarded to typst watch after `--`

Options:

--format <FORMAT>

Output format passed to typst watch

[possible values: pdf, png, svg, html]

--serve

Serve the website while watching a directory

--open

Open the served website in the default browser

--host <HOST>

Interface to bind when serving a watched website

[default: 127.0.0.1]

--port <PORT>

Port to bind when serving a watched website (default: first free port from 8000)

--config <CONFIG>

Path to project config TOML

-q, --quiet

Quiet mode

--timeout <TIMEOUT>

Per-chunk timeout in seconds

-P, --param <KEY=VALUE>

Override a document parameter as `key=value` (repeatable).

Takes precedence over `calepin.setup(params: ...)` , so the same document can render with different values without editing the source.

-h, --help

Print help (see a summary with '-h')

calepin serve

Serve static files locally

Usage: calepin serve [OPTIONS] <DIR>

Arguments:

<DIR> Directory containing static files to serve

Options:

--host <HOST> Interface to bind [default: 127.0.0.1]
-p, --port <PORT> Port to bind (default: first free port from 8000)
--open Open the website in the default browser
-h, --help Print help

calepin stop

Stop a running calepin watch process

Usage: calepin stop [INPUT]

Arguments:

[INPUT] Input .typ file to stop the matching calepin watch. Omit this value to stop all active watches under the current project's `.calepin` directory

Options:

-h, --help Print help

calepin clean

Remove `.calepin` directories and generated artifacts

Usage: calepin clean [OPTIONS]

Options:

-d, --depth <DEPTH> Maximum recursion depth when searching for `.calepin` directories
-y, --yes Skip interactive confirmation and delete immediately
-h, --help Print help