

Website navigation

Side bar

The sidebar is the main navigation for documentation-style sites. Configure it with `[sidebar]`; a section can list pages one by one:

```
[sidebar]

[[sidebar.section]]
title = "Guide"

[[sidebar.section.item]]
target = "install.typ"
```

or include several pages with a glob:

```
[[sidebar.section.item]]
glob = "guide/*.typ"
```

Use `target` for one source page and `glob` for a list of source pages. Sidebar entries always point to Typst source files, not rendered `.html` files. *Calepin* resolves those pages and writes the right `.html` links in the generated site.

The sidebar label comes from the page source, not from `calepin.toml`. Put the label in the page's website metadata:

```
#set document(title: [Install])
#metadata((title: "Install")) <website-metadata>

#title()
```

If a page has no `website-metadata.title`, *Calepin* falls back to the document title, then the filename stem. This keeps multilingual sidebars in one place: each translated page carries its own translated title.

If you do not configure a sidebar, *Calepin* builds one from `.typ` files in the source directory. Hidden files are skipped.

Titled sections are foldable: each page loads with the section that contains it open and the others folded. Opening a different section folds the previous one. To keep every section expanded instead, disable folding:

```
[sidebar]
fold = false
```

Site menus

Use `[menus]` for named navigation groups. Menu names describe what the links mean; themes decide where to render them. The bundled themes understand `main`, `social`, and `footer`. Custom themes can use any additional menu name.

```
[[menus.main]]
target = "index.typ"
label = "Home"
weight = 10

[[menus.social]]
target = "https://github.com/user/repo"
label = "{icon:github}"
aria-label = "GitHub"
```

Menu items use `target` or `glob`. Use a `.typ` `target` or `glob` for internal source pages; use any other `target` for external links or a literal already-rendered URL. Omit `label` for internal pages to use the page metadata title, document title, or filename stem.

Use `weight` to control ordering within one menu. Lower weights appear first. Items without weights keep their config order after weighted items.

Labels can include Iconify icons with `{icon: ...}`. If the prefix is omitted, *Calepin* uses `lucide`, so `{icon:github}` means `{icon:lucide:github}`. Icon prefixes are Iconify collection names. Search available icons in the Iconify icon sets browser.

For icon-only visible labels, set `aria-label` so screen readers get a human-readable name:

```
aria-label = "GitHub"
```

(If you omit `aria-label`, *Calepin* uses fallback text if available; for an icon-only label with no fallback text this will be less readable.)

Local SVG icons are also supported with source-relative paths:

```
[[menu.social]]
target = "https://example.com/project"
label = "{icon:assets/icons/project.svg} Project"
```

Local icon paths must stay inside the website source directory. *Calepin* sanitizes local and downloaded SVGs before inlining them.