

CSS

CSS tokens

Built-in HTML themes expose stable CSS custom properties in the `--calepin-*` namespace. Prefer overriding these tokens from local theme CSS rather than targeting private theme internals.

```
/* themes/my-theme/css/custom.css */
:root {
  --calepin-color-background: #f6f7f9;
  --calepin-color-text: #111827;
  --calepin-color-accent: #2563eb;
  --calepin-color-border: #d1d5db;
}

body {
  font-family: Inter, system-ui, sans-serif;
  background: var(--calepin-color-background);
  color: var(--calepin-color-text);
}

pre {
  border: 1px solid var(--calepin-color-border);
}
```

In Calepin HTML output, `#title()` is rendered as the page `<h1>`, so the first Typst heading `=` becomes `<h2>`, `=` as `<h3>`, and so on. If you target heading selectors in CSS, use this mapping unless your theme remaps heading markup.

Light and dark themes

To define distinct values for light and dark mode, use `html[data-theme="light"]` and `html[data-theme="dark"]` selectors in your local theme stylesheet:

```
html[data-theme="light"] {
  --calepin-color-background: #f6f7f9;
  --calepin-color-text: #111827;
  --calepin-color-accent: #2563eb;
}

html[data-theme="dark"] {
  --calepin-color-background: #101826;
  --calepin-color-text: #f8faff;
  --calepin-color-accent: #60a5fa;
}
```

Calepin sets `html[data-theme="light"]` or `html[data-theme="dark"]` when the theme toggle is forced by user preference, explicit control, or URL/state storage. If no explicit mode is set, the browser preference is used for initial mode.

Style raw HTML

Use a local theme that extends `typst` when you want a simple, unstyled HTML base.

Create a directory with a manifest, a layout, and a stylesheet:

```
raw/
  theme.toml
  layouts/
    document.html
  css/
    raw.css
```

Edit the manifest `raw/theme.toml`:

```
extends = "typst"
```

Edit `raw/layouts/document.html` to wrap Typst's generated HTML and inline the theme CSS files:

```
{{ doc.head }}
<meta charset="UTF-8">
<title>{{ doc.title }}</title>
{% for file in css %}
<style>
{{ file.content }}
</style>
{% endfor %}
{{ doc.body_open }}
```

```
<main class="page">
  {{ doc.body }}
</main>
{{ doc.body_close }}
```

The important pieces are `doc.head`, `doc.body_open`, `doc.body`, and `doc.body_close`, which preserve the HTML shell Typst produced. The `css` loop loads files from the theme's `css/` directory, including `raw.css`.

Edit the project config file `calepin.toml`:

```
theme = "raw"
```

Compile the notebook:

```
calepin compile notebook.typ --config calepin.toml --format html
```

List of tokens

Group	Token	Purpose
Colors	<code>--calepin-color-background</code>	Page background in normal UI surfaces.
	<code>--calepin-color-text</code>	Primary body text color.
	<code>--calepin-color-muted</code>	Muted/de-emphasized text.
	<code>--calepin-color-border</code>	UI border color.
	<code>--calepin-color-accent</code>	Primary accent color (links, buttons, highlights).
	<code>--calepin-color-accent-hover</code>	Accent color for hover states.
	<code>--calepin-color-accent-soft</code>	Soft tint derived from accent.
	<code>--calepin-color-accent-contrast</code>	Text/icon contrast color on accent backgrounds.
	<code>--calepin-color-link</code>	Default link color.
	<code>--calepin-color-link-hover</code>	Link hover color.
	<code>--calepin-color-focus</code>	Focus ring/text emphasis color.
	<code>--calepin-color-selection</code>	Text-selection background color.
	<code>--calepin-color-info</code>	Info state color.
	<code>--calepin-color-success</code>	Success state color.
	<code>--calepin-color-warning</code>	Warning state color.

Callouts	--calepin-color-danger	Danger/error state color.
	--calepin-color-important	Important state color.
	--calepin-color-info-soft	Translucent info variant.
	--calepin-color-success-soft	Translucent success variant.
	--calepin-color-warning-soft	Translucent warning variant.
	--calepin-color-danger-soft	Translucent danger variant.
	--calepin-color-important-soft	Translucent important variant.
	--calepin-callout-note-color	Callout tone for note blocks.
	--calepin-callout-tip-color	Callout tone for tip blocks.
	--calepin-callout-warning-color	Callout tone for warning blocks.
Surfaces	--calepin-callout-caution-color	Callout tone for caution blocks.
	--calepin-callout-important-color	Callout tone for important blocks.
	--calepin-surface	Primary surface color for cards/panels.
	--calepin-surface-muted	Muted surface tone.
	--calepin-surface-raised	Raised surface tone.
	--calepin-surface-inset	Inset surface tone.
Typography	--calepin-surface-code	Code block background.
	--calepin-surface-output	Code/output container background.
	--calepin-font-body	Primary text font stack.
	--calepin-font-heading	Heading font stack.

Spacing	--calepin-font-mono	Monospace font stack.
	--calepin-font-size	Base font size multiplier.
	--calepin-font-size-sm	Small text font size.
	--calepin-font-size-aside	Aside/sidenote font size.
	--calepin-line-height	Default line height for body text.
	--calepin-line-height-tight	Tighter line height for headings.
	--calepin-heading-weight	Default heading weight.
	--calepin-code-font-size	Code and preformatted font size.
	--calepin-space-xs	Extra-small spacing token.
	--calepin-space-sm	Small spacing token.
	--calepin-space-md	Medium spacing token.
	--calepin-space-lg	Large spacing token.
	--calepin-space-xl	Extra-large spacing token.
	--calepin-space-2xl	2XL spacing token.
Layout	--calepin-block-gap	Vertical block spacing.
	--calepin-inline-gap	Horizontal inline spacing.
	--calepin-section-gap	Vertical section spacing.
	--calepin-content-width	Max width for main content regions.
	--calepin-wide-width	Max width for wide content regions.
	--calepin-page-width	Computed page width for two-column layout.
	--calepin-margin-width	Sidenote/margin note width.
	--calepin-margin-gap	Gap between body and margin region.

	<code>--calepin-page-padding-inline</code>	Inline page padding.
	<code>--calepin-topbar-height</code>	Topbar height token.
	<code>--calepin-sidebar-width</code>	Desktop sidebar width.
	<code>--calepin-sidebar-mobile-width</code>	Mobile drawer width.
	<code>--calepin-shell-gap</code>	Gap between shell grid tracks.
	<code>--calepin-toc-indent</code>	Indent used by generated TOC trees.
Borders	<code>--calepin-border-width</code>	Border width used across theme.
	<code>--calepin-border</code>	Shorthand border style using <code>--calepin-color-border`</code> .
	<code>--calepin-radius-sm</code>	Small corner radius.
	<code>--calepin-radius-md</code>	Medium corner radius.
	<code>--calepin-radius-lg</code>	Large corner radius.
Shadows	<code>--calepin-shadow-card</code>	Default card shadow.
	<code>--calepin-focus-ring</code>	Focus ring style.
Layers	<code>--calepin-z-topbar</code>	Z-index for top bar.
	<code>--calepin-z-backdrop</code>	Backdrop and overlays.
	<code>--calepin-z-drawer</code>	Side drawer z-index.
	<code>--calepin-z-popover</code>	Popover/dialog z-index.
	<code>--calepin-z-modal</code>	Modal z-index.
Syntax	<code>--calepin-syntax-foreground</code>	Syntax text color for code blocks.
	<code>--calepin-syntax-background</code>	Syntax background color for code blocks.
	<code>--calepin-syntax-border</code>	Syntax border color derived from foreground/background.