

Parameters

Parameters let you render the same notebook with different inputs. Declare them in `#calepin.setup`, and chunks read them through a `params` object. For the `r` and `python` engines, *Calepin* creates the binding automatically: `R` receives a named list read as `params$Species`, and `Python` receives a dict read as `params["Species"]`.

This complete document filters the built-in `R` `iris` data to one species and a minimum petal length, then uses a third parameter to choose the color palette:

```
#import "@preview/calepin:0.0.1" as calepin

#calepin.setup(
  params: (
    Species: "versicolor",
    min_petal_length: 4.5,
    palette: "viridis",
  ),
)

The selected species is #calepin.inline("r")["cat(params$Species)"].

```r
#| fig-caption: Iris rows selected by document parameters
filtered <- subset(
 iris,
 Species == params$Species & Petal.Length >= params$min_petal_length
)

colors <- hcl.colors(3, palette = params$palette)

plot(
 Sepal.Length ~ Petal.Length,
 data = filtered,
 pch = 19,
 col = colors[2],
 xlab = "Petal length",
 ylab = "Sepal length",
 main = paste(params$Species, "with Petal.Length >=", params$min_petal_length)
)
```
```


The selected species is `versicolor`.

```
filtered <- subset(
  iris,
  Species == params$Species & Petal.Length >= params$min_petal_length
)

colors <- hcl.colors(3, palette = params$palette)

plot(
  Sepal.Length ~ Petal.Length,
  data = filtered,
  pch = 19,
  col = colors[2],
  xlab = "Petal length",
  ylab = "Sepal length",
```

```
main = paste(params$Species, "with Petal.Length >=", params$min_petal_length)
)
```



Overriding at render time

Because parameters live in `#calepin.setup`, you can override them on the command line with `-P key=value` (repeatable). This renders the same source with different inputs, without editing the notebook:

```
calepin compile iris.typ -P Species=setosa -P min_petal_length=1.5 -P palette=magma
```

Command-line values are typed the same way as `#|` header values, so `1.5` is a number, `true` is a boolean, and `setosa` is a string.

Value types

A parameter may be `none`, a boolean, an integer, a float, a string, an array, or a dictionary, nested freely. Other Typst values such as content, functions, lengths, colors, and dates cannot be passed directly; supply them as strings or numbers instead. An unsupported value fails the build with a message naming the offending parameter.

Parameters are also written to `.calepin/<document>/params.json`. Engines reached through a Jupyter kernel, including `julia` and any other kernel, do not yet receive an automatic params binding. Read that JSON file yourself using the `CALEPIN_PARAMS_PATH` environment variable that *Calepin* sets in the kernel. Parameters are not secret: treat them as build inputs written to disk.