

Site configuration

Website settings live in `calepin.toml` at the root of your website source directory. A small site can start with:

```
title = "My Site"
description = "A static website built from Typst documents."
base_url = "https://example.com"
theme = "academic"
pdf = false

[sidebar]

[[sidebar.section]]
title = "Guide"

  [[sidebar.section.item]]
  path = "index.typ"
  label = "Home"

  [[sidebar.section.item]]
  path = "about.typ"
  label = "About"
```

Use `--config <path>` only when the config file lives somewhere else.

Basic settings

Key	Default	Use it for
title	none	The site name shown by the bundled themes and in page metadata.
description	none	A short site description for metadata and previews.
base_url	none	The public site URL. Set this to generate <code>sitemap.xml</code> and canonical URLs.
theme	"calepin"	"calepin", "academic", a local theme directory, or <code>false</code> for raw output.
pdf	false	When true, also render <code>.pdf</code> files. Individual pages can override this with <code>pdf</code> in their <code><website-metadata></code> metadata.

Use `--format html` for a one-time HTML-only build, regardless of `pdf`.

Branding

Set a logo and links for the top bar:

```
logo = "assets/logo.svg"
logo_alt = "My Site"
home = "index.html"
github_url = "https://github.com/user/repo"
```

Relative logo paths are resolved from the output directory, so the same logo works from nested pages. If no logo is set, the bundled theme uses `title` as the site name.

Navigation

The sidebar is the main navigation for documentation-style sites. A section can list pages one by one:

```
[[sidebar.section]]
title = "Guide"

[[sidebar.section.item]]
path = "install.typ"
label = "Install"
```

or include several pages with a glob:

```
[[sidebar.section.item]]
glob = "guide/*.typ"
```

If you do not configure a sidebar, *Calepin* builds one from `.typ` files in the source directory. Hidden files are skipped.

Labels can include icons:

```
label = "{icon:lucide:download} Install"
```

If the prefix is omitted, *Calepin* uses `lucide`, so `{icon:home}` means `{icon:lucide:home}`. Icons are downloaded during the build and cached under `.calepin/icons/`.

Top navigation

Use `[navbar]` for a small top navigation bar:

```
[navbar]

[[navbar.item]]
position = "left"
path = "index.typ"
label = "Home"

[[navbar.item]]
position = "right"
url = "https://github.com/user/repo"
label = "{icon:simple-icons:github} GitHub"
```

Navbar items can use `path`, `glob`, `url`, or a theme widget such as `widget = "theme"` or `widget = "language"`. `position` can be `left`, `center`, or `right`.

Page titles and hidden pages

Set a page title in the Typst file when you want something clearer than the file name:

```
#metadata((title: "Getting started")) <website-metadata>
```

Navigation labels are chosen in this order:

1. the label in `calepin.toml`
2. the page's title metadata
3. the file name

Use `[pages]` for pages that should be built but should not appear in navigation, such as blog posts or legal pages:

```
[pages]
include = ["blog/*.typ", "legal/privacy.typ"]
exclude = ["drafts/**"]
```

Then hide individual pages from generated navigation with page metadata:

```
#metadata((title: "First post", hidden: true)) <website-metadata>
```

`index.typ` and `404.typ` are always built when present. If `404.typ` exists, *Calepin* writes `404.html`; if PDF rendering is enabled for that page, it also writes `404.pdf`.

Page listings

Pages can list other pages in the site. This is useful for a blog index, project index, or publication list.

```
#import "@preview/calepin:0.0.1" as calepin

#for post in calepin.pages()
  .filter(p => p.path.starts-with("blog/"))
  .sorted(key: p => p.meta.at("date", default: ""))
  .rev() [
    - #link(post.href)[#post.title]
  ]
```

Each page entry includes `path`, `href`, `title`, `language`, `translations`, `pdf`, and `meta`. The `meta` field contains the page's `<website-metadata>` values, so you can sort or filter on your own fields such as dates, tags, authors, or categories.

Multilingual sites

Configure languages with one content directory per language:

```
default_language = "en"

[languages.en]
label = "English"
content_dir = "."

[languages.fr]
label = "Français"
content_dir = "fr"
```

With this layout, `about.typ` and `fr/about.typ` are treated as translations of the same page. The default language keeps root URLs like `about.html`; other languages use their language code as a URL prefix, such as `fr/about.html`.

Use page metadata when translations move or need different slugs:

```
#metadata((
  title: "À propos",
  translation_key: "about",
  slug: "a-propos",
)) <website-metadata>
```

When more than one language is configured, the bundled themes show a language picker. Local navigation links are shown only for the current language; external links stay global.