

CLI reference

calepin

Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:

- new Create a new example Typst file
- compile Preprocess, then invoke typst compile
- watch Watch, preprocess, and delegate recompiles to typst watch
- stop Stop a running calepin watch process
- help Print this message or the help of the given subcommand(s)

Options:

- v, --version Print version
- h, --help Print help

calepin compile

Preprocess, then invoke typst compile

Usage: calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

- <INPUT>
 Input .typ file
- [OUTPUT]
 Output path passed to typst compile
- [TYPST_ARGS]...
 Arguments forwarded to typst compile after `--`

Options:

- format <FORMAT>
 Output format passed to typst compile

 [possible values: pdf, png, svg, html]
- template <TEMPLATE>
 Output template applied after compilation.

 Use `basic` or `pico` to apply a built-in HTML theme.

 Possible values:
 - basic: Render HTML using the built-in `basic` theme
 - pico: Render HTML using the built-in `pico` theme
- results <RESULTS>
 Override results JSON path
- clean
 Remove generated results and figures before preprocessing
- q, --quiet
 Quiet mode

`--timeout <TIMEOUT>`
Per-chunk timeout in seconds

`-h, --help`
Print help (see a summary with `'-h'`)

calepin watch

Watch, preprocess, and delegate recompiles to typst watch

Usage: `calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...`

Arguments:

`<INPUT>` Input .typ file
`[OUTPUT]` Output path passed to typst watch
`[TYPST_ARGS]...` Arguments forwarded to typst watch after `--``

Options:

`--format <FORMAT>` Output format passed to typst watch [possible values: pdf, png, svg, html]
`--results <RESULTS>` Override results JSON path
`--clean` Remove generated results and figures before preprocessing
`-q, --quiet` Quiet mode
`--timeout <TIMEOUT>` Per-chunk timeout in seconds
`-h, --help` Print help

calepin stop

Stop a running calepin watch process

Usage: `calepin stop [INPUT]`

Arguments:

`[INPUT]` Input .typ file to stop the matching calepin watch. Omit this value to stop all active watches under the current project's ``.calepin`` directory

Options:

`-h, --help` Print help