

Configuration

config.toml

Calepin does not auto-discover configuration. For compile and watch, pass the config path explicitly with `--config=PATH`:

```
calepin compile --config config.toml paper.typ
```

If `--config` is omitted, Calepin uses defaults.

Relative paths written inside the config resolve relative to the config file's own directory, not the document being compiled. Absolute paths are used as is.

`asset-dir` controls where Calepin writes generated runtime files and browser-facing assets, including theme CSS, JavaScript, and fonts. The default is `.calepin`, which works in local preview. Some hosts like Netlify do not serve files from dot-directories, so deployed pages can sometimes load without styling, search, dark-mode toggles, or other theme JavaScript even though they looked correct locally. For sites published to those hosts, set `asset-dir = "_calepin"` before building.

```
# config.toml

# Directory for generated Calepin runtime and website assets.
# Default: ".calepin". Use "_calepin" for Netlify or GitHub Pages.
asset-dir = ".calepin"

[executables]
typst = "typst"           # Typst binary (can be name or full path)
python = ".venv/bin/python" # Python interpreter
rscript = "Rscript"       # R executable
mmdc = "mmdc"             # Mermaid
#dot = "/opt/homebrew/bin/dot" # optional, if needed
#d2 = "d2"                 # optional
#tectonic = "tectonic"      # optional
#dvisvgm = "dvisvgm"        # optional
#pdf2svg = "pdf2svg"        # optional
```

If `python` is not configured, set `CALEPIN_PYTHON` in the environment to pick it. If that is absent, Calepin uses a local `.venv` interpreter when available.