

CLI reference

calepin

Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:

new	Create a new example Typst file or website scaffold
health	Check Calepin's local runtime environment
compile	Preprocess, then invoke typst compile
watch	Watch, preprocess, and delegate recompiles to typst watch
serve	Serve static files locally
stop	Stop a running calepin watch process
clean	Remove <code>`.calepin`</code> directories and generated artifacts
help	Print this message or the help of the given subcommand(s)

Options:

-v, --version	Print version
-h, --help	Print help

calepin new

Create a new example Typst file or website scaffold

Usage: calepin new [OPTIONS] <PATH>

Arguments:

<PATH> Path to the new `.typ` file, or ``website`` to scaffold a website

Options:

-f, --force	Overwrite the file if it already exists
-h, --help	Print help

calepin health

Check Calepin's local runtime environment

Usage: calepin health [OPTIONS]

Options:

--config <CONFIG>	Path to project config TOML
--json	Print machine-readable JSON
--strict	Exit with an error when warnings are present
-h, --help	Print help

calepin compile

Preprocess, then invoke typst compile

Usage: calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

<INPUT>
Input `.typ` file, or a website source directory when `--config` is supplied

[OUTPUT]

Output file path, or website output directory when INPUT is a directory

[TYPST_ARGS]...

Arguments forwarded to typst compile after `--`

Options:

--format <FORMAT>

Output format passed to typst compile

[possible values: pdf, png, svg, html]

--template <TEMPLATE>

Output template name applied after compilation.

Use `basic`, `pico`, or a directory name under the configured themes directory.

--config <CONFIG>

Path to project config TOML

-q, --quiet

Quiet mode

--timeout <TIMEOUT>

Per-chunk timeout in seconds

-P, --param <KEY=VALUE>

Override a document parameter as `key=value` (repeatable).

Takes precedence over `calepin.setup(params: ...)` , so the same document can render with different values without editing the source.

-h, --help

Print help (see a summary with '-h')

calepin watch

Watch, preprocess, and delegate recompiles to typst watch

Usage: calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

<INPUT>

Input .typ file, or a website source directory when --config is supplied

[OUTPUT]

Output file path, or website output directory when INPUT is a directory

[TYPST_ARGS]...

Arguments forwarded to typst watch after `--`

Options:

--format <FORMAT>

Output format passed to typst watch

```

    [possible values: pdf, png, svg, html]

--serve
    Serve the website while watching a directory

--host <HOST>
    Interface to bind when serving a watched website

    [default: 127.0.0.1]

--port <PORT>
    Port to bind when serving a watched website

    [default: 8000]

--config <CONFIG>
    Path to project config TOML

-q, --quiet
    Quiet mode

--timeout <TIMEOUT>
    Per-chunk timeout in seconds

-P, --param <KEY=VALUE>
    Override a document parameter as `key=value` (repeatable).

    Takes precedence over `calepin.setup(params: ...)` , so the same document
    can render with different values without editing the source.

-h, --help
    Print help (see a summary with '-h')
```

calepin serve

Serve static files locally

Usage: calepin serve [OPTIONS] <DIR>

Arguments:

<DIR> Directory containing static files to serve

Options:

```

    --host <HOST>  Interface to bind [default: 127.0.0.1]
    -p, --port <PORT>  Port to bind [default: 8000]
    -h, --help          Print help
```

calepin stop

Stop a running calepin watch process

Usage: calepin stop [INPUT]

Arguments:

[INPUT] Input .typ file to stop the matching calepin watch. Omit this value to stop all active watches under the current project's `.calepin` directory

Options:
-h, --help Print help

calepin clean

Remove ``.calepin`` directories and generated artifacts

Usage: `calepin clean [OPTIONS]`

Options:

-d, --depth <DEPTH>	Maximum recursion depth when searching for <code>`.calepin`</code> directories
-y, --yes	Skip interactive confirmation and delete immediately
-h, --help	Print help