

config.toml

Calepin does not auto-discover configuration. For compile and watch, pass the config path explicitly with `--config=PATH`:

```
calepin compile --config config.toml paper.typ
```

If `--config` is omitted, Calepin uses defaults.

Relative paths written inside the config (the executables, `themes_dir`, and `pdf_theme`) resolve relative to the config file's own directory, not the document being compiled. Absolute paths are used as is.

```
# config.toml

[executables]
typst = "typst"           # Typst binary (can be name or full path)
python = ".venv/bin/python" # Python interpreter
rscript = "Rscript"       # R executable
mmdc = "mmdc"             # Mermaid
#dot = "/opt/homebrew/bin/dot" # optional, if needed
#d2 = "d2"                 # optional
#tectonic = "tectonic"     # optional
#dvisvgm = "dvisvgm"       # optional
#pdf2svg = "pdf2svg"       # optional

themes_dir = "themes"     # folder for user template themes
pdf_theme = "themes/pdf.typ" # optional Typst theme for PDF/paged output
```

If `pdf_theme` is omitted, Calepin uses its bundled PDF theme. Set `pdf_theme = false` to disable the bundled theme and let Typst render source blocks with its defaults.

If `python` is not configured, set `CALEPIN_PYTHON` in the environment to pick it. If that is absent, Calepin uses a local `.venv` interpreter when available.