

Static website generator

Calepin can build a Typst document directory as a static website. This is the same workflow used to render this documentation site: source `.typ` files live in `docs/`, and the generated `.html`, `.pdf`, and `sitemap.xml` files are written back into `docs/` for GitHub Pages.

Feature summary

- Scaffold a new website with `calepin new website`.
- Compile a directory with `calepin compile docs docs --config website.toml`.
- Render HTML for each page.
- Render matching PDFs for each page by default.
- Render HTML only with `--format html`.
- Build in place, so GitHub Pages can publish from `docs/`.
- Reuse cached chunk results across repeated `compile`, `website`, and `serve` runs.
- Watch a website directory with `calepin watch docs docs --config website.toml`.
- Rebuild only changed existing `.typ` pages during watch using xxh3 fingerprints.
- Skip rebuilds when watched `.typ` files are touched but their content hash has not changed.
- Fall back to a full rebuild for structural changes.
- Serve a static output directory with `calepin serve docs`.
- Watch and serve together with `calepin watch docs docs --config website.toml --serve`.
- Auto-refresh browser pages after successful watched rebuilds when `--serve` is enabled.
- Configure navigation manually with `website.toml`.
- Generate navigation automatically when no sidebar is configured.
- Render `404.typ` as a fallback page when present.
- Exclude `404.typ` from automatic navigation and sitemap output.
- Configure `title`, `description`, `base_url`, and `github_url`.
- Emit page titles, description metadata, Open Graph metadata, and canonical URLs in the bundled website theme.
- Generate `sitemap.xml` when `base_url` is configured.
- Remove stale generated files after pages are deleted or renamed.
- Track generated outputs locally with `.calepin/website-manifest.json`.
- Preserve unrelated static assets while cleaning stale generated `.html` and `.pdf` files.
- Use Calepin HTML themes, including the bundled `calepin-website` theme.
- Expose site navigation, sectioned navigation, TOC, metadata, and current URL to HTML themes.
- Embed each page's source `.typ` content in the generated HTML for the source view in the bundled website theme.
- Inline local images referenced by Typst HTML output.

Create a website

Use `calepin new website` to scaffold a minimal site:

```
calepin new website
```

This creates:

- `website.toml`
- `docs/index.typ`
- `docs/404.typ`

The scaffold separates site settings from build paths. Pass the source directory as the first positional argument and the output directory as the second positional argument when compiling.

Build

Compile a website directory with the same `compile` command used for a single Typst document:

```
calepin compile docs public --config website.toml
```

When the input path is a directory, `--config website.toml` is required. The first positional argument is the website source directory. The optional second positional argument is the website output directory.

For GitHub Pages publishing from `docs/`, build in place by passing `docs` as both the input and output directory:

```
calepin compile docs docs --config website.toml
```

If the output directory is omitted, *Calepin* writes output beside the source files:

```
calepin compile docs --config website.toml
```

By default, each `.typ` page produces two outputs:

- `page.html`
- `page.pdf`

Use `--format html` to write only HTML:

```
calepin compile docs public --config website.toml --format html
```

Directory website builds do not support `--format pdf`, `--format png`, or `--format svg`; those formats are for single-document `calepin compile`.

Website builds use the same preprocess cache as single-document compilation. After a successful page build, *Calepin* writes a fingerprint next to the page's `results.json`. Later builds reuse that file when the chunk code, parameters, execution options, configured tools, and source-relative cache paths match. This means `make serve` does not need to re-execute expensive chunks in pages such as `example.typ` when nothing relevant changed.

Watch

During development, watch the website source directory:

```
calepin watch docs docs --config website.toml
```

As with `compile`, the first positional argument is the source directory and the optional second positional argument is the output directory. The initial watch build renders the whole site. After that, existing `.typ` page edits go through a fast xxh3 fingerprint lookup:

- If the changed page hash is new, *Calepin* rebuilds only that page.
- If the file was touched but the hash is unchanged, *Calepin* skips the rebuild.
- If navigation changed after an incremental rebuild, *Calepin* falls back to a full rebuild.

Calepin also falls back to a full rebuild for changes that can affect more than one page:

- `website.toml`
- theme files
- assets
- new `.typ` pages
- removed `.typ` pages
- renamed `.typ` pages
- unknown or non-page inputs

Watch and serve

To rebuild and serve in one command:

```
calepin watch docs docs --config website.toml --serve
```

The server injects a small reload script into HTML responses. Open browser pages poll the server and refresh after successful rebuilds.

The default bind address is 127.0.0.1:8000. If that port is busy, choose another one:

```
calepin watch docs docs --config website.toml --serve --port 8001
```

You can also bind another interface:

```
calepin watch docs docs --config website.toml --serve --host 0.0.0.0 --port 8001
```

Serve

Serve an already-built static directory with:

```
calepin serve docs
```

The static server:

- serves files from the requested directory
- maps directory requests to index.html
- rejects path traversal
- supports GET and HEAD
- guesses content types from file extensions
- reports a clear error when the port is already in use

Use --host and --port to change the bind address:

```
calepin serve docs --host 127.0.0.1 --port 8001
```

Configuration

Website settings live in website.toml:

```
template = "calepin-website"
title = "My Site"
description = "A website built with Calepin."
base_url = "https://example.com"
github_url = "https://github.com/user/repo"
```

Source and output directories are positional CLI arguments, not website config fields. This mirrors normal single-file compilation, where `calepin compile file.typ file.pdf` takes input and output from the first two positional arguments.

template selects the HTML theme. It can be a built-in theme such as pico, or a theme directory under the configured themes_dir.

title, description, base_url, and github_url are optional. The bundled website theme uses these values to emit:

- browser page titles
- description metadata
- Open Graph metadata
- canonical URLs
- a GitHub link in the top bar

When base_url is set, *Calepin* writes sitemap.xml.

Navigation

Navigation can be explicit:

```
[sidebar]

[[sidebar.section]]
title = "Guide"

    [[sidebar.section.item]]
    path = "index.typ"
    label = "Home"

    [[sidebar.section.item]]
    path = "usage.typ"
    label = "Usage"
```

Each section can contain any number of `item` entries. An item can point to one file with `path`:

```
[[sidebar.section.item]]
path = "install.typ"
label = "Install"
```

An item can also include files with a simple glob:

```
[[sidebar.section.item]]
glob = "guide/*.typ"
```

If no sidebar is configured, *Calepin* builds navigation from `.typ` files in the source directory. Hidden paths are skipped by default. Set `show_hidden = true` under `[sidebar]` to include hidden paths in manual navigation file discovery.

Special pages

If `404.typ` exists, *Calepin* renders it as `404.html` and `404.pdf`.

`404.typ` is excluded from automatic navigation and from `sitemap.xml`. This keeps the error page available to GitHub Pages without presenting it as a normal documentation page.

Sitemap

When `base_url` is configured, *Calepin* writes `sitemap.xml` in the output directory:

```
base_url = "https://example.com/project"
```

The sitemap is built from navigation entries. URLs are absolute and use `base_url` plus the page's generated `.html` path.

If `base_url` is removed from the config, a stale generated sitemap is removed on the next build.

Generated file cleanup

Calepin writes a local manifest to:

```
.calepin/website-manifest.json
```

The manifest records generated website outputs. Later builds use it to remove stale generated files when pages are deleted or renamed.

Full builds also scan the output directory for unexpected generated `.html` and `.pdf` files. The scan skips directories such as `assets/`, `.calepin/`, `.git/`, `target/`, `node_modules/`, and `.venv/`, so static assets are preserved.

Theme context

Website builds pass site data into HTML themes. Theme templates can access:

- `site.nav`
- `site.nav_sections`
- `site.toc`
- `site.title`
- `site.description`
- `site.base_url`
- `site.github_url`
- `site.current_url`
- `site.page_title`

The bundled `calepin-website` theme uses this data for sidebar navigation, previous and next page links, table of contents, metadata, and the GitHub link.

Source and PDF views

The bundled website theme includes a view switcher for rendered HTML, source, and PDF.

The source view is powered by a JSON script embedded in each generated HTML page. The PDF view expects the matching `.pdf` output generated by the default website build.

If you build with `--format html`, the PDF files are not generated. In that mode, the theme can still render HTML and source views, but the PDF view will not have a matching file.

Current limitations

The website generator is intentionally small. It does not yet implement:

- dependency-aware rebuilds for imported shared `.typ` files
- drafts
- taxonomies
- pagination
- search indexes
- feeds
- robots.txt generation
- Sass or SCSS compilation
- link checking
- automatic browser opening

These can be added without changing the current command shape: `new`, `compile`, `watch`, and `serve`.