

Website navigation

Side bar

The sidebar is the main navigation for documentation-style sites. Configure it with `[sidebar]`; a section can list pages one by one:

```
[sidebar]

[[sidebar.section]]
title = "Guide"

[[sidebar.section.item]]
target = "install.typ"
```

or include several pages with a glob:

```
[[sidebar.section.item]]
glob = "guide/*.typ"
```

Use `target` for one source page and `glob` for a list of source pages. Page targets point to Typst source files, not rendered `.html` files. *Calepin* resolves those pages and writes the right `.html` links in the generated site.

The sidebar label comes from the page source, not from `calepin.toml`. Put the label in the page's website metadata:

```
#set document(title: [Install])
#metadata((title: "Install")) <website-metadata>

#title()
```

If a page has no `website-metadata.title`, *Calepin* falls back to the document title, then the filename stem. This keeps multilingual sidebars in one place: each translated page carries its own translated title.

Use an external URL as `target` when you want a sidebar link to leave the site. External targets must set `label` because there is no page metadata to read:

```
[[sidebar.section.item]]
target = "https://example.com/reference"
label = "External reference"
```

Add non-link subheadings inside a section with an item that sets only `label`:

```
[[sidebar.section.item]]
label = "Language"

[[sidebar.section.item]]
target = "reference/syntax.typ"

[[sidebar.section.item]]
target = "reference/styling.typ"

[[sidebar.section.item]]
label = "Library"

[[sidebar.section.item]]
target = "reference/model.typ"
```

Subheadings are rendered in sidebar order with the `calepin-website-sidebar-subheading` class so themes can style them separately. They do not link anywhere, add build pages, or affect which folded section opens. A sidebar item with a `.typ` target or glob cannot also set `label`; page labels still come from page metadata.

If you do not configure a sidebar, *Calepin* builds one from `.typ` files in the source directory. Hidden files are skipped.

Titled sections are foldable: each page loads with the section that contains it open and the others folded. Opening a different section folds the previous one. To keep every section expanded instead, disable folding:

```
[sidebar]
fold = false
```

Table of contents

Pages can show an “On this page” table of contents built from their own headings (levels 1-3 by default). The calepin theme shows one by default; other themes, including academic, are opt-in.

Set a site-wide default with [toc]:

```
[toc]
enabled = true
depth = 2
```

depth is the maximum heading level included, from 1 to 6.

Override either field for a single page with <website-metadata>:

```
#metadata[{toc: {enabled: false}}] <website-metadata>
```

```
#metadata[{toc: {depth: 2}}] <website-metadata>
```

Page metadata and calepin.toml merge field by field: a page can override just depth and still inherit enabled from calepin.toml, or the reverse. Whatever is left unset falls back to the theme’s own default.

Site menus

Use [menus] for named navigation groups. Menu names describe what the links mean; themes decide where to render them. The bundled themes understand main and social. Custom themes can use any additional menu name.

```
[[menus.main]]
target = "index.typ"
label = "Home"
weight = 10

[[menus.social]]
target = "https://github.com/user/repo"
label = "{icon:github}"
aria-label = "GitHub"
```

Menu items use target or glob. Use a .typ target or glob for internal source pages; use any other target for external links or a literal already-rendered URL. Omit label for internal pages to use the page metadata title, document title, or filename stem.

Footer

Configure the site footer with [[footer.item]]. Footer items can be links or plain text rows for copyright and legal notices:

```
[[footer.item]]
label = "© 2026 Example"

[[footer.item]]
target = "https://example.com/privacy"
label = "Privacy"
```

A footer row with only label is rendered as text (no hyperlink).

Use weight to control ordering within one menu or footer. Lower weights appear first. Items without weights keep their config order after weighted items.

Labels can include Iconify icons with `{icon: ...}`. If the prefix is omitted, *Calepin* uses `lucide`, so `{icon:github}` means `{icon:lucide:github}`. Icon prefixes are Iconify collection names. Search available icons in the Iconify icon sets browser.

For icon-only visible labels, set `aria-label` so screen readers get a human-readable name:

```
aria-label = "GitHub"
```

(If you omit `aria-label`, *Calepin* uses fallback text if available; for an icon-only label with no fallback text this will be less readable.)

Local SVG icons are also supported with source-relative paths:

```
[[menu.social]]
target = "https://example.com/project"
label = "{icon:assets/icons/project.svg} Project"
```

Local icon paths must stay inside the website source directory. *Calepin* sanitizes local and downloaded SVGs before inlining them.