

Static website generator

Calepin can turn a directory of Typst documents into a website. In fact, the website you are reading now was entirely generated with *Calepin*.

New website

Use this command to scaffold an example site:

```
calepin new website
```

This creates a website source directory with enough structure to exercise the bundled themes:

- `calepin_website/calepin.toml`: the site configuration file, where you set the title, base URL, navigation, theme, and output options.
- `calepin_website/index.typ`: the home page source file, which builds to `index.html`.
- `calepin_website/404.typ`: the not-found page source file, used by static hosts such as GitHub Pages for missing routes.
- `calepin_website/about.typ`, `calepin_website/guide/*.typ`, and `calepin_website/fr/*.typ`: regular pages in two languages, with site menu and sidebar entries.
- `calepin_website/blog.typ` and `calepin_website/posts/*.typ`: a small blog index and post source files using `calepin.pages()`.

The scaffold uses the `calepin` theme by default. Use `--theme` to start from another built-in theme:

```
calepin new website --theme academic
```

Build

Compile a website directory with the same compile command used for a single Typst document:

```
calepin new website --theme academic
```

This compiles the website in place: source files are read from `my_site/`, and generated outputs are written back into `my_site/`.

To compile the same source directory somewhere else, pass an output directory as the second path:

```
calepin compile my_site/
```

When the input path is a directory, *Calepin* looks for `calepin.toml` at the root of that directory. An explicit `--config <path>` supersedes the automatic lookup; if no config is found either way, the build fails.

By default, website pages render to HTML. Configure PDF output and site settings in Site configuration.

Serve

Serve the built site locally with:

```
calepin compile my_site/
```

This is useful for a quick preview after `calepin compile`. By default, *Calepin* uses `127.0.0.1` and the first available port from 8000.

Use `--host` and `--port` when you need a specific address:

```
calepin compile my_site/ public/
```

Add `--open` to launch the served site in your default browser:

```
calepin compile my_site/ public/
```

Watch

During development, watch the website source directory for changes, and re-compile automatically:

```
calepin serve my_site/
```

As with `compile`, the first positional argument is the source directory and the optional second positional argument is the output directory. The first build renders the whole site. After that, *Calepin* hashes each edited page and rebuilds only the pages whose content actually changed; files that were touched but not modified are skipped.

Changes that can affect more than one page trigger a full rebuild instead. This includes edits to `calepin.toml`, themes, or assets, pages that are added, removed, or renamed, and edits that change the site navigation or page metadata.

Add `--serve` to run the local server while watching; it uses the same `--host`, `--port`, and `--open` options as `calepin serve`.

```
calepin serve my_site/
```

Features

- Directory builds from Typst source files.
- In-place or separate output directories.
- Sidebar and site menu navigation from configuration or discovered pages.
- HTML output with optional PDF twins.
- Page metadata and `calepin.pages()` for listings and indexes.
- Multilingual site navigation.
- Static file copying for assets, downloads, and host-specific files.
- Generated `sitemap.xml` and `robots.txt`, with template overrides for `robots.txt`.
- Optional Pagefind search index generation, with cached no-op rebuilds.
- Optional HTML minification, including inline CSS and JavaScript.
- Local serving and incremental watch builds.