

CLI reference

calepin

Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:

- new Create a new example Typst file
- compile Preprocess, then invoke typst compile
- watch Watch, preprocess, and delegate recompiles to typst watch
- stop Stop a running calepin watch process
- clean Remove ``.calepin`` directories and generated artifacts
- help Print this message or the help of the given subcommand(s)

Options:

- v, --version Print version
- h, --help Print help

calepin new

Create a new example Typst file

Usage: calepin new [OPTIONS] <PATH>

Arguments:

<PATH> Path to the new `.typ` file

Options:

- f, --force Overwrite the file if it already exists
- h, --help Print help

calepin compile

Preprocess, then invoke typst compile

Usage: calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

<INPUT> Input `.typ` file

[OUTPUT] Output path passed to typst compile

[TYPST_ARGS]... Arguments forwarded to typst compile after `--``

Options:

- format <FORMAT>
Output format passed to typst compile

[possible values: pdf, png, svg, html]

- template <TEMPLATE>
Output template name applied after compilation.

Use ``basic``, ``pico``, or a directory name under the configured themes

directory.

```
--config <CONFIG>
    Path to project config TOML

-q, --quiet
    Quiet mode

--timeout <TIMEOUT>
    Per-chunk timeout in seconds

-h, --help
    Print help (see a summary with '-h')
```

calepin watch

Watch, preprocess, and delegate recompiles to typst watch

Usage: calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

```
<INPUT>      Input .typ file
[OUTPUT]     Output path passed to typst watch
[TYPST_ARGS]... Arguments forwarded to typst watch after '--'
```

Options:

```
--format <FORMAT>  Output format passed to typst watch [possible values: pdf,
png, svg, html]
--config <CONFIG>  Path to project config TOML
-q, --quiet        Quiet mode
--timeout <TIMEOUT> Per-chunk timeout in seconds
-h, --help        Print help
```

calepin stop

Stop a running calepin watch process

Usage: calepin stop [INPUT]

Arguments:

```
[INPUT] Input .typ file to stop the matching calepin watch. Omit this value to
stop all active watches under the current project's `.calepin` directory
```

Options:

```
-h, --help Print help
```

calepin clean

Remove `.calepin` directories and generated artifacts

Usage: calepin clean [OPTIONS]

Options:

```
-d, --depth <DEPTH> Maximum recursion depth when searching for `.calepin`
directories
-y, --yes            Skip interactive confirmation and delete immediately
-h, --help          Print help
```