

CLI reference

calepin

```
Preprocess Typst documents with executable code chunks

Usage: calepin <COMMAND>

Commands:
  new      Create a notebook file, website scaffold, or ejected theme
  health   Check Calepin's local runtime environment and local links
  compile  Preprocess, then invoke typst compile
  watch    Watch, preprocess, and delegate recompiles to typst watch
  serve    Serve static files locally
  update   Update Calepin using the official installer updater
  clean    Remove `.calepin` directories and generated artifacts
  help     Print this message or the help of the given subcommand(s)

Options:
  -v, --version  Print version
  -h, --help     Print help
```

calepin new

```
Create a notebook file, website scaffold, or ejected theme

Usage: calepin new [OPTIONS] <PATH|website|theme> [DIR]

Arguments:
  <PATH|website|theme>  What to create: a .typ notebook path, `website`, or `theme`
  [DIR]                Destination directory when creating a website scaffold or ejected theme

Options:
  --theme <THEME>  Built-in theme to use when creating a website scaffold or ejected theme
                   [possible values: calepin, academic]
  -f, --force       Overwrite the file if it already exists
  -h, --help        Print help

Examples:
  calepin new paper.typ
  calepin new website
  calepin new website --theme academic
  calepin new theme
  calepin new theme --theme academic
  calepin new theme themes/my-theme
```

calepin health

```
Check Calepin's local runtime environment and local links

Usage: calepin health [OPTIONS]

Options:
  --config <CONFIG>  Path to project config TOML
  -d, --depth <DEPTH>  Maximum recursion depth when searching for links
  --json              Print machine-readable JSON
  --strict            Exit with an error when warnings are present
  --check-external-links  Also check external links
  -h, --help          Print help
```

calepin compile

```
Preprocess, then invoke typst compile

Usage: calepin compile [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:
  <INPUT>          Input .typ file, or a website source directory containing calepin.toml
  [OUTPUT]         Output file path, or website output directory when INPUT is a directory
  [TYPST_ARGS]...  Arguments forwarded to typst compile after `..`

Options:
  --format <FORMAT>  Output format passed to typst compile
                     [possible values: pdf, png, svg, html]
  --minify            Minify HTML output after theming and asset processing
  --config <CONFIG>  Path to project config TOML
  -q, --quiet         Quiet mode
  --timeout <TIMEOUT>  Per-chunk timeout in seconds
  -P, --param <KEY=VALUE>
```

Override a document parameter as `key=value` (repeatable).

Takes precedence over `calepin.setup(params: ...)` , so the same document can render with different values without editing the source.

-h, --help
Print help (see a summary with '-h')

calepin watch

Watch, preprocess, and delegate recompiles to typst watch

Usage: calepin watch [OPTIONS] <INPUT> [OUTPUT] [TYPST_ARGS]...

Arguments:

<INPUT>
Input .typ file, or a website source directory containing calepin.toml

[OUTPUT]
Output file path, or website output directory when INPUT is a directory

[TYPST_ARGS]...
Arguments forwarded to typst watch after `--`

Options:

--format <FORMAT>
Output format passed to typst watch

[possible values: pdf, png, svg, html]

--serve
Serve the website while watching a directory

--open
Open the served website in the default browser

--host <HOST>
Interface to bind when serving a watched website

[default: 127.0.0.1]

--port <PORT>
Port to bind when serving a watched website (default: first free port from 8000)

--config <CONFIG>
Path to project config TOML

-q, --quiet
Quiet mode

--timeout <TIMEOUT>
Per-chunk timeout in seconds

-P, --param <KEY=VALUE>
Override a document parameter as `key=value` (repeatable).

Takes precedence over `calepin.setup(params: ...)` , so the same document can render with different values without editing the source.

-h, --help
Print help (see a summary with '-h')

calepin serve

Serve static files locally

Usage: calepin serve [OPTIONS] <DIR>

Arguments:

<DIR> Directory containing static files to serve

Options:

--host <HOST> Interface to bind [default: 127.0.0.1]

-p, --port <PORT> Port to bind (default: first free port from 8000)

--open Open the website in the default browser

-h, --help Print help

calepin update

Update Calepin using the official installer updater

Usage: calepin update

Options:

-h, --help Print help

calepin clean

Remove `.calepin` directories and generated artifacts

Usage: calepin clean [OPTIONS]

Options:

-d, --depth <DEPTH> Maximum recursion depth when searching for `.calepin` directories

-y, --yes Skip interactive confirmation and delete immediately

-h, --help Print help