

02 : 52 : 34
HRS MIN SEC

Shopee Code League 2022 - Qualification Round

LIVE INVITE ONLY ACCESS

Mar 19, 2022, 02:00 PM WIB - Mar 19, 2022, 05:00 PM WIB

[INSTRUCTIONS](#) [PROBLEMS](#) [SUBMISSIONS](#) [LEADERBOARD](#) [ANALYTICS](#) [JUDGE](#)[← Problems](#) / Money Transfer

Money Transfer

Max. score: 100

SeaMoney has a feature to transfer money between users. Let's imagine a simple scenario.

N usernames—consisting of lowercase Latin characters—each starts with a balance b . Amongst them, T transactions happened, where user u_a transfers x amount of money to u_b . If x is larger than the u_a 's balance when the transaction happens, the transaction is automatically rejected.

Output the final balance of each user.

Input

The first line contains two numbers N and T ($1 \leq N, T \leq 1000$). Each of the next N following lines contain username u_i ($1 \leq |u_i| \leq 10$) and integer b_i ($1 \leq b_i \leq 10^9$), denoting the balance of user u_i . Following that are T lines, each containing two usernames u_a and u_b ($u_a \neq u_b$) followed by an integer x ($1 \leq x \leq 10^9$), denoting the amount of money transferred from u_a to u_b .

Output

Output the balance of all users in alphabetical order.

SAMPLE INPUT



```
3 4
amir 10
brenda 10
charlie 10
amir brenda 5
brenda charlie 5
charlie amir 20
charlie amir 7
```

SAMPLE OUTPUT



```
amir 12
brenda 10
charlie 8
```

Explanation

NA

Time Limit: 1.0 sec(s) for each input file.**Memory Limit:** 256 MB**Source Limit:** 1024 KB**Marking Scheme:** Score is assigned when all the testcases pass.**Allowed Languages:** Bash, C, C++, C++14, C++17, Clojure, C#, D, Erlang, F#, Go, Groovy, Haskell, Java, Java 8, Java 14, JavaScript(Rhino), JavaScript(Node.js), Julia, Kotlin, Lisp, Lisp (SBCL), Lua, Objective-C, OCaml, Octave, Pascal, Perl, PHP, Python, Python 3, Python 3.8, Racket, Ruby, Rust, Scala, Swift-4.1, Swii ?

CODE EDITOR

Save

C (gcc 10.3)

```
1  /*
2  // Sample code to perform I/O:
3  #include <stdio.h>
4
5  int main(){
6      int num;
7      scanf("%d", &num);          // Reading input from STDIN
8      printf("Input number is %d.\n", num);    // Writing output to STDOUT
9  }
10
11 // Warning: Printing unwanted or ill-formatted data to output will cause the test cases to fail
12 */
13
14 // Write your code here
15
```

1:1

vscode

Test against custom input ▼

Compile & Test code

Submit code

Tip: You can submit any number of times you want. Your best submission is considered for computing total score.

Your Rating:

Like 0

Share

View all comments

	Resources	Solutions	Company	Service & Support
<div>+1-650-461-4192</div> <div>contact@hackerearth.com</div> <div> </div>	Tech Recruitment Blog	Assess Developers	About Us	Technical Support
	Product Guides	Conduct Remote Interviews	Press	Contact Us
	Developer hiring guide	Assess University Talent	Careers	
	Engineering Blog	Organize Hackathons		
	Developers Blog			
	Developers Wiki			
	Competitive Programming			
	Start a Programming Club			

Practice Machine Learning

© 2022 HackerEarth All rights reserved | [Terms of Service](#) | [Privacy Policy](#)