

Horn SAT

Implications:

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Negative clauses:

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Negative clauses:

Or of negative literals.

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Negative clauses:

Or of negative literals.

$$\overline{u} \vee \overline{v}$$

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Negative clauses:

Or of negative literals.

$$\bar{u} \vee \bar{v}$$

Taint Example:

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Negative clauses:

Or of negative literals.

$$\bar{u} \vee \bar{v}$$

Taut Example:

$$\implies A, A \implies B, \bar{B}.$$

Horn SAT

Implications:

And of positive literals imply **one** positive literal.

$$x \wedge y \rightarrow z$$

Negative clauses:

Or of negative literals.

$$\bar{u} \vee \bar{v}$$

Taint Example:

$$\implies A, A \implies B, \bar{B}.$$

Is this satisfiable?

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm:

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true so x_4 must be true

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true so x_4 must be true

Solution:

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true so x_4 must be true

Solution: $\{x_1, x_2, x_3, x_4\}$ are True

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true so x_4 must be true

Solution: $\{x_1, x_2, x_3, x_4\}$ are True

Could also set x_5 to true, or both x_5 and x_6 to true...

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true so x_4 must be true

Solution: $\{x_1, x_2, x_3, x_4\}$ are True

Could also set x_5 to true, or both x_5 and x_6 to true...but don't!

Horn Sat: another view.

$$x_1 \wedge x_2 \implies x_4$$

$$x_3 \implies x_2$$

$$x_1 \implies x_3$$

$$x_5 \wedge x_1 \implies x_3$$

$$x_2 \wedge x_6 \implies x_5$$

$$\implies x_1$$

Problem: Find consistent assignment with fewest “True” variables.

Greedy algorithm: Only set variables to true if you have to.

Example:

x_1 must be true so x_3 must be true

so x_2 must be true so x_4 must be true

Solution: $\{x_1, x_2, x_3, x_4\}$ are True

Could also set x_5 to true, or both x_5 and x_6 to true...but don't!

Same as horn sat!

Why same as HornSAT?

Horn SAT had negative clauses.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true...

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true
is set to true to satisfy a clause

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true
is set to true to satisfy a clause
so it must be true.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true
is set to true to satisfy a clause
so it must be true.

Horn has negative clauses.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true
is set to true to satisfy a clause
so it must be true.

Horn has negative clauses.

Negative clauses only problem for true variables.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true
is set to true to satisfy a clause
so it must be true.

Horn has negative clauses.

Negative clauses only problem for true variables.

Any variable that is true must be true.

Why same as HornSAT?

Horn SAT had negative clauses.

No negative clauses for above algorithm.

Algorithm: Set a variable true ..if you have to!

Property: any variable set to true must be true in *any* satisfying assignment.

By induction. First k set to true... must be!

The $k + 1$ set variable set to true
is set to true to satisfy a clause
so it must be true.

Horn has negative clauses.

Negative clauses only problem for true variables.

Any variable that is true must be true.

So if a negative clause is false, it must be.

Efficient implementation

$$\begin{array}{lll} x_1 \wedge x_2 & \implies & x_4 \\ x_3 & \implies & x_2 \\ x_1 & \implies & x_3 \\ x_5 \wedge x_1 & \implies & x_3 \\ x_2 \wedge x_6 & \implies & x_5 \\ & \implies & x_1 \end{array}$$

Efficient implementation

$$\begin{array}{lll} x_1 \wedge x_2 & \implies & x_4 \\ x_3 & \implies & x_2 \\ x_1 & \implies & x_3 \\ x_5 \wedge x_1 & \implies & x_3 \\ x_2 \wedge x_6 & \implies & x_5 \\ & \implies & x_1 \end{array}$$

For each clause: keep count of true antecedents:

Efficient implementation

$$\begin{array}{lll} x_1 \wedge x_2 & \implies & x_4 \\ x_3 & \implies & x_2 \\ x_1 & \implies & x_3 \\ x_5 \wedge x_1 & \implies & x_3 \\ x_2 \wedge x_6 & \implies & x_5 \\ & \implies & x_1 \end{array}$$

For each clause: keep count of true antecedents:
When all antecedents true, then make consequent true.

Efficient implementation

$$\begin{array}{lll} x_1 \wedge x_2 & \implies & x_4 \\ x_3 & \implies & x_2 \\ x_1 & \implies & x_3 \\ x_5 \wedge x_1 & \implies & x_3 \\ x_2 \wedge x_6 & \implies & x_5 \\ & \implies & x_1 \end{array}$$

For each clause: keep count of true antecedents:

When all antecedents true, then make consequent true.

Data Structure:

Efficient implementation

$$\begin{array}{lll} x_1 \wedge x_2 & \implies & x_4 \\ x_3 & \implies & x_2 \\ x_1 & \implies & x_3 \\ x_5 \wedge x_1 & \implies & x_3 \\ x_2 \wedge x_6 & \implies & x_5 \\ & \implies & x_1 \end{array}$$

For each clause: keep count of true antecedents:

When all antecedents true, then make consequent true.

Data Structure:

Connect variable to clauses with var as antecedent.

Efficient implementation

$$\begin{array}{lll} x_1 \wedge x_2 & \implies & x_4 \\ x_3 & \implies & x_2 \\ x_1 & \implies & x_3 \\ x_5 \wedge x_1 & \implies & x_3 \\ x_2 \wedge x_6 & \implies & x_5 \\ & \implies & x_1 \end{array}$$

For each clause: keep count of true antecedents:

When all antecedents true, then make consequent true.

Data Structure:

Connect variable to clauses with var as antecedent.

When variable is set to true see if connected clauses are invoked.

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

x_1 being true may mean nothing for x_3 ?

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

x_1 being true may mean nothing for x_3 ?

don't have to set it to true.

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

x_1 being true may mean nothing for x_3 ?

don't have to set it to true.

No known polynomial time algorithm.

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

x_1 being true may mean nothing for x_3 ?

don't have to set it to true.

No known polynomial time algorithm.

...no polynomial time algorithm unless $NP = P$...

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

x_1 being true may mean nothing for x_3 ?

don't have to set it to true.

No known polynomial time algorithm.

...no polynomial time algorithm unless $NP = P$...

More about this...

Any SAT formula?

$$x_1 \implies x_2 \vee x_3.$$

x_1 being true may mean nothing for x_3 ?

don't have to set it to true.

No known polynomial time algorithm.

...no polynomial time algorithm unless $NP = P$...

More about this... later in the course.

Set Cover.

Input:

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Sets: Walmart locations covers subset of customers.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Sets: Walmart locations covers subset of customers.

Items: Job responsibilities (ruby, perl, python, web, unix,...).

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Sets: Walmart locations covers subset of customers.

Items: Job responsibilities (ruby, perl, python, web, unix,...).

Sets: People with job capabilities.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Sets: Walmart locations covers subset of customers.

Items: Job responsibilities (ruby, perl, python, web, unix,...).

Sets: People with job capabilities.

Items: factory needs (touch screens, chips).

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Sets: Walmart locations covers subset of customers.

Items: Job responsibilities (ruby, perl, python, web, unix,...).

Sets: People with job capabilities.

Items: factory needs (touch screens, chips).

Sets: suppliers.

Set Cover.

Input:

Items: $B = \{1, \dots, n\}$

Sets: $S_1, \dots, S_m \subseteq B$

Find fewest sets that cover B (so that union is B)

Items: City Blocks.

Sets: Possible cellphone tower location.

Each cell phone tower location covers some subset of blocks.

Items: Customers.

Sets: Walmart locations covers subset of customers.

Items: Job responsibilities (ruby, perl, python, web, unix,...).

Sets: People with job capabilities.

Items: factory needs (touch screens, chips).

Sets: suppliers.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

In iteration t , cover $\frac{1}{k}n_t$ remaining elements.

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

In iteration t , cover $\frac{1}{k}n_t$ remaining elements.

$$n_{t+1} \leq$$

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

In iteration t , cover $\frac{1}{k}n_t$ remaining elements.

$$n_{t+1} \leq n_t - \frac{1}{k}n_t$$

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

In iteration t , cover $\frac{1}{k}n_t$ remaining elements.

$$n_{t+1} \leq n_t - \frac{1}{k}n_t = (1 - \frac{1}{k})n_t.$$

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

In iteration t , cover $\frac{1}{k}n_t$ remaining elements.

$$n_{t+1} \leq n_t - \frac{1}{k}n_t = (1 - \frac{1}{k})n_t.$$

$$n_t \leq (1 - \frac{1}{k})^t n_0$$

Greedy Algorithm

Choose set S_i that has largest number of elements.

Remove elements in S_i from all sets.

Repeat.

Number of sets is number of iterations.

How many iterations?

Property: Set cover of size k (best solution)

\implies there exists a set that contains $\frac{1}{k}$ of remaining elements.

Analysis:

n_t elements remain at time t (after using t sets.)

In iteration t , cover $\frac{1}{k}n_t$ remaining elements.

$$n_{t+1} \leq n_t - \frac{1}{k}n_t = (1 - \frac{1}{k})n_t.$$

$$n_t \leq (1 - \frac{1}{k})^t n_0$$

When do we stop?

Bound iterations.

When do we stop?

Bound iterations.

When do we stop?

When $n_t < 1$?

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

For what t must $n_t < 1$?

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

For what t must $n_t < 1$?

- (A) $t = \log n$
- (B) $t = k$
- (C) $t = k \ln n.$

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

For what t must $n_t < 1$?

(A) $t = \log n$

(B) $t = k$

(C) $t = k \ln n$.

(C).

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

For what t must $n_t < 1$?

(A) $t = \log n$

(B) $t = k$

(C) $t = k \ln n$.

(C).

Plug in $t = k \ln n + 1$

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

For what t must $n_t < 1$?

(A) $t = \log n$

(B) $t = k$

(C) $t = k \ln n$.

(C).

Plug in $t = k \ln n + 1$ and clearly $n_t < 1$.

Bound iterations.

When do we stop?

When $n_t < 1$?

Recall: $n_t \leq (1 - \frac{1}{k})^t n_0$

For what t must $n_t < 1$?

(A) $t = \log n$

(B) $t = k$

(C) $t = k \ln n$.

(C).

Plug in $t = k \ln n + 1$ and clearly $n_t < 1$. (More in a moment.)

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Bound iterations (really)

$$n_t \leq (1 - \frac{1}{k})^t n_0$$

When must $n_t < 1$?

Remember:

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?


Remember: $(1 - x) \leq e^{-x}$

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$




Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$




$$\text{So, } n_t \leq \left(1 - \frac{1}{k}\right)^t n$$

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$




$$\text{So, } n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n$$

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$




So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right) n$.

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right) n$.


For $t = k \ln n$,

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right) n$.


For $t = k \ln n$, $n_t < (e^{-\ln n}) n$

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right) n$.


For $t = k \ln n$, $n_t < \left(e^{-\ln n}\right) n = \left(\frac{1}{n}\right) n$

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right) n$.


For $t = k \ln n$, $n_t < \left(e^{-\ln n}\right) n = \left(\frac{1}{n}\right) n = 1$.

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right) n$.

For $t = k \ln n$, $n_t < \left(e^{-\ln n}\right) n = \left(\frac{1}{n}\right) n = 1$.


No elements are uncovered at this time!

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < \left(e^{-\frac{1}{k}}\right)^t n \leq \left(e^{-\frac{t}{k}}\right)n$.

For $t = k \ln n$, $n_t < \left(e^{-\ln n}\right)n = \left(\frac{1}{n}\right)n = 1$.

No elements are uncovered at this time!


So $t \leq k \ln n + 1$. Number of sets for greedy is at most $k \ln n + 1$!

Bound iterations (really)

$$n_t \leq \left(1 - \frac{1}{k}\right)^t n_0$$

When must $n_t < 1$?

Remember: $(1 - x) \leq e^{-x}$



So, $n_t \leq \left(1 - \frac{1}{k}\right)^t n < (e^{-\frac{1}{k}})^t n \leq (e^{-\frac{t}{k}}) n$.

For $t = k \ln n$, $n_t < (e^{-\ln n}) n = \left(\frac{1}{n}\right) n = 1$.

No elements are uncovered at this time!

So $t \leq k \ln n + 1$. Number of sets for greedy is at most $k \ln n + 1$!

Within $\ln n$ factor (almost) of the best possible!

Can we do better?

We did not find optimal solution!

Can we do better?

We did not find optimal solution!

Is there a better analysis?

Can we do better?

We did not find optimal solution!

Is there a better analysis?

No.

Can we do better?

We did not find optimal solution!

Is there a better analysis?

No. Problem 5.33!

Can we do better?

We did not find optimal solution!

Is there a better analysis?

No. Problem 5.33!

Is there a better algorithm?

Can we do better?

We did not find optimal solution!

Is there a better analysis?

No. Problem 5.33!

Is there a better algorithm?

“Probably” not!

Can we do better?

We did not find optimal solution!

Is there a better analysis?

No. Problem 5.33!

Is there a better algorithm?

“Probably” not!

Again, only if $P=NP$.

Can we do better?

We did not find optimal solution!

Is there a better analysis?

No. Problem 5.33!

Is there a better algorithm?

“Probably” not!

Again, only if $P=NP$.

More later in the course.

Recipe for Dynamic Programming

- Define a set of problems, such that

Recipe for Dynamic Programming

- Define a set of problems, such that
 - base case - easy to solve

Recipe for Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.

Recipe for Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)

Recipe for Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8

Greedy??

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8

Greedy??

- (A) Choose first number, delete higher, continue.
- (B) Choose lowest number, continue with rest of sequence.

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8

Greedy??

- (A) Choose first number, delete higher, continue.
 - (B) Choose lowest number, continue with rest of sequence.
- (A) seems bad.

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8

Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B):

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8

Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8



Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1 2

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8



Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1 2 4

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8



Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1 2 4 8

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8



Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1 2 4 8

7 3 5 6 8 2 9 4 1

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8



Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1 2 4 8

7 3 5 6 8 2 9 4 1

Not good!

Longest Increasing Subsequence

Given sequence of numbers: a_1, a_2, \dots, a_n .

Find longest increasing sequence of numbers.

7 3 5 6 1 2 9 4 8



Greedy??

(A) Choose first number, delete higher, continue.

(B) Choose lowest number, continue with rest of sequence.

(A) seems bad.

Try method (B): 1 2 4 8

7 3 5 6 8 2 9 4 1

Not good!

What to do?

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer?

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(j) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(j) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG?

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(j) = \max_{j < i \wedge a[j] < a[i]} \{L(i) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(i) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

$O(n^2)$ time

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(i) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

$O(n^2)$ time $O(n)$ space.

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(i) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

$O(n^2)$ time $O(n)$ space. Find longest subsequence?

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(i) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

$O(n^2)$ time $O(n)$ space. Find longest subsequence?(maintain pointers)

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(i) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$L(i) = 1$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$L(i) = \max(L(i), L(j) + 1)$

$O(n^2)$ time $O(n)$ space. Find longest subsequence?(maintain pointers)

For $i = 1, 2, \dots, n$

$L(i) = 1$, $\text{prev}(i) = i$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

if $L(j) + 1 > L(i)$

$L(i) = L(j) + 1$; $\text{prev}(i) = j$

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(j) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

$O(n^2)$ time $O(n)$ space. Find longest subsequence? (maintain pointers)

For $i = 1, 2, \dots, n$

$$L(i) = 1, \text{prev}(i) = i$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

if $L(j) + 1 > L(i)$

$$L(i) = L(j) + 1; \text{prev}(i) = j$$

Chase $\text{prev}(j)$ pointers backwards to construct path!

Dynamic Programming Solution.

$L(i)$ is length of longest increasing subsequence ending at position i .

Do I know $L(1)$? Is $L(n)$ good enough for the answer? ($\max_j L(j)$)

Recursion

$$L(i) = \max_{j < i \wedge a[j] < a[i]} \{L(j) + 1\}$$

Think of the DAG? **For** $i = 1, 2, \dots, n$

$$L(i) = 1$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

$$L(i) = \max(L(i), L(j) + 1)$$

$O(n^2)$ time $O(n)$ space. Find longest subsequence? (maintain pointers)

For $i = 1, 2, \dots, n$

$$L(i) = 1, \text{prev}(i) = i$$

For $j = 1, \dots, i - 1$

if $a[j] < a[i]$

if $L(j) + 1 > L(i)$

$$L(i) = L(j) + 1; \text{prev}(i) = j$$

Chase $\text{prev}(j)$ pointers backwards to construct path! Similar to finding sp tree.

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Longest increasing subsequence.

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Longest increasing subsequence.

Subproblems:

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Longest increasing subsequence.

Subproblems:

$L(i)$ - longest increasing subsequence ending at i .

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Longest increasing subsequence.

Subproblems:

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Dynamic Programming

- Define a set of problems, such that
 - ▶ base case - easy to solve
 - ▶ final case - matches (closely) the final problem we want to solve.
- Write it as a recursion: Solve bigger problem in terms of the smaller problems. (Should be a DAG on the problem instances!)
- Compute the problems on the DAG in the linearized order!

Longest increasing subsequence.

Subproblems:

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

“DAG of problems to solve.”

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”. Exponential time!!

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”. Exponential time!!

Memoization.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”. Exponential time!!

Memoization.

Answer $L(i)$ same each time, so remember, return.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”. Exponential time!!

Memoization.

Answer $L(i)$ same each time, so remember, return.

Only n different arguments provided to $L(\cdot)$.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”. Exponential time!!

Memoization.

Answer $L(i)$ same each time, so remember, return.

Only n different arguments provided to $L(\cdot)$.

Each call takes $O(n)$ time the *first* time.

Dynamic Programming and Recursion.

$L(i)$ - longest increasing subsequence ending at i .

Only need $L(j)$ for $j < i$ to find $L(i)$.

Recursion \equiv dynamic programming?

sub problem solutions...built from smaller subproblems.

Recursive instead of iterative?

def $L(i)$:

$val = 1$

for $j = 1, \dots, n$:

if $a[j] < a[i]$:

if $L(j) + 1 > val$:

$val = L(j) + 1$

Enumerates all paths in “DAG”. Exponential time!!

Memoization.

Answer $L(i)$ same each time, so remember, return.

Only n different arguments provided to $L(\cdot)$.

Each call takes $O(n)$ time the *first* time.

Same as “iterative”.