


Announcements

- Project 1: Search
 - Due Fri 9/16 at 5:00pm.
 - Solo or in group of two. See Piazza for instructions.
- (Optional) Project 1 Mini-Contest
 - Due Sun 9/18 at 11:59pm.
- Homework 3: Game Trees
 - Due Mon 9/19 at 11:59pm.
- Midterm 1: Thursday October 6, 7-9pm
 - See Piazza if you need to reschedule.

CS 188: Artificial Intelligence


Uncertainty and Utilities






Instructors: Josh Hug & Adam Janin

University of California, Berkeley

Uncertain Outcomes




Worst-Case vs. Average Case




Idea: Uncertain outcomes controlled by chance, not an adversary!

Expectimax Search


- Why wouldn't we know what the result of an action will be?
 - Explicit randomness: rolling dice
 - Unpredictable opponents: the ghosts respond randomly
 - Actions can fail: when moving a robot, wheels might slip
- Values should now reflect average-case (expectimax) outcomes, not worst-case (minimax) outcomes
- **Expectimax search:** compute the average score under optimal play
 - Max nodes as in minimax search
 - Chance nodes are like min nodes but the outcome is uncertain
 - Calculate their **expected utilities**
 - I.e. take weighted average (expectation) of children
- Later, we'll learn how to formalize the underlying uncertain-result problems as **Markov Decision Processes**



Video of Demo Minimax vs Expectimax (Min)



Video of Demo Minimax vs Expectimax (Exp)



Expectimax Pseudocode

```
def value(state):
```

 if the state is a terminal state: return the state's utility

 if the next agent is MAX: return max-value(state)

 if the next agent is EXP: return exp-value(state)

```
def max-value(state):
```

 initialize $v = -\infty$

 for each successor of state:

$v = \max(v, \text{value}(\text{successor}))$

 return v

```
def exp-value(state):
```


 initialize $v = 0$

 for each successor of state:

$p = \text{probability}(\text{successor})$


$v += p * \text{value}(\text{successor})$

 return v




Expectimax Pseudocode

```
def exp-value(state):
    initialize v = 0
    for each successor of state:
        p = probability(successor)
        v += p * value(successor)
    return v
```





$$v = (1/2)(8) + (1/3)(24) + (1/6)(-12) = 10$$


Expectimax Example




Expectimax Pruning?



Depth-Limited Expectimax




Probabilities



Reminder: Probabilities

- A **random variable** represents an event whose outcome is unknown
- A **probability distribution** is an assignment of weights to outcomes
- Example: Traffic on freeway
 - Random variable: T = whether there's traffic
 - Outcomes: $T \in \{\text{none}, \text{light}, \text{heavy}\}$
 - Distribution: $P(T=\text{none}) = 0.25, P(T=\text{light}) = 0.50, P(T=\text{heavy}) = 0.25$
- Some laws of probability (more later):
 - Probabilities are always non-negative
 - Probabilities over all possible outcomes sum to one
- As we get more evidence, probabilities may change:
 - $P(T=\text{heavy}) = 0.25, P(T=\text{heavy} \mid \text{Hour}=8\text{am}) = 0.60$
 - We'll talk about methods for reasoning and updating probabilities later



0.25




0.50





0.25

Reminder: Expectations

- The expected value of a function of a random variable is the average, weighted by the probability distribution over outcomes
- Example: How long to get to the airport?




Time:	20 min	x	+	30 min	x	+	60 min	x	35 min
Probability:	0.25			0.50			0.25		



What Probabilities to Use?

- In expectimax search, we have a probabilistic model of how the opponent (or environment) will behave in any state
 - Model could be a simple uniform distribution (roll a die)
 - Model could be sophisticated and require a great deal of computation
 - We have a chance node for any outcome out of our control: opponent or environment
 - The model might say that adversarial actions are likely!
- For now, assume each chance node magically comes along with probabilities that specify the distribution over its outcomes





Having a probabilistic belief about another agent's action does not mean that the agent is flipping any coins!

Quiz: Informed Probabilities




- Let's say you know that your opponent is actually running a depth 2 minimax, using the result 80% of the time, and moving randomly otherwise
- Question: What tree search should you use?



- Answer: Expectimax!**

- To figure out EACH chance node's probabilities, you have to run a simulation of your opponent
- This kind of thing gets very slow very quickly
- Even worse if you have to simulate your opponent simulating you...
- ... except for minimax, which has the nice property that it all collapses into one game tree

Modeling Assumptions



The Dangers of Optimism and Pessimism

Dangerous Optimism

Assuming chance when the world is adversarial




Dangerous Pessimism

Assuming the worst case when it's not likely



Assumptions vs. Reality




	Adversarial Ghost	Random Ghost
Minimax Pacman	Matched, Hard	Pessimistic
Expectimax Pacman	Optimistic	Matched, Easy

Pacman used depth 4 search with an eval function that avoids trouble
Ghost used depth 2 search with an eval function that seeks Pacman

[Demos: world assumptions (L7D3,4,5,6)]


Video of Demo World Assumptions

Random Ghost – Expectimax Pacman




Video of Demo World Assumptions

Adversarial Ghost – Minimax Pacman




Video of Demo World Assumptions

Adversarial Ghost – Expectimax Pacman




Video of Demo World Assumptions

Random Ghost – Minimax Pacman



Which is Easiest? Which is Hardest?




	Adversarial Ghost	Random Ghost
Minimax Pacman		
Expectimax Pacman		

Results from playing 5 games

Pacman used depth 4 search with an eval function that avoids trouble
Ghost used depth 2 search with an eval function that seeks Pacman



[Demos: world assumptions (L7D3,4,5,6)]

Other Game Types



Mixed Layer Types

- E.g. Backgammon
- Expectiminimax
 - Environment is an extra “random agent” player that moves after each min/max agent
 - Each node computes the appropriate combination of its children



Example: Backgammon

- Dice rolls increase b : 21 possible rolls with 2 dice
 - Backgammon ≈ 20 legal moves
 - Depth 2 = $20 \times (21 \times 20)^3 = 1.2 \times 10^9$
- As depth increases, probability of reaching a given search node shrinks
 - So usefulness of search is diminished
 - So limiting depth is less damaging
 - But pruning is trickier...
- Historic AI: TDGammon uses depth-2 search + very good evaluation function + reinforcement learning: world-champion level play
- 1st AI world champion in any game!






Multi-Agent Utilities


- What if the game is not zero-sum, or has multiple players?

- Generalization of minimax:

- Terminals have utility tuples
- Node values are also utility tuples
- Each player maximizes its own component
- Can give rise to cooperation and competition dynamically...




Utilities




Maximum Expected Utility

- Why should we average utilities? Why not minimax?
- Principle of maximum expected utility:
 - A rational agent should chose the action that **maximizes its expected utility, given its knowledge**
- Questions:
 - Where do utilities come from?
 - How do we know such utilities even exist?
 - How do we know that averaging even makes sense?
 - What if our behavior (preferences) can't be described by utilities?




What Utilities to Use?



- For worst-case minimax reasoning, terminal function scale doesn't matter
 - We just want better states to have higher evaluations (get the ordering right)
 - We call this **insensitivity to monotonic transformations**

What Utilities to Use?




- For average-case expectimax reasoning, we need *magnitudes* to be meaningful
 - Sensitivity to monotonic transformations

Utilities

- Utilities are functions from outcomes (states of the world) to real numbers that describe an agent's preferences
- Where do utilities come from?
 - In a game, may be simple (+1/-1)
 - Utilities summarize the agent's goals
 - Theorem: any “rational” preferences can be summarized as a utility function
- We hard-wire utilities and let behaviors emerge
 - Why don't we let agents pick utilities?
 - Why don't we prescribe behaviors?



Utilities: Uncertain Outcomes




Preferences

- An agent must have preferences among:


- Prizes: A , B , etc.
- Lotteries: situations with uncertain prizes

$$L = [p, A; (1-p), B]$$

A Prize



A Lottery




- Notation:

- Preference: $A \succ B$
- Indifference: $A \sim B$



Rationality




Rational Preferences

- We want some constraints on preferences before we call them rational, such as:

Axiom of Transitivity: $(A \succ B) \wedge (B \succ C) \Rightarrow (A \succ C)$

- For example: an agent with **intransitive preferences** can be induced to give away all of its money

- If $B > C$, then an agent with C would pay (say) 1 cent to get B
- If $A > B$, then an agent with B would pay (say) 1 cent to get A
- If $C > A$, then an agent with A would pay (say) 1 cent to get C



Rational Preferences

The Axioms of Rationality

Orderability

$$(A \succ B) \vee (B \succ A) \vee (A \sim B)$$

Transitivity

$$(A \succ B) \wedge (B \succ C) \Rightarrow (A \succ C)$$

Continuity

$$A \succ B \succ C \Rightarrow \exists p [p, A; 1-p, C] \sim B$$

Substitutability

$$A \sim B \Rightarrow [p, A; 1-p, C] \sim [p, B; 1-p, C]$$

Monotonicity

$$A \succ B \Rightarrow$$

$$(p \geq q \Leftrightarrow [p, A; 1-p, B] \succeq [q, A; 1-q, B])$$



Theorem: Rational preferences imply behavior describable as maximization of expected utility


MEU Principle

- Theorem [Ramsey, 1931; von Neumann & Morgenstern, 1944]
 - Given any preferences satisfying these constraints, there exists a real-valued function U such that:

$$U(A) \geq U(B) \Leftrightarrow A \succeq B$$


$$U([p_1, S_1; \dots; p_n, S_n]) = \sum_i p_i U(S_i)$$

- I.e. values assigned by U preserve preferences of both prizes and lotteries!



- Maximum expected utility (MEU) principle:
 - Choose the action that maximizes expected utility
 - Note: an agent can be entirely rational (consistent with MEU) without ever representing or manipulating utilities and probabilities
 - E.g., a lookup table for perfect tic-tac-toe, a reflex vacuum cleaner

Human Utilities



Utility Scales

- Normalized utilities: $u_+ = 1.0, u_- = 0.0$
- Micromorts: one-millionth chance of death, useful for paying to reduce product risks, etc.
- QALYs: quality-adjusted life years, useful for medical decisions involving substantial risk
- Note: behavior is invariant under positive linear transformation


$$U'(x) = k_1 U(x) + k_2 \quad \text{where } k_1 > 0$$

- With deterministic prizes only (no lottery choices), only ordinal utility can be determined, i.e., total order on prizes




Human Utilities

- Utilities map states to real numbers. Which numbers?
- Standard approach to assessment (elicitation) of human utilities:
 - Compare a prize A to a **standard lottery** L_p between
 - “best possible prize” u_+ with probability p
 - “worst possible catastrophe” u_- with probability $1-p$
 - Adjust lottery probability p until indifference: $A \sim L_p$
 - Resulting p is a utility in $[0,1]$



Pay \$30

~




Money


- Money does not behave as a utility function, but we can talk about the utility of having money (or being in debt)
- Given a lottery $L = [p, \$X; (1-p), \$Y]$
 - The **expected monetary value** $EMV(L)$ is $p*X + (1-p)*Y$
 - $U(L) = p*U(\$X) + (1-p)*U(\$Y)$
 - Typically, $U(L) < U(EMV(L))$
 - In this sense, people are **risk-averse**
 - When deep in debt, people are **risk-prone**



Money vs. Utility




Money vs. Utility



Example: Insurance

- Consider the lottery [0.5, \$1000; 0.5, \$0]
 - What is its **expected monetary value**? (\$500)
 - What is its **certainty equivalent**?
 - Monetary value acceptable in lieu of lottery
 - \$400 for most people
 - Difference of \$100 is the **insurance premium**
 - There's an insurance industry because people will pay to reduce their risk
 - If everyone were risk-neutral, no insurance needed!
 - It's win-win: you'd rather have the \$400 and the insurance company would rather have the lottery (their utility curve is flat and they have many lotteries)



Example: Human Rationality?


- Famous example of Allais (1953)

- A: [0.8, \$4k; 0.2, \$0] ←
- B: [1.0, \$3k; 0.0, \$0]
- C: [0.2, \$4k; 0.8, \$0]
- D: [0.25, \$3k; 0.75, \$0]

- Most people prefer B > A, C > D

- But if $U(\$0) = 0$, then

- $B > A \Rightarrow U(\$3k) > 0.8 U(\$4k)$
- $C > D \Rightarrow 0.8 U(\$4k) > U(\$3k)$



Next Time: MDPs!

What are Probabilities?

- Objectivist / frequentist answer:
 - Averages over repeated *experiments*
 - E.g. empirically estimating $P(\text{rain})$ from historical observation
 - Assertion about how future experiments will go (in the limit)
 - New evidence changes the *reference class*
 - Makes one think of *inherently random* events, like rolling dice
- Subjectivist / Bayesian answer:
 - Degrees of belief about unobserved variables
 - E.g. an agent's belief that it's raining, given the temperature
 - E.g. pacman's belief that the ghost will turn left, given the state
 - Often *learn* probabilities from past experiences (more later)
 - New evidence *updates beliefs* (more later)

Uncertainty Everywhere

- Not just for games of chance!
 - I'm sick: will I sneeze this minute?
 - Email contains "FREE!": is it spam?
 - Tooth hurts: have cavity?
 - 60 min enough to get to the airport?
 - Robot rotated wheel three times, how far did it advance?
 - Safe to cross street? (Look both ways!)
- Sources of uncertainty in random variables:
 - Inherently random process (dice, etc)
 - Insufficient or weak evidence
 - Ignorance of underlying processes
 - Unmodeled variables
 - The world's just noisy – it doesn't behave according to plan!
- Compare to *fuzzy logic*, which has *degrees of truth*, rather than just *degrees of belief*