

Announcements

- Project 4: Due Friday Oct 28 5:00pm
- Homework 8: Due Monday Oct 31 11:59pm
- Midterm 2: Wednesday 11/9 7-9pm
 - Up to and including today's lecture.
- Upcoming Lectures - exact order TBD
 - Naïve Bayes
 - Perceptrons
 - Deep Learning
 - Advanced Topics

CS 188: Artificial Intelligence


Hidden Markov Models -- Filters



Instructors: Pieter Abbeel & Anca Dragan --- University of California, Berkeley

[These slides were created by Dan Klein, Pieter Abbeel, Anca Dragan for CS188 Intro to AI at UC Berkeley. All CS188 materials are available at <http://ai.berkeley.edu>.]

Example: Weather HMM




- An HMM is defined by:

- Initial distribution: $P(X_1)$
- Transitions: $P(X_t | X_{t-1})$
- Emissions: $P(E_t | X_t)$

R_{t-1}	R_t	$P(R_t R_{t-1})$
$+r$	$+r$	0.7
$+r$	$-r$	0.3
$-r$	$+r$	0.3
$-r$	$-r$	0.7

R_t	U_t	$P(U_t R_t)$
$+r$	$+u$	0.9
$+r$	$-u$	0.1
$-r$	$+u$	0.2
$-r$	$-u$	0.8

Online Belief Update




$$B_3(X) = P(X_3|e_{1:3})$$

$$B'_4(X) = P(X_4|e_{1:3}) = \sum_{x_3} P(X_4|x_3)B_3(X)$$

$$B_4(X) = P(X_4|e_{1:4}) \propto_{X_4} P(e_4|X_4)B'_4(X)$$


Example: Weather HMM




R_t	R_{t+1}	$P(R_{t+1} R_t)$
$+r$	$+r$	0.7
$+r$	$-r$	0.3
$-r$	$+r$	0.3
$-r$	$-r$	0.7

R_t	U_t	$P(U_t R_t)$
$+r$	$+u$	0.9
$+r$	$-u$	0.1
$-r$	$+u$	0.2
$-r$	$-u$	0.8

Video of Demo Pacman - Sonar (with beliefs)



Particle Filtering



Particle Filtering


- Filtering: approximate solution
- Sometimes $|X|$ is too big to use exact inference
 - $|X|$ may be too big to even store $B(X)$
 - E.g. X is continuous
- Solution: approximate inference
 - Track samples of X , not all values
 - Samples are called particles
 - Time per step is linear in the number of samples
 - But: number needed may be large
 - In memory: list of particles, not states
- This is how robot localization works in practice
- Particle is just new name for sample

0.0	0.1	0.0
0.0	0.0	0.2
0.0	0.2	0.5



	●	
		● ●
	● ●	● ● ● ●


When is Exact Inference Too Big?



- For an HMM, when would you want to avoid *exact* inference?
 - The domain of X is big, but the domain of E is small?
 - The domain of E is big, but the domain of X is small?
 - Both domains are big?

Representation: Particles



- Our representation of $P(X)$ is now a list of N particles (samples)
 - Generally, $N \ll |X|$
 - Storing map from X to counts would defeat the point
- $P(x)$ approximated by number of particles with value x
 - So, many x may have $P(x) = 0$!
 - More particles, more accuracy
- For now, all particles have a weight of 1



Particles:

(3,3)
(2,3)
(3,3)
(3,2)
(3,3)
(3,2)
(1,2)
(3,3)
(3,3)
(2,3)

Particle Filtering: Elapse Time



Particle Filtering: Elapse Time


- Each particle is moved by sampling its next position from the transition model

$$x' = \text{sample}(P(X'|x))$$

- This is like prior sampling - samples' frequencies reflect the transition probabilities
 - Here, most samples move clockwise, but some move in another direction or stay in place
- This captures the passage of time
 - If enough samples, close to exact values before and after (consistent)


Particles:

(3,3)
(2,3)
(3,3)
(3,2)
(3,3)
(3,2)
(1,2)
(3,3)
(3,3)
(2,3)





Particles:

(3,2)
(2,3)
(3,2)
(3,1)
(3,3)
(3,2)
(1,3)
(2,3)
(3,2)
(2,2)



Particle Filtering: Observe



Particle Filtering: Observe

- Slightly trickier:

- Don't sample observation, fix it
- Similar to likelihood weighting, downweight samples based on the evidence


$$w(x) = P(e|x)$$

$$B(X) \propto P(e|X)B'(X)$$

- As before, the probabilities don't sum to one, since all have been downweighted (in fact they now sum to (N times) an approximation of $P(e)$)


Particles:

(3,2)
(2,3)
(3,2)
(3,1)
(3,3)
(3,2)
(1,3)
(2,3)
(3,2)
(2,2)



Particles:

(3,2) w=.9
(2,3) w=.2
(3,2) w=.9
(3,1) w=.4
(3,3) w=.4
(3,2) w=.9
(1,3) w=.1
(2,3) w=.2
(3,2) w=.9
(2,2) w=.4





Particle Filtering: Resample

- Rather than tracking weighted samples, we resample
- N times, we choose from our weighted sample distribution (i.e. draw with replacement)
- This is equivalent to renormalizing the distribution
- Now the update is complete for this time step, continue with the next one


Particles:

(3,2) $w=.9$
(2,3) $w=.2$
(3,2) $w=.9$
(3,1) $w=.4$
(3,3) $w=.4$
(3,2) $w=.9$
(1,3) $w=.1$
(2,3) $w=.2$
(3,2) $w=.9$
(2,2) $w=.4$




(New) Particles:

(3,2)
(2,2)
(3,2)
(2,3)
(3,3)
(3,2)
(1,3)
(2,3)
(3,2)
(3,2)




Recap: Particle Filtering


- Particles: track samples of states rather than an explicit distribution




Video of Demo - Moderate Number of Particles



Video of Demo - One Particle





Video of Demo - Huge Number of Particles



Robot Localization


- In robot localization:
 - We know the map, but not the robot's position
 - Observations may be vectors of range finder readings
 - State space and readings are typically continuous (works basically like a very fine grid) and so we cannot store $B(X)$
 - Particle filtering is a main technique



Particle Filter Localization (Sonar)




Particle Filter Localization (Laser)




Robot Mapping


- SLAM: Simultaneous Localization And Mapping
 - We do not know the map or our location
 - State consists of position AND map!
 - Main techniques: Kalman filtering (Gaussian HMMs) and particle methods




DP-SLAM, Ron Parr




Particle Filter SLAM - Video 1



Particle Filter SLAM - Video 2





Dynamic Bayes Nets




Dynamic Bayes Nets (DBNs)

- We want to track multiple variables over time, using multiple sources of evidence
- Idea: Repeat a fixed Bayes net structure at each time
- Variables from time t can condition on those from $t-1$




- Dynamic Bayes nets are a generalization of HMMs

Video of Demo Pacman Sonar Ghost DBN Model



Exact Inference in DBNs

- Variable elimination applies to dynamic Bayes nets
- Procedure: “unroll” the network for T time steps, then eliminate variables until $P(X_T | e_{1:T})$ is computed



- Online belief updates: Eliminate all variables from the previous time step; store factors for current time only

DBN Particle Filters

- A particle is a complete sample for a time step
- **Initialize:** Generate prior samples for the $t=1$ Bayes net
 - Example particle: $\mathbf{G}_1^a = (3,3)$ $\mathbf{G}_1^b = (5,3)$
- **Elapse time:** Sample a successor for each particle
 - Example successor: $\mathbf{G}_2^a = (2,3)$ $\mathbf{G}_2^b = (6,3)$
- **Observe:** Weight each entire sample by the likelihood of the evidence conditioned on the sample
 - Likelihood: $P(\mathbf{E}_1^a | \mathbf{G}_1^a) * P(\mathbf{E}_1^b | \mathbf{G}_1^b)$
- **Resample:** Select prior samples (tuples of values) in proportion to their likelihood

Most Likely Explanation




HMMs: MLE Queries

- HMMs defined by
 - States X
 - Observations E
 - Initial distribution:
 - Transitions:
 - Emissions:

- New query: most likely explanation:


$$P(X_1)$$
$$P(X|X_{-1})$$
$$P(E|X)$$



$$\arg \max_{x_{1:t}} P(x_{1:t}|e_{1:t})$$

State Trellis


- State trellis: graph of states and transitions over time



- Each arc represents some transition $x_{t-1} \rightarrow x_t$
- Each arc has weight $P(x_t|x_{t-1})P(e_t|x_t)$
- Each path is a sequence of states
- The product of weights on a path is that sequence's probability along with the evidence
- Forward algorithm computes sums of paths, Viterbi computes best paths

State Trellis


- State trellis: graph of states and transitions over time



- Each arc represents some transition $x_{t-1} \rightarrow x_t$
- Each arc has weight $P(x_t|x_{t-1})P(e_t|x_t)$
- Each path is a sequence of states
- The product of weights on a path is that sequence's probability along with the evidence
- Forward algorithm computes sums of paths, Viterbi computes best paths


State Trellis

- State trellis: graph of states and transitions over time



- Each arc represents some transition $x_{t-1} \rightarrow x_t$
- Each arc has weight $P(x_t|x_{t-1})P(e_t|x_t)$
- Each path is a sequence of states
- The product of weights on a path is that sequence's probability along with the evidence
- Forward algorithm computes sums of paths, Viterbi computes best paths

Forward / Viterbi Algorithms



Forward Algorithm (Sum)

$$\begin{aligned} f_t[x_t] &= P(x_t, e_{1:t}) \\ &= P(e_t|x_t) \sum_{x_{t-1}} P(x_t|x_{t-1}) f_{t-1}[x_{t-1}] \end{aligned}$$

Viterbi Algorithm (Max)

$$\begin{aligned} m_t[x_t] &= \max_{x_{1:t-1}} P(x_{1:t-1}, x_t, e_{1:t}) \\ &= P(e_t|x_t) \max_{x_{t-1}} P(x_t|x_{t-1}) m_{t-1}[x_{t-1}] \end{aligned}$$