

Advanced Machine Learning

Lecture 7: Model Order Selection

Nora Ouzir : nora.ouzir@centralesupelec.fr

Lucca Guardiola : lucca.guardiola@centralesupelec.fr

Oct. - Nov. 2020



CentraleSupélec


Content

1. Reminders on ML
2. Robust regression
3. Hierarchical clustering
4. Classification and supervised learning
5. Non-negative matrix factorization
6. Mixture models fitting
7. Model order selection
8. Dimension reduction and data visualization

Model Selection and Evaluation

- ▶ How to set an algorithm's unknown parameters in practice?
- ▶ How to make choices about the model (e.g., *kernel type*)?
- ▶ How to choose the best algorithm for a particular problem?

Today's Lecture



Today's Lecture

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example

Today's course

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example


Motivations

Goal: Make high-level decisions about the model we want to use.

Examples from the course

- ▶ Number of components in a mixture model
 - ▶ Target dimension for matrix factorization
 - ▶ Density/minimum points parameters for density clustering
 - ▶ Type of kernel in a support vector machine
 - ▶ Degree of a polynomial in a regression problem
-
- ▶ But also a network architecture of (deep) neural networks, ...

Curve fitting example



True data generated from a sinusoid ($\sin(2\pi x)$) + (small) Gaussian noise (Bishop, 2006)

Goal: predict the value of t for some new value of x , without knowledge of the green curve → **Model selection**

Curve fitting example

We want to learn a prediction function y such that

$$y(x, \mathbf{w}) = \sum_{i=1}^M w_i x^i$$

- ▶ where M is the polynomial order (**unknown**) and $\mathbf{w} = (w_0, \dots, w_M)$ are the polynomial coefficients (**to be learnt**).

Recall:


For \mathbf{w} , one minimizes an *error function*, e.g.,

$$e(\mathbf{w}) = \sum_{n=1}^N \rho(y(x_n, \mathbf{w}) - t_n)$$

- ▶ N : number of observed data.
- ▶ $e(\mathbf{w})$ is a quadratic function w.r.t $\mathbf{w} \Rightarrow$ **unique solution \mathbf{w}^***


Problem: still need to choose M !!!

Curve fitting example



How to evaluate the “best model”?



Curve fitting example: Test vs training data



Differences btw training and test datasets

- ▶ Model fits training data perfectly, but may not do well on test data: ($M = 9$, $e_{RMS} = 0$, but poor estimation of $\sin(2\pi x)$) → **Overfitting**
- ▶ Training performance \neq test performance, but we are mainly interested in test performance → **Generalization**
- ▶ Need mechanisms for assessing how a model generalizes to unseen test data → **Model selection**

Curve fitting example: Sample size




Solutions for $M = 9$ with different numbers of data points

Increasing the size of the data set reduces over-fitting

Example: SVM with Gaussian Kernel



(1) Kernel mapping:

$$x \rightarrow K(x_i, x) = \exp\left(-\frac{\|x_i - x\|^2}{2\sigma^2}\right)$$




(2) Learn the decision function:


$$f(x) = \text{sign}\left(\sum_{i \in \text{SV}} \alpha_i y_i \exp\left(-\frac{\|x_i - x\|^2}{2\sigma^2}\right)\right)$$



σ too small




nice σ



σ too large

Model choice - Occam's (Ockham) Razor



(Normalized) dist. of data sets for three models of different complexity, in which \mathcal{M}_1 is the simplest and \mathcal{M}_3 is the most complex - \mathcal{D}_0 : observed dataset - \mathcal{M}_2 with intermediate complexity has the largest evidence (Bishop, 2006)

Key Idea: choose the simplest model that explains “reasonably” well the data

Model selection and evaluation

Raised issues

- ▶ Model evaluation : what measure(s) of performance?
- ▶ Estimation of the generalisation capacity of the model
- ▶ Practical model selection procedures

True vs Empirical Risk

True vs Empirical Risk

True vs Empirical Risk

Supremum on generalization error

$$R(y) \leq \frac{1}{N} \sum_{i=1}^N \rho(y(x_i), t_i) + \text{term}(N, h(\mathcal{M}))$$

where h stands for the complexity of the model \mathcal{M} .

- ▶ The empirical risk is not sufficient for estimating the true error R
- ▶ If h increases \rightarrow overfitting
- ▶ The bigger the N the better!

Generalization

We are looking at $R(\mathcal{D}_\infty, y)$ the theoretical performance of y on all possible future data


\rightarrow Idea: test on data other than those used for training

Today's course

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example

Validation set

Key Idea: Choose the best model without testing on \mathcal{D}_{test}




1. Randomly split $\mathcal{D} = \mathcal{D}_{train} \cup \mathcal{D}_{val} \cup \mathcal{D}_{test}$
2. Train all possible models on \mathcal{D}_{train}
3. Evaluate the performance on \mathcal{D}_{val}
4. Select the model with the best performance on \mathcal{D}_{val}
5. Test the selected model on \mathcal{D}_{test} (used only once)

If data is limited we are wasting training data...

K-fold Cross-validation

Key Idea: give an accurate estimate of the true error without wasting too much data



1. Randomly split the data into $\mathcal{D} = \mathcal{D}_{train} \cup \mathcal{D}_{test}$
2. Randomly split $\mathcal{D}_{train} = \mathcal{D}_1 \cup \dots \cup \mathcal{D}_K$ into K subsets
3. For $k = 1, \dots, K$
 - 3.1 Train the model on $K - 1$ sets
 - 3.2 Evaluate performance on the remaining set \mathcal{D}_k
4. Average the K measures of performance

N.B: To reduce variability, multiple rounds of cross-validation are performed using different partitions then averaged.

K-fold Cross-validation


The averaged error can be expressed as

$$R_{CV} = \frac{1}{K} \sum_{k=1}^K \frac{1}{N_k} \sum_{i=1}^{N_k} \rho(t_i^k, y^{k'}(x_i^k))$$


where $y^{k'}$ is learnt using the $K - 1$ partitions except the k -th one.

- ▶ if $K = N$, cross-validation is approximately an unbiased estimator of the generalization error → too expensive!
- ▶ Potential high variance
- ▶ Typically we choose $K = 5$ or $K = 10$ for a satisfactory bias-variance trade-off.

Cross-validation: Practical procedure



Cross-validation: Practical procedure



Other performance measures to evaluate the model...

Today's course

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example

Today's course

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example

The Bayesian viewpoint

Key Idea: Place a prior $p(\mathcal{M})$ on the class of models

Ingredients

- ▶ Given a training set \mathcal{D} , the posterior distribution over models is

$$p(\mathcal{M}_i|\mathcal{D}) \propto p(\mathcal{M}_i)p(\mathcal{D}|\mathcal{M}_i)$$

- ▶ Model evidence (marginal likelihood):

$$p(\mathcal{D}|\mathcal{M}_i) = \int p(\mathcal{D}|\theta_i) p(\theta_i|\mathcal{M}_i) d\theta_i$$

Highest evidence: If we don't have any prior knowledge of the model
→ uniform $p(\mathcal{M})$ and

$$\text{choose } \mathcal{M}_1 \text{ over } \mathcal{M}_2 \iff p(\mathcal{D}|\mathcal{M}_1) > p(\mathcal{D}|\mathcal{M}_2)$$

Powerful rule but the integral is intractable in practice...

Bayesian Model Averaging

Key Idea: Do not choose a model but make predictions using average over several models with weights given by the posterior probability of each model given the data

- ▶ Place a prior $p(\mathcal{M})$ on the class of models
- ▶ Instead of selecting the “best” model, integrate out the corresponding **model parameters** $\theta_{\mathcal{M}}$ and **average over all models** $\mathcal{M}_i, i = 1, \dots, L$

$$\begin{aligned} p(\mathcal{D}) &= \sum_{i=1}^L p(\mathcal{M}_i) p(\mathcal{D}|\theta_i) p(\theta_i|\mathcal{M}_i) d\theta_i \\ &= \sum_{i=1}^L p(\mathcal{M}_i) p(\mathcal{D}|\mathcal{M}_i) \end{aligned}$$

- ▶ Generally gives better answers than a single model
- ▶ Computationally expensive and integral often intractable

Today's course

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example

Information criteria

Key Idea: Correct for the bias of MLE by adding a **penalty term** to compensate for the overfitting of more complex models (large nbr of parameters)

Let M_j be the number of unknown parameters for model \mathcal{M}_j and N the data size

Akaike Information Criterion (AIC)

$$AIC(j) = \ln(p(\mathbf{x}|\hat{\theta}_{ML})) - M_j$$

Information criteria

Key Idea: Correct for the bias of MLE by adding a **penalty term** to compensate for the overfitting of more complex models (large nbr of parameters)

Let M_j be the number of unknown parameters for model \mathcal{M}_j and N the data size

Akaike Information Criterion (AIC)

$$AIC(j) = \ln(p(\mathbf{x}|\hat{\theta}_{ML})) - M_j$$

Bayesian Information Criterion (BIC) / Minimum Description Length (MDL)

$$BIC(j) = \ln(p(\mathbf{x}|\hat{\theta}_{ML})) - \frac{1}{2} M_j N$$

Information criteria

Key Idea: Correct for the bias of MLE by adding a **penalty term** to compensate for the overfitting of more complex models (large nbr of parameters)

Let M_j be the number of unknown parameters for model \mathcal{M}_j and N the data size

Akaike Information Criterion (AIC)

$$AIC(j) = \ln(p(\mathbf{x}|\hat{\theta}_{ML})) - M_j$$

Bayesian Information Criterion (BIC) / Minimum Description Length (MDL)

$$BIC(j) = \ln(p(\mathbf{x}|\hat{\theta}_{ML})) - \frac{1}{2} M_j N$$

No integrals or posteriors involved \rightarrow Much easier to compute!!

Information Criteria: Practical guidelines

No clear choice between AIC and BIC, but generally:

- ▶ BIC penalizes model complexity more heavily than AIC
 - For finite samples, BIC often chooses models that are too simple, because of its heavy penalty on complexity

Information Criteria: Practical guidelines

No clear choice between AIC and BIC, but generally:

- ▶ BIC penalizes model complexity more heavily than AIC
 - For finite samples, BIC often chooses models that are too simple, because of its heavy penalty on complexity
- ▶ BIC usually works better if the true model is among $\mathcal{M}_1, \dots, \mathcal{M}_L$
 - BIC is asymptotically consistent
 - AIC tends to choose models which are too complex as $N \rightarrow \infty$

Information Criteria: Practical guidelines

No clear choice between AIC and BIC, but generally:

- ▶ BIC penalizes model complexity more heavily than AIC
 - For finite samples, BIC often chooses models that are too simple, because of its heavy penalty on complexity
- ▶ BIC usually works better if the true model is among $\mathcal{M}_1, \dots, \mathcal{M}_L$
 - BIC is asymptotically consistent
 - AIC tends to choose models which are too complex as $N \rightarrow \infty$
- ▶ AIC is usually preferable otherwise (“all models are wrong”)

Information Criteria: Practical guidelines

No clear choice between AIC and BIC, but generally:

- ▶ BIC penalizes model complexity more heavily than AIC
 - For finite samples, BIC often chooses models that are too simple, because of its heavy penalty on complexity
- ▶ BIC usually works better if the true model is among $\mathcal{M}_1, \dots, \mathcal{M}_L$
 - BIC is asymptotically consistent
 - AIC tends to choose models which are too complex as $N \rightarrow \infty$
- ▶ AIC is usually preferable otherwise (“all models are wrong”)
- ▶ Both are mainly suited to N much larger than p (typically $d \ll \sqrt{N}$)

Other techniques and criteria

Many others techniques:

- ▶ Minimum Message Length (see application - Bayesian criterion)
- ▶ Modified AIC accounting for small sample size:
$$mAIC(j) = \ln(p(\mathbf{x}|\hat{\theta}_{ML})) - M_j - \frac{M_j(M_j + 1)}{N - M_j - 1}$$
- ▶ Hypothesis testing vs Bayesian model comparison, ...

For mixture models

- ▶ All previous techniques
- ▶ Split and merge¹(see applications + lab)
- ▶ Reversible jump²

¹ Zhang, Z. et al., (2003). EM algorithms for Gaussian mixtures with split-and-merge operation. Pattern recognition, 36(9), 1973-1983.

² Zhang, Z. et al., (2004). Learning a multivariate Gaussian mixture model with the reversible jump MCMC algorithm. Statistics and Computing, 14(4), 343-355.

Today's course

1. Introduction / Motivations
2. Cross-validation
3. Bayesian approaches and Information criteria
 1. The Bayesian viewpoint
 2. Information Criteria
4. Application example