

Derivations

Concepts of Programming Languages Lecture 6

Practice Problem

Recall the = operator in OCaml. Write down (to the best of your ability) the syntax, typing, and semantic rules for =

Practice Problem

Some students suggested this rule in the previous class for let-expressions. What is the problem in this rule?

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma \vdash x : \tau_1 \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash \text{let } x = e_1 \text{ in } e_2 : \tau} \text{(let)}$$

Outline

- » Discuss derivations in general
- » See how to read and write derivations
- » Go through a couple examples

Recap

Let-Expressions

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma, x : \tau_1 \vdash e_2 : \tau}{\Gamma \vdash \text{let } x = e_1 \text{ in } e_2 : \tau} \text{ (let)}$$

$$\frac{e_1 \Downarrow v_1 \quad [v_1/x]e_2 \Downarrow v}{\text{let } x = e_1 \text{ in } e_2 \Downarrow v} \text{ (letEval)}$$

If-Expressions

$$\frac{\Gamma \vdash e_1 : \text{bool} \quad \Gamma \vdash e_2 : \tau \quad \Gamma \vdash e_3 : \tau}{\Gamma \vdash \text{if } e_1 \text{ then } e_2 \text{ else } e_3 : \tau} \text{(if)}$$

$$\frac{e_1 \Downarrow \text{true} \quad e_2 \Downarrow v_2}{\text{if } e_1 \text{ then } e_2 \text{ else } e_3 \Downarrow v_2} \text{(ifEvalTrue)}$$

$$\frac{e_1 \Downarrow \text{false} \quad e_3 \Downarrow v_3}{\text{if } e_1 \text{ then } e_2 \text{ else } e_3 \Downarrow v_3} \text{(ifEvalFalse)}$$

Derivations

High Level

$$\frac{\frac{}{\{\} \vdash 2 : \text{int}} \text{(intLit)} \quad \frac{\frac{}{\{y : \text{int}\} \vdash y : \text{int}} \text{(var)} \quad \frac{\frac{}{\{y : \text{int}\} \vdash y : \text{int}} \text{(var)}}{\{y : \text{int}\} \vdash y + y : \text{int}} \text{(intAdd)}}{\{\} \vdash \text{let } y = 2 \text{ in } y + y : \text{int}} \text{(let)}$$

Derivations *prove* that a judgment holds w.r.t some rules

A **derivation** is a tree in which:

- » each node is labeled with a judgment
- » and judgment *follows* from the judgments at its children by an **inference rule**

Applying Rules

$$\frac{}{\Gamma \vdash [] : \tau \text{ list}} \text{ (nil)} \quad \frac{\Gamma \vdash e_1 : \tau \quad \Gamma \vdash e_2 : \tau \text{ list}}{\Gamma \vdash e_1 :: e_2 : \tau \text{ list}} \text{ (cons)}$$

$\{x : \text{int}\} \vdash x + 1 : \text{int}$	$\{x : \text{int}\} \vdash [] : \text{int list}$	(cons)
$\{x : \text{int}\} \vdash (x + 1) :: [] : \text{int list}$		

So far, we've used rules as ways of describing the behavior of a PL

When we build typing derivations, we *instantiate* the meta-variables in the rule at *particular* expressions, contexts, etc.

Building from the Ground Up

$\frac{}{\{x : \text{int}\} \vdash x : \text{int}} \text{ (var)}$	$\frac{}{\{x : \text{int}\} \vdash 1 : \text{int}} \text{ (intLit)}$	
$\frac{}{\{x : \text{int}\} \vdash x + 1 : \text{int}} \text{ (intAdd)}$	$\frac{}{\{x : \text{int}\} \vdash [] : \text{int list}} \text{ (nil)}$	
$\frac{}{\{x : \text{int}\} \vdash (x + 1) :: [] : \text{int list}} \text{ (cons)}$		

But we can't *just* apply rules, because it's possible that the premises of a rule **also need to be demonstrated**

This is how we get our tree structure: we apply rules from the ground up

Axioms (When are we done?)

$\frac{}{\{x : \text{int}\} \vdash x : \text{int}} \text{ (var)}$	$\frac{}{\{x : \text{int}\} \vdash 1 : \text{int}} \text{ (intLit)}$	
$\frac{}{\{x : \text{int}\} \vdash x + 1 : \text{int}} \text{ (intAdd)}$	$\frac{}{\{x : \text{int}\} \vdash [] : \text{int list}} \text{ (nil)}$	
	$\frac{}{\{x : \text{int}\} \vdash (x + 1) :: [] : \text{int list}} \text{ (cons)}$	

The leaves of the tree are **axioms**, i.e., a rules with no premises

In our case, this will almost always be "literal" or "variable" rules

Integer Literals

(1)

$$\frac{n \text{ is an int lit}}{\Gamma \vdash n : \text{int}} \quad (\text{intLit})$$

(2)

$$\frac{n \text{ is an int lit}}{n \Downarrow n} \quad (\text{intLitEval})$$

1. If n is an integer literal, then it is of type int in any context
2. If n is an integer literal, then it evaluates to the number it represents

A Note about Side Conditions

we don't write "1 is an integer literal"

$\frac{}{\{x : \text{int}\} \vdash x : \text{int}} \text{ (var)}$	$\frac{}{\{x : \text{int}\} \vdash 1 : \text{int}} \text{ (intLit)}$	
$\frac{}{\{x : \text{int}\} \vdash x + 1 : \text{int}} \text{ (intAdd)}$	$\frac{}{\{x : \text{int}\} \vdash [] : \text{int list}} \text{ (nil)}$	
$\frac{\{x : \text{int}\} \vdash x + 1 : \text{int} \quad \{x : \text{int}\} \vdash [] : \text{int list}}{\{x : \text{int}\} \vdash (x + 1) :: [] : \text{int list}} \text{ (cons)}$		

If a premise is a side-condition this *it is not included in the derivation*

Side conditions need to hold in order to apply the rule, but they don't appear in the derivation itself

We will always make side conditions clear

Float Literals

$$(1) \quad \frac{n \text{ is an float lit}}{\Gamma \vdash n : \text{float}} \quad (\text{floatLit})$$

$$(2) \quad \frac{n \text{ is an float lit}}{n \Downarrow n} \quad (\text{floatLitEval})$$

1. If n is an float literal, then it is of type float in any context
2. If n is an float literal, then it evaluates to the number it represents

Boolean Literals

$$(1) \quad \frac{}{\Gamma \vdash \text{true} : \text{bool}} \text{ (trueLit)}$$

$$(2) \quad \frac{}{\Gamma \vdash \text{false} : \text{bool}} \text{ (falseLit)}$$

$$(3) \quad \frac{}{\text{true} \Downarrow \text{true}} \text{ (trueLitEval)}$$

$$(4) \quad \frac{}{\text{false} \Downarrow \text{false}} \text{ (falseLitEval)}$$

1. `true` is of type `bool` in any context
2. `false` is of type `bool` in any context
3. `true` evaluates to the value $\top$
4. `false` evaluates to the value $\perp$

Variables

$$\frac{(v : \tau) \in \Gamma}{\Gamma \vdash v : \tau} \text{ (intLit)}$$

If v is declared to be of type τ in the context Γ , then v is of type τ in Γ

Variables cannot be evaluated (more on this when we talk about substitution and well-scopedness)

Back to the Example


$$\frac{\frac{}{\{\} \vdash 2 : \text{int}} \text{(intLit)} \quad \frac{\frac{}{\{y : \text{int}\} \vdash y : \text{int}} \text{(var)} \quad \frac{\frac{}{\{y : \text{int}\} \vdash y : \text{int}} \text{(var)}}{\{y : \text{int}\} \vdash y + y : \text{int}} \text{(intAdd)}}{\{\} \vdash \text{let } y = 2 \text{ in } y + y : \text{int}} \text{(let)}$$

We need $\{\} \vdash 2 : \text{int}$ in order to proof that the bottom typing judgment holds

Now we know that this follows from the **intLit** rule, which says that 2 is always an int, *by fiat*

Okay, I know that was a
lot, let's take a step back

Derivations Encode Natural Language Arguments



$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma, x : \tau_1 \vdash e_2 : \tau_2}{\Gamma \vdash \text{let } x = e_1 \text{ in } e_2 : \tau_2} \text{ (let)}$$

$$\frac{\text{n is an integer literal}}{\Gamma \vdash n : \text{int}} \text{ (intLit)}$$

The expression **let y = 2 in y + y** is an **int** *because*

» **2** is an **int** by fiat (and so **y** is being assigned to a well-typed

» and, assuming **y** is an int, **y + y** is an **int** *because*

- **y** is an **int** (by assumption)
- and so is **y** (by assumption)

and so integer-adding these two expressions (**y** and **y**) yields an **int**


and so assigning **y** to **2** in **y + y** yields an **int**

$$\frac{\Gamma \vdash e_1 : \text{int} \quad \Gamma \vdash e_2 : \text{int}}{\Gamma \vdash e_1 + e_2 : \text{int}} \text{ (addInt)}$$

$$\frac{(x : \tau) \in \Gamma}{\Gamma \vdash x : \tau} \text{ (var)}$$

And all this works for
semantics judgements as well

Recall: Semantic Judgements



A **semantic judgment** is a compact way of representing the statement:

The expression e evaluates to the value v

A **semantic rule** is an inference rule with semantic judgments

Recall: Integer Addition Semantic Rule

$$\frac{e_1 \Downarrow v_1 \quad e_2 \Downarrow v_2 \quad v_1 + v_2 = v}{e_1 + e_2 \Downarrow v} \text{ (evalInt)}$$

If e_1 evaluates to the (integer) v_1 and e_2 evaluates to the (integer) v_2 , and $v_1 + v_2 = v$, then $e_1 + e_2$ evaluates to the (integer) v

Semantic Derivations

$$\frac{\frac{}{\text{true} \Downarrow \text{true}} \text{ (trueEval)} \quad \frac{}{2 \Downarrow 2} \text{ (intEval)}}{\text{if true then 2 else 3} \Downarrow 2 \text{ (ifEval)}}$$

We can also write derivations to prove semantic judgments

The principle is the same, except that the judgments are semantic judgments instead of typing judgments

Examples

Example (Typing)

$\{\} \vdash \text{if true then 2 else 5} : \text{int}$

Example (Evaluation)

if true then 2 else 5 $\Downarrow$ 2

Example (Typing)

$\{\} \vdash 2 + 3 \triangleleft 4 : \text{bool}$

Example (Evaluation)

$2 + 3 \lessgtr 4 \Downarrow \text{true}$

Example (Evaluation)

let $x = 2$ in $x + x \Downarrow 4$

Summary

Derivations are **tree-like proofs** that judgments hold with respect to a collection of inference rules

Derivations are **compact mathematical representations** of English language arguments

Learning to write derivations takes *practice*