Robot Controller v1.0 - Step-by-Step Explanation

1. Power Management System:

- Provides stable power to the controller and peripherals.

- Key Components:

  * Voltage Regulator (e.g., TLV62568DBVR): Converts higher input voltage to a stable output.

  * Capacitors (e.g., 10uF, 0.1uF): Stabilize voltage levels and filter noise.

  * Inductor (e.g., 2.2uH): Maintains efficient power conversion.

  * Protection Diodes: Prevents backflow of current and protects circuits.

- The system converts input voltage (VIN) to regulated 3.3V and 5V power lines.

2. Microcontroller Unit (MCU) - STM32F103C8T6:

- Central processor for controlling connected devices.

- Key Features:

  * I/O pins for UART, I2C, SPI communication.

  * GPIO pins for external device control (LEDs, motors).

- Connections: Power pins (3.3V, GND), communication lines, and control lines.

3. Communication Interfaces:

- CAN Bus (MCP2551): Robust communication between devices with 120Ohm termination resistors.

- I2C: Communication with sensors like BMI055, PCA9685, using pull-up resistors.

- SPI: High-speed connections for sensors like LIS3MDLTR.

4. Sensor Integration:

- Inertial Sensors:

Robot Controller v1.0 - Step-by-Step Explanation

 * BMI055 (Accelerometer): Tracks motion and orientation, connected via SPI/I2C.

 * ICM20602 (Gyroscope): Measures rotational motion over SPI.

- Environmental Sensors:

 * BMP388 (Barometer): Measures atmospheric pressure for altitude calculation.

- Magnetometer (LIS3MDLTR): Measures magnetic fields for navigation.

5. Peripheral Control - PCA9685:

- Controls multiple PWM outputs for motors and LEDs.

- Features:

 * 16 PWM channels.

 * Communicates over I2C.

6. Connectors and Interfaces:

- GPIO Headers: Input/output pins for IO0, IO1, etc.

- CAN Bus: Connectors for CANH and CANL lines.

- Analog Inputs: Reads sensor data like voltage or current.

7. Debugging and User Interaction:

- User Buttons: Manual inputs for resetting or triggering events.

- LED Indicators: Provide visual feedback for status or errors.

8. Summary:

- Power system supplies stable 3.3V and 5V.

- MCU processes data and communicates with peripherals.

- Interfaces enable data exchange with sensors.

- Sensors collect motion/environmental data for control and decision-making.

Robot Controller v1.0 - Step-by-Step Explanation

- Modular connectors simplify integration and debugging.