



T24-HS Handheld Telemetry Display Unit

This wireless handheld display module provides an 8 digit LCD reading from a T24 loadcell data acquisition module.

This wireless handheld display module is designed to show readings from a connected T24 load cell acquisition unit on a clear 8-character LCD screen. When the operator activates the handheld device, the linked acquisition unit can switch its power state automatically, helping streamline setup and conserve energy during field use. Visual alerts on the display help users identify issues such as weak input signals, battery level concerns, measurement limits being exceeded, or other system notifications.

Users can alternate the measurement view between the main applied force and a user-set reference value, allowing quick adjustments during testing or calibration. The unit communicates using a 2.4GHz spread-spectrum radio system that supports dependable wireless performance, even in environments where multiple wireless networks, such as Wi-Fi, Bluetooth® and Zigbee®, are active. This makes it a practical component within modern load cell telemetry systems, especially in facilities requiring stable, interference-resistant communication.

Power is supplied by two readily available AA alkaline cells, making replacements simple in both workshop and on-site environments. Configuration of the handheld device is handled through the free T24 Toolkit software, accessed via a computer

Features

- ✓ Licence free 2.4GHz band
- ✓ Two key operation
- ✓ Very high resolution
- ✓ Battery powered
- ✓ Sealed to IP67
- ✓ 1 year warranty

linked to a T24 base station, allowing operators to tailor settings to the needs of their measurement task.

The module meets key compliance standards, including EMC Directive 2004/108/EC and the R&TTE Directive 1999/5/EC, and is fully RoHS compliant. Its combination of portability, intuitive operation, and reliable wireless communication makes it a dependable accessory for applications requiring accurate and efficient remote force measurement.

FAQ's:

How reliable is the wireless connection when using the T24-HS in busy environments?

The T24-HS uses a robust 2.4GHz spread-spectrum radio system designed to maintain stable communication even in areas where Wi-Fi, Bluetooth®, or Zigbee® are active. This ensures dependable operation within demanding load cell telemetry systems.

Can the handheld automatically manage the power of the connected acquisition module?

Yes. When the T24-HS is activated, it can trigger the linked acquisition module to power on or off automatically. This helps save battery life, simplifies field operation, and reduces the need for manual adjustments during measurement tasks.

How is the T24-HS configured for different testing or calibration requirements?

Configuration is done through the free T24 Toolkit software using a computer connected to a T24 base station. This allows operators to adjust display settings, measurement modes, and system behaviour so the handheld aligns precisely with the task's requirements.

Specifications

Parameter	Value	Unit
Licence	Licence exempt	
Modulation method	MS (QPSK)	
Radio type	Transceiver (2 way)	
Data rate	250	kbits/sec
Radio frequency	2.4000 (Min) / 2.4835 (Max)	GHz
Power	10	mW
Line of sight transmission distance	400	m
Channels (DSSS)	16	
Power supply voltage	2.2 (Min) / 3.0 (Typical) / 3.6 (Max)	V
Supply current - active	35 (Typical) / 40 (Max)	mA
Supply current - standby	120 (Typical) / 160 (Max)	µA
Battery life - active	35	hours
Battery life - standby	1.5	years
Case dimensions	H 34 W 90 L 152	mm
Operating temperature range	-10 (Min) / 50 (Max)	°C
Storage temperature	-40 (Min) / 85 (Max)	°C
Humidity	0 (Min) / 95 (Max)	%RH Non condensing
Sealing	IP67	

Order Codes

Code	Description
T24-HS	Handheld battery powered single channel display unit.
	T24 manual is available for download. The T24 system can be calibrated in a number of different ways depending upon the application. Please consult our engineering department for help with your requirements.
	Please see Engineering Sheet E035 for Frequently Asked Questions for the T24 Telemetry system.

Notes

- FR = full range
- RH = relative humidity.
- Line of sight transmission distance assumes ideal conditions with the data acquisition unit 3m above the ground.
- The batteries used may reduce the operating temperature range. Storage temperature is without batteries.