

Digital Ring Torsion Load Cell

FEATURES

- Capacity range: 10t to 30t
- Low profile, stainless steel construction
- Welded seal, IP66/IP69K/IP68
- OIML R-60 and NTEP approval pending
- Digital CAN Open output


APPLICATIONS

- Platform scales
- Belt scales
- Silo hopper weighing

DESCRIPTION

The RLCD is a low profile, high performance Digital stainless steel ring torsion type load cell.


The fully welded construction ensure that this product can be used successfully in harsh environments found in the food, chemical and process industries.



This product is suitable for small and medium platform scales, hoppers and process weighing.

This product meets the stringent Weights and Measures requirements throughout Europe and USA.

OUTLINE DIMENSIONS in millimeters



	A	B	C	D	E	F	H	W	n	X	d
10 t	29.1	24.9	15.1	95.0	75.0	83.0	35.3	1.3	3	6	8.0
10 t - II	28.0	6.5	14.6	92.0	75.2	80.0	33.0	1.5	2	5	5.8
20 & 30 t	29.0	4.0	26.3	110.0	101.0	102.0	50.1	1.5	2	5	7.5
50 t	42.0	4.0	29.2	125.0	111.5	114.5	57.7	2.3	2	5	8.0

Digital Ring Torsion Load Cell

SPECIFICATIONS					
PARAMETER	VALUE				UNIT
Standard capacities ($E_{\max}$)	10, 20, 30				t
Accuracy designation		C1MR3	C3MR10		
Maximum no. of verification intervals (nlc)		1000	3000		
Y ($E_{\max}/V_{\min}$)		3000	10000		
Rated Output (RO)	200000				Counts
Rated output tolerance	200				±Counts
Zero balance	10000				±Counts
Combined error		0.06	0.020		±% RO
Zero return (30 minutes)		0.050	0.017		±% RO
Temperature effect on zero		0.0267	0.008		±% RO/5°C
Temperature effect on sensitivity (output)		0.0131	0.0069		±% Load/5°C
Compensated temperature range	-10 to +40				°C
Operating temperature range	-30 to +70				°C
Minimum dead load	0				% $E_{\max}$
Maximum safe overload	150				% $E_{\max}$
Ultimate overload	300				% $E_{\max}$
Communication	CAN Open				
Supply voltage range	9...32				VDC
Cable length	1.0				m
Cable type	4-wire, twisted pairs, CAN rated, braided shield, PU jacket				Ω
Construction	Stainless steel, welded seal				
Environmental protection	IP66/IP69K/IP68 (100 hr. @ 1 m tap water)				
Recommended mounting torque	6...10				N*m

All specifications subject to change without notice.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase.

To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.