Where Should Resident Layers Go? Optimal Placement for Weight Streaming in Offloaded LLM Inference

Quang-Vinh Dang[a,*], Dat Le[b], Minh Ngoc Dinh[c]

[a] British University Vietnam, Hung Yen, Vietnam
[b] Department of Science, Technology, and International Projects, Ho Chi Minh City University of Economics and Finance, Ho Chi Minh City 700000, Vietnam
[c] Millennia Education, Ho Chi Minh City, Vietnam

[*] Corresponding author: Quang-Vinh Dang, vinh.dq4@buv.edu.vn, ORCID 0000-0002-3877-8024

E-mail addresses: vinh.dq4@buv.edu.vn (Q.-V. Dang), datla@uef.edu.vn (D. Le), minh.dinh@maeducation.com (M. N. Dinh)

ORCID: Q.-V. Dang 0000-0002-3877-8024; D. Le 0009-0005-5038-8570; M. N. Dinh 0000-0003-4026-6068

CRediT authorship contribution statement. Quang-Vinh Dang: Conceptualization, Methodology, Formal analysis, Software, Investigation, Writing – original draft, Visualization, Supervision. Dat Le: Validation, Writing – review & editing. Minh Ngoc Dinh: Validation, Writing – review & editing.

Data availability. The model code, the GPU runtime, the raw measurements and the analysis scripts are available at https://github.com/vinhqdang/Enabling-CXL-Based-Memory-Disaggregation-for-Large-Scale-AI-Systems.