**Research Article** **Open Access**

Quang-Vinh Dang, Dat Le*, and Minh Ngoc Dinh

# What can real cause–effect benchmarks resolve? Sampling noise, marginal shortcuts and assumption regimes

DOI: DOI, Received ..; revised ..; accepted ..

**Abstract:** Causal-discovery methods are compared by small accuracy gains on a few real benchmarks. We ask what these benchmarks can resolve and why rules that test the conditional structure of a pair rarely beat simple rules. Twelve direction rules were run under one protocol fixed before the runs on eight real pair collections (four new) and on graph benchmarks. No rule leads across collections. On 102 Tübingen pairs a paired test needs a difference of 19 accuracy points for 80% power, and among ten non-degenerate rules no pairwise difference reaches a raw $p < 0.05$. Unreported conventions move a rule as much: a rounding convention that a baseline's description does not fix changes its weighted accuracy by six points, and the treatment of tied values changes IGCI from 94% to 6% on one collection. Two mechanisms are supported: the chamber pairs can be oriented from the marginals alone, a property of their actuator-to-sensor design, and additive-noise rules are near-perfect when the noise scale is independent of the cause and reversed when it depends on it. Attempts to turn this into a rule or a predictive model fail their predictions fixed in advance, so the account is partial. We give recommendations.

**Keywords:** causal discovery, cause–effect pairs, benchmark evaluation, reproducibility, additive noise models

**MSC:** 62D20, 68T05

## 1 Introduction

Cause–effect benchmarks drive method development in causal discovery. For two variables the reference is the Tübingen collection [1], 108 pairs of real measurements of which 102 are univariate; for graphs it is the protein-signalling data of Sachs et al. [2] with 17 consensus arcs. A new rule is typically presented in a table in which its number is larger than those of earlier rules. This paper asks how much information such a table carries. It runs a panel of direction rules under one protocol fixed before the runs on eight real pair collections, and asks how large a difference the benchmarks can resolve and why rules that test the conditional structure of a pair [3–7] so rarely beat simpler rules that read the scale of regression errors or the marginal density [8–10]. On Tübingen all of them lie between 55% and 67% with intervals of $\pm 10$ points; the ordering of the rules on the Causal Chambers [11] is negatively, but not significantly, correlated with it.

**Quang-Vinh Dang:** British University Vietnam, Hung Yen, Vietnam; E-mail: vinh.dq4@buv.edu.vn; ORCID: 0000-0002-3877-8024

***Corresponding Author: Dat Le:** Department of Science, Technology, and International Projects, Ho Chi Minh City University of Economics and Finance, Ho Chi Minh City, 700000, Vietnam; E-mail: datla@uef.edu.vn; ORCID: 0009-0005-5038-8570

**Minh Ngoc Dinh:** Millennia Education, Ho Chi Minh City, Vietnam; E-mail: minh.dinh@maeducation.com; ORCID: 0000-0003-4026-6068

**Contributions.**
(1) A same-protocol comparison of twelve pair rules on eight real collections (Tübingen; six Causal Chambers collections, four of them new; the Sachs pairs), with the stored decision of every rule on every pair, cluster-aware inference and a reproduction of a published headline number (Section 4). (2) A resolution analysis: a paired test on 102 pairs has 80% power only for a difference of about 19 accuracy points, and among ten non-degenerate rules none of 45 comparisons reaches a raw $p < 0.05$; ten reporting universes move a single rule by 11 to 26 points and its rank by up to nine places, and 50 preprocessing configurations by 7 to 22 points (Section 3). (3) Two unreported implementation conventions, the rounding of a quantiser and the treatment of tied values, that move a rule's accuracy by six and by up to 88 points (Section 4). (4) Mechanism evidence, tested by prediction, matched manipulation with a control and leakage-free validation (Section 5): the chamber collections, whose causes are experimenter-set actuators, can be oriented from their marginals alone, a cue that does not transfer to Tübingen; additive-noise rules are near-perfect when the noise scale does not depend on the cause and reversed when it does; two attempts to build a rule or a predictive model on this account fail their predictions fixed in advance, which bounds it. (5) Recommendations for reporting (Section 6), and an accounting of the attempts to build a better rule (Appendix C).

## 1.1 Related work

*Direction rules.* Identifiability results for linear non-Gaussian [12], additive-noise [3, 4, 13] and post-nonlinear models underlie most pair rules; IGCI [9] rests on the independence of the cause distribution and the mechanism, RECI [8] compares regression errors after scaling, LOCI [6] fits location-scale models, SLOPE [14] uses minimum description length, and learned rules are trained on simulated pairs [7, 15]. *Evaluation.* Real data with known cause–effect structure are scarce: Tübingen for pairs, the Causal Chambers [11] for physical devices with a documented graph, and the Sachs network, a consensus rather than a ground truth. On simulated graphs, Reisach et al. [16] showed that the variance structure of additive-noise models can be read by a trivial rule; our marginal-only classifier is a pair-level analogue on real data. A same-hands re-evaluation on Tübingen that also introduced the compression baseline we use is Stienstra [10]; we reproduce its main figure. For graphs we also ran BF-BIC with BOSS [17] and an SNOE-style [18] orientation (Appendix G).

*What this paper does not claim.* It does not claim that published methods misreport their results; we audited one published table and reproduced it. It does not claim that dependence-based methods are worse in general: they are among the best rules in the regimes that fit their assumptions and the worst in others, and a benchmark that mixes regimes averages them.

# 2 Collections, rules and protocol

## 2.1 Pair collections

Table 1 lists the eight collections ("Walks, all 19", the pairs of all 19 untouched recordings, contains the five recordings of the walk collection and fourteen more). A *pair* is an ordered pair of variables with a known direction; the cause is the first variable of an edge of the documented graph. Two features of the table matter for every later statement. First, only Tübingen is a collection of unrelated mechanisms; the seven others consist of pairs taken from one or two devices or, for Sachs, one data set, so the number of *distinct edges* is much smaller than the number of pair-runs (47 distinct edges behind the 94 i.i.d. chamber pair-runs, at most 65 distinct cause–effect names behind the 122 walk pairs, 8 behind the Bernoulli collection, 7 behind the changepoint collection and 4 behind the Malus collection, whose pairs share their cause variable). Intervals and tests that treat pairs as independent therefore overstate the information; Appendix

**Table 1.** The eight real pair collections. "Pairs": pair-runs scored; "edges": distinct edges of the documented graph; "units": independent recordings or experiments. Rows: rows per pair after the cap of 2000 random rows (Tübingen: at most 2000 rows, dequantised; chamber collections: raw values).

| Collection | Pairs | Edges | Units | Rows | Source and cause |
|---|---|---|---|---|---|
| Tübingen | 102 | 102 | 102 | $\leq 2000$ | Univariate pairs of the CEP benchmark [1]; official weights |
| Chambers iid | 94 | 47 | 2 | 2000 | Wind and light tunnel with i.i.d. actuator settings [11]; two seeds per edge |
| Walks, all 19 | 486 | $\leq 65$ | 19 | 2000 | All untouched recordings (wind-tunnel random-walk actuators, the pressure-control recording, light-tunnel walks); every edge of each documented graph |
| Chambers walks | 122 | $\leq 65$ | 5 | 2000 | First recording of each type of random-walk experiments (actuators are random walks); the same cause–effect names recur across the five recordings |
| Sachs | 17 | 17 | 1 | 853 | Consensus arcs among 11 proteins, log scale [2] |
| Bernoulli | 16 | 8 | 1 | 2000 | Wind tunnel, `random_loads_both`; the cause `load_in` takes 101 levels (steps of 0.01), so after subsampling it has about 20 rows per value; cause always `load_in` |
| Changepoints | 70 | 7 | 10 | 2000 | Wind tunnel, piecewise-constant actuator (change points); cause always `load_in` |
| Malus | 48 | 4 | 12 | 1000 | Light tunnel with polarisers, Malus's law; causes `pol_1`, `pol_2` |

Table 11 gives cluster-bootstrap intervals (clusters: distinct edge, or recording for the walks). Second, in the chamber collections the cause is an actuator whose value the experimenter sets, which gives it a recognisable marginal law (uniform on a grid of levels, piecewise constant, a random walk) while the effects are sensors.

Appendix Table 18 gives descriptive diagnostics of the collections and Figure 1 one pair from each.

## 2.2 Rules

Twelve rules, all run by us; IGCI, RECI, ANM-HSIC, pairwise LiNGAM, compression, TRA and PDM are our own implementations (statements about them below are statements about these implementations), LOCI, AVICI, RESIT and the Gaussian-process ANM come from the packages named. Each returns a score whose sign gives the direction; a score of exactly zero counts as half correct. Settings were fixed in the script before the run (Appendix A) and none was tuned on a collection in which it is scored. *Tie handling:* every rule receives the raw arrays (ties kept), as for the chambers in the first experiments; Tübingen arrays are dequantised (experiment 14) and have no ties. Giving the rules a copy with a $10^{-6}$ jitter on tied values reverses IGCI (Section 4.2) and breaks TRA's spline fit, so jitter is used only in the sensitivity analysis of Section 4.2 and for the simulations.

- **IGCI** [9]: entropy estimator with a uniform reference. **RECI** [8]: the direction with the smaller regression error of a spline fit after min–max scaling. Both are short re-implementations (`sprint_cd/pair_baselines.py`).
- **ANM-HSIC** [3]: additive-noise model with a spline regression and an HSIC independence test; **ANM-GP**: the `causal-learn` Gaussian-process version on 400 rows; **RESIT** (`lingam`): random-forest regression of depth 4 with $\alpha = 0.01$.
- **Pairwise LiNGAM** [5]: first-order likelihood-ratio statistic.

- **LOCI** [6]: the authors' code in its default setting (neural networks, 5000 steps, HSIC test, at most 1000 rows).
- **Compression** [10]: quantise both variables to 256 levels, sort one by the other (stable), take the first difference as `int8`, compress with bzip2 (level 9), and compare the two normalised lengths. Two variants: "floor256" (`floor`$(256q)$, rows capped at 2000, the first implementation) and "round255" (`round`$(255q)$, all rows thinned linearly above 8000, raw values), the convention that reproduces the published figure (Section 4.1); they are named by their quantiser because the published text does not say which is meant.
- **TRA** [19]: cross-fitted smoothing-spline residuals, a rank-uniform residual cloud and the zero-dimensional persistence of its minimum spanning tree in a window; the constants $\kappa = 1$, $c_\beta = 4$, five folds, at most 1000 rows are ours because the preprint does not fix them. It returns no value when the spline fit is ill-posed (cause with many tied values), which excludes it from the changepoint collection (four piecewise-constant levels).
- **AVICI** [7]: the pretrained `scm-v0` model on the two-variable input, score $P(x \to y) - P(y \to x)$ (run in a separate environment with pinned JAX).
- **PDM**: a gradient-boosting classifier trained on simulated pairs with 32 features (ours; Appendix C).

Reference implementations of IGCI, RECI, CDS, ANM and BivariateFit from the `cdt` package (v0.6.0, defaults) were also run to check ours (experiment 55; Section 4.2). Not run: PNL (880 s per pair on 400 rows), CAM and SCORE (no package available offline), SLOPE (code not run), and rules that need the authors' trained weights.

### 2.3 Protocol and provenance

Every evaluation script was committed before it was run; Appendix A lists the 47 experiment scripts (numbers 17 to 61; 31 and 34 have two parts) with the commit that fixed them. Stored per-pair decisions are in `results/`, and every number in this paper is computed from them by the scripts in `scripts/`. Three analyses were designed after seeing per-pair results and are labelled as such where they appear: the multiverse and subset analyses of Section 3.3 (their ten universes are declared as the design in Appendix Table 12), the terciles of Table 7, and the revised protocol of Section E.3. The study includes departures that we report rather than hide: the floor256 variant of the compression rule did not reproduce the published figure, because of a detail that the published text does not fix; the first run of the marginal-only classifier leaked information between training and test variables; one pre-specified test (Section E.3) was invalid as implemented and was rerun in a revised form, with both runs reported.

## 3 Resolution, rankings and reporting freedom

### 3.1 No rule leads across collections

Table 2 gives the accuracy of every rule on every collection (Figure 2 in the appendix).

**(1) The leader changes.**
Round255 compression leads Tübingen (66.7%; LOCI and TRA at 64.7 and 64.6%) and Malus (60.4%), RECI the two chamber collections with independent or random-walk actuators (97.9% and 94.3%), IGCI the 19 untouched walk recordings (95.7%; RECI 82.9%) and the Bernoulli collection (100%), floor256 compression the 17 Sachs pairs (76.5%; round255 64.7%), and IGCI, RECI and round255 compression tie on the changepoint pairs (100%). Four of the twelve rules lead at least one collection. IGCI is above 70% on five collections and at 8.3% on Malus and 55.9% on Tübingen; RECI is above 70% on four; pairwise

**Table 2.** Accuracy (fraction of pairs oriented correctly; exact ties half) of twelve rules on eight collections. All rules see the raw arrays, except that Tübingen is dequantised (Section 2.2). "–": not run, or no value for most pairs (TRA on the changepoint collection; PDM and the first compression implementation only on the original collections). "Walks (19)" contains all 19 untouched recordings (486 pairs; the 122 pairs of "walks" come from five of them). The new collections have 8, 7 and 4 distinct edges; intervals that account for clusters are in Appendix Table 11.

| Rule | Tüb. (102) | iid (94) | walks (122) | Walks (19: 486) | Sachs (17) | Bern. (16) | Chgpt. (70) | Malus (48) |
|---|---|---|---|---|---|---|---|---|
| IGCI | 0.56 | 0.94 | 0.89 | 0.96 | 0.65 | 1.00 | 1.00 | 0.08 |
| RECI | 0.61 | 0.98 | 0.94 | 0.83 | 0.53 | 0.25 | 1.00 | 0.56 |
| ANM-HSIC | 0.61 | 0.72 | 0.63 | 0.43 | 0.59 | 0.31 | 0.57 | 0.31 |
| Pairwise LiNGAM | 0.61 | 0.78 | 0.71 | 0.67 | 0.53 | 0.88 | 0.43 | 0.40 |
| PDM | 0.40 | 0.93 | 0.84 | – | – | – | – | – |
| LOCI | 0.65 | 0.77 | 0.68 | – | 0.47 | 0.56 | 0.80 | 0.38 |
| ANM, Gaussian process | 0.55 | 0.77 | 0.67 | – | 0.56 | 0.47 | 0.54 | 0.33 |
| Compression, floor256 | 0.61 | 0.30 | 0.61 | – | 0.76 | – | – | – |
| Compression, round255 | 0.67 | 0.38 | 0.52 | 0.50 | 0.65 | 0.50 | 1.00 | 0.60 |
| TRA | 0.65 | 0.86 | 0.61 | 0.56 | 0.59 | 0.62 | – | 0.54 |
| AVICI | 0.59 | 0.90 | 0.56 | 0.63 | 0.53 | 0.62 | 0.40 | 0.02 |
| RESIT | 0.61 | 0.71 | 0.65 | 0.48 | 0.47 | 0.25 | 0.53 | 0.50 |

LiNGAM on three; no other rule on more than two. The additive-noise rules lead nowhere: ANM-HSIC is at 43.4% on the 19 walk recordings, RESIT at 47.5%.

**(2) Rules that agree on one collection disagree on the next.**

In our implementation IGCI orients the Bernoulli and changepoint pairs correctly in every case and the Malus pairs wrongly in 44 of 48. RECI is at 25% on the Bernoulli pairs. The pretrained AVICI model, run on two-variable inputs, is at 90.4% on the i.i.d. chambers and 2.1% on Malus. Round255 compression is at 100% on the changepoint pairs, 60.4% on Malus and 38.3% on the i.i.d. chambers. With the recordings as clusters, sign-flip tests give IGCI above RECI on the 19 walk recordings ($p = 0.019$) and RECI above ANM-HSIC, AVICI and pairwise LiNGAM ($p < 0.001$); on the i.i.d. chambers (47 edges as clusters) RECI is above ANM-HSIC ($p < 0.001$) and IGCI above ANM-HSIC ($p = 0.012$), while IGCI and RECI are not separated ($p = 0.63$); with five recordings the smallest attainable $p$ is 0.0625.

**(3) Rankings do not clearly transfer.**

Kendall's $\tau$ between the ordering of the rules on Tübingen and on the i.i.d. chambers is $-0.38$, on the walks $-0.30$ ($-0.42$ for all 19 recordings), on Sachs $-0.12$, on Bernoulli $-0.19$; it is $+0.24$ against the changepoints and $+0.51$ against Malus. Of the 28 correlations one has a raw permutation $p < 0.05$ (i.i.d. against walks, 0.02) and none survives a Holm correction (smallest adjusted $p = 0.49$): the Tübingen accuracies span twelve points with intervals of $\pm 0.10$, so the ordering of the rules on that collection is mostly noise, and the data support no statement of agreement or disagreement between collections at the level of rank correlations.

**Cautions.**

The i.i.d., walk, Bernoulli, changepoint and Malus collections are best read as case studies of regimes of two devices, not as samples of mechanisms: they have 47, $\leq 65$, 8, 7 and 4 distinct edges, the cause is an experimenter-set actuator and the effect a sensor. Cluster-bootstrap intervals (Appendix Table 11) are degenerate with fewer than nine clusters. The Tübingen arrays are dequantised, a convention that matters (on raw arrays IGCI is at 63.8% on average over the configurations of Section 3.4 against 52.4%

dequantised). The leads of round255 compression on Tübingen and Malus rest on one pair over LOCI ($p = 0.88$) and on three points with four clusters.

## 3.2 Sampling noise

Table 3 gives the accuracies on Tübingen with exact Clopper–Pearson intervals. The half-width is about 0.10 for every rule, and the intervals treat the pairs as independent, which they are not exactly (the official weights downweight groups of similar pairs; unweighted accuracy is used). All rules are evaluated on the same pairs, so the right comparison between two rules is the exact McNemar test on the pairs on which exactly one is correct; exact ties (a score of zero) and pairs on which a rule returned no value (TRA, 20 pairs) are left out of the discordant counts, so TRA is compared on a different sample.

**Two families of comparisons.**
The first family has the twelve rules of Table 2 plus the floor256 compression with raw rows: 78 comparisons. Twelve have a raw $p < 0.05$ and two survive a Holm correction (smallest adjusted $p = 0.015$); both involve the learned classifier PDM, which is below chance (PDM against round255 compression and against LOCI; all 12 raw-significant comparisons involve PDM), so they say nothing about the other rules. The second family fixes the ten rules that are not degenerate and not duplicated (IGCI, RECI, ANM-HSIC, pairwise LiNGAM, LOCI, ANM-GP, round255 compression, TRA, AVICI, RESIT; without PDM and without the other compression variants): 45 comparisons, *none* with a raw $p < 0.05$ (smallest raw $p = 0.11$, ANM-GP against RESIT). The result is the same on the common set of the 82 pairs on which all ten rules return a value (exact ties counted as half in both cells of the discordance table): none of the 45 comparisons has a raw $p < 0.05$ (smallest 0.078, ANM-GP against TRA). PDM's accuracy of 40.2% is not a sign error: the same classifier and sign convention give 93% and 84% on the two chamber collections, so its failure on Tübingen is a failure to transfer from the simulator, which we did not diagnose further. For the best rule, round255 compression (66.7%), the tests against RECI, LOCI, IGCI, ANM-GP and AVICI have $p = 0.39$, 0.88, 0.14, 0.20 and 0.35 (discordant pairs 20/14, 23/21, 29/18, 24/15, 32/24).

**Detectable difference.**
With the observed rate of discordant pairs (42%, computed on pairs where both rules have a value and neither ties; averaged over the 78 comparisons), a simulated paired comparison on 102 pairs reaches 80% power for a difference in accuracy of 0.19 at level 0.05 and of 0.27 with a Bonferroni correction over the 78 comparisons. The simulation draws the number of discordant pairs from the observed rate, splits them with the alternative probability, uses 1000 replications per step of 0.01, and treats pairs as independent. The figure agrees with the normal approximation of the exact test: with $n$ pairs and a fraction $d$ of discordant pairs, a difference in accuracy $\Delta$ is detected with power $1 - \beta$ at level $\alpha$ when $\Delta \geq (z_{1-\alpha/2} + z_{1-\beta})\sqrt{d/n}$, which gives 0.180 at $\alpha = 0.05$ and 0.273 at $\alpha = 0.05/78$ for $n = 102$, $d = 0.42$. Inverting, the number of pairs needed to resolve a difference $\Delta$ at 80% power is $7.85\, d/\Delta^2$: about 330 pairs for $\Delta = 0.10$, 1320 for 0.05 and 8240 for 0.02 at $d = 0.42$. Differences of two to five points, which separate most of the rules in recent papers, are far below it: the collection cannot resolve them, whatever the rules.

## 3.3 A multiverse of reporting choices

A reader of a pair-rule paper meets choices that are each reasonable and that each change the number: whether to use the benchmark's official weights; whether to restrict to pairs with enough rows; whether to report accuracy on all pairs or only on the pairs on which the rule is most confident (decided-only accuracy, as for a rule that abstains). We cross them: official weights or none; all pairs or only pairs with at least

**Table 3.** Rules on the 102 Tübingen pairs: unweighted accuracy with a 95% interval (TRA: the 82 pairs on which it returned a value) and the multiverse summary of Section 3.3. "Range": minimum and maximum accuracy over the ten reporting universes with at least 30 pairs per rule; "Rank": best and worst rank; "First": universes in which the rule is first (ties share the rank); ">RECI": universes in which it is above RECI; "Best of 10": expected best accuracy after trying ten random subsets of 50 pairs.

| Rule | Accuracy [interval] | Range | Rank | First | >RECI | Best of 10 |
|---|---|---|---|---|---|---|
| IGCI | 0.559 [0.46, 0.66] | 0.47–0.71 | 4–12 | 0 | 0 | 0.635 |
| RECI | 0.608 [0.51, 0.70] | 0.61–0.87 | 1–6 | 1 | 0 | 0.684 |
| ANM-HSIC | 0.608 [0.51, 0.70] | 0.57–0.70 | 3–12 | 0 | 1 | 0.682 |
| Pairwise LiNGAM | 0.608 [0.51, 0.70] | 0.54–0.74 | 4–13 | 0 | 0 | 0.682 |
| PDM | 0.402 [0.31, 0.50] | 0.40–0.61 | 10–13 | 0 | 0 | 0.477 |
| LOCI | 0.647 [0.55, 0.74] | 0.63–0.77 | 1–9 | 1 | 2 | 0.722 |
| ANM, Gaussian process | 0.554 [0.45, 0.65] | 0.55–0.75 | 3–12 | 0 | 0 | 0.628 |
| Compression, floor256 | 0.608 [0.51, 0.70] | 0.61–0.79 | 3–8 | 0 | 0 | 0.686 |
| Compression, floor256, raw rows | 0.647 [0.55, 0.74] | 0.64–0.76 | 2–8 | 0 | 2 | 0.721 |
| TRA | 0.646 [0.53, 0.75] | 0.65–0.76 | 2–6 | 0 | 4 | 0.729 |
| Compression, round255 | 0.667 [0.57, 0.76] | 0.67–0.88 | 1–3 | 8 | 9 | 0.740 |
| AVICI | 0.588 [0.49, 0.68] | 0.54–0.65 | 5–12 | 0 | 0 | 0.665 |
| RESIT | 0.613 [0.52, 0.71] | 0.47–0.66 | 5–13 | 0 | 1 | 0.686 |

250, 500 or 1000 rows; accuracy on the 100, 75, 50 or 25% of the pairs with the largest absolute score. This gives 32 universes. The coverage is taken exactly (top $k$ by |score|, ties broken at random with a fixed seed); the score of several rules is not a calibrated confidence, so this is the operation a reader could apply, not each rule's own abstention. A universe is kept only if every rule is evaluated on at least 30 pairs: 10 of 32 qualify (all pairs, or pairs with $\geq 250$ rows; coverage 100, 75, and for all pairs 50%; each with and without weights). The other 22 (for example the 25% of the 36 pairs with at least 1000 rows, which is nine pairs) cannot be reported. A first run kept them, and the ranges were far wider (0.27 to 0.75 for IGCI, up to 1.00 for RECI); an accuracy on nine pairs is not a defensible report, and we dropped them on review.

**Results.**

In the ten universes the accuracy of a single rule still moves by 11 to 26 points (Table 3): 0.47 to 0.71 for IGCI, 0.61 to 0.87 for RECI, 0.67 to 0.88 for the round255 compression, 0.63 to 0.77 for LOCI. Ranks move by up to nine places (ANM-HSIC from third to twelfth, pairwise LiNGAM from fourth to thirteenth, RESIT from fifth to thirteenth); RESIT's score takes only the values $-1$, 0, 1, so its coverage ranking is mostly random tie-breaking and its range is not informative. Three rules are first in at least one universe: round255 compression in 8, RECI and LOCI in 1 each; the round255 compression is above RECI in 9 universes and no other rule is above RECI in more than four. The coverage tie-breaking is immaterial except for RESIT: over 50 tie-break seeds the range of every other rule is unchanged and the first counts are identical (8, 1, 1), while RESIT's range varies by 0.03 (its score has only three values). Without the round255 variant in the panel RECI is first in 6 universes, LOCI and TRA in 2 and the raw-row floor256 compression in 1. The first counts are over universes, not within one universe, ties share the first rank, and they depend on which variants of a rule are in the panel: the round255 compression convention was selected because it reproduces a published figure (Section 4.1), and under the other conventions its unweighted accuracy ranges from 60.8% to 69.6%, so its lead in 8 of the 10 universes is partly a consequence of that selection. TRA returned no value on 20 pairs; these are excluded from its accuracy (82 pairs) and from its coverage ranking.

Single choices can be large. The official weights move RECI from 60.8% to 70.9%, round255 compression from 66.7% to 74.7%, and the floor256 variant from 60.8% to 68.0%, while LOCI goes from 64.7% to 63.9%. The quantisation convention of the compression rule (Section 4.1) moves the weighted accuracy between 68.8 and 74.7%.

**Table 4.** Tübingen, 50 protocol configurations (five row caps × dequantisation or not × five seeds). Range of the unweighted and of the official-weight accuracy over all configurations, and the range (in points) between the best and the worst level of each factor, averaged over the others.

| Rule | unweighted | weighted | rows | dequant. | seed |
|---|---|---|---|---|---|
| IGCI (ours, uniform ref.) | 0.49–0.66 | 0.57–0.68 | 1 | 11 | 1 |
| RECI | 0.56–0.67 | 0.58–0.73 | 2 | 1 | 2 |
| ANM-HSIC | 0.54–0.61 | 0.52–0.60 | 3 | 0 | 2 |
| Pairwise LiNGAM | 0.56–0.64 | 0.58–0.67 | 2 | 0 | 3 |
| Compression, round255 | 0.61–0.71 | 0.60–0.78 | 2 | 1 | 1 |
| IGCI (cdt, Gaussian ref.) | 0.40–0.63 | 0.40–0.64 | 1 | 18 | 0 |
| RECI (cdt) | 0.60–0.68 | 0.66–0.79 | 2 | 2 | 1 |
| CDS (cdt) | 0.54–0.66 | 0.50–0.65 | 7 | 4 | 2 |

Selecting among random subsets of 50 pairs inflates the expected best accuracy of every rule by seven to eight points after ten tries without changing the order of the rules (Appendix H).

### 3.4 A protocol multiverse on Tübingen

Section 3.3 varied how a result is reported. Here we vary how the data are prepared, for the same rule and the same pairs (experiment 61): the number of rows (250, 500, 1000, 2000 or all, drawn at random), whether tied values are dequantised, and the seed (which changes the subsample and the rule's own randomness): 50 configurations. Table 4 gives the range of each rule's accuracy and the range of the marginal means of each factor.

The same rule on the same pairs moves by 7 to 22 points unweighted and 8 to 23 points weighted: IGCI with a uniform reference from 49.0 to 65.7%, with cdt's Gaussian reference from 40.2 to 62.7% (the dequantisation alone: 52.4% against 63.8% on average for ours, so on raw Tübingen arrays IGCI is better than RECI, and with dequantisation worse), RECI weighted from 58.4 to 72.5%, round255 compression weighted from 59.9 to 78.4%, CDS unweighted from 53.9 to 65.7%. The number of rows matters little on average (a few points) but through the random subsample the seed alone moves RECI, LiNGAM and ANM-HSIC by two to three points. The range of a single rule across protocol choices is as large as the range between the twelve rules of Table 2 on Tübingen (40 to 67%, or 55 to 67% without the classifier below chance), and larger than the 2 to 5 points by which methods are usually separated. A comparison between two rules is therefore informative only under one identical protocol, run with the same preprocessing and several seeds; a comparison against a number quoted from a paper is not.

## 4 Implementation conventions: reproduction audit and tie handling

### 4.1 A reproduction audit

We audited one published table in detail, because it is the one for which the protocol is specified closely enough to repeat and for which the claims concern exactly the question of this paper. Stienstra [10] re-evaluate bivariate rules on the same 102 Tübingen pairs with the official weights, no tuning and a decision forced on every pair. They report 74.7% weighted accuracy for a parameter-free compression rule (68 of 102 pairs, 66.7% unweighted), 76.0% for the same rule on the 100 pairs on which SLOPE [14] is evaluated, 77.2% for SLOPE under a forced decision on those pairs (from the authors' stored output) and 82.4% as published (a decided-subset figure; 81.7% when the pairs answered by SLOPE's significance test are

**Table 5.** Reproduction of the compression baseline on the 102 Tübingen pairs (official weights). The published value is 68 of 102 pairs, 74.7% weighted.

| Quantisation and rows | pairs correct | unweighted | weighted |
|---|---|---|---|
| $\lfloor 256q \rfloor$, all rows | 67 | 0.657 | 0.688 |
| $\lfloor 255q \rfloor$, all rows | 71 | 0.696 | 0.705 |
| round$(255q)$, all rows | 68 | 0.667 | 0.747 |
| round$(255q)$, 2000 rows | 69 | 0.676 | 0.744 |
| round$(255q)$, no thinning | 69 | 0.676 | 0.753 |
| round$(255q)$, 500 rows | 71 | 0.696 | 0.717 |
| floor256, 2000 random dequantised rows (experiment 42) | 62 | 0.608 | 0.680 |

scored), and 70.7% for a faithful re-run of RECI; they trace the commonly quoted 77.5% for RECI to a mis-copied cell. Their point is that figures obtained with test-set model selection or with abstention gated by a significance test are not comparable with forced-decision figures.

**What we reproduce.**
Our RECI re-implementation gives 70.9% weighted (and 60.8% unweighted) on the same pairs, within 0.2 points of their 70.7%. Compression is the instructive case (Table 5). Our floor256 variant followed the published description (both variables quantised to 256 levels by linear min–max scaling, stable sort, first difference as `int8`, bzip2 level 9, normalised lengths, sign of the difference) but with the quantiser $\lfloor 256\,q \rfloor$ clipped to 255, and with the rows capped at 2000 and dequantised in the variant we ran at first; it gave 60.8% (dequantised) and 64.7% (raw rows), and 68.0% and 65.9% weighted. The text does not state how the integer levels are obtained from the scaled values. With round$(255\,q)$, all rows (linearly thinned above 8000) and raw values the same code gives exactly 68 of 102 pairs and 74.66% weighted: the published figure. With $\lfloor 255\,q \rfloor$ it gives 71 pairs and 70.5%. A one-pair difference in the count moves the weighted accuracy by up to six points because the official weights are unequal. Capping the rows changes the round255 variant by at most four weighted points (71.7% at 500 rows, 74.4% at 2000, 74.7% at 8000, 75.3% without thinning) and the floor variant by up to eight (62.7 to 70.8%); the conventions and caps are in `results/exp54_audit_conventions.json`. We adopted the round255 convention only after the reproduction check against the published figure, from three quantisation conventions and six row caps (all 18 in Appendix Table 15), and we say so: it is chosen to match a published target, not to maximise accuracy on any data of ours, and the exact match is fragile to the row cap.

**What we do not reproduce or compare.**
We did not run SLOPE, and so cannot confirm the 77.2% or 82.4% figures. For LOCI, our run of the authors' code gives 64.7% unweighted and 63.9% weighted (65.7% and 66.4% with 2000 rows instead of 1000); we did not locate a published Tübingen accuracy for LOCI that we could verify offline and make no comparison. The TRA preprint does not fix the constants we had to choose; our 64.6% on the 82 pairs it scores is for our constants and is not a test of its claims. SNOE, BF-BIC and AVICI make claims on graphs or simulated data that we did not attempt to reproduce.

**What the audit shows for the argument.**
(i) Two numbers that a reader would call "the compression baseline on Tübingen" differ by six weighted points because of a rounding convention that the description does not fix (the quantiser $\lfloor 256q \rfloor$ against round$(255q)$; rounding alone, $\lfloor 255q \rfloor$ against round$(255q)$, is 4.2 points); a comparison between methods whose gaps are three to five points is therefore inside the variation produced by conventions that the descriptions we checked do not fix. (ii) The reproduced baseline is, on Tübingen, among the best rules in

**Table 6.** Accuracy of rules under two tie conditions (raw arrays; $10^{-6}$ range jitter on tied values), same pairs (experiment 59). Tübingen is dequantised in both. cdt: `cdt` package defaults.

| Rule | Ties | Tüb. | iid | walks | Sachs | Bern. | Chgpt. | Malus |
|---|---|---|---|---|---|---|---|---|
| IGCI (ours, uniform reference) | raw | 0.56 | 0.94 | 0.89 | 0.65 | 1.00 | 1.00 | 0.08 |
| IGCI (ours, uniform reference) | jitter | 0.56 | 0.06 | 0.13 | 0.47 | 0.00 | 0.00 | 0.94 |
| IGCI (cdt, Gaussian reference) | raw | 0.42 | 0.94 | 0.84 | 0.47 | 1.00 | 1.00 | 0.08 |
| IGCI (cdt, Gaussian reference) | jitter | 0.42 | 0.06 | 0.12 | 0.53 | 0.00 | 0.00 | 0.94 |
| ANM-HSIC | raw | 0.57 | 0.73 | 0.62 | 0.59 | 0.31 | 0.57 | 0.31 |
| ANM-HSIC | jitter | 0.57 | 0.72 | 0.62 | 0.59 | 0.31 | 0.47 | 0.33 |
| RECI | raw | 0.61 | 0.98 | 0.94 | 0.53 | 0.25 | 1.00 | 0.56 |
| RECI | jitter | 0.61 | 0.98 | 0.94 | 0.53 | 0.25 | 1.00 | 0.56 |
| Pairwise LiNGAM | raw | 0.61 | 0.78 | 0.71 | 0.53 | 0.88 | 0.43 | 0.40 |
| Pairwise LiNGAM | jitter | 0.61 | 0.78 | 0.71 | 0.53 | 0.88 | 0.43 | 0.40 |

our panel (66.7%, 74.7% weighted), above RECI and LOCI but not significantly (exact McNemar $p = 0.39$ and 0.88), and it is at 38.3% on the i.i.d. chamber pairs, where RECI is at 97.9%. (iii) Its authors state that the rule's signal is partly marginal-geometric (a rank transform of the inputs, which flattens marginal shape, costs sixteen points in their experiments); this is the mechanism of Section 5.1.

## 4.2 Tie handling and implementation variants

The compression audit of Section 4.1 is one case of a general problem: choices that no paper reports and that a rule is sensitive to. Two more we measured.

**Ties reverse IGCI.**
The chamber arrays contain many tied values (discretised sensors, actuator levels). IGCI estimates the entropy of each scaled variable from the spacings between consecutive sorted values and prefers the direction in which the effect has the smaller entropy. Our implementation discards zero spacings; the alternative is to break ties with a tiny jitter, which turns the repeated values into spacings of order $10^{-6}$ and lowers the entropy of the tied variable. Table 6 gives the accuracy of IGCI under the two conditions on every collection (experiment 59, the same pairs): on the raw arrays 94% on the i.i.d. chamber pairs, 89% on the walk pairs, 100% on the Bernoulli and the changepoint pairs and 8% on Malus; with a jitter of one millionth of the range on the tied values 6%, 13%, 0%, 0% and 94%. The two conditions give approximately complementary accuracies ($a$ against $1 - a$) on the collections with many ties (i.i.d. chambers 0.94 and 0.06, Bernoulli and changepoints 1.00 and 0.00, Malus 0.08 and 0.94, walks 0.89 and 0.13), and not on Sachs (0.65 and 0.47), so for most collections the verdict that IGCI is "best on the chambers" or "best on Malus" is determined by a convention of one line of code. Tübingen, which is dequantised in both conditions and so has no ties, is unaffected (55.9%); on the raw Tübingen arrays, however, IGCI is at 63.8% on average over the protocol configurations of Section 3.4 against 52.4% when they are dequantised. RECI, pairwise LiNGAM and the cdt version of RECI do not change; cdt's CDS changes by up to six points (Sachs 0.53 to 0.59); ANM-HSIC changes by up to ten points on one collection (changepoints, 0.57 raw, 0.47 jittered). TRA fails on the jittered arrays (its smoothing-spline fit is ill-posed) and works on the raw ones. We use the raw arrays for every rule (Section 2.2). A first pass of this study gave the new collections the jittered arrays, reported IGCI at 0% on the Bernoulli and the changepoint pairs and offered a conjecture about it; the conjecture was wrong, the cause was the jitter, and the stored raw results replace that analysis.

**Reference implementations.**
Running the `cdt` implementations (experiment 55) gives a check of ours. Our IGCI makes exactly the decisions of cdt's IGCI with a uniform reference measure on every pair of every collection (100% agreement), whereas cdt's default reference is Gaussian (standardised variables): on Tübingen the two references give 55.9% and 42.2% (80% of the decisions agree) and on the raw Sachs pairs 64.7% and 47.1%; on the i.i.d. chamber pairs they agree (94% in both, raw) and on the walks they differ little (89% and 84%). The IGCI reference measure is thus a free parameter with a 14-point effect on Tübingen. Our RECI makes the same decision as cdt's RECI on 97.9% of the i.i.d. chamber pairs, 97.5% of the walk pairs and all pairs of the other chamber collections, Sachs and the new collections, but on 85.3% of the Tübingen pairs (60.8% against 63.7% accuracy on Tübingen): the two differ in the regression used for the error. cdt's CDS reaches 61.8% on Tübingen, 90.4% on the i.i.d. chambers and 79.5% on the walks; cdt's ANM (Gaussian-process regression with an HSIC test) and BivariateFit, run on the jittered arrays of experiment 55, are at 51.5% and 48.0% on Tübingen and at 46% and 5% on the i.i.d. chambers. We did not obtain the authors' code for these rules; the cdt versions are themselves re-implementations.

**Seed variability.**
The HSIC-based rule has a random component: the same ANM-HSIC on the same Tübingen pairs gives 60.8% with the seed of the first experiments and 56.9% with the seed of experiment 59 (2000 rows, de-quantised); on the i.i.d. chambers the same rule gives 72.3% and 73.4% under the two seeds. LOCI on the changepoint collection gives 0.80 on raw arrays and 0.73 on jittered ones. Differences of this size are within what separates published rules.

# 5 Why dependence-based rules do not lead: mechanisms

Section 3 says that the benchmarks are small and that no rule leads across them. They do not say why the rules that test the conditional structure of the pair do not do better. We tested three explanations, each with a prediction fixed before the run (experiments 49–52, 56, 57), and report the ones that failed.

## 5.1 The benchmarks can be solved from the marginals

*Hypothesis.* On the real collections, a classifier that never sees the joint distribution of $(x, y)$, only the two marginal distributions, orients the pairs about as well as the best rule. If so, the benchmark rewards a rule's sensitivity to marginal asymmetry between cause and effect, a property that conditional-structure rules do not use.

*Classifier.* Each variable is scaled to $[0, 1]$ and described by five numbers: skewness, excess kurtosis, Vasicek spacing entropy ($m = \sqrt{n}$), the logarithm of the fraction of unique values, and the 1–99% range. The pair feature is the difference of the two vectors; both orientations enter training with labels 1 and 0; the model is a standardised logistic regression. The first protocol (experiment 49) uses five-fold cross-validation with folds over pairs (50 repetitions): 59.0% on Tübingen, 100% on the i.i.d. chamber pairs, 92.6% on the walk pairs and 89.8% on the Sachs pairs.

*These first numbers leak.* The chamber edges share their cause variable (`load_in` causes many sensors) and the 17 Sachs arcs reuse eleven proteins, so a held-out pair often had its variable's marginal in the training folds. Review of the first version identified the problem; experiment 52 removes it:

– i.i.d. chambers: training on the wind-tunnel recording and testing on the light-tunnel recording and conversely, 97.9% (93.6% without the unique-fraction feature);

– walk recordings: leaving one of the five recordings out, 86.9% (90.2%) (recordings of the same tunnel share variable names, so this is a weaker test than the wind-to-light transfer above, which is cross-device);
– Sachs: training on the arcs that involve neither protein of the test arc, 94.1% (all 17 arcs evaluated; same with or without the feature);
– Tübingen: leave one pair out, 57.8%.

The unique-fraction feature separates discrete actuators from continuous sensors and is a measurement artefact when sets are preprocessed differently (Tübingen is dequantised, so the feature is constant there); dropping it leaves the picture unchanged. The prediction held: above 80% without leakage.

*Transfer across collections.* A classifier trained on the 102 Tübingen pairs orients 87.2% of the i.i.d. chamber pairs and 91.8% of the walk pairs; one trained on the 17 Sachs pairs orients 100% of the i.i.d. chamber pairs (96.8% without the unique-fraction feature) and 81.1% of the walk pairs; one trained on the chambers does not orient Tübingen (52% for the i.i.d.-trained and 58% for the walk-trained model); Sachs is oriented by the walk-trained model (100%, 88% without the unique-fraction feature) but not by the i.i.d.-trained one (53%; the Sachs set has 17 pairs). Appendix Figure 3 shows the matrix. The marginal asymmetry between an experimenter-set actuator and a sensor is a property shared by every device, and it is not present in Tübingen in a way that transfers: on Tübingen the marginal-only accuracy (57.8–59.0%) is within the sampling error of chance and of most dependence-based rules.

*Design confound.* In the chamber collections the cause is an actuator set by the experimenter and the effect a sensor, so a classifier that separates "actuator-like" from "sensor-like" marginals orients the pairs without any information about causation in general; the result concerns what these benchmarks reward, not what marginals say about cause and effect. The Sachs result rests on 17 pairs and the Sachs transfer in the other direction is at chance (Tübingen to Sachs 47%, i.i.d. chambers to Sachs 53%; only the walk-trained model reaches 100% on it).

*What this does and does not show.* It does not show that RECI or IGCI use only the marginals: both read the scale of regression errors and the marginal density. It shows that the chamber collections can be oriented from the marginals alone, so a rule that is sensitive to marginal asymmetry will do well on them for reasons that have nothing to do with conditional structure, and that a rule that tests only the conditional model, such as an additive-noise test, has no reason to profit. That the chamber rankings (Figure 2) look like the marginal cue and the Tübingen ranking does not is consistent with this and is the first leg of the explanation.

## 5.2 Additive-noise rules work in one regime and reverse in another

*Hypothesis.* The additive-noise family loses where its assumption fails. For every Tübingen pair we measured the heteroscedasticity of the residuals of a cross-fitted additive-spline regression of the true effect on the true cause: $h = |\rho_S(|r|, x)|$ with $\rho_S$ the Spearman correlation (six knots, ridge penalty one, two folds). Appendix Table 19 gives, for each rule, the mean $h$ on the pairs it orients wrongly and rightly. The four noise-model rules show a large difference: ANM-HSIC 0.32 against 0.13, the Gaussian-process ANM 0.29 against 0.10, RESIT 0.34 against 0.13, LOCI 0.27 against 0.17 (one-sided Mann–Whitney; Holm-adjusted $p \leq 0.014$ for each, $3 \times 10^{-8}$ for ANM-HSIC and the Gaussian-process ANM); also TRA (adjusted $p = 0.036$); not RECI and PDM (raw 0.021, adjusted 0.17), IGCI, pairwise LiNGAM, AVICI or the compression rules (adjusted $p \geq 0.45$). Pooling the decisions of the four noise-model rules (396 decisions) in a logistic regression of correctness on the standardised $h$ and $\log n$, one standard deviation of $h$ multiplies the odds of a correct decision by 0.26 (we do not report the $p$-value, which is not interpretable because the four rules are scored on the same pairs); $n$ has no effect.

Splitting Tübingen into thirds by $h$ (bounds 0.094 and 0.268, 34 pairs each; TRA has 24, 31 and 27 pairs with a value) shows the regimes (Table 7, Appendix Figure 4). In the least heteroscedastic third ANM-HSIC, RESIT and the Gaussian-process ANM are right on 97%, 96% and 91% of the pairs, far above RECI (68%); in the most heteroscedastic third on 29%, 24% and 22%, below chance. Averaged over the

**Table 7.** Tübingen accuracy by tercile of $h$ (34 pairs per tercile; TRA 24, 31, 27).

| Rule | low $h$ | middle | high $h$ |
|---|---|---|---|
| ANM-HSIC | 0.97 | 0.56 | 0.29 |
| RESIT | 0.96 | 0.65 | 0.24 |
| ANM, Gaussian process | 0.91 | 0.53 | 0.22 |
| TRA | 0.83 | 0.68 | 0.44 |
| LOCI | 0.82 | 0.62 | 0.50 |
| RECI | 0.68 | 0.68 | 0.47 |
| IGCI | 0.59 | 0.44 | 0.65 |
| Pairwise LiNGAM | 0.65 | 0.53 | 0.65 |
| Compression, round255 | 0.74 | 0.74 | 0.53 |
| Compression, floor256, raw | 0.71 | 0.68 | 0.56 |
| AVICI | 0.53 | 0.56 | 0.68 |
| PDM | 0.56 | 0.35 | 0.29 |

**Table 8.** Matched simulated pairs: accuracy against the strength $a$ (100 pairs per level). Left: noise scale depends on the cause. Right: independent random scale with the same kind of marginal (control).

| | scale depends on cause | | | | independent scale | | | |
|---|---|---|---|---|---|---|---|---|
| Rule | 0 | 0.5 | 1 | 1.5 | 0 | 0.5 | 1 | 1.5 |
| ANM-HSIC | 1.00 | 0.49 | 0.12 | 0.21 | 1.00 | 1.00 | 0.99 | 0.89 |
| IGCI | 0.64 | 0.72 | 0.91 | 0.99 | 0.64 | 0.73 | 0.95 | 0.99 |
| RECI | 0.78 | 0.77 | 0.87 | 0.93 | 0.78 | 0.84 | 0.96 | 0.98 |

three thirds, ANM-HSIC (0.61) and RESIT (0.62) equal the baselines and the Gaussian-process ANM is lower (0.55): a rule that is excellent in one regime and reversed in another has the accuracy of one that is mediocre in both. This reading is descriptive: $h$ is computed in the true direction, so it is not a predictor; its bounds come from the same data; it is close to the dependence between the scale and the cause that the additive-noise tests probe, so part of the association is by construction.

## 5.3 Manipulation with a marginal control

An association across pairs cannot separate heteroscedasticity from whatever else differs between pairs, and making the noise scale depend on the cause also changes the marginal of the effect (a scale mixture). We therefore set the factor by hand (experiment 52). Pairs $e = f(c) + \sigma\varepsilon$, $f \in \{\tanh 2c, c^3/3, \sin 1.5c\}$, $c$ uniform or Gaussian, $n = 500$, the same $c$, $f$ and $\varepsilon$ at every level, $a \in \{0, 0.5, 1, 1.5\}$, 100 pairs per level, a random half swapped. In the heteroscedastic arm $\sigma(c) \propto \exp(ac)$; in the control arm $\sigma_i \propto \exp(au_i)$ with $u_i \sim N(0, 1)$ independent of $c$, which gives the effect a similar heavy-tailed marginal but no dependence of the scale on the cause; the average noise variance is fixed in both. Table 8 and Appendix Figure 5: ANM-HSIC falls from 100% to 21% with cause-dependent noise and only to 89% with the independent scale, so the collapse is due to the dependence of the scale on the cause (ANM-HSIC is not monotone in $a$, 0.12 at $a = 1$ and 0.21 at $a = 1.5$, within the sampling error of 100 pairs per level). IGCI and RECI rise in both arms (64 → 99% and 78 → 93% with cause-dependent noise; 64 → 99% and 78 → 98% with the independent scale): they profit from the heavy-tailed marginal of the effect, not from heteroscedasticity. An earlier unmatched run without the control showed the same rise and we had attributed it to heteroscedasticity; the control refutes that, and the correct reading ties this experiment to Section 5.1: IGCI and RECI are sensitive to marginal asymmetry.

### 5.4 What we could not build on the account

Three further analyses, in Appendix E, test whether the account extends. A factorial simulation (experiment 56; five factors, 3600 pairs, seven rules; Appendix Section E.1) reproduces the regimes: ANM-HSIC and RESIT are at 0.95 in the clean cell, 0.06 and 0.17 with a cause-dependent noise scale and 0.69 and 0.74 with measurement noise alone, and RECI has the highest average accuracy in 12 of 14 factor levels. A regime-gated rule (GATE, experiment 51; Section E.2) that switches between ANM-HSIC and RECI on a symmetric heteroscedasticity diagnostic, frozen on simulation, failed both predictions fixed in advance (65.7% against RECI's 60.8% on Tübingen, $p = 0.30$; 75.5% against 97.9% on the i.i.d. chambers, $p < 10^{-6}$). A nearest-neighbour prediction of each rule's accuracy on the real collections from the factorial simulation (experiment 57; Section E.3) failed as well (Spearman 0.006 against the required 0.5, RMSE 0.31 against 0.24 for a constant prediction); the real pairs lie two to thirteen standard deviations from the simulation's support, so the test could not have succeeded with this simulator and is uninformative about the account beyond showing that the simulator does not cover the real collections. The account is therefore a set of demonstrated mechanisms, not a validated predictive model.

### 5.5 Summary of the evidence on mechanisms

Two mechanisms are directly supported. (1) The chamber collections can be oriented from the marginals alone (we rely on the marginal-only classifier and on RECI, which ties do not change; IGCI's chamber accuracy depends on the tie convention), validated across recordings (wind to light tunnel and back) and, on 17 pairs, across proteins; the cue is a property of the experimental design, in which the cause is an actuator and the effect a sensor, and it does not transfer to Tübingen. In simulation IGCI and RECI gain accuracy when the effect has a heavy-tailed marginal even if the conditional structure is unchanged, which we offer as a conjecture about why they are sensitive to marginal asymmetry; we did not test it directly. (2) Additive-noise rules are regime-specific: near-perfect when the noise scale does not depend on the cause and reversed when it does (manipulation with a control, factorial map, Tübingen terciles), and degraded by measurement noise. The Tübingen average of these rules equals the baselines because the collection mixes regimes. Two attempts to build on the account fail (Section 5.4). What the evidence leaves unexplained is why the additive-noise rules lose on the chambers and how much of the differences between collections the two mechanisms jointly account for.

## 6 Discussion, recommendations and limitations

**What the evidence supports.**
On the collections we examined, rules that test a model of the conditional distribution do not beat rules that read marginal asymmetry or error scale, and no rule leads across collections. This is not because the dependence-based rules are poor: ANM-HSIC, RESIT and the Gaussian-process ANM are right on 91 to 97% of the least heteroscedastic third of the Tübingen pairs and ANM-HSIC is perfect in simulation when its assumption holds. They are reversed when the noise scale depends on the cause, degraded by measurement noise, and unable to use the marginal cue that orients the chamber collections; averaged over a collection that mixes regimes they equal the baselines. The baselines are not robust either: IGCI is at 8% on the Malus pairs and, with or without a jitter on ties, at 6% or 94% on the i.i.d. chambers; RECI is at 25% on the Bernoulli pairs; compression is at 38% on the i.i.d. chambers. We do not claim that published methods misreport (we reproduced the one table we audited), nor that dependence-based rules cannot be improved: the failed regime-gated rule and the failed predictive validation show the account is incomplete.

**Recommendations.**

1. *Test paired and state the power.* With 102 pairs the detectable difference is about 19 points (27 after correcting for 78 comparisons); a gain of two to five points is not resolvable, and about 330 pairs are needed for 10 points.
2. *Report the coverage curve and both weightings.* A single decided-only, weighted or unweighted number selects one point of a multiverse that moves a rule by 11 to 26 points and its rank by up to nine places.
3. *Fix preprocessing and settings before the data are seen and publish the code,* including conventions the text does not fix: a rounding rule moved a weighted headline by six points, IGCI's reference measure moved its accuracy by 14 points, and the treatment of ties turned 94% into 6%.
4. *Report several collections and test a marginal-only classifier,* which is cheap and shows how much of a benchmark can be solved without dependence structure; rankings on one collection say little about another.
5. *Report the effective sample size and the number of distinct edges* (seventeen of the nineteen untouched chamber recordings have an effective sample size of about three out of 4000 rows; the new pair collections have four to eight distinct edges).
6. *For learned methods, show real-data accuracy next to the simulated test* and how far the real diagnostics lie from the simulator's support.

## 6.1 Limitations

Tübingen has 102 pairs, Sachs 17 arcs and the other collections four to 47 distinct edges, so all inference is as imprecise as Section 3 says. IGCI, RECI, ANM-HSIC, pairwise LiNGAM, compression and TRA are our implementations (RECI agrees with a published re-run within 0.2 weighted points; TRA uses our constants); we did not run SLOPE, CAM, SCORE or PNL, and tuning could change a ranking. The multiverse is finite, its choices are ours, its accuracies are computed on overlapping pairs and several scores are not confidences. The heteroscedasticity measure is computed in the true direction and the tercile analysis is post hoc; the manipulation and factorial map use one family of mechanisms, and the factorial simulator does not cover the real collections (Appendix E). The marginal-only classifier is small, and its chamber results concern an actuator-to-sensor design. Why additive-noise rules lose on the chambers and why IGCI fails on Malus are not diagnosed. Analyses designed after the data are labelled as such, and several errors found on internal review (leakage in the marginal classifier, a confounded manipulation, universes with too few pairs) are described where they occurred.

# References

[1] Joris M. Mooij, Jonas Peters, Dominik Janzing, Jakob Zscheischler, and Bernhard Schölkopf. Distinguishing cause from effect using observational data: Methods and benchmarks. *Journal of Machine Learning Research*, 17(32):1–102, 2016.

[2] Karen Sachs, Omar Perez, Dana Pe'er, Douglas A. Lauffenburger, and Garry P. Nolan. Causal protein-signaling networks derived from multiparameter single-cell data. *Science*, 308(5721):523–529, 2005. 10.1126/science.1105809.

[3] Patrik O. Hoyer, Dominik Janzing, Joris M. Mooij, Jonas Peters, and Bernhard Schölkopf. Nonlinear causal discovery with additive noise models. In *Advances in Neural Information Processing Systems 21*, pages 689–696, 2009.

[4] Jonas Peters and Peter Bühlmann. Identifiability of Gaussian structural equation models with equal error variances. *Biometrika*, 101(1):219–228, 2014. 10.1093/biomet/ast043.

[5] Aapo Hyvärinen and Stephen M. Smith. Pairwise likelihood ratios for estimation of non-Gaussian structural equation models. *Journal of Machine Learning Research*, 14:111–152, 2013.

[6] Alexander Immer, Christoph Schultheiss, Julia E. Vogt, Bernhard Schölkopf, Peter Bühlmann, and Alexander Marx. On the identifiability and estimation of causal location-scale noise models. In *Proceedings of the 40th International Conference on Machine Learning*, 2023.

[7] Lars Lorch, Scott Sussex, Jonas Rothfuss, Andreas Krause, and Bernhard Schölkopf. Amortized inference for causal structure learning. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

[8] Patrick Blöbaum, Dominik Janzing, Takashi Washio, Shohei Shimizu, and Bernhard Schölkopf. Cause-effect inference by comparing regression errors. In *Proceedings of the 21st International Conference on Artificial Intelligence and Statistics*, 2018.

[9] Povilas Daniušis, Dominik Janzing, Joris Mooij, Jakob Zscheischler, Bastian Steudel, Kun Zhang, and Bernhard Schölkopf. Inferring deterministic causal relations. In *Proceedings of the 26th Conference on Uncertainty in Artificial Intelligence*, 2010.

[10] Wietse Stienstra. One ruler: A same-hands re-evaluation of bivariate causal direction on Tuebingen, with a parameter-free compression baseline. *arXiv preprint arXiv:2606.23767*, 2026.

[11] Juan L. Gamella, Jonas Peters, and Peter Bühlmann. Causal chambers as a real-world physical testbed for AI methodology. *Nature Machine Intelligence*, 2025. 10.1038/s42256-024-00964-x.

[12] Shohei Shimizu, Patrik O. Hoyer, Aapo Hyvärinen, and Antti Kerminen. A linear non-Gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7:2003–2030, 2006.

[13] Kun Zhang and Aapo Hyvärinen. On the identifiability of the post-nonlinear causal model. In *Proceedings of the 25th Conference on Uncertainty in Artificial Intelligence*, pages 647–655, 2009.

[14] Alexander Marx and Jilles Vreeken. Telling cause from effect using MDL-based local and global regression. In *2017 IEEE International Conference on Data Mining*, 2017.

[15] David Lopez-Paz, Krikamol Muandet, Bernhard Schölkopf, and Ilya Tolstikhin. Towards a learning theory of cause-effect inference. In *Proceedings of the 32nd International Conference on Machine Learning*, 2015.

[16] Alexander G. Reisach, Christof Seiler, and Sebastian Weichwald. Beware of the simulated DAG! causal discovery benchmarks may be easy to game. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[17] Joseph Ramsey, Bryan Andrews, and Peter Spirtes. Scalable causal discovery from recursive nonlinear data via truncated basis function scores and tests. *arXiv preprint arXiv:2510.04276*, 2025.

[18] Stella Huang and Qing Zhou. Nonlinear causal discovery through a sequential edge orientation approach. *arXiv preprint arXiv:2506.05590*, 2025.

[19] Mouad El Bouchattaoui. Topological residual asymmetry for bivariate causal direction. *arXiv preprint arXiv:2602.00427*, 2026.

# A Log of pre-specified experiments

Each row is an experiment script (`experiments/expNN_*.py`) with the short hash of the commit that first added it, before it was run, and the date. The first line of each script's docstring is quoted. Scripts were revised after a first run only where stated in their docstrings (experiments 47, 49, 57; each revision is a separate commit and the first version is retrievable). Experiments 1–16 belong to the earlier theory paper on sequential certificates and are not used here.

| # | Commit | Date | Purpose |
|---|---|---|---|
| 17 | `98de084` | 2026-10-23 | Experiment 17: scaling with graph size and ablation of CERT-CD. |
| 18 | `0318781` | 2026-10-23 | Experiment 18: held-out simulated pair families, sample-size sweep, baselines. |
| 19 | `0318781` | 2026-10-23 | Experiment 19: sensitivity of the Tuebingen result to the random seed. |
| 20 | `c5cd9b0` | 2026-10-23 | Experiment 20: real physical data with a known causal graph (Causal Chambers). |
| 21 | `269ae7a` | 2026-10-23 | Experiment 21: direction of the known edges of the Causal Chambers. |
| 22 | `aa99d05` | 2026-10-23 | Experiment 22: nonparametric sequential adjacency certificate vs the linear primitive. |
| 23 | `aa99d05` | 2026-10-23 | Experiment 23: nonparametric adjacency certificate on the Causal Chambers. |
| 24 | `9f32aaa` | 2026-10-23 | Experiment 24: Causal Chambers with conditioning-set order k = 3. |
| 25 | `7045b1b` | 2026-10-23 | Experiment 25: the nonparametric certificate on the exp13 and exp17 DAG data. |
| 26 | `b59a1c6` | 2026-10-23 | Experiment 26: PC with the same nonparametric test, under monitoring. |
| 27 | `ba2f7ac` | 2026-10-23 | Experiment 27: untouched Causal Chamber recordings, final algorithm frozen. |
| 28 | `06bffaf` | 2026-10-23 | Experiment 28: abstaining comparison of the pair rules at matched coverage. |
| 29 | `f85302f` | 2026-10-23 | Experiment 29: BTAD against PC, GES, DirectLiNGAM and PC with an iid nonparametric test |
| 30 | `ced1b11` | 2026-10-23 | Experiment 30: BTAD on the untouched Causal Chamber recordings, time-ordered. |
| 31 | `9dddc37` | 2026-10-24 | Fit the LRG classifier on exp31 features; choose the threshold on validation; report held-out simulation metrics. |
| 31 | `d682048` | 2026-10-24 | Experiment 31: train the learned replicated-gain skeleton model (LRG) on simulated data. |
| 32 | `9dddc37` | 2026-10-24 | Experiment 32: the frozen LRG model on the untouched, time-ordered Causal Chamber recordings. |

| # | Commit | Date | Purpose |
|---|---|---|---|
| 33 | b91cbf1 | 2026-10-24 | Experiment 33: frozen LRG and BTAD on the two Causal Chamber recordings with i.i.d. random actuators. |
| 34 | 985335e | 2026-10-24 | Experiment 34: train the learned pair-direction model (PDM) on simulated pairs. |
| 34 | ddb1d8f | 2026-10-24 | Fit the pair-direction classifier on exp34 features; report held-out simulated accuracy. |
| 35 | ddb1d8f | 2026-10-24 | Experiment 35: the frozen pair-direction model (PDM) on real and held-out pair sets. |
| 36 | 5e7f00b | 2026-10-24 | Experiment 36: Sachs data and NOTEARS, added to the graph benchmark. |
| 37 | a83a699 | 2026-10-24 | Experiment 37: PC with the nonparametric test on the two i.i.d. chamber recordings (exp20 subsamples). |
| 38 | c8e01d1 | 2026-10-24 | Experiment 38: LOCI and ANM added to the pair benchmark, and the Sachs pairs. |
| 39 | 6387fdc | 2026-10-24 | Experiment 39: DAGMA and PCMCI+ added to the graph benchmark. |
| 40 | ba11744 | 2026-10-24 | Experiment 40: LOCI on the Tuebingen pairs with up to 2000 rows per pair. |
| 41 | c94369a | 2026-10-24 | Experiment 41 (negative result): block-ICP pilot on five wind-tunnel walk recordings (development only). |
| 42 | bbdeb3a | 2026-10-24 | Experiment 42: 2025-2026 pair rules on the same pair sets as exp38. |
| 43 | bbdeb3a | 2026-10-24 | Experiment 43: BF-BIC with BOSS (arXiv 2510.04276) on the graph benchmark. |
| 44 | cdf776c | 2026-10-24 | Experiment 44: SNOE-style edge orientation (arXiv 2506.05590, see sprint_cd/snoe_lite.py). |
| 45 | 37f8d52 | 2026-10-25 | Experiment 45: published methods with public code on the graph benchmark. |
| 46 | 101841b | 2026-10-25 | Experiment 46: published pair rules with public code (AVICI pretrained, RESIT) on the exp38 pair sets. |
| 47 | b805f02 | 2026-10-25 | Experiment 47 (revision 4: the discordance rate and McNemar counts exclude missing values and exact ties, the Bonferroni |
| 48 | 211fb35 | 2026-10-25 | Experiment 48: resolution of the Sachs graph benchmark. |
| 49 | 02dfe48 | 2026-10-25 | Experiment 49: why do direction rules that exploit dependence lose to RECI/IGCI on real pairs? |
| 50 | c17d1ad | 2026-10-25 | Experiment 50: does heteroscedastic noise cause the loss of the noise-model rules? (simulation, dose-response) |
| 51 | 31dadda | 2026-10-25 | Experiment 51: an assumption-gated direction rule (GATE), frozen on simulation, tested once on real pairs. |
| 52 | 4282166 | 2026-10-25 | Experiment 52: controls for experiments 49-50 (leakage-free marginal classifier, matched dose-response with marginal con |
| 53 | 37fc958 | 2026-10-25 | Experiment 53: three further real pair collections from the Causal Chambers, and the diagnostics of exp49. |
| 54 | 37d6d13 | 2026-10-25 | Experiment 54: sorted-conditional compression with the quantisation convention that reproduces its published figure. |
| 55 | 8f63bb7 | 2026-10-25 | Experiment 55: reference implementations from the cdt package, and LOCI/ANM-GP/PDM on the three new collections. |
| 56 | 04de9ce | 2026-10-25 | Experiment 56: a factorial simulation of the regimes found in exp49-52, with label-free diagnostics. |
| 57 | 241d7b0 | 2026-10-25 | Experiment 57 (revision 3: the observed decisions of the three new collections are the raw-array ones of exp59 (IGCI, RE |
| 58 | 5c1c168 | 2026-10-25 | Experiment 58: pair rules on every untouched Causal Chambers recording (not only the first of each type). |
| 59 | 8b388ce | 2026-10-25 | Experiment 59: tie handling as a free parameter, and raw-array versions for the three new collections. |
| 60 | b592bf7 | 2026-10-25 | Experiment 60: TRA on raw arrays for the all-recordings walk pairs (exp58) and the three new collections (exp53). |
| 61 | d68bf71 | 2026-10-25 | Experiment 61: how much does the evaluation protocol move each rule on Tuebingen? |

# B Implementation details

**Preprocessing.**

Tübingen: at most 2000 rows drawn with a seed that depends on the pair identifier; each variable with tied values dequantised by adding uniform noise in $\pm\frac{1}{2}$ of the smallest positive gap between distinct values (experiment 14). Chamber and Sachs collections: raw values (Sachs on the log scale with a floor at $10^{-3}$), at most 2000 random rows; walk recordings use random rows of the first 4000 rows for pairs and the first

4000 (graphs) or 2000 (45) rows in time order for graphs. All rules see the raw arrays; a copy with a $10^{-6}$ range jitter on tied values is used only in the sensitivity analysis of Section 4.2 and in the simulations.

**Scores.**
All rules return a signed score, positive for $x \to y$. IGCI, RECI, ANM-HSIC and pairwise LiNGAM return a direction label and a magnitude that we convert to a sign. A score of exactly zero counts as half correct (this affected 23 pairs of the Gaussian-process ANM). A rule that returns no value on a pair (TRA's spline failure) is excluded from that pair and the denominator is reduced.

**Compression.**
Section 4.1. In both variants the score is $s = \mathrm{sc}(q_y, q_x)/\max(\mathrm{dc}(q_x), 1) - \mathrm{sc}(q_x, q_y)/\max(\mathrm{dc}(q_y), 1)$ with $\mathrm{sc}(\mathrm{key}, \mathrm{val}) = |\mathrm{bz2}(\Delta\,\mathrm{val}[\mathrm{argsort}(\mathrm{key})])|$ and $\mathrm{dc}(q) = |\mathrm{bz2}(\Delta q)|$, a stable sort, differences cast to `int8`, bzip2 level 9; $s > 0$ means $x \to y$.

**TRA.**
Cross-fitted smoothing-spline residuals (5 folds), a rank-uniform point cloud, the total length of the zero-dimensional persistence (minimum spanning tree) in the window $\alpha = \kappa n^{-2/3}$, $\beta = c_\beta \alpha$ with $\kappa = 1$, $c_\beta = 4$, at most 1000 rows; the direction is the sign of the difference of the two residual functionals. The conservative variant TRA-C ($B = 100$ Gaussian-copula bootstrap draws) took 27 s per pair at $n = 800$ and was not run.

**AVICI.**
The pretrained model `scm-v0`; edge probability matrix of the standardised data ($\leq 2000$ rows for graphs, $\leq 1000$ for pairs); graphs: skeleton from probability $\geq 0.5$; pairs: $P(x \to y) - P(y \to x)$. Run in a virtual environment with `jax 0.4.30`, `flax 0.8.5`, `dm-haiku 0.0.12`, `optax 0.2.2`, `numpy<2`.

**Graph packages.**
GOLEM (gCastle, $10^4$ iterations), NOTEARS-MLP and GraN-DAG and DAG-GNN (gCastle defaults), GRaSP and BOSS (`causal-learn`, BIC), RESIT (random forest depth 4, $\alpha = 0.01$) and CAM-UV ($\alpha = 0.01$, three explanatory values; `lingam`); a run over 900 s is a timeout.

**Marginal-only classifier.**
Features as in Section 5.1; scikit-learn `LogisticRegression` with $C = 1$ on standardised features; both orientations of every training pair; 50 repetitions of five-fold cross-validation for the first protocol, deterministic splits for the others.

**Heteroscedasticity.**
Cubic B-splines with six knots on the standardised cause, ridge penalty one, two-fold cross-fitting, residual scale correlation $|\rho_S(|r|, x)|$.

**Factorial simulation.**
Seeds are `default_rng([20263200, mechanism, cause, scale, measurement, n, k])`; the scale of the noise is normalised so that the mean noise variance is $(0.3\,\mathrm{sd}\,f(c))^2$; measurement noise is Gaussian with 0.3 times the sample sd of each variable.

**Software.**
Python 3.11, `numpy 1.26`, `scipy 1.13`, `scikit-learn 1.9`, `statsmodels 0.15`, `causal-learn 0.1.4.8`, `lingam 1.13`, `gcastle`, `causalchamber 0.2.8`; four CPU cores, no GPU.

# C Negative results of the algorithm search

Each attempt was fixed before its run. Numbers are strict skeleton $F_1$ or forced accuracy against the reference.

| Attempt | Idea | Outcome on real data |
|---|---|---|
| CERT-CD (sequential certificates) | assert edges only by rejecting; anytime-valid | False-edge control holds in simulation (2.7% against 27–91%), not on the chambers |
| BTAD | block-replicated additive gains | highest precision (0.60) but recall 0.16; $F_1$ 0.25–0.28 on walk recordings |
| LRG | gradient boosting on block-gain features, trained on simulations | $F_1$ 0.36 (chambers), 0.67 (Sachs); within-recording AUC 0.55 |
| PDM | pair classifier trained on 40000 simulated pairs | 95% on simulated pairs, 40.2% on Tübingen |
| Block-ICP | invariant causal prediction with time blocks | empty graphs, $F_1 \leq 0.07$ on development recordings |
| Compression, TRA, BF-BIC (exp 42–43, 54) | re-implemented 2025–2026 methods | compression: 60.8–64.7% with the floor256 variant, 66.7% (74.7% weighted) round255, 38.3% on i.i.d. chambers; TRA 64.6% (86.2% on i.i.d. chambers); BF-BIC with BOSS: Sachs 0.67, walks 0.42 |
| Interventional route (pilot) | shift of each sensor under each intervened actuator (light tunnel) | KS: precision 1.00, recall 0.72 (28 of 39 arcs), AUC 0.91; the missed arcs show no shift; conditional version recall 0.79 at precision 0.51 |
| Published packages (exp 45–46) | AVICI, GOLEM, NOTEARS-MLP, GraN-DAG, DAG-GNN, GRaSP, BOSS, RESIT, CAM-UV | best: BOSS 0.55 i.i.d. chambers; GRaSP 0.68, BOSS 0.65 large-ESS; Sachs $\leq 0.56$; walks $\leq 0.37$; many neural timeouts |
| GATE (exp 51) | ANM-HSIC when a symmetric heteroscedasticity diagnostic is low, else RECI | Tübingen 65.7% against 60.8% ($p = 0.30$); chambers 75.5%, 77.0% against 97.9%, 94.3% |
| Predictive validation (exp 57) | nearest simulated neighbours predict each rule's accuracy | Spearman 0.006 in the reported revision (needed 0.5); RMSE 0.31 against 0.24 for the constant; real pairs are 2–13 sd from the simulation |

# D Additional tables

The accuracy of each of the 144 cells of the factorial simulation is in `results/exp56_factorial.json`.

**Table 11.** Accuracy with 95% cluster-bootstrap intervals for every rule and collection (clusters: pairs for Tübingen and Sachs, edges for the i.i.d. chambers and the three new collections, recordings for the walks); for collections with 8 or fewer clusters (the five-recording walks, Bernoulli, changepoints, Malus) only the accuracy is given because the interval is degenerate.

| Rule | Tübingen | iid | walks | walks (19) |
|---|---|---|---|---|
| IGCI | 0.56 [0.46,0.66] | 0.94 [0.85,1.00] | 0.89 | 0.96 [0.91,0.99] |
| RECI | 0.61 [0.51,0.70] | 0.98 [0.94,1.00] | 0.94 | 0.83 [0.79,0.87] |
| ANM-HSIC | 0.61 [0.51,0.71] | 0.72 [0.61,0.83] | 0.63 | 0.43 [0.38,0.50] |
| Pairwise LiNGAM | 0.61 [0.51,0.70] | 0.78 [0.68,0.87] | 0.71 | 0.67 [0.62,0.72] |
| PDM | 0.40 [0.30,0.50] | 0.93 [0.84,0.99] | 0.84 | – |
| LOCI | 0.65 [0.56,0.74] | 0.77 [0.66,0.86] | 0.68 | – |
| ANM, Gaussian process | 0.55 [0.46,0.65] | 0.77 [0.68,0.87] | 0.67 | – |
| Compression, floor256 | 0.61 [0.52,0.70] | 0.30 [0.19,0.40] | 0.61 | – |
| Compression, round255 | 0.67 [0.58,0.75] | 0.38 [0.29,0.48] | 0.52 | 0.50 [0.43,0.57] |
| TRA | 0.65 [0.54,0.75] | 0.86 [0.77,0.94] | 0.61 | 0.56 [0.50,0.61] |
| AVICI | 0.59 [0.49,0.69] | 0.90 [0.82,0.97] | 0.56 | 0.63 [0.58,0.68] |
| RESIT | 0.61 [0.52,0.70] | 0.71 [0.61,0.81] | 0.65 | 0.48 [0.43,0.53] |

| Rule | Sachs | Bernoulli | Changepoints | Malus |
|---|---|---|---|---|
| IGCI | 0.65 [0.41,0.88] | 1.00 | 1.00 | 0.08 |
| RECI | 0.53 [0.29,0.76] | 0.25 | 1.00 | 0.56 |
| ANM-HSIC | 0.59 [0.35,0.82] | 0.31 | 0.57 | 0.31 |
| Pairwise LiNGAM | 0.53 [0.29,0.76] | 0.88 | 0.43 | 0.40 |
| PDM | – | – | – | – |
| LOCI | 0.47 [0.24,0.71] | 0.56 | 0.80 | 0.38 |
| ANM, Gaussian process | 0.56 [0.32,0.79] | 0.47 | 0.54 | 0.33 |
| Compression, floor256 | 0.76 [0.53,0.94] | – | – | – |
| Compression, round255 | 0.65 [0.41,0.88] | 0.50 | 1.00 | 0.60 |
| TRA | 0.59 [0.35,0.82] | 0.62 | – | 0.54 |
| AVICI | 0.53 [0.29,0.76] | 0.62 | 0.40 | 0.02 |
| RESIT | 0.47 [0.29,0.65] | 0.25 | 0.53 | 0.50 |

# E Further mechanism evidence

## E.1 A factorial map

To see the regimes together we crossed five factors (experiment 56): the mechanism ($\tanh 2c$, $c^3/3$, $\sin 1.5c$), the cause marginal (uniform, normal, bimodal, five-level discrete), the noise scale (homoscedastic, cause-dependent, independent random), measurement noise on both variables (0 or 0.3 sd), and $n \in \{200, 1000\}$: 144 cells of 25 pairs (3600 pairs), seven rules. Table 16 gives the accuracy by factor level and Table 17 the interaction of the noise scale with measurement noise.

The additive-noise rules are near-perfect only without cause-dependent scale and without measurement noise (ANM-HSIC 0.95 and RESIT 0.95 with homoscedastic noise, 0.91 and 0.89 with the independent scale), fall to 0.69 and 0.74 with measurement noise alone, and to 0.06 and 0.17 with a cause-dependent scale; measurement noise partly masks the reversal (0.49, 0.54). IGCI and the round255 compression are the weakest rules when the cause is discrete (0.47 and 0.39; the simulated arrays carry the $10^{-6}$ jitter under which IGCI reverses, Section 4.2, so the IGCI figure is partly a tie artefact); IGCI is more accurate with measurement noise than without (0.77 against 0.61); the round255 compression depends on $n$ (0.62 at 200, 0.81 at 1000); AVICI fails on the cubic mechanism (0.19) and is at 0.49 for the uniform cause. RECI has the highest average accuracy in 12 of the 14 factor levels (the exceptions are the normal cause, where

**Table 12.** The ten reporting universes with at least 30 pairs per rule: weighting, minimum number of rows, coverage (%), pairs in the subset, smallest number of pairs evaluated for any rule, and the accuracy of each rule (a subset of the columns of Table 3; CmpF: round255 compression; the other four columns are in the repository file `results/exp47_multiverse.json`).

| Weights | Rows | Cov. | $n$ | min | IGCI | RECI | ANM-H | LiNGAM | LOCI | TRA | CmpF | AVICI | RESIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| official | 0 | 100 | 102 | 82 | 0.66 | 0.71 | 0.61 | 0.62 | 0.64 | 0.65 | 0.75 | 0.61 | 0.62 |
| official | 0 | 75 | 102 | 62 | 0.64 | 0.77 | 0.58 | 0.65 | 0.67 | 0.71 | 0.78 | 0.60 | 0.57 |
| official | 0 | 50 | 102 | 41 | 0.66 | 0.87 | 0.57 | 0.74 | 0.63 | 0.74 | 0.88 | 0.58 | 0.47 |
| official | 250 | 100 | 76 | 56 | 0.71 | 0.75 | 0.65 | 0.54 | 0.71 | 0.70 | 0.75 | 0.59 | 0.63 |
| official | 250 | 75 | 76 | 42 | 0.69 | 0.84 | 0.63 | 0.56 | 0.77 | 0.74 | 0.77 | 0.60 | 0.56 |
| none | 0 | 100 | 102 | 82 | 0.56 | 0.61 | 0.61 | 0.61 | 0.65 | 0.65 | 0.67 | 0.59 | 0.61 |
| none | 0 | 75 | 102 | 62 | 0.50 | 0.68 | 0.57 | 0.63 | 0.63 | 0.71 | 0.72 | 0.63 | 0.58 |
| none | 0 | 50 | 102 | 41 | 0.47 | 0.76 | 0.57 | 0.71 | 0.63 | 0.76 | 0.84 | 0.65 | 0.55 |
| none | 250 | 100 | 76 | 56 | 0.55 | 0.67 | 0.70 | 0.55 | 0.72 | 0.68 | 0.71 | 0.54 | 0.66 |
| none | 250 | 75 | 76 | 42 | 0.51 | 0.75 | 0.67 | 0.58 | 0.75 | 0.76 | 0.77 | 0.61 | 0.63 |

AVICI is at 0.89 against 0.72, and homoscedastic noise, where RESIT is at 0.84 against 0.82). Which factor breaks which rule is rule-specific.

## E.2 An assumption-gated rule fails

If the regimes explain the Tübingen average, a rule that identifies the regime should beat both of its branches. We froze GATE on simulation before touching a real pair (experiment 51): $h_{\min} = \min(h(x \to y), h(y \to x))$, symmetric in the variables, threshold at the 95th percentile of $h_{\min}$ on 200 homoscedastic simulated pairs (0.058 at $n = 500$); GATE returns the ANM-HSIC direction when $h_{\min} \le 0.058$ and the RECI direction otherwise. The pre-specified predictions were an accuracy of at least 0.70 on Tübingen and, on the chambers, within 0.05 of RECI. Both failed. On Tübingen GATE has 65.7% (77.1% with the official weights) against 60.8% (70.9%) for RECI; it routes 34% of the pairs to ANM-HSIC and the difference to RECI is not significant (exact McNemar 10 against 5, $p = 0.30$). On the i.i.d. chambers GATE has 75.5% against 97.9% (0 against 21 discordant pairs, $p < 10^{-6}$) and on the walks 77.0% against 94.3% ($p < 10^{-6}$), because it sends 88% and 62% of those pairs to ANM-HSIC, which is right on 72% and 63% of the whole collections (we did not store its accuracy on the routed subset). The threshold was set at $n = 500$, the chamber pairs have $n = 2000$ and the null spread of $|\rho|$ shrinks with $n$, so the routing is not comparable across sets; an $n$-aware threshold was not tried. The Sachs pairs were not evaluated (no stored ANM-HSIC decision under the same preprocessing). GATE is a negative result and is not offered as a method.

## E.3 An attempt to predict real accuracy from the factorial map fails

The strongest test of an explanation is that it predicts. For every real pair we computed seven label-free diagnostics (minimum heteroscedasticity over the two directions, log fraction of unique values, minimum and maximum excess kurtosis, maximum absolute skewness, log absolute Spearman correlation, $\log n$), found its 100 nearest neighbours among the 3600 simulated pairs of Section E.1, and predicted each rule's accuracy by the neighbours' mean correctness (experiment 57). The pre-specified criteria were a Spearman correlation of at least 0.5 between predicted and observed accuracy over the 49 (collection, rule) cells, a smaller RMSE than the constant prediction (each rule's overall simulation accuracy), and the rule predicted best being among the two best observed on at least four of the seven collections.

The first run was invalid as implemented: the unique-fraction diagnostic was constant in the simulation (computed on jittered arrays), so real pairs with tied values had standardised values around $-3 \times 10^9$ and the neighbours were arbitrary (Spearman $-0.01$). Revision 2 computes simulated and real diagnostics

**Table 13.** Sachs: skeleton $F_1$ of 22 configurations with a 95% bootstrap interval over the 55 variable pairs.

| Configuration | $F_1$ | interval |
|---|---|---|
| LRG | 0.67 | [0.42, 0.85] |
| BF-BIC+BOSS | 0.67 | [0.42, 0.85] |
| PC-GCM $\alpha$ =0.01 | 0.64 | [0.38, 0.83] |
| PC-GCM $\alpha$ =0.05 | 0.62 | [0.36, 0.81] |
| BTAD | 0.62 | [0.35, 0.81] |
| PC $\alpha$ =0.05 | 0.58 | [0.30, 0.80] |
| GES-BIC | 0.58 | [0.30, 0.80] |
| AVICI | 0.56 | [0.29, 0.77] |
| NOTEARS-MLP | 0.56 | [0.29, 0.77] |
| PC $\alpha$ =0.01 | 0.52 | [0.24, 0.74] |
| DirectLiNGAM | 0.52 | [0.24, 0.74] |
| PCMCI+ | 0.52 | [0.24, 0.74] |
| GRaSP | 0.52 | [0.24, 0.74] |
| BOSS | 0.52 | [0.24, 0.74] |
| CERT-CD nonparametric k=3 | 0.45 | [0.15, 0.69] |
| DAGMA | 0.45 | [0.15, 0.69] |
| RESIT | 0.45 | [0.24, 0.63] |
| NOTEARS | 0.30 | [0.00, 0.56] |
| GOLEM | 0.30 | [0.00, 0.56] |
| DAG-GNN | 0.30 | [0.00, 0.56] |
| GraN-DAG | 0.11 | [0.00, 0.32] |
| CAM-UV | 0.11 | [0.00, 0.33] |

**Table 14.** Kendall rank correlation between the orderings of the rules on two collections, with a permutation $p$-value (5000 permutations of one ordering) in parentheses; rules run on both collections, at least five.

| | Tüb. | iid | walks | walks19 | Sachs | Bern. | Chgpt. | Malus |
|---|---|---|---|---|---|---|---|---|
| Tübingen | – | -0.38 (0.11) | -0.30 (0.21) | -0.42 (0.20) | -0.12 (0.68) | -0.19 (0.54) | +0.24 (0.46) | +0.51 (0.06) |
| iid | -0.38 (0.11) | – | +0.53 (0.02) | +0.57 (0.06) | -0.17 (0.53) | +0.34 (0.21) | -0.03 (1.00) | -0.16 (0.60) |
| walks | -0.30 (0.21) | +0.53 (0.02) | – | +0.43 (0.18) | -0.27 (0.30) | +0.07 (0.86) | +0.26 (0.41) | -0.02 (1.00) |
| walks19 | -0.42 (0.20) | +0.57 (0.06) | +0.43 (0.18) | – | +0.04 (1.00) | +0.52 (0.11) | +0.21 (0.65) | -0.07 (0.90) |
| Sachs | -0.12 (0.68) | -0.17 (0.53) | -0.27 (0.30) | +0.04 (1.00) | – | +0.27 (0.35) | +0.41 (0.18) | -0.02 (1.00) |
| Bernoulli | -0.19 (0.54) | +0.34 (0.21) | +0.07 (0.86) | +0.52 (0.11) | +0.27 (0.35) | – | -0.06 (0.92) | -0.25 (0.37) |
| Changepoints | +0.24 (0.46) | -0.03 (1.00) | +0.26 (0.41) | +0.21 (0.65) | +0.41 (0.18) | -0.06 (0.92) | – | +0.26 (0.40) |
| Malus | +0.51 (0.06) | -0.16 (0.60) | -0.02 (1.00) | -0.07 (0.90) | -0.02 (1.00) | -0.25 (0.37) | +0.26 (0.40) | – |

identically (the simulator is deterministic) and reports how far the real pairs are from the simulation; it failed (Spearman 0.17, RMSE 0.30 against 0.26). Revision 3 replaces the observed decisions of the three new collections, which had been computed on jittered arrays, by the raw-array ones (Section 4.2); it is the version reported here. It fails as well: Spearman 0.006 (criterion 0.5), RMSE 0.31 against 0.24 for the constant prediction, while the criterion that the predicted best rule is among the two best observed is met on 4 of 7 collections (it is nearly degenerate: RECI is predicted best for every collection, and is among the two best observed on four of the seven; IGCI is observed best or second on five). The pair-level criterion, the AUC of the predicted correctness for the observed correctness, was also pre-specified and gives 0.66 for RESIT, 0.62 for ANM-HSIC, 0.55 for RECI and AVICI and 0.41 to 0.48 for IGCI, pairwise LiNGAM and compression, so the prediction carries some pair-level information for the two additive-noise rules and none for the others. The reason for the failure is visible in the support: the median distance from a real pair to its nearest simulated pair, in units of the simulation's standard deviations (a Euclidean metric on seven standardised diagnostics), is 2.3 for Tübingen, 2.8–3.4 for the chamber collections, 4.4–4.6 for the Bernoulli and changepoint collections, 8.9 for Sachs and 13.1 for Malus, against a 95th-percentile

**Table 15.** All 18 conventions of the compression rule on the 102 Tübingen pairs (quantiser × row cap; rows thinned linearly above the cap). The published value is 68 pairs, 74.7% weighted. Source: `results/exp54_audit_conventions.json`.

| Quantiser | Row cap | Pairs correct | Unweighted | Weighted |
|---|---|---|---|---|
| floor256 | 500 | 64 | 0.627 | 0.627 |
| floor256 | 1000 | 67 | 0.657 | 0.697 |
| floor256 | 2000 | 63 | 0.618 | 0.648 |
| floor256 | 4000 | 69 | 0.676 | 0.708 |
| floor256 | 8000 | 67 | 0.657 | 0.688 |
| floor256 | none | 67 | 0.657 | 0.688 |
| floor255 | 500 | 69 | 0.676 | 0.697 |
| floor255 | 1000 | 69 | 0.676 | 0.695 |
| floor255 | 2000 | 67 | 0.657 | 0.682 |
| floor255 | 4000 | 71 | 0.696 | 0.702 |
| floor255 | 8000 | 71 | 0.696 | 0.705 |
| floor255 | none | 71 | 0.696 | 0.705 |
| round255 | 500 | 71 | 0.696 | 0.717 |
| round255 | 1000 | 70 | 0.686 | 0.740 |
| round255 | 2000 | 69 | 0.676 | 0.744 |
| round255 | 4000 | 68 | 0.667 | 0.740 |
| round255 | 8000 | 68 | 0.667 | 0.747 |
| round255 | none | 69 | 0.676 | 0.753 |

leave-one-out distance of 0.76 within the simulation; at most 5% of the pairs of any collection lie within the simulation's support. The factorial simulator illustrates mechanisms and cannot be used to predict accuracy on these real collections. (The simulated rules ran on jittered arrays; only the discrete-cause cells have ties, where IGCI's simulated accuracy would change with the tie convention.) The explanation of Sections 5.1–E.1 is therefore a set of demonstrated mechanisms, not a validated predictive model, and we do not claim that it accounts for the whole of the differences between the collections.

# F Descriptive diagnostics

Table 18 describes the collections with the quantities used later: the median number of rows, the median absolute Spearman correlation, the median residual heteroscedasticity $h$ of Section 5.2 (true direction), the median excess kurtosis of the cause and of the effect, the median number of distinct values of the cause, and the share of pairs with many ties (fewer distinct values than 90% of the rows) in either variable before any jitter (Tübingen is reported after dequantisation, hence zero). Figure 1 shows one randomly chosen pair per collection.

# G Graph benchmarks

The same question for graphs. We score skeletons only, against the 17-arc Sachs consensus (853 cells, log scale) and against the documented graphs of Causal Chambers recordings: two i.i.d. recordings (ten random subsamples of 4000 shuffled rows each), two further recordings with an effective sample size above 1000, and seventeen new wind-tunnel and light-tunnel recordings whose actuators are random walks and whose effective sample size, by the heuristic $n(1-\rho)/(1+\rho)$, is about three out of 4000 rows. For the walk recordings the first 4000 rows in time order are used. Table 20 gives precision/recall/$F_1$ for 22 method configurations: the classical rules (PC at two levels, GES, DirectLiNGAM, NOTEARS, DAGMA, PCMCI+), nine published packages at library defaults (experiment 45; AVICI, GOLEM, NOTEARS-MLP, GraN-DAG,

**Table 16.** Factorial simulation (3600 pairs): accuracy of seven rules averaged over the other factors.

| Factor | Level | IGCI | RECI | ANM-HSIC | LiNGAM | Compr. | RESIT | AVICI |
|---|---|---|---|---|---|---|---|---|
| mechanism | tanh | 0.66 | 0.71 | 0.42 | 0.16 | 0.65 | 0.46 | 0.66 |
| mechanism | cubic | 0.87 | 1.00 | 0.70 | 0.54 | 0.75 | 0.75 | 0.19 |
| mechanism | sin | 0.55 | 0.95 | 0.73 | 0.81 | 0.74 | 0.75 | 0.85 |
| cause marginal | uniform | 0.94 | 0.95 | 0.52 | 0.34 | 0.84 | 0.53 | 0.49 |
| cause marginal | normal | 0.61 | 0.72 | 0.64 | 0.36 | 0.84 | 0.68 | 0.89 |
| cause marginal | bimodal | 0.75 | 0.89 | 0.63 | 0.59 | 0.79 | 0.68 | 0.36 |
| cause marginal | discrete5 | 0.47 | 0.97 | 0.68 | 0.71 | 0.39 | 0.72 | 0.53 |
| noise scale | homoscedastic | 0.56 | 0.82 | 0.82 | 0.50 | 0.68 | 0.84 | 0.55 |
| noise scale | cause | 0.74 | 0.90 | 0.28 | 0.56 | 0.72 | 0.36 | 0.66 |
| noise scale | independent scale | 0.78 | 0.94 | 0.75 | 0.45 | 0.74 | 0.76 | 0.49 |
| measurement noise | 0 | 0.61 | 0.92 | 0.64 | 0.50 | 0.70 | 0.67 | 0.58 |
| measurement noise | 1 | 0.77 | 0.85 | 0.59 | 0.50 | 0.73 | 0.64 | 0.56 |
| n | 200 | 0.66 | 0.87 | 0.61 | 0.52 | 0.62 | 0.66 | 0.58 |
| n | 1000 | 0.73 | 0.90 | 0.62 | 0.48 | 0.81 | 0.65 | 0.55 |

**Table 17.** Factorial simulation: noise scale × measurement noise.

| Noise scale | Meas. noise | IGCI | RECI | ANM-HSIC | LiNGAM | Compr. | RESIT | AVICI |
|---|---|---|---|---|---|---|---|---|
| homoscedastic | no | 0.47 | 0.89 | 0.95 | 0.49 | 0.67 | 0.95 | 0.54 |
| homoscedastic | yes | 0.64 | 0.76 | 0.69 | 0.50 | 0.69 | 0.74 | 0.55 |
| cause-dependent | no | 0.68 | 0.91 | 0.06 | 0.55 | 0.71 | 0.17 | 0.68 |
| cause-dependent | yes | 0.81 | 0.89 | 0.49 | 0.56 | 0.73 | 0.54 | 0.65 |
| independent scale | no | 0.69 | 0.98 | 0.91 | 0.46 | 0.70 | 0.89 | 0.52 |
| independent scale | yes | 0.86 | 0.90 | 0.60 | 0.45 | 0.78 | 0.64 | 0.47 |

DAG-GNN, GRaSP, BOSS, RESIT, CAM-UV), BF-BIC with BOSS, and the methods we developed (PC with a nonparametric test, BTAD, LRG, sequential certificates, Appendix C).

**The ranking depends on the family.**
On the i.i.d. chamber recordings the best are DirectLiNGAM and BOSS ($F_1 = 0.55$) and GRaSP (0.52); on the two recordings with a large effective sample size GES (0.70), GRaSP (0.68) and DirectLiNGAM (0.66); on Sachs LRG and BF-BIC with BOSS (0.67), PC with the nonparametric test (0.62–0.64) and BTAD (0.62), against 0.58 for PC and GES. No method has a strict $F_1$ above 0.42 on the seventeen random-walk recordings, where most methods report tens of false edges. The neural methods are weaker: GraN-DAG finds almost no edges ($F_1 \leq 0.12$), GOLEM and DAG-GNN report 22 to 36 false edges per recording, NOTEARS with an MLP timed out on 16 of 17 walk recordings (16 variables) and AVICI on 9 of 17 and on 6 of 20 i.i.d. subsamples; their means in Table 20 are over the data sets on which they finished and are not comparable to the others.

**Resolution and structure of the benchmarks.**
One Sachs arc changes recall by 0.06; 16 of 22 configurations have a bootstrap interval that contains the best $F_1$ (Section 3.2). The chamber graphs are bipartite (actuators to sensors), so skeleton recovery is feature selection from actuators to measurements, and the actuators are recognisable by their marginals (Section 5.1). An interventional pilot on the light tunnel (a pilot, not pre-specified; `results/lt_interventions_check.json`) shows how little a graph benchmark with documented interventions leaves to a new method: a two-sample test of each sensor against the reference recording under each actuator intervention has precision 1.00 and recall 0.72 (28 of the 39 arcs among observed variables,

**Table 18.** Descriptive diagnostics of the seven collections other than the all-recordings walks (medians over pairs unless stated; the 486-pair walk collection has the same kind of pairs as the walk collection).

| Collection | Pairs | $n$ | $\lvert\rho_S\rvert$ | $h$ | kurt. cause | kurt. effect | distinct cause values | ties |
|---|---|---|---|---|---|---|---|---|
| Tübingen | 102 | 392 | 0.50 | 0.18 | -0.2 | 0.2 | 392 | 0.00 |
| Chambers iid | 94 | 2000 | 0.27 | 0.02 | -1.2 | -0.4 | 86 | 1.00 |
| Chambers walks | 122 | 2000 | 0.26 | 0.08 | -1.2 | -0.6 | 255 | 1.00 |
| Sachs | 17 | 853 | 0.08 | 0.08 | 3.1 | 2.3 | 276 | 1.00 |
| Bernoulli | 16 | 2000 | 0.53 | 0.18 | -1.2 | -1.2 | 101 | 1.00 |
| Changepoints | 70 | 1983 | 0.45 | 0.22 | -0.7 | -0.1 | 4 | 1.00 |
| Malus | 48 | 1000 | 0.02 | 0.02 | -1.2 | -1.4 | 732 | 1.00 |





**Figure 1.** One randomly chosen pair (seed 7) from each collection; 800 random rows, cause on the horizontal axis.

which here are also the ancestral pairs; AUC 0.91 from the $p$-values), and the missed arcs, all from light sources to their sensors, show no shift in the data ($p$ between 0.06 and 0.86); a conditional version (residuals of a boosted regression on the estimated non-descendants) raises recall to 0.79 at a precision of 0.51.

**What we do not conclude.**

The reference networks are small, the Sachs consensus is contested, and several baselines (CAM, SCORE) were not run. The differences between graph methods are mostly within sampling error, and the effective sample size of the walk recordings limits what any method can show. We read the graph results as consistent with the pair results: no rule leads across families.

# H Selective subsets

Pair benchmarks are often evaluated on a subset of pairs (a given variable type or sample size, or pairs where the other rules disagree). We drew 10000 random subsets of 50 of the 102 pairs. The accuracy of a rule on a subset has a standard deviation of about 0.05. For the eight rules whose full-sample accuracy is within 0.04 of RECI the probability that a rule beats RECI on a subset lies between 0.34 and 0.71, so most subsets would support either order; for round255 compression, 0.059 above RECI, it is 0.79. The expected best accuracy over $m$ independently drawn subsets, which is what a researcher reports after trying

**Table 19.** Tübingen: mean residual heteroscedasticity $h$ (true direction) on the pairs a rule orients wrongly and rightly; $p$: one-sided Mann–Whitney test that $h$ is larger on the wrong pairs. Twelve rules; $p_{\mathrm{adj}}$: Holm over the twelve.

| Rule | wrong/right | $h$ wrong | $h$ right | $p$ | $p_{\mathrm{adj}}$ |
|---|---|---|---|---|---|
| IGCI | 45/57 | 0.19 | 0.22 | 0.707 | 1 |
| RECI | 40/62 | 0.25 | 0.17 | 0.0214 | 0.165 |
| ANM-HSIC | 40/62 | 0.32 | 0.13 | 2.67e-09 | 3.2e-08 |
| Pairwise LiNGAM | 40/62 | 0.22 | 0.19 | 0.245 | 0.736 |
| PDM | 61/41 | 0.22 | 0.18 | 0.0206 | 0.165 |
| LOCI | 36/66 | 0.27 | 0.17 | 0.00141 | 0.0141 |
| ANM, Gaussian process | 42/53 | 0.29 | 0.10 | 2.83e-09 | 3.2e-08 |
| Compression, floor256 | 40/62 | 0.22 | 0.19 | 0.0879 | 0.452 |
| Compression, floor256, raw | 36/66 | 0.22 | 0.19 | 0.0946 | 0.452 |
| TRA | 29/53 | 0.26 | 0.17 | 0.00405 | 0.0365 |
| Compression, round255 | 34/68 | 0.23 | 0.19 | 0.0753 | 0.452 |
| AVICI | 42/60 | 0.18 | 0.22 | 0.926 | 1 |
| RESIT | 37/60 | 0.34 | 0.13 | 7.98e-10 | 1.04e-08 |





**Figure 2.** Left: accuracy of each rule on each collection. Right: Kendall rank correlation between the orderings of the rules on two collections (rules run on both; at least five).

$m$ subsets and keeping the best, grows with $m$: RECI 0.608 ($m = 1$), 0.650 (3), 0.684 (10); LOCI 0.647, 0.688, 0.722; round255 compression 0.667, 0.707, 0.740. The inflation at $m = 10$ is seven to eight points for every rule, which leaves the order of the rules unchanged; what it changes is the claim of an absolute level. Each subset is half of the same 102 pairs, so this measures selection noise about a known full-sample accuracy, not how a researcher actually chooses subsets (by type or size, not at random).

**Table 20.** Skeleton precision/recall/$F_1$ against the reference (strict), mean over data sets. Sachs: one data set; Chambers iid: $2 \times 10$ subsamples; ESS$> 1000$: 2 recordings; ESS$< 20$: 17 recordings. A number in parentheses is the number of data sets on which the method finished within $900$ s when fewer than the full number. Experiments 36, 39, 43, 45.

| Method | Sachs | Chambers iid | ESS $> 1000$ | ESS $< 20$ |
|---|---|---|---|---|
| PC $\alpha$ =0.05 | 1.00/0.41/0.58 | 0.40/0.38/0.37 | 0.48/0.28/0.35 | 0.36/0.39/0.37 |
| PC $\alpha$ =0.01 | 1.00/0.35/0.52 | 0.39/0.33/0.34 | 0.51/0.27/0.36 | 0.36/0.36/0.36 |
| GES-BIC | 1.00/0.41/0.58 | 0.45/0.64/0.49 | 0.74/0.67/0.70 | 0.26/0.71/0.38 |
| DirectLiNGAM | 1.00/0.35/0.52 | 0.55/0.60/0.55 | 0.71/0.63/0.66 | 0.26/0.63/0.37 |
| NOTEARS | 1.00/0.18/0.30 | 0.41/0.21/0.27 | 0.33/0.24/0.26 | 0.26/0.45/0.33 |
| DAGMA | 1.00/0.29/0.45 | 0.44/0.33/0.36 | 0.44/0.41/0.39 | 0.25/0.52/0.34 |
| PCMCI+ | 1.00/0.35/0.52 | 0.39/0.33/0.34 | 0.53/0.29/0.37 | 0.27/0.17/0.20 |
| GRaSP | 1.00/0.35/0.52 | 0.53/0.57/0.52 | 0.78/0.63/0.68 | 0.27/0.50/0.35 |
| BOSS | 1.00/0.35/0.52 | 0.57/0.61/0.55 | 0.77/0.57/0.65 | 0.29/0.54/0.37 |
| BF-BIC + BOSS | 0.90/0.53/0.67 | 0.43/0.63/0.49 | 0.57/0.61/0.58 | 0.30/0.68/0.42 |
| NOTEARS-MLP | 0.88/0.41/0.56 | 0.42/0.51/0.43 | 0.45/0.27/0.34 (1) | 0.17/0.25/0.21 (1) |
| GOLEM | 1.00/0.18/0.30 | 0.26/0.39/0.31 | 0.36/0.49/0.41 | 0.25/0.47/0.33 |
| DAG-GNN | 1.00/0.18/0.30 | 0.36/0.45/0.36 | 0.45/0.34/0.38 | 0.27/0.45/0.34 (16) |
| GraN-DAG | 1.00/0.06/0.11 | 0.55/0.04/0.06 | 0.20/0.04/0.06 | 0.54/0.07/0.12 |
| RESIT | 0.39/0.53/0.45 | 0.33/0.80/0.43 | 0.37/0.74/0.49 | 0.23/0.99/0.37 |
| CAM-UV | 1.00/0.06/0.11 | 0.67/0.31/0.42 | 0.74/0.43/0.53 | 0.06/0.01/0.02 (15) |
| AVICI | 0.88/0.41/0.56 | 0.48/0.36/0.37 (14) | 0.54/0.17/0.26 | 0.36/0.23/0.28 (8) |
| PC-GCM $\alpha$ =0.05 | 0.89/0.47/0.62 | 0.38/0.33/0.34 | 0.54/0.34/0.41 | 0.35/0.54/0.42 |
| PC-GCM $\alpha$ =0.01 | 1.00/0.47/0.64 | 0.39/0.30/0.32 | 0.47/0.26/0.33 | 0.34/0.46/0.39 |
| BTAD | 0.89/0.47/0.62 | 0.56/0.36/0.41 | 0.82/0.46/0.58 | 0.60/0.16/0.25 |
| LRG | 0.90/0.53/0.67 | 0.39/0.48/0.43 | 0.52/0.55/0.53 | 0.51/0.28/0.36 |
| CERT-CD nonparametric | 1.00/0.29/0.45 | 0.29/0.16/0.20 | 0.60/0.18/0.28 | 0.24/0.87/0.37 |





**Figure 3.** Marginal-only classifier trained on one collection (rows) and tested on another (columns), accuracy. The cue learned on Tübingen, Sachs or the chambers orients the chamber pairs; nothing learned on the chambers or Sachs transfers to Tübingen.





**Figure 4.** Tübingen accuracy by tercile of the residual heteroscedasticity $h$.





**Figure 5.** Accuracy against the strength $a$ of the noise-scale variation. Left: scale depends on the cause. Right: independent scale (control).