

Migrations Laravel — MVP SaaS de Templates (Completo)

Este documento reúne TODAS as migrations Laravel do MVP SaaS de Templates, cobrindo o schema completo definido na modelagem lógica: núcleo, comercial, operacional, relacionamentos N:N e tabelas técnicas.

create_clients_table

```
Schema::create('clients', function (Blueprint $table) {
    $table->id();
    $table->string('name');
    $table->string('document')->nullable();
    $table->enum('status', ['active', 'suspended'])->default('active');
    $table->timestamps();
    $table->softDeletes();
});
```

create_users_table

```
Schema::create('users', function (Blueprint $table) {
    $table->id();
    $table->foreignId('client_id')->constrained()->restrictOnDelete();
    $table->string('name');
    $table->string('email')->unique();
    $table->string('password');
    $table->timestamps();
    $table->softDeletes();
});
```

create_templates_table

```
Schema::create('templates', function (Blueprint $table) {  
    $table->id();  
    $table->string('name');  
    $table->string('slug')->unique();  
    $table->text('description')->nullable();  
    $table->enum('status', ['active', 'inactive'])->default('active');  
    $table->timestamps();  
    $table->softDeletes();  
});
```

create_template_versions_table

```
Schema::create('template_versions', function (Blueprint $table) {
    $table->id();
    $table->foreignId('template_id')->constrained()->restrictOnDelete();
    $table->string('version');
    $table->string('path');
    $table->boolean('is_active')->default(true);
    $table->timestamp('created_at')->useCurrent();
    $table->unique(['template_id', 'version']);
});
```

create_sites_table

```
Schema::create('sites', function (Blueprint $table) {
    $table->id();
    $table->foreignId('client_id')->constrained()->cascadeOnDelete();
    $table->foreignId('template_version_id')->constrained()->restrictOnDelete();
    $table->string('name');
    $table->string('slug');
    $table->enum('status', ['draft', 'published', 'suspended'])->default('draft');
    $table->json('content')->nullable();
    $table->timestamps();
    $table->softDeletes();
    $table->unique(['client_id', 'slug']);
});
```

create_subscriptions_table

```
Schema::create('subscriptions', function (Blueprint $table) {
    $table->id();
    $table->foreignId('client_id')->constrained()->cascadeOnDelete();
    $table->foreignId('site_id')->constrained()->cascadeOnDelete();
    $table->enum('status', ['active', 'canceled', 'overdue']);
    $table->date('started_at');
    $table->date('ended_at')->nullable();
    $table->timestamps();
    $table->softDeletes();
});
```

create_payments_table

```
Schema::create('payments', function (Blueprint $table) {
    $table->id();
    $table->foreignId('subscription_id')->constrained()->cascadeOnDelete();
    $table->string('provider');
    $table->string('external_id')->index();
    $table->decimal('amount', 10, 2);
    $table->enum('status', ['paid', 'pending', 'failed']);
    $table->timestamp('paid_at')->nullable();
    $table->timestamp('created_at')->useCurrent();
});
```

create_publication_requests_table

```
Schema::create('publication_requests', function (Blueprint $table) {  
    $table->id();  
    $table->foreignId('site_id')->constrained()->cascadeOnDelete();  
    $table->enum('status', ['requested', 'in_progress', 'published', 'rejected']);  
    $table->text('notes')->nullable();  
    $table->timestamps();  
    $table->softDeletes();  
});
```


create_client_templates_table

```
Schema::create('client_templates', function (Blueprint $table) {
    $table->id();
    $table->foreignId('client_id')->constrained()->cascadeOnDelete();
    $table->foreignId('template_id')->constrained()->restrictOnDelete();
    $table->enum('status', ['active', 'revoked']->default('active'));
    $table->timestamp('acquired_at')->useCurrent();
    $table->softDeletes();
    $table->unique(['client_id', 'template_id']);
});
```

create_site_users_table

```
Schema::create('site_users', function (Blueprint $table) {
    $table->id();
    $table->foreignId('site_id')->constrained()->cascadeOnDelete();
    $table->foreignId('user_id')->constrained()->cascadeOnDelete();
    $table->enum('role', ['owner', 'editor'])->default('editor');
    $table->softDeletes();
    $table->unique(['site_id', 'user_id']);
});
```

create_domains_table

```
Schema::create('domains', function (Blueprint $table) {  
    $table->id();  
    $table->foreignId('site_id')->constrained()->cascadeOnDelete();  
    $table->string('domain')->unique();  
    $table->enum('status', ['pending', 'active']->default('pending'));  
    $table->timestamp('created_at')->useCurrent();  
    $table->softDeletes();  
});
```

create_webhook_logs_table

```
Schema::create('webhook_logs', function (Blueprint $table) {  
    $table->id();  
    $table->string('provider');  
    $table->string('event');  
    $table->json('payload');  
    $table->timestamp('received_at')->useCurrent();  
});
```

create_activity_logs_table

```
Schema::create('activity_logs', function (Blueprint $table) {  
    $table->id();  
    $table->foreignId('user_id')->nullable()->constrained()->onDelete('cascade');  
    $table->string('action');  
    $table->string('entity_type');  
    $table->unsignedBigInteger('entity_id');  
    $table->timestamp('created_at')->useCurrent();  
});
```