

## Table of Contents

1. GREATEST and LEAST.....	1
1.1. Examples using the demo tables.....	2
2. IF.....	3

This discusses the following

Greatest ()

Least ()

If ()

## 1. GREATEST and LEAST

GREATEST and LEAST return the largest and smallest value from the list of arguments. Notice what happens with nulls. If there is a null in the list then the functions treat this as an unknown value and therefore the function cannot “know” which value in the list is the largest.

Warning: in the next unit we discuss the functions Max and Min in which sound very much like Greatest and Least. They are NOT the same. Greatest and Least. are row functions- they work on multiple columns in a single row of data. You can use them with literals.

Demo 01:

```
select A
, GREATEST (B,C,D,E,F)
, LEAST (B, C, D, E,F)
from a_testbed.z_numbers;
```

A	GREATEST (B,C,D,E,F)	LEAST (B, C, D, E,F)
1	90	10
2	NULL	NULL
3	NULL	NULL
4	NULL	NULL
5	0	0
6	10	10
7	210	-10
8	85	-210
9	200	-1
10	200	-1

Data type Issues: A function returns a single value. GREATEST (list), LEAST (list) returns the largest, smallest in the list. Avoid mixing incompatible data types.

Demo 02:

```
select
  greatest (4, 45.78, 9)
, least (4, 45.78, 9);
```

greatest (4, 45.78, 9)	least (4, 45.78, 9)
45.78	4.00

**Demo 03:** The string values are treated as numeric and evaluated to 0

```
select greatest( 'flea', 4, 45.78, 9, 'elephant');
+-----+
| greatest( 'flea', 4, 45.78, 9, 'elephant') |
+-----+
| 45.78 |
+-----+
1 row in set, 2 warnings (0.00 sec)
```

Warning (Code 1292): Truncated incorrect DOUBLE value: 'flea'

Warning (Code 1292): Truncated incorrect DOUBLE value: 'elephant'

MySQL's general approach is to treat type issues as something to be compensated for more than as an error. You need to develop the habit of checking for the warning messages.

**Demo 04:**

```
select least( 'flea', 4, 45.78, 9, 'elephant');
+-----+
| least( 'flea', 4, 45.78, 9, 'elephant') |
+-----+
| 0 |
+-----+
1 row in set, 2 warnings (0.00 sec)
```

Warning (Code 1292): Truncated incorrect DOUBLE value: 'flea'

Warning (Code 1292): Truncated incorrect DOUBLE value: 'elephant'

**Demo 05:** Data types matter; as numbers 25 is smaller than 125; as string '125' sorts before '25' and is considered least.

```
select least(25, 125) as Numbers, least('25', '125') as Strings;
+-----+-----+
| Numbers | Strings |
+-----+-----+
| 25 | 125 |
+-----+-----+
```

**1.1. Examples using the demo tables****Demo 06:** This query returns the largest of the two columns `quoted_price` and `prod_list_price`

```
select ord_id
, prod_id
, quoted_price
, prod_list_price
, GREATEST (quoted_price, prod_list_price) as HigherPrice
From a_oe.order_details
Join a_prd.products using (prod_id)
where prod_id in (1000, 1010);
+-----+-----+-----+-----+-----+
| ord_id | prod_id | quoted_price | prod_list_price | HigherPrice |
+-----+-----+-----+-----+-----+
| 115 | 1000 | 100.00 | 125.00 | 125.00 |
| 303 | 1000 | 125.00 | 125.00 | 125.00 |
| 313 | 1000 | 125.00 | 125.00 | 125.00 |
| 608 | 1000 | 100.00 | 125.00 | 125.00 |
| 3808 | 1000 | 100.00 | 125.00 | 125.00 |
| 105 | 1010 | 150.00 | 150.00 | 150.00 |
| 390 | 1010 | 175.00 | 150.00 | 175.00 |
```

395	1010	195.00	150.00	195.00
405	1010	150.00	150.00	150.00
528	1010	150.00	150.00	150.00
550	1010	175.00	150.00	175.00
551	1010	175.00	150.00	175.00
605	1010	125.00	150.00	150.00
609	1010	175.00	150.00	175.00
2120	1010	175.00	150.00	175.00
2121	1010	175.00	150.00	175.00
3808	1010	125.00	150.00	150.00

17 rows in set (0.01 sec)

**Demo 07:** The Greatest function just returns a number. You probably want to know which is bigger; that uses a Case. (In our tables these price columns are not null, but that is not true for all tables. So you always have to think about those nulls.)

```
select ord_id
, prod_id
, quoted_price as "quoted"
, prod_list_price as "List"
, GREATEST (quoted_price, prod_list_price) as "higher"
, case when quoted_price = prod_list_price then 'same price'
      when quoted_price > prod_list_price then 'quoted is higher'
      when quoted_price < prod_list_price then 'list is higher'
      else 'one or more is null'
      end "PriceComparison"
from a_oe.order_details
join a_prd.products using (prod_id)
where prod_id in (1000, 1010)
;
```

ord_id	prod_id	quoted	List	higher	PriceComparison
115	1000	100.00	125.00	125.00	list is higher
303	1000	125.00	125.00	125.00	same price
313	1000	125.00	125.00	125.00	same price
608	1000	100.00	125.00	125.00	list is higher
3808	1000	100.00	125.00	125.00	list is higher
105	1010	150.00	150.00	150.00	same price
390	1010	175.00	150.00	175.00	quoted is higher
395	1010	195.00	150.00	195.00	quoted is higher
405	1010	150.00	150.00	150.00	same price
528	1010	150.00	150.00	150.00	same price
550	1010	175.00	150.00	175.00	quoted is higher
551	1010	175.00	150.00	175.00	quoted is higher
605	1010	125.00	150.00	150.00	list is higher
609	1010	175.00	150.00	175.00	quoted is higher
2120	1010	175.00	150.00	175.00	quoted is higher
2121	1010	175.00	150.00	175.00	quoted is higher
3808	1010	125.00	150.00	150.00	list is higher

## 2. IF

The IF function takes three arguments; the first should be an expression that has a true/false value. If its value is true then the return value is the value of argument 2; if the value of the first expression is not true then the return value is the value of argument 3.

You can write this logic with a case to have more portable code and code that is easier to understand.

## Demo 08:

```

select if(curdate() > '1888-08-08', 'passed the test', 'this is really old');
+-----+
| if(curdate() > '1888-08-08', 'passed the test', 'this is really old') |
+-----+
| passed the test |
+-----+

```

```

select if(month(curdate()) in (6,7,8), 'Summer!', 'Not summer');
+-----+
| if(month(curdate()) in (6,7,8), 'Summer!', 'Not summer') |
+-----+
| Not Summer |
+-----+

```

```

select if( 5 > null, 'passed the test', 'nulls make unknown values');
+-----+
| if(5 > null, 'passed the test', 'nulls make unknown values') |
+-----+
| nulls make unknown values |
+-----+

```

Using case

```

select case when month(curdate()) in (6,7,8) then 'Summer!'
           else 'Not summer'
           end as Message;

```

Demo 09: We want to give customers a 5% savings for each pet supply item or sporting goods item. As a first step we will determine the percent to apply to the price.

```

select catg_id, prod_id, prod_list_price
, if(catg_id IN('PET','SPG'), 0.95, 1) as "Price Multiplier"
from a_prd.products products
order by prod_id;

```

Selected rows

catg_id	prod_id	prod_list_price	Price Multiplier
HW	1000	125.00	1
SPG	1010	150.00	0.95
SPG	1050	269.95	0.95
SPG	1060	255.95	0.95
APL	1125	500.00	1
APL	1130	149.99	1
PET	1140	14.99	0.95
PET	4577	29.95	0.95

Demo 10: The if test could be nested for another test. Suppose that APL were to get a 10% discount.

```

select catg_id, prod_id, prod_list_price
, if(catg_id IN('PET','SPG'), 0.95, if(catg_id IN('APL'), 0.90, 1)
) as "Price Multiplier"
from a_prd.products products
order by prod_id;

```

Selected rows

catg_id	prod_id	prod_list_price	Price Multiplier
HW	1000	125.00	1

	SPG		1010		150.00		0.95	
	SPG		1050		269.95		0.95	
	SPG		1060		255.95		0.95	
	APL		1125		500.00		0.90	
	APL		1130		149.99		0.90	
	PET		1140		14.99		0.95	
	PET		4577		29.95		0.95	
+-----+-----+-----+-----+								

Nesting IF tests like this quickly becomes hard to read and is error prone. For anything other than a simple single test, use a case expression. Also case expressions are standard SQL supported by most dbms; the If function is not widely supported.