

Package ‘SNPtools’

July 11, 2025

Title S4 Tools for Reading and Organizing Genetic Data

Version 0.1.0

Maintainer Vinícius Junqueira <junqueiravinicius@hotmail.com>

Description SNPtools provides an integrated suite of tools for handling SNP genotype data in large-scale genetic studies. The package supports importing and merging genotype files, performing quality control on SNP markers and samples, and preparing data for downstream analyses using popular software such as FImpute and PLINK. It offers S4 classes and methods to efficiently encapsulate SNP data, along with utilities for generating genotype summary statistics and visualization. Additional functionalities in the current version include anticlustering approaches for batch effect control, automated script generation for external software, and streamlined workflows for large datasets commonly encountered in animal and plant breeding programs. The package is designed to facilitate reproducible and scalable SNP data analyses in quantitative and statistical genetics.

Depends R (>= 4.1.0),
snpStats,
tidyverse,
dplyr

Imports methods,
data.table,
Rcpp,
stringi

LinkingTo Rcpp

Suggests knitr,
rmarkdown

VignetteBuilder knitr

Encoding UTF-8

License GPL-3

URL <https://viniciusjunqueira.github.io/SNPtools>

BugReports <https://github.com/viniciusjunqueira/SNPtools/issues>

RoxygenNote 7.3.2

Contents

cbind_SnpMatrix	3
check.call.rate	3
check.ibs	4
check.identical.samples	4
check.identical.samples.by.block	5
check.mendelian.inconsistencies	6
check.mendelian.inconsistencies.pair	6
check.sample.call.rate	7
check.sample.heterozygosity	7
check.snp.chromo	8
check.snp.hwe	9
check.snp.maf	9
check.snp.mgf	10
check.snp.monomorf	10
check.snp.no.position	11
check.snp.same.position	11
combinarSNPData	12
do.pca	13
exploratory.plots	13
FImputeRunner	14
genoToDF	15
get.correl.fc	16
get.gender	16
get.hwe.chi2	17
getGeno	17
ibs.pair	18
importAllGenos	19
importFImputeResults	19
import_geno_list	20
pairs2sets	20
plotPCAgroups	21
qcSamples	22
qcSNPs	23
qc_header	24
rbindSnpFlexible	25
rbind_SnpMatrix	25
read.fimpute	26
runAnticlusteringPCA	27
runFImpute	27
saveFImpute	28
saveFImputeRaw	29
savePlink	29
Subset	30
summary,SNPDataLong-method	31

Index

32

cbind_SnpMatrix	<i>Safe cbind for SnpMatrix preserving dimnames</i>
-----------------	---

Description

This function performs a column-wise binding of multiple `SnpMatrix` objects, explicitly preserving row names and column names, avoiding unexpected "object has no names" warnings.

Usage

```
cbind_SnpMatrix(...)
```

Arguments

... `SnpMatrix` objects to combine (must have identical row names).

Value

A single combined `SnpMatrix` with preserved row and column names.

Examples

```
## Not run:  
cbind_SnpMatrix(matrix1, matrix2)  
  
## End(Not run)
```

check.call.rate	<i>Check SNP call rate</i>
-----------------	----------------------------

Description

Identifies SNPs with call rates below a minimum threshold.

Usage

```
check.call.rate(summary, min.call.rate)
```

Arguments

summary A data frame with SNP summary statistics (must contain 'Call.rate' column).
min.call.rate Numeric value specifying the minimum acceptable call rate.

Value

Character vector with SNP names below threshold. Returns 'NULL' if none.

Author(s)

Roberto Higa, adapted by Vinícius

Examples

```
df <- data.frame(Call.rate = c(0.85, 0.95), row.names = c("SNP1", "SNP2"))
check.call.rate(df, 0.9)
```

check.ibs

Check Identity-By-State (IBS) for a genotype pair

Description

Checks IBS status for two genotypes.

Usage

```
check.ibs(gen)
```

Arguments

gen Numeric vector of length two with genotype codes.

Value

Integer: 2 if identical non-heterozygotes, 0 if opposite homozygotes, -1 otherwise.

Examples

```
check.ibs(c(1, 1))
check.ibs(c(1, 3))
```

check.identical.samples

Check identical samples based on distance

Description

Identifies sample pairs considered identical based on genotype distances.

Usage

```
check.identical.samples(genotypes, threshold = 0)
```

Arguments

genotypes	Genotype matrix (samples x SNPs).
threshold	Numeric distance threshold. Default 0.

Value

List of identical sample pairs.

Examples

```
mat <- matrix(sample(0:2, 20, TRUE), nrow = 5)
rownames(mat) <- paste0("S", 1:5)
check.identical.samples(mat, 0.5)
```

check.identical.samples.by.block
Check identical samples by block

Description

Identifies identical samples within SNP blocks.

Usage

```
check.identical.samples.by.block(genotypes, blcsize, threshold = 0)
```

Arguments

genotypes	Genotype matrix.
blcsize	Block size (number of SNPs).
threshold	Distance threshold. Default 0.

Value

List of identical sample pairs.

Examples

```
# See check.identical.samples example
```

`check.mendelian.inconsistencies`*Check Mendelian inconsistencies*

Description

Identifies Mendelian inconsistencies between father-child pairs.

Usage

```
check.mendelian.inconsistencies(genotypes, father, child)
```

Arguments

genotypes	Genotype matrix.
father	Vector of father sample IDs.
child	Vector of child sample IDs.

Value

Data frame summarizing inconsistencies per pair.

Examples

```
# Requires proper parent-child genotype data
```

`check.mendelian.inconsistencies.pair`*Check Mendelian inconsistencies for a pair*

Description

Calculates number of inconsistencies and total comparable SNPs for a parent-child pair.

Usage

```
check.mendelian.inconsistencies.pair(g1, g2)
```

Arguments

g1	Genotype vector for parent.
g2	Genotype vector for child.

Value

Numeric vector: [# inconsistencies, # comparable SNPs].

Examples

```
# Used internally by check.mendelian.inconsistencies
```

```
check.sample.call.rate
```

Check Sample Call Rate

Description

Identifies samples with call rate below a given threshold.

Usage

```
check.sample.call.rate(sample.summary, min.call.rate)
```

Arguments

`sample.summary` A data frame with a "Call.rate" column for each sample.

`min.call.rate` Minimum acceptable call rate (between 0 and 1).

Value

A character vector with the names of samples to remove.

```
check.sample.heterozygosity
```

Check sample heterozygosity

Description

Identifies samples with heterozygosity values deviating beyond a specified threshold.

Usage

```
check.sample.heterozygosity(sample.summary, max.dev)
```

Arguments

`sample.summary` Data frame containing sample summary (must have 'Heterozygosity' column).

`max.dev` Maximum number of standard deviations allowed from mean.

Value

Character vector with sample names considered outliers. Returns ‘NULL’ if none.

Examples

```
ss <- data.frame(Heterozygosity = c(0.2, 0.5, 0.7))
rownames(ss) <- c("Ind1", "Ind2", "Ind3")
check.sample.heterozygosity(ss, 1)
```

check.snp.chromo	<i>Check SNP by chromosome</i>
------------------	--------------------------------

Description

Filters SNP names belonging to specified chromosomes.

Usage

```
check.snp.chromo(snpmap, chromosomes)
```

Arguments

- snpmap Data frame with SNP map info (must contain columns ‘Chromosome’ and ‘Name’).
- chromosomes Vector of chromosome identifiers to filter.

Value

Character vector with SNP names.

Examples

```
snpmap <- data.frame(Chromosome = c(1, 1, 2), Name = c("SNP1", "SNP2", "SNP3"))
check.snp.chromo(snpmap, 1)
```

check.snp.hwe	<i>Check SNP Hardy-Weinberg equilibrium deviation</i>
---------------	---

Description

Identifies SNPs deviating from HWE beyond a z-score threshold.

Usage

```
check.snp.hwe(snp.summary, max.dev)
```

Arguments

snp.summary	Data frame with SNP summary (must contain 'z.HWE' column).
max.dev	Maximum z-score allowed.

Value

Character vector with SNP names deviating from HWE. Returns 'NULL' if none.

Examples

```
df <- data.frame(z.HWE = c(2, 5), row.names = c("SNP1", "SNP2"))
check.snp.hwe(df, 3)
```

check.snp.maf	<i>Check SNP minor allele frequency</i>
---------------	---

Description

Identifies SNPs with minor allele frequency below a minimum threshold.

Usage

```
check.snp.maf(snp.summary, min.maf)
```

Arguments

snp.summary	Data frame with SNP summary (must contain 'MAF' column).
min.maf	Minimum MAF allowed.

Value

Character vector with SNP names below threshold. Returns 'NULL' if none.

Examples

```
df <- data.frame(MAF = c(0.01, 0.2), row.names = c("SNP1", "SNP2"))
check.snp.maf(df, 0.05)
```

check.snp.mgf	<i>Check SNP missing genotype frequencies</i>
---------------	---

Description

Identifies SNPs with genotype frequencies below a minimum threshold.

Usage

```
check.snp.mgf(snp.summary, min.mgf)
```

Arguments

snp.summary	Data frame with columns 'P.AA', 'P.AB', 'P.BB'.
min.mgf	Minimum genotype frequency allowed.

Value

Character vector with SNP names below threshold. Returns 'NULL' if none.

Examples

```
df <- data.frame(P.AA = c(0.01, 0.5), P.AB = c(0.02, 0.4), P.BB = c(0.01, 0.1))
rownames(df) <- c("SNP1", "SNP2")
check.snp.mgf(df, 0.05)
```

check.snp.monomorf	<i>Check SNP monomorphic status</i>
--------------------	-------------------------------------

Description

Identifies SNPs considered monomorphic.

Usage

```
check.snp.monomorf(snp.summary)
```

Arguments

snp.summary	Data frame with columns 'P.AA', 'P.AB', 'P.BB'.
-------------	---

Value

Character vector with monomorphic SNP names. Returns 'NULL' if none.

Examples

```
df <- data.frame(P.AA = c(1, 0.5), P.AB = c(0, 0.5), P.BB = c(0, 0))
rownames(df) <- c("SNP1", "SNP2")
check.snp.monomorf(df)
```

check.snp.no.position *Check SNP no position*

Description

Identifies SNPs with position equal to zero in the SNP map.

Usage

```
check.snp.no.position(snpmap)
```

Arguments

snpmap Data frame with columns 'Position' and 'Name'.

Value

Character vector with SNP names without position. Returns 'NULL' if none.

Examples

```
df <- data.frame(Position = c(0, 100), Name = c("SNP1", "SNP2"))
check.snp.no.position(df)
```

check.snp.same.position *Check SNPs mapped to the same position*

Description

Identifies groups of SNPs that are mapped to the exact same genomic position on each chromosome. Returns a list where each element corresponds to one group of overlapping SNPs.

Identifies SNPs that share the same position on the same chromosome.

Usage

```
check.snp.same.position(snpmap)
```

```
check.snp.same.position(snpmap)
```

Arguments

snpmap Data frame with columns 'Chromosome', 'Position', and 'Name'.

Value

A list of character vectors, each with names of SNPs found at the same position.

List of SNP groups sharing positions.

Examples

```
df <- data.frame(Chromosome = c(1, 1, 2), Position = c(100, 100, 200), Name = c("SNP1", "SNP2", "SNP3"))
check.snp.same.position(df)
```

combinarSNPData

Combine multiple SNPDataLong objects

Description

This function merges a list of SNPDataLong objects, typically representing different SNP panels or datasets, into a single unified SNPDataLong object. It ensures that all genotype matrices have the same set of SNPs (filling missing SNPs with NA), and merges the marker map information while removing duplicate SNP entries.

Usage

```
combinarSNPData(lista)
```

Arguments

lista A list of SNPDataLong objects to be combined.

Value

A single SNPDataLong object containing the combined genotype matrix, merged map, and a concatenated path string.

Examples

```
## Not run:
combined <- combinarSNPData(list(snp_obj1, snp_obj2, snp_obj3))

## End(Not run)
```

do.pca

*Do genome relationship matrix PCA***Description**

Performs PCA using the genome relationship matrix (GRM).

Usage

```
## S3 method for class 'pca'
do(genotypes)
```

Arguments

genotypes Genotype matrix.

Value

List containing ‘pcs’ (principal components) and ‘eigen’ (eigenvalues).

Examples

```
# Requires matrix of numeric genotypes
```

exploratory.plots

*Exploratory plots for SNP and sample summary***Description**

Generates exploratory plots: MAF histograms, HWE plots, heterozygosity scatter, MDS, and dendrogram.

Usage

```
exploratory.plots(
  snp.summary,
  snps.plot,
  sample.summary,
  samples.plot,
  distm,
  glabels,
  mds.plot,
  hierq.plot
)
```

Arguments

snp.summary	Data frame with SNP summary.
snps.plot	Filename for SNP histogram plot.
sample.summary	Data frame with sample summary.
samples.plot	Filename for heterozygosity plot.
distm	Distance matrix for samples.
glabels	Sample labels for plots.
mds.plot	Filename for MDS plot.
hierq.plot	Filename for hierarchical cluster plot.

Value

None. Plots are saved as JPEG files.

Examples

```
# Requires proper SNP and sample summary data frames
```

FImputeRunner

Build FImputeRunner object

Description

A convenience function to construct a ‘FImputeRunner’ object from basic inputs.

Usage

```
FImputeRunner(object, path, exec_path = "FImpute3", name = "data")
```

Arguments

path	A character string indicating the directory to save FImpute files.
exec_path	Path to the FImpute executable (default = "FImpute3").
name	Name for the dataset (used internally, default = "gen_data").
geno	A SnpMatrix object.
map	A data.frame with SNP metadata (columns: Name, Chromosome, Position).

Value

An object of class 'FImputeRunner'.

genoToDF	<i>Convert geno slot from SNPDataLong to a data.frame</i>
----------	---

Description

Converts the genotype matrix (geno slot) of a SNPDataLong object to a data.frame, with optional centering and scaling per SNP (column).

Usage

```
genoToDF(object, center = FALSE, scale = FALSE)
```

Arguments

object	An object of class SNPDataLong.
center	Logical or numeric. If TRUE (default FALSE), center columns to mean zero.
scale	Logical or numeric. If TRUE (default FALSE), scale columns to standard deviation one.

Value

A data.frame with individuals as rows and SNPs as columns (numeric 0/1/2, or centered/scaled values).

Examples

```
## Not run:
df <- genoToDF(nelore_imputed, center = TRUE, scale = TRUE)
head(df[, 1:5])

## End(Not run)
```

get.correl.fc	<i>Get correlation (fc method)</i>
---------------	------------------------------------

Description

Calculates genotype correlation using a fast check (fc) method.

Usage

```
get.correl.fc(g1, g2)
```

Arguments

g1	Genotype vector.
g2	Genotype vector.

Value

Numeric value of correlation.

Examples

```
g1 <- sample(0:2, 10, TRUE)
g2 <- sample(0:2, 10, TRUE)
get.correl.fc(g1, g2)
```

get.gender	<i>Get gender based on heterozygosity</i>
------------	---

Description

Infers gender using heterozygosity thresholds.

Usage

```
get.gender(sample.summary, threshM, threshF)
```

Arguments

sample.summary	Data frame with 'Heterozygosity' column.
threshM	Numeric threshold for males.
threshF	Numeric threshold for females.

Value

Data frame with columns 'heterozygosity' and 'sex'.

Examples

```
df <- data.frame(Heterozygosity = c(0.1, 0.3, 0.6))
rownames(df) <- c("A", "B", "C")
get.gender(df, 0.2, 0.5)
```

get.hwe.chi2	<i>Get HWE chi-square p-values</i>
--------------	------------------------------------

Description

Calculates Hardy-Weinberg equilibrium chi-square p-values for SNPs.

Usage

```
get.hwe.chi2(snp.summary)
```

Arguments

snp.summary Data frame with columns 'Calls', 'P.AA', 'P.AB', 'P.BB'.

Value

Numeric vector with p-values.

Examples

```
df <- data.frame(Calls = c(100, 100), P.AA = c(0.6, 0.4), P.AB = c(0.3, 0.4), P.BB = c(0.1, 0.2))
get.hwe.chi2(df)
```

getGeno	<i>Flexible and efficient genotype file reading with autodetection using fread</i>
---------	--

Description

This generic and method allow flexible import of SNP genotype data from Illumina FinalReport files, supporting fast initial column detection using `data.table::fread`, followed by full genotype matrix construction via `snpStats::read.snps.long`.

Usage

```
getGeno(...)
```

Arguments

path	Path to the directory containing FinalReport.txt
fields	A list specifying column indices for sample, SNP, allele1, allele2, and confidence
codes	A character vector with allele codes (e.g., c("A", "B"))
threshold	Confidence threshold for genotype calling
sep	Field separator used in the files
skip	Number of lines to skip at the start of the file
verbose	Logical; if TRUE, displays progress messages
every	Frequency of progress update (number of SNPs)

Value

An SNPDataLong object containing the genotype matrix and map, or NULL if an error occurs

ibs.pair	<i>IBS pair statistics</i>
----------	----------------------------

Description

Calculates IBS mean and standard deviation between two samples.

Usage

```
ibs.pair(g1, g2)
```

Arguments

g1	Genotype vector for first sample.
g2	Genotype vector for second sample.

Value

Numeric vector: [mean IBS, standard deviation].

Examples

```
g1 <- sample(0:2, 10, TRUE)
g2 <- sample(0:2, 10, TRUE)
ibs.pair(g1, g2)
```

importAllGenos	<i>Import and combine multiple genotype configurations</i>
----------------	--

Description

This generic method imports genotype data from multiple configurations defined in an `SNPImportList` object, then combines them into a single unified `SNPDataLong` object.

Usage

```
importAllGenos(object)
```

Arguments

object	An object of class <code>SNPImportList</code> containing import configurations
--------	--

Value

A single combined `SNPDataLong` object

importFImputeResults	<i>Import imputed FImpute results from disk</i>
----------------------	---

Description

Reads existing imputed results from a given path and returns an object of class `SNPDataLong`.

Usage

```
importFImputeResults(path, method = "R")
```

Arguments

path	Character. Path to the folder containing 'output_fimpute' (e.g., "fimpute_run_nelore").
method	Character. "R" (default) or "Rcpp". Passed to <code>read.fimpute()</code> .

Value

An object of class `SNPDataLong` containing the imputed genotypes and SNP map.

import_geno_list	<i>Import multiple genotype datasets from a list of configurations</i>
------------------	--

Description

Reads and imports multiple genotype datasets specified in a list of configurations. Each configuration must include the path to the genotype data and information on field mapping. Optionally, you can also specify codes, quality threshold, separator, lines to skip, and a subset of IDs to retain. The function automatically fills the 'xref_path' slot per individual and combines maps into a single data.frame, adding a 'SourcePath' column indicating their origin and removing duplicated SNP rows (by Name). Prints progress messages indicating the current path being loaded (with counter).

Usage

```
import_geno_list(config_list)
```

Arguments

config_list	A list of configuration lists. Each element should contain: - 'path' (character): Path to the genotype file or folder. - 'fields' (list): Named list defining the columns (e.g., SNP ID, sample ID, alleles, confidence). - 'codes' (character vector, optional): Allele codes (default is c("A", "B")). - 'threshold' (numeric, optional): Maximum allowed missingness or confidence threshold (default 0.15). - 'sep' (character, optional): Field separator in the input file (default "tab-delimited"). - 'skip' (integer, optional): Number of lines to skip at the beginning of the file (default 0). - 'verbose' (logical, optional): Whether to print detailed messages (default TRUE). - 'subset' (character vector, optional): Vector of sample IDs to retain after import.
-------------	---

Value

An object of class 'SNPDataLong' containing: - Combined genotype matrix ('geno'). - Combined map ('map') as a single data.frame with 'SourcePath' column and without duplicated rows. - Combined 'xref_path' vector (one entry per individual). - 'path' slot as a semicolon-separated string of all input dataset paths.

pairs2sets	<i>Convert pairs to sets</i>
------------	------------------------------

Description

Groups sample pairs into sets of related samples.

Usage

```
pairs2sets(pairs)
```

Arguments

`pairs` Matrix or list of sample pairs.

Value

List of sets of samples.

Examples

```
pairs <- matrix(c("A", "B", "B", "C", "D", "E"), ncol = 2, byrow = TRUE)
pairs2sets(pairs)
```

plotPCAgroups	<i>Plot PCA groups from anticlustering result</i>
---------------	---

Description

Plot PCA groups from anticlustering result

Usage

```
plotPCAgroups(pca_res, groups, pcs = c(1, 2), filename = NULL)
```

Arguments

`pca_res` A prcomp object.

`groups` A factor or vector of group assignments.

`pcs` Vector of length 2 indicating which PCs to plot (default: c(1, 2)).

`filename` Optional. If provided, saves plot to this file (e.g., "antic.png").

Value

A ggplot object (also prints to screen).

Examples

```
## Not run:
res <- runAnticlusteringPCA(nelore_imputed, K = 2, n_pcs = 20)
plotPCAgroups(res$pca, res$groups)

## End(Not run)
```

qcSamples	<i>Quality control on samples</i>
-----------	-----------------------------------

Description

Applies quality control (QC) procedures to samples in a ‘SNPDataLong’ object, based on heterozygosity and call rate thresholds.

Usage

```
qcSamples(x, ...)

## S4 method for signature 'SNPDataLong'
qcSamples(
  x,
  heterozygosity = NULL,
  smp_cr = NULL,
  action = c("report", "filter", "both")
)
```

Arguments

x	An object of class ‘SNPDataLong’.
heterozygosity	A numeric threshold or range for heterozygosity. Samples outside this threshold are removed.
smp_cr	Minimum acceptable sample call rate (between 0 and 1). Samples below this value are removed.
action	Character string indicating the action to perform. One of: - “report”: only returns a list of samples to remove and those kept; - “filter”: returns a filtered object without reporting; - “both”: performs filtering and returns the filtered object.

Value

Depending on the ‘action’ argument: - “report”: returns a list with removed and kept samples; - “filter”: returns a new ‘SNPDataLong’ object with filtered genotypes; - “both”: returns a list with: - ‘filtered’: the filtered ‘SNPDataLong’ object; - ‘report’: a list of removed and kept samples.

Description

Applies flexible quality control filters on an object of class `SNPDataLong`. Supports call rate filtering, minor allele frequency (MAF), Hardy-Weinberg equilibrium (HWE), removal of monomorphic SNPs, exclusion of specific chromosomes, optionally removing SNPs without positions, and optionally removing SNPs at the same genomic position (keeping the one with highest MAF).

Usage

```
qcSNPs(x, ...)
```

Arguments

<code>x</code>	An object of class <code>SNPDataLong</code> .
<code>missing_ind</code>	Maximum allowed proportion of missing data per individual (currently not implemented).
<code>missing_snp</code>	Maximum allowed proportion of missing data per SNP (currently not implemented).
<code>min_snp_cr</code>	Minimum acceptable call rate for SNPs (e.g., 0.95). SNPs below this threshold are removed.
<code>min_maf</code>	Minimum minor allele frequency allowed for SNPs (e.g., 0.05). SNPs with lower MAF are removed.
<code>hwe</code>	p-value threshold for Hardy-Weinberg equilibrium test (e.g., 1e-6). SNPs violating this are removed.
<code>snp_position</code>	Logical. If TRUE, removes SNPs mapped to the same position, retaining only the one with highest MAF.
<code>no_position</code>	Logical. If TRUE, removes SNPs without defined genomic positions.
<code>snp_mono</code>	Logical. If TRUE, removes monomorphic SNPs (with no variation).
<code>remove_chr</code>	Character vector of chromosomes to exclude (e.g., <code>c("X", "Y")</code>).
<code>action</code>	One of "report" (returns a list of removed SNPs), "filter" (returns filtered <code>SNPDataLong</code>), or "both" (returns both).

Value

Depending on the action argument: - "report": list of SNPs removed by each filter and SNPs retained. - "filter": filtered `SNPDataLong` object. - "both": list containing the filtered object and detailed report.

Examples

```
## Not run:
set.seed(123)
mat <- matrix(sample(c(0, 1, 2, NA), 100, replace = TRUE, prob = c(0.4, 0.4, 0.15, 0.05)),
              nrow = 10, ncol = 10)
colnames(mat) <- paste0("snp", 1:10)
rownames(mat) <- paste0("ind", 1:10)
map <- data.frame(Name = colnames(mat), Chromosome = 1, Position = 1:10)
x <- new("SNPDataLong", geno = mat, map = map, path = "dummy_path", xref_path = rep("chip1", 10))

# Example using multiple filters
qcSNPs(x, min_snp_cr = 0.8, min_maf = 0.05, snp_mono = TRUE, no_position = TRUE, snp_position = TRUE, action = "filter")

## End(Not run)
```

qc_header

Formatted header message

Description

Prints a formatted message with a border for section titles in the console.

Usage

```
qc_header(title)
```

Arguments

title Character string to be printed inside the header box.

Value

No return value. Used for side effects (message).

Examples

```
qc_header("Quality Control on Samples")
```

rbindSnpFlexible	<i>Faster row-bind for SnpMatrix objects with differing columns</i>
------------------	---

Description

Combines multiple SnpMatrix objects by rows, automatically handling differing SNP columns, optimized for large matrices.

Usage

```
rbindSnpFlexible(...)
```

Arguments

... One or more SnpMatrix objects.

Value

A single SnpMatrix object with all rows combined.

Examples

```
## Not run:  
combined <- rbindSnpFlexible(brangus_geno, batch_BM@geno)  
  
## End(Not run)
```

rbind_SnpMatrix	<i>Safe rbind for SnpMatrix preserving dimnames</i>
-----------------	---

Description

This function performs a row-wise binding of multiple SnpMatrix objects, explicitly preserving row names and column names, avoiding unexpected "object has no names" warnings.

Usage

```
rbind_SnpMatrix(...)
```

Arguments

... SnpMatrix objects to combine (must have identical column names).

Value

A single combined SnpMatrix with preserved row and column names.

Examples

```
## Not run:
rbind_SnpMatrix(matrix1, matrix2)

## End(Not run)
```

read.fimpute	<i>Read imputed genotypes from FImpute output and return SNPData-Long object</i>
--------------	--

Description

Reads imputed genotypes and SNP information from FImpute output, builds a SnpMatrix and a corresponding map, and returns an SNPDataLong object.

Usage

```
read.fimpute(file, method = c("R", "Rcpp"))
```

Arguments

file	Character. Path to the FImpute output directory (usually "output_fimpute").
method	Character. "R" (default) for vectorized R implementation, or "Rcpp" for compiled C++ implementation.

Value

An object of class SNPDataLong containing the imputed genotypes and SNP map.

Examples

```
## Not run:
snp_long <- read.fimpute("output_fimpute", method = "R")

## End(Not run)
```

runAnticlusteringPCA *Run PCA and Anticlustering on SNPDataLong*

Description

Converts a SNPDataLong object to a data.frame, runs PCA, and performs anticlustering grouping.

Usage

```
runAnticlusteringPCA(object, K = 2, n_pcs = 20, center = TRUE, scale = TRUE)
```

Arguments

object	An object of class SNPDataLong.
K	Number of groups for anticlustering.
n_pcs	Number of top principal components to use (default: 20).
center	Logical or numeric. Center columns before PCA (default: TRUE).
scale	Logical or numeric. Scale columns before PCA (default: TRUE).

Value

A list with: - groups: vector with group assignments. - pca: the PCA result object (prcomp). - pcs: matrix of top PCs used in anticlustering.

Examples

```
## Not run:
res <- runAnticlusteringPCA(nelore_imputed, K = 2, n_pcs = 20)
table(res$groups)

## End(Not run)
```

runFImpute *Run FImpute from a FImputeRunner object*

Description

This function runs the external FImpute software using a 'FImputeRunner' object, ensuring that all required input files are present and the results are imported.

Usage

```
runFImpute(object, verbose = TRUE)

## S4 method for signature 'FImputeRunner'
runFImpute(object, verbose = TRUE)
```

Arguments

object An object of class 'FImputeRunner'.

verbose Logical. If TRUE (default), FImpute output will be printed to the console.

Value

An updated 'FImputeRunner' object with the 'results' slot populated (SnpMatrix).

Examples

```
## Not run:
# Example: Running FImpute from a FImputeRunner object

path_fimpute <- "fimpute_run_example"
param_file <- file.path(path_fimpute, "fimpute.par")
fimpute_exec <- "FImpute3" # assuming it is in PATH

export_obj <- new("FImputeExport",
                  geno = geno_obj@geno,
                  map = geno_obj@map,
                  path = path_fimpute)

runner <- new("FImputeRunner",
              export = export_obj,
              par_file = param_file,
              exec_path = fimpute_exec)

runner <- runFImpute(runner, verbose = TRUE)
head(runner@results)

## End(Not run)
```

saveFImpute	<i>Save genotype and map files in FImpute format</i>
-------------	--

Description

S4 method to export genotype (.gen), map (.map), and parameter (fimpute.par) files compatible with [FImpute](<https://www.aps.uoguelph.ca/~msargol/fimpute/>).

Usage

```
saveFImpute(object, ...)
```

S4 method for signature 'FImputeExport'

```
saveFImpute(object)
```

S4 method for signature 'SNPDataLong'

```
saveFImpute(object, path = NULL)
```

Arguments

object	An object of class 'FImputeExport' or 'SNPDataLong'.
...	Additional arguments passed to methods.
path	Output directory (default: "fimpute_run" for SNPDataLong).

Value

No return value. Files are saved to disk.

saveFImputeRaw	<i>Export genotypes and map using basic arguments</i>
----------------	---

Description

Convenience function to export FImpute files directly from a 'SnpMatrix' and map 'data.frame'.

Usage

```
saveFImputeRaw(geno, map, path, xref = NULL)
```

Arguments

geno	A 'SnpMatrix' object.
map	A data.frame with columns 'Name', 'Chromosome', 'Position', and 'SourcePath'.
path	Output directory.
xref	Optional vector of identifiers per individual (used to assign numeric chip IDs).

savePlink	<i>Save SNPDataLong object to PLINK format</i>
-----------	--

Description

Saves genotype and map data from an SNPDataLong object in PLINK format (.ped/.map and optionally binary files).

Usage

```
savePlink(
  object,
  path = "plink_out",
  name = "plink_data",
  run_plink = TRUE,
  chunk_size = 1000
)
```

Arguments

object	An object of class <code>SNPDataLong</code> .
path	Character. Directory where files will be saved.
name	Character. Base name for PLINK output files.
run_plink	Logical. If TRUE (default), runs PLINK1 to convert to binary files. If FALSE, only .ped and .map files are saved.
chunk_size	Integer. Number of individuals per chunk for writing .ped file (default: 1000).

Value

No return value. Files are saved to disk.

Examples

```
## Not run:
savePlink(genotypes_qc, path = "plink_out", name = "nelore_qc", run_plink = TRUE, chunk_size = 2000)

## End(Not run)
```

Subset

Subset method for SNPDataLong

Description

Subset method for `SNPDataLong`

Usage

```
Subset(object, index, margin = 1, keep = TRUE)
```

Arguments

object	A <code>SNPDataLong</code> object.
index	Character vector with row (individual) or column (SNP) names to filter.
margin	Integer: 1 = rows (individuals), 2 = columns (SNPs).
keep	Logical: TRUE to keep specified levels, FALSE to discard them.

Value

A new `SNPDataLong` object, subsetting accordingly.

`summary,SNPDataLong-method`*Summary for SNPDataLong objects*

Description

Provides a detailed summary of an SNPDataLong object, including sample and SNP counts, proportion of missing data, and SNP distribution by chromosome if mapping information is available.

Usage

```
## S4 method for signature 'SNPDataLong'  
summary(object, ...)
```

Arguments

`object` An object of class SNPDataLong.

Value

Prints a summary to the console. Returns NULL (invisible).

Index

`cbind_SnpMatrix`, [3](#)
`check.call.rate`, [3](#)
`check.ibs`, [4](#)
`check.identical.samples`, [4](#)
`check.identical.samples.by.block`, [5](#)
`check.mendelian.inconsistencies`, [6](#)
`check.mendelian.inconsistencies.pair`,
 [6](#)
`check.sample.call.rate`, [7](#)
`check.sample.heterozygosity`, [7](#)
`check.snp.chromo`, [8](#)
`check.snp.hwe`, [9](#)
`check.snp.maf`, [9](#)
`check.snp.mgf`, [10](#)
`check.snp.monorf`, [10](#)
`check.snp.no.position`, [11](#)
`check.snp.same.position`, [11](#)
`combinarSNPData`, [12](#)

`do.pca`, [13](#)

`exploratory.plots`, [13](#)

`FImputeRunner`, [14](#)

`genoToDF`, [15](#)
`get.correl.fc`, [16](#)
`get.gender`, [16](#)
`get.hwe.chi2`, [17](#)
`getGeno`, [17](#)

`ibs.pair`, [18](#)
`import_geno_list`, [20](#)
`importAllGenos`, [19](#)
`importFImputeResults`, [19](#)

`pairs2sets`, [20](#)
`plotPCAgroups`, [21](#)

`qc_header`, [24](#)
`qcSamples`, [22](#)

`qcSamples`, `SNPDataLong`-method
 (`qcSamples`), [22](#)
`qcSNPs`, [23](#)

`rbind_SnpMatrix`, [25](#)
`rbindSnpFlexible`, [25](#)
`read.fimpute`, [26](#)
`runAnticlusteringPCA`, [27](#)
`runFImpute`, [27](#)
`runFImpute`, `FImputeRunner`-method
 (`runFImpute`), [27](#)

`saveFImpute`, [28](#)
`saveFImpute`, `FImputeExport`-method
 (`saveFImpute`), [28](#)
`saveFImpute`, `SNPDataLong`-method
 (`saveFImpute`), [28](#)
`saveFImputeRaw`, [29](#)
`savePlink`, [29](#)
`Subset`, [30](#)
`summary`, `SNPDataLong`-method, [31](#)