

GUIA COMPLETO DJANGO REST FRAMEWORK 2025: APIS PROFISSIONAIS DO ZERO

Guia completo DRF 3.15 em 2025: serializers, viewsets, authentication, permissions, filtros, paginação, testes. Construa APIs REST profissionais com Django REST Framework do básico ao avançado.

Gere ebooks como este com



em <https://ebookr.ai>

Crie ebooks profissionais incríveis em minutos com IA



Chega de formatar texto no Google Docs, Word ou ferramentas que só te fazem perder tempo...

E deixe que nossa IA faça o trabalho pesado!



Capas gerados por IA



Infográficos feitos por IA



Edite em Markdown em Tempo Real



Adicione Banners Promocionais

TESTE AGORA

PRIMEIRO CAPÍTULO 100% GRÁTIS

Salve salve Pythonista!

Django REST Framework (DRF) é o padrão de facto para construir **APIs REST profissionais** com Python e Django.

Em 2025, com a versão **3.15+**, o DRF continua sendo a escolha número 1 para desenvolvedores que precisam criar APIs robustas, escaláveis e bem documentadas.

Este é o **guia definitivo de Django REST Framework**: um artigo pilar que cobre desde a configuração inicial até técnicas avançadas de autenticação, filtros, paginação, versionamento e testes.

Se você quer dominar a criação de APIs REST profissionais com Django, este guia é para você! 🚀

Vá Direto ao Assunto...

- Do not remove this line (it will not be displayed)
-

1. Por Que Usar Django REST Framework em 2025?

Vantagens do DRF

✅ **Serialização Poderosa** Converte tipos Python complexos (QuerySets, Models) para JSON/XML automaticamente

- ✓ **Autenticação Robusta** Token, Session, OAuth2, JWT nativamente suportados
- ✓ **Browsable API** Interface web automática para testar endpoints
- ✓ **Validação Integrada** Validação de dados com Serializers (similar ao Pydantic)
- ✓ **Documentação Automática** OpenAPI/Swagger integration out-of-the-box
- ✓ **Performance** ViewSets e QuerySets otimizados para alta performance

DRF vs Outras Opções

Critério	DRF	FastAPI	Flask-RESTful
Maturidade	✓ 10+ anos	⚠ 5 anos	✓ 8 anos
ORM Integrado	✓ Django ORM	✗ Depende SQLAlchemy	✗ Manual
Admin	✓ Django Admin	✗ Não	✗ Não
Async	⚠ Parcial	✓ Completo	✗ Não
Documentação	✓ Excelente	✓ Excelente	⚠ Média
Comunidade	✓ Muito grande	✓ Crescendo rápido	⚠ Média
Ideal para	Apps completas	Microserviços	APIs simples

2. Instalação e Configuração

Criar Ambiente Virtual

```
python -m venv venv  
source venv/bin/activate # Linux/Mac  
venv\Scripts\activate    # Windows
```

Instalar Django + DRF

```
pip install django==5.1 djangorestframework==3.15  
pip install markdown django-filter # Opcionais mas úteis
```

Criar Projeto Django

```
django-admin startproject myapi  
cd myapi  
python manage.py startapp products
```


Configurar settings.py


```
# myapi/settings.py


INSTALLED_APPS = [
    'django.contrib.admin',
    'django.contrib.auth',
    'django.contrib.contenttypes',
    'django.contrib.sessions',
    'django.contrib.messages',
    'django.contrib.staticfiles',

    # DRF
    'rest_framework',
    'django_filters',

    # Suas apps
    'products',
]

# Configurações DRF
REST_FRAMEWORK = {
    'DEFAULT_PERMISSION_CLASSES': [
        'rest_framework.permissions.IsAuthenticatedOrReadOnly',
    ],
    'DEFAULT_AUTHENTICATION_CLASSES': [
        'rest_framework.authentication.TokenAuthentication',
        'rest_framework.authentication.SessionAuthentication',
    ],
    'DEFAULT_PAGINATION_CLASS': 'rest_framework.pagination.PageNumberPagination',
    'PAGE_SIZE': 10,
    'DEFAULT_FILTER_BACKENDS': [
        'django_filters.rest_framework.DjangoFilterBackend',
        'rest_framework.filters.SearchFilter',
        'rest_framework.filters.OrderingFilter',
    ],
}
```

 **Leia mais:** [Configurando um Projeto DRF](#)



3. Models e Serializers

Criar Model

```

# products/models.py
from django.db import models
from django.contrib.auth.models import User

class Category(models.Model):
    name = models.CharField(max_length=100)
    slug = models.SlugField(unique=True)
    created_at = models.DateTimeField(auto_now_add=True)

    class Meta:
        verbose_name_plural = "Categories"

    def __str__(self):
        return self.name

class Product(models.Model):
    STATUS_CHOICES = [
        ('draft', 'Draft'),
        ('published', 'Published'),
        ('archived', 'Archived'),
    ]

    name = models.CharField(max_length=200)
    slug = models.SlugField(unique=True)
    description = models.TextField()
    price = models.DecimalField(max_digits=10, decimal_places=2)
    stock = models.PositiveIntegerField(default=0)
    category = models.ForeignKey(Category, on_delete=models.CASCADE,
        related_name='products')
    status = models.CharField(max_length=20, choices=STATUS_CHOICES,
        default='draft')
    created_by = models.ForeignKey(User, on_delete=models.CASCADE)
    created_at = models.DateTimeField(auto_now_add=True)
    updated_at = models.DateTimeField(auto_now=True)

    class Meta:
        ordering = ['-created_at']
        indexes = [
            models.Index(fields=['slug']),
            models.Index(fields=['status']),
        ]

```

```
def __str__(self):  
    return self.name
```

Serializers: Básico ao Avançado

Serializer Simples

```

# products/serializers.py
from rest_framework import serializers
from .models import Product, Category

class CategorySerializer(serializers.ModelSerializer):
    products_count = serializers.SerializerMethodField()

    class Meta:
        model = Category
        fields = ['id', 'name', 'slug', 'created_at', 'products_count']
        read_only_fields = ['id', 'created_at']

    def get_products_count(self, obj):
        return obj.products.count()

class ProductSerializer(serializers.ModelSerializer):
    category_name = serializers.CharField(source='category.name',
        read_only=True)
    created_by_username =
        serializers.CharField(source='created_by.username',
            read_only=True)

    class Meta:
        model = Product
        fields = [
            'id', 'name', 'slug', 'description', 'price', 'stock',
            'category', 'category_name', 'status',
            'created_by', 'created_by_username',
            'created_at', 'updated_at'
        ]
        read_only_fields = ['id', 'created_at', 'updated_at',
            'created_by']

    def validate_price(self, value):
        """Validação customizada"""
        if value <= 0:
            raise
            serializers.ValidationError("Preço deve ser maior que zero")
        if value > 999999.99:
            raise serializers.ValidationError("Preço muito alto")
        return value

```

```
def validate(self, data):
    """Validação de múltiplos campos"""
    if data.get('status') == 'published' and data.get('stock', 0) == 0:
        raise serializers.ValidationError(
            "Não é possível publicar produto sem estoque"
        )
    return data
```

Serializer Nested (Aninhado)

```
class ProductDetailSerializer(serializers.ModelSerializer):
    """Serializer com relacionamentos aninhados"""
    category = CategorySerializer(read_only=True)
    category_id = serializers.PrimaryKeyRelatedField(
        queryset=Category.objects.all(),
        source='category',
        write_only=True
    )

    class Meta:
        model = Product
        fields = '__all__'

    def to_representation(self, instance):
        """Customizar resposta JSON"""
        data = super().to_representation(instance)

        # Adicionar campo calculado
        data['in_stock'] = instance.stock > 0
        data['formatted_price'] = f"R$ {instance.price:.2f}"

        return data
```

 **Leia mais:** [Serializers no DRF](#)

4. Views e ViewSets

Function-Based Views (FBV)

```
# products/views.py
from rest_framework.decorators import api_view, permission_classes
from rest_framework.permissions import IsAuthenticated
from rest_framework.response import Response
from rest_framework import status

@api_view(['GET', 'POST'])
@permission_classes([IsAuthenticated])
def product_list(request):
    if request.method == 'GET':
        products = Product.objects.all()
        serializer = ProductSerializer(products, many=True)
        return Response(serializer.data)

    elif request.method == 'POST':
        serializer = ProductSerializer(data=request.data)
        if serializer.is_valid():
            serializer.save(created_by=request.user)
            return Response(serializer.data,
                            status=status.HTTP_201_CREATED)
        return Response(serializer.errors,
                        status=status.HTTP_400_BAD_REQUEST)
```


Class-Based Views (CBV)

```
from rest_framework.views import APIView
from rest_framework.response import Response
from rest_framework import status

class ProductListView(APIView):
    """API para listar e criar produtos"""

    def get(self, request):
        products = Product.objects.select_related('category').all()
        serializer = ProductSerializer(products, many=True)
        return Response(serializer.data)

    def post(self, request):
        serializer = ProductSerializer(data=request.data)
        if serializer.is_valid():
            serializer.save(created_by=request.user)
            return Response(serializer.data,
                            status=status.HTTP_201_CREATED)
        return Response(serializer.errors,
                        status=status.HTTP_400_BAD_REQUEST)
```

Generic Views

```
from rest_framework import generics

class ProductListCreateView(generics.ListCreateAPIView):
    queryset = Product.objects.select_related('category', 'created_by')
    serializer_class = ProductSerializer

    def perform_create(self, serializer):
        serializer.save(created_by=self.request.user)

class ProductDetailView(generics.RetrieveUpdateDestroyAPIView):
    queryset = Product.objects.all()
    serializer_class = ProductDetailSerializer
    lookup_field = 'slug'
```

ViewSet (Recomendado)

```

from rest_framework import viewsets
from rest_framework.decorators import action
from rest_framework.response import Response

class ProductViewSet(viewsets.ModelViewSet):
    """
    ViewSet completo para Product

    list: GET /products/
    create: POST /products/
    retrieve: GET /products/{id}/
    update: PUT /products/{id}/
    partial_update: PATCH /products/{id}/
    destroy: DELETE /products/{id}/
    """

    queryset = Product.objects.select_related('category', 'created_by')
    serializer_class = ProductSerializer
    lookup_field = 'slug'
    filterset_fields = ['status', 'category']
    search_fields = ['name', 'description']
    ordering_fields = ['price', 'created_at', 'stock']

    def get_serializer_class(self):
        """Usar serializer diferente para detail"""
        if self.action == 'retrieve':
            return ProductDetailSerializer
        return ProductSerializer

    def perform_create(self, serializer):
        serializer.save(created_by=self.request.user)

    @action(detail=True, methods=['post'])
    def publish(self, request, slug=None):
        """Custom action: /products/{slug}/publish/"""
        product = self.get_object()

        if product.stock == 0:
            return Response(
                {'error': 'Produto sem estoque'},
                status=status.HTTP_400_BAD_REQUEST
            )

```

```
product.status = 'published'
product.save()

serializer = self.get_serializer(product)
return Response(serializer.data)

@action(detail=False, methods=['get'])
def low_stock(self, request):
    """Custom action: /products/low_stock/"""
    products = self.queryset.filter(stock__lt=10,
    status='published')
    serializer = self.get_serializer(products, many=True)
    return Response(serializer.data)
```

5. URLs e Routers

URLs Manual

```
# products/urls.py
from django.urls import path
from . import views

urlpatterns = [
    path('products/', views.ProductListCreateView.as_view(),
    name='product-list'),
    path('products/<slug:slug>/', views.ProductDetailView.as_view(),
    name='product-detail'),
]
```

Routers (ViewSets)

```
# myapi/urls.py
from django.contrib import admin
from django.urls import path, include
from rest_framework.routers import DefaultRouter
from products.views import ProductViewSet, CategoryViewSet

# Router automático
router = DefaultRouter()
router.register(r'products', ProductViewSet, basename='product')
router.register(r'categories', CategoryViewSet, basename='category')

urlpatterns = [
    path('admin/', admin.site.urls),
    path('api/', include(router.urls)),
    path('api-auth/', include('rest_framework.urls')), # Login/Logout
]

# URLs geradas automaticamente:
# GET    /api/products/
# POST   /api/products/
# GET    /api/products/{slug}/
# PUT    /api/products/{slug}/
# PATCH  /api/products/{slug}/
# DELETE /api/products/{slug}/
# POST   /api/products/{slug}/publish/
# GET    /api/products/low_stock/
```

6. Autenticação e Permissões

Autenticação: Token

```
# settings.py
INSTALLED_APPS += ['rest_framework.authtoken']

REST_FRAMEWORK = {
    'DEFAULT_AUTHENTICATION_CLASSES': [
        'rest_framework.authentication.TokenAuthentication',
    ],
}
```

```
python manage.py migrate
python manage.py drf_create_token <username>
```

```
# Criar token automaticamente para novos usuários
from django.conf import settings
from django.db.models.signals import post_save
from django.dispatch import receiver
from rest_framework.authtoken.models import Token

@receiver(post_save, sender=settings.AUTH_USER_MODEL)
def create_auth_token(sender, instance=None, created=False, **kwargs):
    if created:
        Token.objects.create(user=instance)
```

Autenticação: JWT

```
pip install djangorestframework-simplejwt
```

```
# settings.py
REST_FRAMEWORK = {
    'DEFAULT_AUTHENTICATION_CLASSES': [
        'rest_framework_simplejwt.authentication.JWTAuthentication',
    ],
}

from datetime import timedelta

SIMPLE_JWT = {
    'ACCESS_TOKEN_LIFETIME': timedelta(minutes=60),
    'REFRESH_TOKEN_LIFETIME': timedelta(days=1),
}
```

```
# urls.py
from rest_framework_simplejwt.views import (
    TokenObtainPairView,
    TokenRefreshView,
)

urlpatterns += [
    path('api/token/', TokenObtainPairView.as_view(),
         name='token_obtain_pair'),
    path('api/token/refresh/', TokenRefreshView.as_view(),
         name='token_refresh'),
]
```


Permissões Customizadas

```
# products/permissions.py
from rest_framework import permissions

class IsOwnerOrReadOnly(permissions.BasePermission):
    """Apenas dono pode editar"""

    def has_object_permission(self, request, view, obj):
        # Leitura permitida para todos
        if request.method in permissions.SAFE_METHODS:
            return True

        # Escrita apenas para dono
        return obj.created_by == request.user

class IsAdminOrReadOnly(permissions.BasePermission):
    """Apenas admin pode criar/editar/deletar"""

    def has_permission(self, request, view):
        if request.method in permissions.SAFE_METHODS:
            return True
        return request.user and request.user.is_staff
```

```
# Usar nas views

class ProductViewSet(viewsets.ModelViewSet):
    permission_classes = [IsOwnerOrReadOnly]
    # ou
    permission_classes = [IsAdminOrReadOnly]
```

7. Filtros, Busca e Ordenação

```
pip install django-filter
```

```
# products/filters.py
from django_filters import rest_framework as filters
from .models import Product

class ProductFilter(filters.FilterSet):
    min_price = filters.NumberFilter(field_name='price',
                                     lookup_expr='gte')
    max_price = filters.NumberFilter(field_name='price',
                                     lookup_expr='lte')
    name = filters.CharFilter(lookup_expr='icontains')
    created_after = filters.DateTimeFilter(field_name='created_at',
                                           lookup_expr='gte')

    class Meta:
        model = Product
        fields = ['category', 'status']
```

```
# products/views.py
from django_filters.rest_framework import DjangoFilterBackend
from rest_framework import filters

class ProductViewSet(viewsets.ModelViewSet):
    queryset = Product.objects.all()
    serializer_class = ProductSerializer
    filter_backends = [DjangoFilterBackend, filters.SearchFilter,
                      filters.OrderingFilter]
    filterset_class = ProductFilter
    search_fields = ['name', 'description', 'category__name']
    ordering_fields = ['price', 'created_at', 'stock']
    ordering = ['-created_at']
```

Exemplos de uso:

```
GET /api/products/?status=published
GET /api/products/?min_price=50&max_price=500
GET /api/products/?search=notebook
GET /api/products/?ordering=-price
GET /api/products/?category=1&status=published&ordering=price
```

8. Paginação

PageNumberPagination

```
# settings.py
REST_FRAMEWORK = {
    'DEFAULT_PAGINATION_CLASS': 'rest_framework.pagination.PageNumberPagination',
    'PAGE_SIZE': 10
}
```

Paginação Customizada

```
# myapi/pagination.py
from rest_framework.pagination import PageNumberPagination

class CustomPagination(PageNumberPagination):
    page_size = 20
    page_size_query_param = 'page_size'
    max_page_size = 100
```

```
# products/views.py
class ProductViewSet(viewsets.ModelViewSet):
    pagination_class = CustomPagination
```

Resposta paginada:

```
{
  "count": 125,
  "next": "http://api.example.com/products/?page=2",
  "previous": null,
  "results": [
    {...},
    {...}
  ]
}
```

9. Versionamento de API

```
# settings.py
REST_FRAMEWORK = {
    'DEFAULT_VERSIONING_CLASS': 'rest_framework.versioning.URLPathVersioning',
    'DEFAULT_VERSION': 'v1',
    'ALLOWED_VERSIONS': ['v1', 'v2'],
}
```

```
# urls.py
urlpatterns = [
    path('api/<str:version>/', include(router.urls)),
]
```

```
# views.py
class ProductViewSet(viewsets.ModelViewSet):
    def get_serializer_class(self):
        if self.request.version == 'v2':
            return ProductSerializerV2
        return ProductSerializer
```

10. Testes com DRF

Testes Básicos

```

# products/tests.py
from rest_framework.test import APITestCase, APIClient
from rest_framework import status
from django.contrib.auth.models import User
from .models import Product, Category

class ProductAPITestCase(APITestCase):

    def setUp(self):
        """Executado antes de cada teste"""
        self.client = APIClient()
        self.user = User.objects.create_user(
            username='testuser',
            password='testpass123'
        )
        self.category = Category.objects.create(
            name='Eletrônicos',
            slug='eletronicos'
        )
        self.product = Product.objects.create(
            name='Notebook',
            slug='notebook',
            description='Notebook de teste',
            price=3000.00,
            stock=10,
            category=self.category,
            created_by=self.user,
            status='published'
        )

    def test_list_products(self):
        """Teste GET /api/products/"""
        response = self.client.get('/api/products/')
        self.assertEqual(response.status_code, status.HTTP_200_OK)
        self.assertEqual(len(response.data['results']), 1)

    def test_create_product_authenticated(self):
        """Teste POST /api/products/ (autenticado)"""
        self.client.force_authenticate(user=self.user)

        data = {

```

```

        'name': 'Mouse',
        'slug': 'mouse',
        'description': 'Mouse gamer',
        'price': 150.00,
        'stock': 50,
        'category': self.category.id,
        'status': 'draft'
    }

    response = self.client.post('/api/products/', data,
                                format='json')
    self.assertEqual(response.status_code, status.HTTP_201_CREATED)
    self.assertEqual(Product.objects.count(), 2)

def test_create_product_unauthenticated(self):
    """Teste POST sem autenticação"""
    data = {'name': 'Test'}
    response = self.client.post('/api/products/', data)
    self.assertEqual(response.status_code,
                      status.HTTP_401_UNAUTHORIZED)

def test_update_product(self):
    """Teste PATCH /api/products/{slug}/"""
    self.client.force_authenticate(user=self.user)

    data = {'price': 2500.00}
    response = self.client.patch(
        f'/api/products/{self.product.slug}/',
        data,
        format='json'
    )

    self.assertEqual(response.status_code, status.HTTP_200_OK)
    self.product.refresh_from_db()
    self.assertEqual(float(self.product.price), 2500.00)

def test_delete_product(self):
    """Teste DELETE /api/products/{slug}/"""
    self.client.force_authenticate(user=self.user)

    response = self.client.delete(f'/api/products/{self.product.slug}/')

```



```

self.assertEqual(response.status_code,
status.HTTP_204_NO_CONTENT)
self.assertEqual(Product.objects.count(), 0)

def test_filter_by_status(self):
    """Teste filtros"""
    response = self.client.get('/api/products/?status=published')
    self.assertEqual(response.status_code, status.HTTP_200_OK)
    self.assertEqual(len(response.data['results']), 1)

def test_search(self):
    """Teste busca"""
    response = self.client.get('/api/products/?search=Notebook')
    self.assertEqual(response.status_code, status.HTTP_200_OK)
    self.assertEqual(len(response.data['results']), 1)

```

Executar Testes

```

# Todos os testes
python manage.py test

# Testes específicos
python manage.py test products.tests.ProductAPITestCase

# Com coverage
pip install coverage
coverage run --source='.' manage.py test
coverage report
coverage html # Gera relatório HTML

```

11. Documentação Automática (OpenAPI/Swagger)

```
pip install drf-spectacular
```

```
# settings.py
INSTALLED_APPS += ['drf_spectacular']

REST_FRAMEWORK = {
    'DEFAULT_SCHEMA_CLASS': 'drf_spectacular.openapi.AutoSchema',
}

SPECTACULAR_SETTINGS = {
    'TITLE': 'Products API',
    'DESCRIPTION': 'API REST para gerenciamento de produtos',
    'VERSION': '1.0.0',
    'SERVE_INCLUDE_SCHEMA': False,
}
```

```
# urls.py
from drf_spectacular.views import SpectacularAPIView,
    SpectacularSwaggerView

urlpatterns += [
    path('api/schema/', SpectacularAPIView.as_view(), name='schema'),
    path('api/docs/', SpectacularSwaggerView.as_view(url_name='schema'),
        name='swagger-ui'),
]
```

Acesse: <http://localhost:8000/api/docs/>

12. CORS (Cross-Origin Resource Sharing)

```
pip install django-cors-headers
```

```
# settings.py
INSTALLED_APPS += ['corsheaders']

MIDDLEWARE = [
    'corsheaders.middleware.CorsMiddleware',
    'django.middleware.common.CommonMiddleware',
    # ...
]

# Desenvolvimento
CORS_ALLOWED_ORIGINS = [
    "http://localhost:3000",
    "http://localhost:8080",
]

# Produção (mais restritivo)
CORS_ALLOWED_ORIGINS = [
    "https://meusite.com",
]

# Ou permitir tudo (NÃO recomendado em produção)
CORS_ALLOW_ALL_ORIGINS = True
```

13. Throttling (Rate Limiting)

```
# settings.py
REST_FRAMEWORK = {
    'DEFAULT_THROTTLE_CLASSES': [
        'rest_framework.throttling.AnonRateThrottle',
        'rest_framework.throttling.UserRateThrottle'
    ],
    'DEFAULT_THROTTLE_RATES': {
        'anon': '100/day',
        'user': '1000/day'
    }
}
```

Throttling Customizado

```
from rest_framework.throttling import UserRateThrottle

class BurstRateThrottle(UserRateThrottle):
    rate = '60/minute'

class SustainedRateThrottle(UserRateThrottle):
    rate = '1000/day'

class ProductViewSet(viewsets.ModelViewSet):
    throttle_classes = [BurstRateThrottle, SustainedRateThrottle]
```

14. Boas Práticas DRF

✓ Use ViewSets para CRUD Completo

```
# ✓ Bom
class ProductViewSet(viewsets.ModelViewSet):
    queryset = Product.objects.all()
    serializer_class = ProductSerializer

# ✗ Evite repetir código
class ProductListView(APIView): ...
class ProductDetailView(APIView): ...
class ProductCreateView(APIView): ...
```

✓ Otimize Queries

```
# ✓ Bom - select_related para ForeignKey
Product.objects.select_related('category', 'created_by')

# ✓ Bom - prefetch_related para ManyToMany
Product.objects.prefetch_related('tags')

# ✗ Ruim - N+1 queries
for product in Product.objects.all():
    print(product.category.name) # Query para cada produto!
```

✓ Valide Dados no Serializer

```
# ✓ Bom
class ProductSerializer(serializers.ModelSerializer):
    def validate_price(self, value):
        if value <= 0:
            raise serializers.ValidationError("Preço inválido")
        return value

# ✗ Evite validação na view
```

✓ Use Permissions Adequadas

```
# ✓ Bom - granular
class ProductViewSet(viewsets.ModelViewSet):
    permission_classes = [IsAuthenticatedOrReadOnly]

    def get_permissions(self):
        if self.action in ['create', 'update', 'destroy']:
            return [IsAdminUser()]
        return super().get_permissions()

# ✗ Ruim - tudo aberto
permission_classes = [AllowAny]
```

✓ Versione sua API

```
# ✓ Bom
/api/v1/products/
/api/v2/products/

# ✗ Evite quebrar a API sem aviso
```

15. Deploy e Produção

Checklist de Produção

✓ DEBUG = False

```
DEBUG = False
ALLOWED_HOSTS = ['meusite.com', 'api.meusite.com']
```

✓ Use PostgreSQL

```
DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.postgresql',
        'NAME': 'myapi_db',
        'USER': 'postgres',
        'PASSWORD': os.environ.get('DB_PASSWORD'),
        'HOST': 'localhost',
        'PORT': '5432',
    }
}
```

✓ Segurança

```
SECRET_KEY = os.environ.get('SECRET_KEY')
SECURE_SSL_REDIRECT = True
SESSION_COOKIE_SECURE = True
CSRF_COOKIE_SECURE = True
SECURE_BROWSER_XSS_FILTER = True
```

✓ Logging


```
LOGGING = {
    'version': 1,
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'filename': '/var/log/django/api.log',
        },
    },
    'loggers': {
        'django': {
            'handlers': ['file'],
            'level': 'INFO',
        },
    },
}
```

✓ Servir com Gunicorn + Nginx

```
pip install gunicorn
gunicorn myapi.wsgi:application --bind 0.0.0.0:8000
```

16. Quando Usar DRF vs FastAPI

Cenário	Use DRF	Use FastAPI
App Django existente	✓ Sim	✗ Não
Precisa Django Admin	✓ Sim	✗ Não
API pura (microserviço)	⚠ OK	✓ Melhor
Async/WebSocket	⚠ Limitado	✓ Excelente
Time já conhece Django	✓ Sim	⚠ Depende
Performance máxima	⚠ Boa	✓ Excelente
Documentação auto	✓ drf-spectacular	✓ Built-in

17. Recursos e Próximos Passos

Documentação Oficial



Django REST Framework Docs



Django 5.1 Docs

Posts Relacionados

[🔗 Construção de APIs com DRF](#) [🔗 Configurando Projeto DRF](#) [🔗 Serializers no DRF](#) [🔗 Filtros, Busca e Ordenação](#) [🔗 Guia Completo Django 2025](#)

Continue Aprendendo

1. **GraphQL com Graphene-Django**
 2. **WebSockets com Django Channels**
 3. **Celery para tarefas assíncronas**
 4. **Cache com Redis**
 5. **CI/CD com GitHub Actions**
-

Conclusão

Neste **guia completo de Django REST Framework**, você aprendeu:

✅ **Por que usar DRF** - Vantagens e comparações ✅ **Instalação e setup** - Configuração completa ✅ **Models e Serializers** - Validação e serialização ✅ **Views e ViewSets** - FBV, CBV, Generic, ViewSets ✅ **Autenticação** - Token, JWT, permissões customizadas ✅ **Filtros e paginação** - django-filter, search, ordering ✅ **Testes** - APITestCase completo ✅ **Documentação** - OpenAPI/Swagger ✅ **Produção** - Deploy, segurança, boas práticas

Principais lições:

- **ViewSets** são a forma mais eficiente de criar APIs CRUD
- **Serializers** fazem validação automática de dados

- **Permissions** garantem segurança granular
- **Filtros** tornam a API flexível e poderosa
- **Testes** são essenciais para APIs confiáveis
- **DRF** é ideal para apps Django que precisam de APIs REST

Próximos passos:

- Implemente autenticação JWT em seu projeto
- Adicione testes com cobertura > 80%
- Configure documentação Swagger
- Otimize queries com `select_related/prefetch_related`
- Deploy em produção com Docker + Gunicorn + Nginx

Django REST Framework é a escolha certa quando você precisa de APIs REST robustas, bem documentadas e escaláveis com Django!


Até a próxima! 🚀

Não se esqueça de conferir!



Ebookr

Crie Ebooks profissionais em minutos com IA



Chega de formatar código no Google Docs ou Word



Capas gerados por IA



Infográficos feitos por IA



Adicione Banners Promocionais

Deixe que nossa IA faça o trabalho pesado



Edite em Markdown em Tempo Real

TESTE AGORA



PRIMEIRO CAPÍTULO 100% GRÁTIS