

# ISO/IEC 29341-8-17

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture –
Part 8-17: Internet Gateway Device Control Protocol – Wide Area Network
Ethernet Link Configuration Service





# THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2008 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub
- The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.
- IEC Just Published: <u>www.iec.ch/online\_news/justpub</u>

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: <u>www.iec.ch/webstore/custserv</u>

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: <u>csc@iec.ch</u> Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



## ISO/IEC 29341-8-17

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture –
Part 8-17: Internet Gateway Device Control Protocol – Wide Area Network
Ethernet Link Configuration Service

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

C

ICS 35.200 ISBN 2-8318-1010-4

### CONTENTS

FOREWORD	3
ORIGINAL UPNP DOCUMENTS (informative)	5
1. Overview and Scope	7
2. Service Modeling Definitions	8
2.1. ServiceType	8
2.2. State Variables	8
2.2.1. EthernetLinkStatus	8
2.2.2. Relationships Between State Variables	8
2.3. Eventing and Moderation	9
2.3.1. Event Model	9
2.4. Actions	9
2.4.1. GetEthernetLinkStatus	
2.4.2. Non-Standard Actions Implemented by a UPnP Vendor	
2.4.3. Relationships Between Actions	
2.4.4. Common Error Codes	
2.5. Theory of Operation	
3. XML Service Description	11
4. Test	12
LIST OF TABLES	
Table 1: State Variables	8
Table 1.1: AllowedValueList for EthernetLinkStatus	8
Table 2: Event Moderation	9
Table 3: Actions	9
Table 4: Arguments for GetEthernetLinkStatus	9
Table 5: Common Error Codes	10

# INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

# Part 8-17: Internet Gateway Device Control Protocol – Wide Area Network Ethernet Link Configuration Service

#### **FOREWORD**

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC
   Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation Standards Licensing Department 5200 NE Elam Young Parkway MS: JFS-98 USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation One Microsoft Way USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S High Tech campus, building 44 3A21 NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL) High Tech campus 60 NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd. 1-3-7 Shiromi, Chuoh-ku JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company 1501 Page Mill Road USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd. 416 Maetan-3 Dong, Yeongtang-Gu, KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-8-17 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

# ORIGINAL UPNP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1 ISO/IEC 29341-6-2
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2 ISO/IEC 29341-6-10
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10 ISO/IEC 29341-6-11
UPnP HVAC_FanOperatingMode:1 Service UPnP FanSpeed:1 Service	
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-12
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-13 ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-2 ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-10
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-11
UPnP Scan:1 Service	ISO/IEC 29341-9-12
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

#### UPnP Document Title ISO/IEC 29341 Part

UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

### 1. Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0

This service-type models physical and link layer properties of a WAN Ethernet interface used for Internet access on an *InternetGatewayDevice*. A gateway device that offers Internet connectivity via an external, Ethernet-attached cable or DSL modem would offer this service.

The service is OPTIONAL (for an *InternetGatewayDevice* that has an Ethernet WAN interface) and is specified in

urn:schemas-upnp-org:device: WANConnectionDevice one or more instances of which are specified under the device urn:schemas-upnp-org:device: WANDevice

An instance of *WANDevice* is specified under the root device urn:schemas-upnp-org:device:*InternetGatewayDevice* 

**NOTE**: A *WANDevice* also provides a *WANCommonInterfaceConfig* service that encapsulates Internet access properties common across all WAN interfaces.

### 2. Service Modeling Definitions

### 2.1. ServiceType

The following service type identifies a service that is compliant with this template:

urn:schemas-upnp-org:service: <u>WANEthernetLinkConfig:1</u>.

#### 2.2. State Variables

**Table 1: State Variables** 

Variable Name	Req. or Opt. <sup>1</sup>	Data Type	Allowed Value	Default Value <sup>2</sup>	Eng. Units
EthernetLinkStatus	R	string	See table 1.1	Not specified	N/A
Non-standard state variables implemented by an UPnP vendor go here.	X	TBD	TBD	TBD	TBD

 $<sup>^{1}</sup>$  R = Required, O = Optional, X = Non-standard.

NOTE: Default values are not specified in the DCP. A vendor may however choose to provide default values for SST variables where appropriate.

Table 1.1: AllowedValueList for EthernetLinkStatus

Value	Req. or Opt.
Up	<u>R</u>
Down	<u>R</u>
Unavailable	<u>O</u>

#### 2.2.1. EthernetLinkStatus

This variable indicates the status of the WAN Ethernet link. This only indicates the status of the physical link between the *InternetGatewayDevice* and an externally attached modem, and NOT the status of the external link of the modem itself. It is a **Read-only** variable.

#### 2.2.2. Relationships Between State Variables

None.

<sup>&</sup>lt;sup>2</sup>Values listed in this column are required. To specify standard optional values or to delegate assignment of values to the vendor, you must reference a specific instance of an appropriate table below.

### 2.3. Eventing and Moderation

**Table 2: Event Moderation** 

Variable Name	Evented	Moderated Event	Max Event Rate <sup>1</sup>	Logical Combination	Min Delta per Event <sup>2</sup>
EthernetLinkStatus	Yes	No	N/A	N/A	N/A
Non-standard state variables implemented by an UPnP vendor go here.	TBD	TBD	TBD	TBD	TBD

<sup>&</sup>lt;sup>1</sup> Determined by N, where Rate = (Event)/(N secs).

#### 2.3.1. Event Model

If EthernetLinkStatus changes, subscribed control points are notified. A status change indicates presence or absence of connectivity to an externally attached modem.

#### 2.4. Actions

Immediately following this table is detailed information about these actions, including short descriptions of the actions, the effects of the actions on state variables, and error codes defined by the actions.

**Table 3: Actions** 

Name	Req. or Opt. 1
GetEthernetLinkStatus	<u>R</u>
Non-standard actions implemented by an UPnP vendor go here.	X

R = Required, O = Optional, X = Non-standard.

#### 2.4.1. GetEthernetLinkStatus

This action retrieves the link status of the Ethernet connection to an externally attached modem.

#### 2.4.1.1. Arguments

Table 4: Arguments for GetEthernetLinkStatus

Argument	Direction	relatedStateVariable
NewEthernetLinkStatus	<u>OUT</u>	EthernetLinkStatus

#### 2.4.1.2. Dependency on State (if any)

#### 2.4.1.3. Effect on State (if any)

None.

<sup>&</sup>lt;sup>2</sup> (N) \* (allowedValueRange Step).

#### 2.4.1.4. Errors

errorCode	errorDescription	Description
402	Invalid Args	One of following: not enough IN arguments, too many IN arguments, no IN argument by that name, one or more IN arguments are of the wrong data type. See also the UPnP Device Architecture.
501	Action Failed	May be returned in current state if service prevents invoking of that action.

#### 2.4.2. Non-Standard Actions Implemented by a UPnP Vendor

To facilitate certification, non-standard actions implemented by UPnP vendors should be included in this service template. The UPnP Device Architecture lists naming requirements for non-standard actions (see the section on Description).

#### 2.4.3. Relationships Between Actions

None.

#### 2.4.4. Common Error Codes

The following table lists error codes common to actions for this service type. If an action results in multiple errors, the most specific error should be returned.

**Table 5: Common Error Codes** 

errorCode	errorDescription	Description
401	Invalid Action	See UPnP Device Architecture section on Control.
402	Invalid Args	See UPnP Device Architecture section on Control.
404	Invalid Var	See UPnP Device Architecture section on Control.
501	Action Failed	See UPnP Device Architecture section on Control.
600-699	TBD	Common action errors. Defined by UPnP Forum Technical Committee.
701-799		Common action errors defined by the UPnP Forum working committees.
800-899	TBD	(Specified by UPnP vendor.)

### 2.5. Theory of Operation

As mentioned earlier, this service is implemented if an *InternetGatewayDevice* supports an external, Ethernet-attached modem. If the modem type identification and control operations are possible through other proprietary mechanisms, a vendor may choose to implement a more specific link configuration service; for example *WANDSLLinkConfig* or *WANCableLinkConfig*.

### 3. XML Service Description

```
<?xml version="1.0"?>
< scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <actionList>
    <action>
    <<u>name</u>>GetEthernetLinkStatus</<u>name</u>>
      <argumentList>
        <argument>
          <name>NewEthernetLinkStatus</name>
          < direction > out < / direction >
         <relatedStateVariable>EthernetLinkStatus</relatedStateVariable>
        </argument>
      </argumentList>
    </action>
    <!-- Declarations for other actions added by UPnP vendor (if any) go
here -->
  </actionList>
  <serviceStateTable>
    < stateVariable sendEvents = "yes" >
      <name>EthernetLinkStatus</name>
      <dataType>string</dataType>
      <allowedValueList>
        <allowedValue>Up</allowedValue>
        <allowedValue>Down</allowedValue>
        <allowedValue>Unavailable</allowedValue>
      </allowedValueList>
    </stateVariable>
    <!-- Declarations for other state variables added by UPnP vendor (if
any) go here -->
  </serviceStateTable>
</scpd>
```

### 4. Test

No semantic tests have been defined for this service.

# INTERNATIONAL ELECTROTECHNICAL COMMISSION

3, rue de Varembé PO Box 131 CH-1211 Geneva 20 Switzerland

Tel: + 41 22 919 02 11 Fax: + 41 22 919 03 00 info@iec.ch www.iec.ch