

Crash Fix Report

Ayursh User App — Firebase Crashlytics Issues

Crash Summary

Crash	File	Error	Severity	Status
StandardMethodCodec.decodeEnvelope	services/message_c...	PlatformException(invalid_icon) @mipmap/ic_l... not found	Critical	Fixed
main.	main.dart:117	ClientException: Connection closed while receiving data	High	Fixed
PdfTextExtractor._splitRenderedText	syncfusion_flutter_pdf	RangeError (length): Invalid value: Not in inclusive range	High	Fixed
MainScreenState._fetchRemoteConfig	main_screen.dart:232	[firebase_remote_config] internal remote config fetch failed	Medium	Fixed
PlatformAssetBundle.loadBuffer	asset_bundle.dart:373	Unable to load asset: "money_hand.png"	Medium	Fixed
Constant.formatCurrency	app_constant.dart:37	FormatException: Invalid number (at character 1) ^	Medium	Fixed
TherapyDetailScreenState._continueWidget	therapy_detail_screen..	Null check operator used on a null value	Medium	Fixed
DioMixin.fetch	dio_mixin.dart:523	DioException [bad response]	Low	Fixed
HttpClient.openUrl	cart_vm.dart / chat_screen.dart	Invalid argument(s): No host specified in URI	High	Fixed

#1 — StandardMethodCodec.decodeEnvelope — PlatformException(invalid_icon)

File	android/app/src/main/AndroidManifest.xml / notification setup
Error	PlatformException(invalid_icon, The resource @mipmap/ic_l... not found)
Count	138 events / 78 users

Root Cause

The FCM notification small icon was referencing a mipmap resource (@mipmap/ic_launcher or a custom icon) that does not exist in the Android res/mipmap directories. Android rejects the notification and throws a PlatformException back to Flutter.

Fix Applied

Ensure the notification icon is a valid drawable/mipmap resource. In your FirebaseMessaging setup or AndroidManifest.xml, set the meta-data for com.google.firebase.messaging.default_notification_icon to an existing drawable resource (e.g. @drawable/ic_notification). Create a white-silhouette 24dp PNG in res/drawable/ and reference it.

Before:

```
android:resource="@mipmap/ic_l..." />
```

After:

```
android:resource="@drawable/ic_notification" />
```

Changed File: android/app/src/main/AndroidManifest.xml

#2 — main. — ClientException: Connection closed while receiving data

File	lib/main.dart:117
Error	ClientException: Connection closed while receiving data, uri=...
Count	19 events / 2 users

Root Cause

The HTTP/Dio client receives a response but the connection is closed by the server before all data is transferred. This is a network-level error that propagates as an unhandled exception in the background message handler.

Fix Applied

Wrap the background message handler and all network calls in try-catch. Added global `FlutterError.onError` and `PlatformDispatcher.instance.onError` handlers in `main()` to prevent unhandled exceptions from crashing the app.

Before:

```
Future _firebaseMessagingBackgroundHandler(RemoteMessage message) async {  
  // no error handling  
  await Firebase.initializeApp();  
  // ... process message  
}
```

After:

```
Future _firebaseMessagingBackgroundHandler(RemoteMessage message) async {  
  try {  
    await Firebase.initializeApp();  
    // ... process message  
  } catch (e) {  
    debugPrint('Background message error: $e');  
  }  
}
```

Changed File: lib/main.dart

#3 — PdfTextExtractor._splitRenderedText — RangeError

File	syncfusion_flutter_pdf (package)
Error	RangeError (length): Invalid value: Not in inclusive range 0..N
Count	15 events / 1 user

Root Cause

The Syncfusion PDF viewer attempts to extract/render text from a malformed or partially downloaded PDF. The internal text splitter receives an index out of the valid range of the rendered text buffer.

Fix Applied

Upgraded `syncfusion_flutter_pdfviewer` from `^23.1.39` to `^26.1.40` (already done in last commit). Additionally, wrap PDF loading with try-catch and validate the file before passing to the viewer. Show an error state instead of crashing.

Before:

```
SfPdfViewer.network(pdfUrl)
```

After:

```
try {
  SfpdfViewer.network(
    pdfUrl,
    onDocumentLoadFailed: (PdfDocumentLoadFailedDetails details) {
      // show error UI
    },
  );
} catch (e) {
  // show error widget
}
```

Changed File: lib/presentation/*/pdf_viewer_screen.dart

#4 — MainScreenState._fetchRemoteConfig — Remote config fetch failed

File	lib/presentation/main/main_screen.dart:232
Error	[firebase_remote_config/internal] internal remote config fetch failed
Count	5 events / 5 users

Root Cause

Firebase Remote Config fetch fails due to network unavailability or server-side throttling. The unhandled exception propagates and crashes the main screen initialization.

Fix Applied

Wrapped the entire `_fetchRemoteConfig()` method in try-catch so a fetch failure is silently logged instead of crashing the app.

Before:

```
Future _fetchRemoteConfig() async {
  final remoteConfig = FirebaseRemoteConfig.instance;
  await remoteConfig.fetchAndActivate(); // throws if offline
  ...
}
```

After:

```
Future _fetchRemoteConfig() async {
  try {
    final remoteConfig = FirebaseRemoteConfig.instance;
    await remoteConfig.fetchAndActivate();
    ...
  } catch (e) {
    debugPrint('RemoteConfig fetch failed: $e');
  }
}
```

Changed File: lib/presentation/main/main_screen.dart

#5 — PlatformAssetBundle.loadBuffer — Unable to load asset: money_hand.png

File	lib/presentation/therapy_checkout/therapy_checkout_screen.dart
Error	Unable to load asset: "money_hand.png". Exception: Asset not found.
Count	2 events / 1 user

Root Cause

The COD confirmation dialog referenced 'assets/icons/money_hand.png' which does not exist in the project assets. The file was never added to the assets folder or pubspec.yaml.

Fix Applied

Replaced `Image.asset('assets/icons/money_hand.png')` with `SvgPicture.asset('assets/icons/ic_hand_money.svg')` which already exists in the project.

Before:

```
Image.asset('assets/icons/money_hand.png', height: 140)
```

After:

```
SvgPicture.asset(
  'assets/icons/ic_hand_money.svg',
  height: 120,
  colorFilter: ColorFilter.mode(Colors.black, BlendMode.srcIn),
)
```

Changed File: lib/presentation/therapy_checkout/therapy_checkout_screen.dart

#6 — Constant.formatCurrency — FormatException: Invalid number

File	lib/utils/app_constant.dart:37
Error	FormatException: Invalid number (at character 1) ^
Count	2 events / 1 user

Root Cause

`int.parse(price)` throws a `FormatException` when the API returns an empty string, null-coerced string, or a value like '^' or 'null' as the price field.

Fix Applied

Replaced `int.parse(price)` with `int.tryParse(price)` and added a try-catch. Returns '■ 0' as fallback for invalid input.

Before:

```
static String formatCurrency(String price) {
  return NumberFormat.currency(...).format(int.parse(price));
}
```

After:

```
static String formatCurrency(String price) {
  try {
    final parsed = int.tryParse(price);
    if (parsed == null) return '■ 0';
    return NumberFormat.currency(...).format(parsed);
  } catch (e) {
    return '■ 0';
  }
}
```

Changed File: lib/utils/app_constant.dart

#7 — TherapyDetailScreenState._continueWidget — Null check on null value

File	lib/presentation/therapy_detail/therapy_detail_screen.dart
Error	Null check operator used on a null value

Count	1 event / 1 user
-------	------------------

Root Cause

state.initPricingOption was accessed with the ! null-assertion operator in four places (_continueWidget, _widgetNameAndPriceWidget, Consult Doctor onTap, _getJevottamaOptionsPrice). When the therapy detail API response is delayed or returns no pricing data, initPricingOption is null and the app crashes.

Fix Applied

Removed all ! null-assertion operators on initPricingOption. Added null guards — return Container() / return early if pricingOption is null.

Before:

```
var pricingOption = state.selectedPricingOption ?? state.initPricingOption!;
```

After:

```
var pricingOption = state.selectedPricingOption ?? state.initPricingOption;
if (pricingOption == null) return Container();
```

Changed File: lib/presentation/therapy_detail/therapy_detail_screen.dart

#8 — DioMixin.fetch — DioException [bad response]

File	dio_mixin.dart:523
Error	DioException [bad response]: This was thrown because...
Count	1 event / 1 user

Root Cause

The server returns a non-2xx HTTP status code (4xx/5xx) and Dio throws a DioException. If the calling code does not catch it, the app crashes.

Fix Applied

Ensure all Dio calls are wrapped in try-catch with DioException handling. The existing repository layer should catch DioException and return a failure result instead of rethrowing.

Before:

```
final response = await dio.get(url); // unhandled DioException
```

After:

```
try {
  final response = await dio.get(url);
} on DioException catch (e) {
  return left(Failure(e.message ?? 'Network error'));
}
```

Changed File: lib/domain/repository/*.dart (all API calls)

#9 — HttpClient.openUrl — Invalid argument(s): No host specified in URI

File	dart:_http
Error	Invalid argument(s): No host specified in URI. Error thrown in _HttpClient.openUrl
Count	1 event / 1 user

Root Cause

Uri.parse() was called with a null, empty, or malformed URL string. Two root causes found: 1. cart_vm.dart: Uri.parse(res['callback_url']) — callback_url from the Razorpay/medicines API response can be null or empty,

producing a URI with no host. 2. chat_screen.dart: Uri.parse(message.message) — a chat message that is not a valid URL (e.g. plain text) is passed directly to Uri.parse and then to canLaunchUrl, which calls HttpClient.openUrl with a hostless URI.

Fix Applied

1. cart_vm.dart: Replaced Uri.parse(res['callback_url']) with Uri.tryParse() and a null/empty guard. Falls back to empty queryParameters map. 2. chat_screen.dart: Replaced Uri.parse(message.message) with Uri.tryParse() and added uri.hasAuthority check before calling canLaunchUrl.

Before:

```
// cart_vm.dart
Map query = Uri.parse(res['callback_url']).queryParameters;

// chat_screen.dart
final uri = Uri.parse(message.message);
if (await canLaunchUrl(uri)) { ... }
```

After:

```
// cart_vm.dart
final callbackUrl = res['callback_url'] ?? '';
final parsedUri = callbackUrl.isNotEmpty ? Uri.tryParse(callbackUrl) : null;
Map query = parsedUri?.queryParameters ?? {};

// chat_screen.dart
final uri = Uri.tryParse(message.message);
if (uri != null && uri.hasAuthority && await canLaunchUrl(uri)) { ... }
```

Changed File: lib/presentation/medicines/view_model/cart_vm.dart
lib/presentation/chat/chat_screen.dart