OS

RESTAURANTOS CUSTOMER ONBOARDING KIT

Target: IT TECHNICIANS, SYSTEM INTEGRATORS, FRANCHISE OPERATIONS, STORE ADMINS

Version: 1.4.0 Production Edition | Repeatable SaaS Protocol

DEPLOYMENT & INSTALLATION MANUAL

Multi-Platform Installation Guide

Technical deployment instructions across Web PWA, Windows Desktop (Tauri), an Android Handheld (Capacitor).

DEPLOYMENT SPECIFICATIONS & OPERATIONAL BOUNDARIES

- Audience: IT Technicians, System Integrators, Franchise Operations, Store Admins
- Multi-Tenant Isolation: 100% separate tenant accounts, databases, and permissions.
- Packaging Status: Web/PWA verified; Windows Tauri & Android Capacitor architecture verified.
- Privacy & Credentials: Real customer passwords and private payment keys are never shared.
- Standards: Standardized A4 printable release with customer acceptance sign-off.

RestaurantOS Hospitality Engineering — Published November 2026

Standardized customer deployment stages

Section 1: Universal Web & Progressive Web App (PWA) **[Stage 1]**

1.1 Supported Browser Requirements
1.2 Accessing and Installing as a Standalone PWA

Section 2: Windows Desktop Application (Tauri) **[Stage 2]**

2.1 Architecture & Packaging Status
2.2 Installation & Hardware Pairing

Section 3: Android Handheld Application (Capacitor) **[Stage 3]**

3.1 Installation & Device Permissions

Section 4: LAN Static IPs & Network Ports **[Stage 4]**

4.1 Network Architecture & Firewall Rules

STANDARDIZED SAAS DEPLOYMENT

Follow this protocol sequentially for every new customer. Do not modify the underlying application code per customer; customize only via the setup spreadsheet and configuration screens.

RestaurantOS is built on a high-performance Next.js App Router architecture that runs natively across any modern web browser without plugin requirements:

• Recommended: Google Chrome v100+ or Microsoft Edge v100+ for best thermal printing support.

• Apple: Safari v15+ on macOS and iPadOS.

• Mobile: Chrome for Android v100+.

• Hardware Minimums: 2.0 GHz Dual-Core CPU, 4 GB RAM, 1366x768 display resolution.

1.2 Accessing and Installing as a Standalone PWA

1. Connect the computer or tablet to the restaurant's local area network (LAN).
2. Open Google Chrome and navigate to the application URL (e.g. http://localhost:3000 or https://app.restaurantos.io).
3. Observe the right side of the address bar: click the 'Install RestaurantOS' icon.
4. In the confirmation dialog, click 'Install'.
5. RestaurantOS opens in dedicated standalone kiosk mode without browser tabs or address bars.
6. A shortcut is created on the desktop. Right-click and choose 'Pin to Taskbar' for instant cashier access.

PWA OFFLINE CACHING
When installed as a PWA, core app routes (/pos, /kitchen, /tables, /mobile/waiter) are cached locally. The terminal continues billing even if the internet drops.

• Technology: Built with Tauri v1.5 with native Rust Win32 spooler integration (winspool, wingdi).

• Package Targets: MSI Windows Installer (.msi) and NSIS Setup (.exe).

• Status: Packaging architecture (src-tauri/Cargo.toml, tauri.conf.json, main.rs) is 100% verified. Native compilation on a build machine requires the Rust toolchain (cargo and rustc).

2.2 Installation & Hardware Pairing

1. Download the official installer: restaurantos-desktop_1.0.0_x64_en-US.msi.

2. Double-click the .msi file to launch the setup wizard.

3. Accept the EULA and select the default installation folder (C:\Program Files\RestaurantOS\).

4. Click Install. Grant administrative UAC approval.

5. Launch the desktop app. Navigate to Administration !’ Settings !’ Printers.

6. Select your local thermal billing printer from the Win32 printer list and execute a test print.

7. To uninstall safely: Open Windows Settings !’ Apps !’ Installed apps !’ RestaurantOS !’ Uninstall. Local database backups are preserved.

• Target Devices: Android POS terminals (Sunmi, IMIN, Pax) or standard Android tablets/phones (Android 10+).

• Sideloading: Download RestaurantOS-v1.4.0.apk. In Android Files, tap the APK. If prompted, toggle 'Allow from this source' to ON and tap Install.

• Granting Required Permissions:

1. Camera: Tap 'While using the app' (used for table QR scanning and loyalty cards).
2. Nearby Devices / Bluetooth: Tap 'Allow' (for wireless mobile belt thermal printers).
3. Notifications: Tap 'Allow' (for audio/visual chimes when KOT dishes are ready).
4. Battery Optimization: In Android Settings !' Apps !' RestaurantOS, set battery to 'Unrestricted' so kitchen screens do not sleep.

For reliable communication between counter PCs, kitchen tablets, and thermal printers:

1. Assign static IP addresses: Server PC (192.168.1.100), Kitchen Printer (192.168.1.150), Bar Printer (192.168.1.151).

2. Open Inbound Firewall Ports: Port 3000 (TCP) for web/KDS traffic; Port 9100 (TCP) for RAW ESC/POS network thermal printing.

3. Separate staff tablets onto a dedicated 5 GHz Wi-Fi SSID (RestaurantOS-Staff) away from customer guest Wi-Fi.

- [ ] 1. Verify target browser is Google Chrome v100+ or Microsoft Edge.
- [ ] 2. Access store URL and install Progressive Web App (PWA) to desktop.
- [ ] 3. Pin RestaurantOS to Windows Taskbar or tablet Home screen.
- [ ] 4. Assign static LAN IP to in-store server and thermal network printers.
- [ ] 5. Open inbound firewall ports 3000 and 9100 on host server.
- [ ] 6. Grant Camera, Bluetooth, and Notification permissions on Android tablets.
- [ ] 7. Set Android display sleep / wake-lock to Never for kitchen KDS screens.
- [ ] 8. Execute test print and verify cash drawer solenoid kick pulse.