```
use apptech;

create table employees(id int primary key,name varchar(10),age int,department varchar(20));

create table customers(customer_id int primary key,name varchar(15),email varchar(20),phone int);

create table orders(order_id int primary key,customer_id int,order_date date,total_amount int,foreign key(customer_id) references customers(customer_id));

drop table orders;

desc employees;

desc customers;

desc orders;


insert into employees(id,name,age,department) values(1,"kavya",22,"Marketing"),(2,"vinu",22,"Sales"),(3,"hk",19,"sales");

select * from employees;

insert into customers(customer_id,name,email,phone) values(1,"xyz","xyz@gmail.com",9880),(2,"abc","abc@gmail.com",6364),(3,"hlo","hlo@gmail.com",8088);

select * from customers;

insert into orders(order_id,customer_id,order_date,total_amount) values (1,1,"2025-05-06",10000),(2,2,"2025-06-04",50000);

select * from orders;


create table students(roll_no int primary key,name varchar(15),class varchar(5),marks int);

desc students;

insert into students(roll_no,name,class,marks) values (1,"abc","6a",90),(2,"hlo","6a",85),(3,"xyz","6b",80),(4,"kavya","7a",89),(5,"hk","7b",95);

select * from students;


create table products(product_id int primary key,product_name varchar(20),price decimal(5,2),quantity int);

desc products;

insert into products(product_id,product_name,price,quantity) values (1,"tv",500.0,5),(2,"washing machine",450.0,6);

select * from products;
```

```
update employees set age=25 where id=1;
select * from employees;

update orders set total_amount=45000 where order_id=1;
select * from orders;

update students set marks=70 where roll_no=1;
select * from students;

update products set price="350.0" where product_id=1;
select * from products;

update customers set email="xyz1@gmail.com" where customer_id=1;
select * from customers;

alter table employees add primary key(id);
desc employees;

alter table orders add foreign key(customer_id) references customers(customer_id);
desc orders;

alter table students add unique(roll_no);
desc students;

alter table products add constraint check (price>0);
alter table customers modify column name varchar(15) not null;
desc customers;

desc employees;
select name from employees  union select name from customers;
select order_id orderid from orders union select product_id as productid from products;
```

```
select roll_no  from students union select customer_id from customers;

select distinct department from employees;
select distinct product_name from products;
select distinct class from students;

select avg(age) from employees;
select sum(total_amount) from orders;
select max(marks) from students;
select count(*) from customers;
```