Mini Assessment

Name	Anisetti Charan Teja
Reg No	99230040955
Dept	GEN-AI
Date	11-09-2026

Q1. If an API returns 429, what should your program do?

Answer: A 429 status code means “Too Many Requests” — the client has exceeded the API's rate limit.

The program should not immediately retry. Instead it should:

- Check for a Retry-After header and wait for that duration before retrying.
- Implement exponential backoff (wait progressively longer between retries) if no header is present.
- Limit the number of retry attempts to avoid an infinite loop.
- Log the event and, if retries are exhausted, fail gracefully and notify the user.

Q2. If response.json() fails, what should your program do?

Answer: response.json() fails (raises an exception, e.g. JSONDecodeError) when the response body is empty, malformed, or not valid JSON (often an HTML error page instead). The program should:

- Wrap the call in a try/except block to catch the decoding error.
- Check response.status_code and response.text first to understand what was actually returned.
- Avoid letting the exception crash the whole program — handle it and return a safe default or error message.
- Log the raw response for debugging purposes.

Q3. If a JSON key is missing, why might .get() be safer than []?

Answer: Using square brackets, e.g. data['key'], raises a KeyError and crashes the program if the key does not exist. Using data.get('key') is safer because:

- It returns None (or a default value you specify) instead of raising an error.
- It allows the program to continue running smoothly even with incomplete or inconsistent JSON data.
- You can supply a fallback: data.get('key', 'default_value').
- It leads to more robust, production-ready code that handles real-world API responses gracefully.

End of Mini Assessment